

Question Number	Answer	Mark
2(a)	<ul style="list-style-type: none"> Measure x with a metre rule (1) Ensure the moveable rod is perpendicular to the fixed rods (e.g. use a set-square) Or measure x on both 30 cm rods and calculate the average Or measure to the centre of the moveable rod Or align the metre rule near to the 30 cm rod Or measure x while looking perpendicularly at the metre rule (1) Check for zero error on ohmmeter Or choose appropriate range on ohmmeter Or repeat R readings and calculate mean R for same value of x (1) Minimise contact resistance (e.g. ensure rods are clean) (1) 	4
2(b)	<p>Max 1 of</p> <ul style="list-style-type: none"> (When $x = 0$ m) the ohmmeter will measure the resistance of the (moveable) copper rod (1) Zero error in ohmmeter (1) The connecting leads have a resistance (1) 	1
2(c)	<p>EITHER</p> <ul style="list-style-type: none"> Use of $A = \pi r^2$ (accept $A = \pi d^2 / 4$) (1) Use of $l = 2x + 0.05$ m (1) Use of $R = \rho l / A$ (with a pair of values from the line of best fit) (1) $\rho = 1.7 \times 10^{-8} \Omega \text{ m}$ (1) <p>Accept use of $x = 0$ ($l = 0.05$ m) for MP2 and correct calculated value for MP4</p> <p>OR</p> <ul style="list-style-type: none"> Use of $A = \pi r^2$ (accept $A = \pi d^2 / 4$) (1) Calculates gradient (1) Use of gradient $= 2\rho / A$ (1) $\rho = 1.7 \times 10^{-8} \Omega \text{ m}$ (1) <p><u>Example of calculation</u> $A = \pi r^2 = \pi \times (0.0015 \text{ m})^2 = 7.1 \times 10^{-6} \text{ m}^2$ $l = 2x + 0.05 = (2 \times 0.25 \text{ m}) + 0.05 \text{ m} = 0.55 \text{ m}$ $\rho = RA / l = (1.3 \times 10^{-3} \Omega \times 7.1 \times 10^{-6} \text{ m}^2) / 0.55 \text{ m} = 1.68 \times 10^{-8} \Omega \text{ m}$ OR $A = \pi r^2 = \pi \times (0.0015 \text{ m})^2 = 7.1 \times 10^{-6} \text{ m}^2$ Gradient $= (1.55 \times 10^{-3} \Omega - 0.35 \times 10^{-3} \Omega) / (0.3 \text{ m} - 0.05 \text{ m}) = 4.8 \times 10^{-3} \Omega \text{ m}^{-1}$ $\rho = \text{gradient} \times A / 2 = 1.70 \times 10^{-8} \Omega \text{ m}$</p>	4
2(d)	<ul style="list-style-type: none"> As the cross-sectional area decreases the resistance (per unit length of track) increases (1) The system will estimate the position of the train is further away than it actually is Or the train is actually closer than the system estimates it to be (1) <p>MP2 dependent on MP1</p>	2
Total for question 2		11