

SCCM WQL Queries

Version Date: 06-Nov-2016

Prepared By	A, Karthikeyan
Document Version No	1.00

Contents

1.	All Active Desktops (Worldwide).....	5
2.	All Active Laptops (Worldwide).....	5
3.	All Windows 7 x64 Systems	5
4.	All Windows 7 x86 Systems	5
5.	All Windows x64 Systems	5
6.	All Windows x86 Systems	5
7.	All PCs with Absolute Manage Client Application Installed	6
8.	All PCs with SG-APPL-SCCM AutoCAD_2012_EN AD Group.....	6
9.	All PCs with COUNTRIES/IN/WORKSTATIONS OU.....	6
10.	All PCs with IN-CHN AD Site.....	6
11.	All Desktops (Worldwide)	6
12.	All Laptops (Worldwide).....	6
13.	All PCs with SCCM Client Agent Installed.....	6
14.	All PCs without SCCM Client Agent Installed.....	6
15.	All PCs with Duplicate Hostnames	7
16.	All PCs with Obsolete Clients	7
17.	All PCs with Internet Explorer 11 Installed	7
18.	All PCs less than 2 GB RAM	7
19.	All PCs with newly discovered from Active Directory within 30 Days.....	7
20.	All PCs with HP make and specific model.....	7
21.	All Active Windows Workstations (Desktops)	7
22.	All Active Windows Workstations (Laptops)	7
23.	All Active Windows Workstations (Laptops/Desktops)	8
24.	All VDI Windows Workstations (Laptops/Desktops).....	8
25.	All Windows Servers.....	8
26.	All Windows Servers and Workstations.....	8
27.	All Windows Workstations (Desktops).....	8
28.	All Windows Workstations (Laptops)	8
29.	All Windows Workstations (Laptops/Desktops)	9
30.	All Total Workstations Scope.....	9
31.	All Workstations Windows 7	9
32.	All Workstations Windows 8	9
33.	All Workstations Windows 8.1	9
34.	All Workstations Windows 10	9
35.	All Workstations All x64	9

36.	All Workstations All x86	9
37.	All Workstations All Virtual	10
38.	All Workstations All	10
39.	All Workstations All Desktops	10
40.	All Workstations All Laptops	10
41.	All Workstations All Laptops Dell	10
42.	All Workstations All Laptops HP	10
43.	All Workstations All Laptops Lenovo	10
44.	All Workstations Clients Version SCCM 2012 R2 RTM CU0 (5.00.7958.1000)	11
45.	All Workstations Clients Version SCCM 2012 R2 SP1 (5.00.8239.1000)	11
46.	All Workstations Clients Version SCCM 2012 R2 SP1 CU2 (5.00.8239.1301)	11
47.	All Workstations Clients Version SCCM 2012 R2 SP1 CU3 (5.00.8239.1403)	11
48.	All Lenovo M72 Desktops	11
49.	All Lenovo T440 Laptops	11
50.	All Mac Systems	11
51.	All SCCM Console	11
52.	All SCCM Distribution Points	12
53.	All SCCM Site Servers	12
54.	All SCCM Site Systems	12
55.	All Servers All	12
56.	All Servers Physical	12
57.	All Servers Virtual	12
58.	All Servers Windows 2003 and 2003 R2	12
59.	All Servers Windows 2008 and 2008 R2	12
60.	All Servers Windows 2012 and 2012 R2	13
61.	All PCs with Absolute Manage Client Installed	13
62.	All PCs without Adobe CatalogExtension 3.0.10 Installed	13
63.	All PCs without Adobe Illustrator 19.2.1 Installed	13
64.	All PCs without Cisco AnyconnectSecureMobilityClient 4.2.02075 Installed	13
65.	All PCs without Computrace Installed	13
66.	All PCs without Symantec EndpointProtection 12.1.6867.6400 Installed	13
67.	All PCs without SCCM Client CU3 Installed	13
68.	All PCs without Microsoft OneDrive 17.3.6386.0412 Installed	14
69.	All PCs without Microsoft Silverlight 5.1.41212.0 Installed	14
70.	All PCs without Bit9 Agent 7.2.2.1119 Installed	14
71.	All Assigned Systems	14
72.	All Not Assigned Systems	14
73.	All Client Systems	14
74.	All No Client Systems	14

75.	All Not Obsolete Systems	14
76.	All Obsolete Systems	14
77.	All Approved Systems	15
78.	All Not Approved Systems.....	15
79.	All Active Systems	15
80.	All Inactive Systems	15
81.	All PCs Heartbeat DDR Current within 23 Days.....	15
82.	All PCs Heartbeat DDR Not Current within 23 Days	15
83.	All PCs Hardware Inventory Current within 23 Days.....	15
84.	All PCs Hardware Inventory Not Current within 23 Days	15
85.	All PCs Software Inventory Current within 23 Days	16
86.	All PCs Software Inventory Not Current within 23 Days.....	16
87.	All PCs Physical Memory Current Reported	16
88.	All PCs Physical Memory Not Current Reported	16
89.	All PCs SCCM 2012 R2 SP1 is Installed.....	16
90.	All PCs SCCM 2012 R2 SP1 is Not Installed	16
91.	All PCs with Office 365 2013 Application Installed.....	16
92.	All PCs without Office 365 2013 Application Installed	16
93.	All PCs offline 60+ Days	17
94.	All PCs with a heartbeat within last 30 days.....	17
95.	All PCs without a heartbeat within last 60 days.....	17
96.	All PCs with Adobe Creative Cloud Design Standard 2015 Application Installed	17
97.	All PCs with BitLocker Encrypted	17
98.	All PCs with Cisco AnyconnectSecureMobilityClient 4.2.02075 Installed	17
99.	All PCs with SEP Application Installed	17
100.	All PCs without SEP Application Installed	18

1. All Active Desktops (Worldwide)

select

```
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join SMS_G_System_SYSTEM_ENCLOSURE on SMS_G_System_SYSTEM_ENCLOSURE.ResourceID = SMS_R_System.ResourceID where SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes in ("3","4","5","6","7","15","16") and SMS_R_System.Obsolete = "0" and SMS_R_System.Active = "1" and SMS_R_System.OperatingSystemNameandVersion like "Microsoft Windows NT Workstation%" and SMS_R_System.Client = "1"
```

2. All Active Laptops (Worldwide)

select

```
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join SMS_G_System_SYSTEM_ENCLOSURE on SMS_G_System_SYSTEM_ENCLOSURE.ResourceID = SMS_R_System.ResourceID where SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes = "8" or SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes = "9" or SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes = "10" or SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes = "11" or SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes = "14" and SMS_R_System.Obsolete = "0" and SMS_R_System.Active = "1" and SMS_R_System.OperatingSystemNameandVersion like "Microsoft Windows NT Workstation%" and SMS_R_System.Client = "1"
```

3. All Windows 7 x64 Systems

```
select SMS_R_System.ResourceID, SMS_R_System.ResourceType, SMS_R_System.Name, SMS_R_System.SMSUniqueIdentifier, SMS_R_System.ResourceDomainORWorkgroup, SMS_R_System.Client from SMS_R_System inner join SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceID = SMS_R_System.ResourceID where (SMS_R_System.OperatingSystemNameandVersion like "%Workstation 6.1%" or SMS_R_System.OperatingSystemNameandVersion like "%Windows 7%") and SMS_G_System_COMPUTER_SYSTEM.SystemType = "x64-based PC"
```

4. All Windows 7 x86 Systems

```
select SMS_R_System.ResourceID, SMS_R_System.ResourceType, SMS_R_System.Name, SMS_R_System.SMSUniqueIdentifier, SMS_R_System.ResourceDomainORWorkgroup, SMS_R_System.Client from SMS_R_System inner join SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceID = SMS_R_System.ResourceID where (SMS_R_System.OperatingSystemNameandVersion like "%Workstation 6.1%" or SMS_R_System.OperatingSystemNameandVersion like "%Windows 7%") and SMS_G_System_COMPUTER_SYSTEM.SystemType = "x86-based PC"
```

5. All Windows x64 Systems

```
select SMS_R_System.ResourceID, SMS_R_System.ResourceType, SMS_R_System.Name, SMS_R_System.SMSUniqueIdentifier, SMS_R_System.ResourceDomainORWorkgroup, SMS_R_System.Client from SMS_R_System inner join SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceID = SMS_R_System.ResourceID where (SMS_R_System.OperatingSystemNameandVersion like "%Workstation%") and SMS_G_System_COMPUTER_SYSTEM.SystemType = "x64-based PC"
```

6. All Windows x86 Systems

```
select SMS_R_System.ResourceID, SMS_R_System.ResourceType, SMS_R_System.Name, SMS_R_System.SMSUniqueIdentifier, SMS_R_System.ResourceDomainORWorkgroup, SMS_R_System.Client from SMS_R_System inner join SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceID = SMS_R_System.ResourceID where (SMS_R_System.OperatingSystemNameandVersion like "%Workstation%") and SMS_G_System_COMPUTER_SYSTEM.SystemType = "x86-based PC"
```

7. All PCs with Absolute Manage Client Application Installed

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_INSTALLED_SOFTWARE on SMS_G_System_INSTALLED_SOFTWARE.ResourceID =
SMS_R_System.ResourceId where SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like
"%Absolute%Manage%Agent%"
```

8. All PCs with SG-APPL-SCCM AutoCAD_2012_EN AD Group

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where SMS_R_System.Client = 1 and
SMS_R_System.Obsolete = 0 and SMS_R_System.Active = 1 and SystemGroupName like "%\\ SG-APPL-SCCM AutoCAD_2012_EN"
```

9. All PCs with COUNTRIES/IN/WORKSTATIONS OU

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceID = SMS_R_System.ResourceId
where SMS_R_System.Client = 1 and SMS_R_System.Obsolete = 0 and SMS_R_System.Active = 1
and (SystemOUName like "%/COUNTRIES/IN/WORKSTATIONS")
```

10. All PCs with IN-CHN AD Site

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where SMS_R_System.Client = 1 and
SMS_R_System.Obsolete = 0 and SMS_R_System.Active = 1 and ADSiteName = "IN-CHN"
```

11. All Desktops (Worldwide)

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_SYSTEM_ENCLOSURE on SMS_G_System_SYSTEM_ENCLOSURE.ResourceID = SMS_R_System.ResourceId
where SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes in (3,4,5,6,7,15,16)
```

12. All Laptops (Worldwide)

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_SYSTEM_ENCLOSURE on SMS_G_System_SYSTEM_ENCLOSURE.ResourceId = SMS_R_System.ResourceId
where SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes in (8 , 9, 10, 11, 12, 14, 18, 21)
```

13. All PCs with SCCM Client Agent Installed

```
select Name, SMSAssignedSites, IPAddresses, IPSubnets, ADSiteName, OperatingSystemNameandVersion,
ResourceDomainORWorkgroup, LastLogonUserDomain, LastLogonUserName, SMSUniqueIdentifier, ResourceId, ResourceType,
NetbiosName from sms_r_system where Client = 1
```

14. All PCs without SCCM Client Agent Installed

```
select Name, SMSAssignedSites, IPAddresses, IPSubnets, OperatingSystemNameandVersion, ResourceDomainORWorkgroup,
LastLogonUserDomain, LastLogonUserName, SMSUniqueIdentifier, ResourceId, ResourceType, NetbiosName from sms_r_system
where Client = 0 or Client is null
```

15. All PCs with Duplicate Hostnames

```
select R.ResourceID,R.ResourceType,R.Name,R.SMSUniqueIdentifier,R.ResourceDomainORWorkgroup,R.Client from
SMS_R_System as r full join SMS_R_System as s1 on s1.ResourceId = r.ResourceId full join SMS_R_System as s2 on s2.Name =
s1.Name where s1.Name = s2.Name and s1.ResourceId != s2.ResourceId and R.Client = null
```

16. All PCs with Obsolete Clients

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where SMS_R_System.Obsolete = 1
```

17. All PCs with Internet Explorer 11 Installed

```
select SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,
SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from
SMS_R_System inner join SMS_G_System_SoftwareFile on SMS_G_System_SoftwareFile.ResourceID =
SMS_R_System.ResourceId where SMS_G_System_SoftwareFile.FileName = "iexplore.exe" and
SMS_G_System_SoftwareFile.FileVersion like "11.%"
```

18. All PCs less than 2 GB RAM

```
SELECT SYS.Netbios_Name0 As Computer_Name,CS.Manufacturer0, BIS.SerialNumber0 As System_SerialNumber,
MEM.TotalPhysicalMemory0 As RAM FROM v_R_System SYS
JOIN v_GS_X86_PC_MEMORY MEM on SYS.ResourceID = MEM.ResourceID
JOIN v_GS_COMPUTER_SYSTEM CS on CS.ResourceID=SYS.ResourceID
JOIN v_GS_DISK Dis on Dis.ResourceID=SYS.ResourceID
JOIN v_GS_PC_BIOS BIS on BIS.ResourceID=SYS.ResourceID
where MEM.TotalPhysicalMemory0 <= 2000000
```

19. All PCs with newly discovered from Active Directory within 30 Days

```
Select SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,
SMS_R_SYSTEM.SMSUniqueIdentifier, SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from
SMS_R_System inner join SMS_G_System_SYSTEM on SMS_G_System_SYSTEM.ResourceId = SMS_R_System.ResourceId where
DATEDIFF(dd, SMS_G_System_SYSTEM.TimeStamp,GetDate()) < 30
```

20. All PCs with HP make and specific model

```
Select
SCCM_R_System.ResourceID,SCCM_R_System.ResourceType,SCCM_R_System.Name,SCCM_R_System.SCCMUniqueIdentifier,SCCM_R_System.ResourceDomainORWorkgroup,SCCM_R_System.Client from SCCM_R_System inner join
SCCM_G_System_COMPUTER_SYSTEM on SCCM_G_System_COMPUTER_SYSTEM.ResourceID =
SCCM_R_System.ResourceId where SCCM_G_System_COMPUTER_SYSTEM.Model = "HP EliteBook 2540p" or
SCCM_G_System_COMPUTER_SYSTEM.Model = "HP Elitebook 8540w" or SCCM_G_System_COMPUTER_SYSTEM.Model = "HP
ProBook 6450b"
```

21. All Active Windows Workstations (Desktops)

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_CH_ClientSummary on SMS_G_System_CH_ClientSummary.ResourceId = SMS_R_System.ResourceId inner join
SMS_G_System_SYSTEM_ENCLOSURE on SMS_G_System_SYSTEM_ENCLOSURE.ResourceID = SMS_R_System.ResourceId
where SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes in ("3","4","5","6","7","15","16") and
SMS_R_System.OperatingSystemNameandVersion like "Microsoft Windows NT Workstation%" and
SMS_G_System_CH_ClientSummary.ClientActiveStatus = 1 and SMS_R_System.Client = 1 and SMS_R_System.Obsolete = 0 and
SMS_R_System.Active = 1
```

22. All Active Windows Workstations (Laptops)

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
```

```
SMS_G_System_CH_ClientSummary on SMS_G_System_CH_ClientSummary.ResourceId = SMS_R_System.ResourceId inner join
SMS_G_System_SYSTEM_ENCLOSURE on SMS_G_System_SYSTEM_ENCLOSURE.ResourceID = SMS_R_System.ResourceId
where SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes in ("8","9","10","11","14") and
SMS_R_System.OperatingSystemNameandVersion like "Microsoft Windows NT Workstation%" and
SMS_G_System_CH_ClientSummary.ClientActiveStatus = 1 and SMS_R_System.Client = 1 and SMS_R_System.Obsolete = 0 and
SMS_R_System.Active = 1
```

23. All Active Windows Workstations (Laptops/Desktops)

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_CH_ClientSummary on SMS_G_System_CH_ClientSummary.ResourceId = SMS_R_System.ResourceId inner join
SMS_G_System_SYSTEM_ENCLOSURE on SMS_G_System_SYSTEM_ENCLOSURE.ResourceID = SMS_R_System.ResourceId
where SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes in ("3","4","5","6","7","15","16","8","9","10","11","14") and
SMS_R_System.OperatingSystemNameandVersion like "Microsoft Windows NT Workstation%" and
SMS_G_System_CH_ClientSummary.ClientActiveStatus = 1 and SMS_R_System.Client = 1 and SMS_R_System.Obsolete = 0 and
SMS_R_System.Active = 1
```

24. All VDI Windows Workstations (Laptops/Desktops)

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where
SMS_R_System.IsVirtualMachine = 'True' and SMS_R_System.OperatingSystemNameandVersion like '%Workstation%'
```

25. All Windows Servers

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where
SMS_R_System.OperatingSystemNameandVersion like "Microsoft Windows NT%Server%"
```

26. All Windows Servers and Workstations

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from sms_r_system where
OperatingSystemNameAndVersion like 'Microsoft Windows NT%Server%' or OperatingSystemNameAndVersion like 'Microsoft
Windows NT Workstation%'
```

27. All Windows Workstations (Desktops)

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_SYSTEM_ENCLOSURE on SMS_G_System_SYSTEM_ENCLOSURE.ResourceID = SMS_R_System.ResourceId
where SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes in ( "3", "4", "5", "6", "7", "15", "16" ) and
SMS_R_SYSTEM.OperatingSystemNameAndVersion like 'Microsoft Windows NT Workstation%'
```

28. All Windows Workstations (Laptops)

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_SYSTEM_ENCLOSURE on SMS_G_System_SYSTEM_ENCLOSURE.ResourceID = SMS_R_System.ResourceId
where SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes in ( "8", "9", "10", "11", "14" ) and
SMS_R_SYSTEM.OperatingSystemNameAndVersion like 'Microsoft Windows NT Workstation%'
```

29. All Windows Workstations (Laptops/Desktops)

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where
SMS_R_System.OperatingSystemNameandVersion like "Microsoft Windows NT Workstation%"
```

30. All Total Workstations Scope

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where
SMS_R_System.OperatingSystemNameandVersion like "Microsoft Windows NT Workstation%"
```

31. All Workstations | Windows 7

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where
OperatingSystemNameandVersion like '%Workstation 6.1%'
```

32. All Workstations | Windows 8

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where
OperatingSystemNameandVersion like '%Workstation 6.2%'
```

33. All Workstations | Windows 8.1

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where
OperatingSystemNameandVersion like '%Workstation 6.3%'
```

34. All Workstations | Windows 10

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where
OperatingSystemNameandVersion like '%Workstation 10.0%'
```

35. All Workstations | All x64

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceID = SMS_R_System.ResourceID
where SMS_G_System_COMPUTER_SYSTEM.SystemType = 'X64-based PC' and
SMS_R_SYSTEM.OperatingSystemNameandVersion like '%Workstation%'
```

36. All Workstations | All x86

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceID = SMS_R_System.ResourceID
where SMS_G_System_COMPUTER_SYSTEM.SystemType = 'X86-based PC' and
SMS_R_SYSTEM.OperatingSystemNameandVersion like '%Workstation%'
```

37.All Workstations | All Virtual

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where
SMS_R_System.IsVirtualMachine = 'True' and SMS_R_System.OperatingSystemNameandVersion like '%Workstation%'
```

38.All Workstations | All

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where
OperatingSystemNameandVersion like '%Workstation%'
```

39.All Workstations | All Desktops

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_SYSTEM_ENCLOSURE on SMS_G_System_SYSTEM_ENCLOSURE.ResourceID = SMS_R_System.ResourceID
where SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes in ( "3", "4", "5", "6", "7", "15", "16" ) and SMS_R_System.Obsolete = 0
and SMS_R_System.Active = "1" and OperatingSystemNameandVersion like '%Workstation%'
```

40.All Workstations | All Laptops

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_SYSTEM_ENCLOSURE on SMS_G_System_SYSTEM_ENCLOSURE.ResourceID = SMS_R_System.ResourceID
where SMS_G_System_SYSTEM_ENCLOSURE.ChassisTypes in ( "8", "9", "10", "11", "12", "14", "18", "21" ) and SMS_R_System.Obsolete
= 0 and SMS_R_System.Active = "1" and OperatingSystemNameandVersion like '%Workstation%'
```

41.All Workstations | All Laptops Dell

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceID = SMS_R_System.ResourceID
where SMS_G_System_COMPUTER_SYSTEM.Manufacturer like '%Dell%' and OperatingSystemNameandVersion like
'%Workstation%'
```

42.All Workstations | All Laptops HP

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceID = SMS_R_System.ResourceID
where SMS_G_System_COMPUTER_SYSTEM.Manufacturer like '%HP%' and OperatingSystemNameandVersion like
'%Workstation%'
```

43.All Workstations | All Laptops Lenovo

```
Select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceID = SMS_R_System.ResourceID
where SMS_G_System_COMPUTER_SYSTEM.Manufacturer like '%Lenovo%' and OperatingSystemNameandVersion like
'%Workstation%'
```

44. All Workstations Clients Version | SCCM 2012 R2 RTM CU0 (5.00.7958.1000)

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where SMS_R_System.ClientVersion =
"5.00.7958.1000" and SMS_R_System.OperatingSystemNameandVersion like "%Workstation%"
```

45. All Workstations Clients Version | SCCM 2012 R2 SP1 (5.00.8239.1000)

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where SMS_R_System.ClientVersion =
"5.00.8239.1000" and SMS_R_System.OperatingSystemNameandVersion like "%Workstation%"
```

46. All Workstations Clients Version | SCCM 2012 R2 SP1 CU2 (5.00.8239.1301)

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where SMS_R_System.ClientVersion =
"5.00.8239.1301" and SMS_R_System.OperatingSystemNameandVersion like "%Workstation%"
```

47. All Workstations Clients Version | SCCM 2012 R2 SP1 CU3 (5.00.8239.1403)

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where SMS_R_System.ClientVersion =
"5.00.8239.1403" and SMS_R_System.OperatingSystemNameandVersion like "%Workstation%"
```

48. All Lenovo M72 Desktops

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceID = SMS_R_System.ResourceId
where SMS_G_System_COMPUTER_SYSTEM.Model like "0967%"
```

49. All Lenovo T440 Laptops

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceID = SMS_R_System.ResourceId
where SMS_G_System_COMPUTER_SYSTEM.Model like "20B7%" or SMS_G_System_COMPUTER_SYSTEM.Model like "20B6%"
```

50. All Mac Systems

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where
SMS_R_System.OperatingSystemNameandVersion like "Mac%"
```

51. All SCCM | Console

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_ADD_REMOVE_PROGRAMS on SMS_G_System_ADD_REMOVE_PROGRAMS.ResourceID =
SMS_R_System.ResourceId where SMS_G_System_ADD_REMOVE_PROGRAMS.DisplayName like '%Configuration Manager
Console%'
```

52.All SCCM | Distribution Points

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where SMS_R_System.SystemRoles = 'SMS Distribution Point'
```

53.All SCCM | Site Servers

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where SMS_R_System.SystemRoles = 'SMS Site Server'
```

54.All SCCM | Site Systems

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where SMS_R_System.SystemRoles = 'SMS Site System'
```

55. All Servers | All

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where SMS_R_System.OperatingSystemNameandVersion like 'Microsoft Windows NT%Server%'
```

56. All Servers | Physical

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where SMS_R_System.ResourceId not in (select SMS_R_SYSTEM.ResourceID from SMS_R_System inner join SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceId = SMS_R_System.ResourceId where SMS_R_System.IsVirtualMachine = 'True') and SMS_R_System.OperatingSystemNameandVersion like 'Microsoft Windows NT%Server%'
```

57.All Servers | Virtual

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where SMS_R_System.IsVirtualMachine = 'True' and SMS_R_System.OperatingSystemNameandVersion like 'Microsoft Windows NT%Server%'
```

58.All Servers | Windows 2003 and 2003 R2

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where OperatingSystemNameandVersion like '%Server 5.2%'
```

59.All Servers | Windows 2008 and 2008 R2

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where OperatingSystemNameandVersion like '%Server 6.0%' or OperatingSystemNameandVersion like '%Server 6.1%'
```

60. All Servers | Windows 2012 and 2012 R2

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where
OperatingSystemNameandVersion like '%Server 6.2%' or OperatingSystemNameandVersion like '%Server 6.3%'
```

61. All PCs with Absolute Manage Client Installed

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_INSTALLED_SOFTWARE on SMS_G_System_INSTALLED_SOFTWARE.ResourceID =
SMS_R_System.ResourceID where SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like
"%Absolute%Manage%Agent%"
```

62. All PCs without Adobe CatalogExtension 3.0.10 Installed

```
select SYS.ResourceID,SYS.ResourceType,SYS.Name,SYS.SMSUniqueIdentifier,SYS.ResourceDomainORWorkgroup,SYS.Client
from SMS_R_System as Sys where Sys.ResourceID not in (select SMS_R_System.ResourceID from SMS_R_System inner join
SMS_G_System_INSTALLED_SOFTWARE on SMS_G_System_INSTALLED_SOFTWARE.ResourceID =
SMS_R_System.ResourceID where SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like "%CatalogExtension%" and
SMS_G_System_INSTALLED_SOFTWARE.ProductVersion = "3.0.10")
```

63. All PCs without Adobe Illustrator 19.2.1 Installed

```
select SYS.ResourceID,SYS.ResourceType,SYS.Name,SYS.SMSUniqueIdentifier,SYS.ResourceDomainORWorkgroup,SYS.Client
from SMS_R_System as Sys where Sys.ResourceID not in (select SMS_R_System.ResourceID from SMS_R_System inner join
SMS_G_System_INSTALLED_SOFTWARE on SMS_G_System_INSTALLED_SOFTWARE.ResourceID =
SMS_R_System.ResourceID where SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like "%Adobe Illustrator 19.2.1%")
```

64. All PCs without Cisco AnyconnectSecureMobilityClient 4.2.02075 Installed

```
select SYS.ResourceID,SYS.ResourceType,SYS.Name,SYS.SMSUniqueIdentifier,SYS.ResourceDomainORWorkgroup,SYS.Client
from SMS_R_System as Sys where Sys.ResourceID not in (select SMS_R_System.ResourceID from SMS_R_System inner join
SMS_G_System_INSTALLED_SOFTWARE on SMS_G_System_INSTALLED_SOFTWARE.ResourceID =
SMS_R_System.ResourceID where SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like "Cisco%Anyconnect%Secure
Mobility Client%" and SMS_G_System_INSTALLED_SOFTWARE.ProductVersion < "4.2.02075")
```

65. All PCs without Computrace Installed

```
select SYS.ResourceID,SYS.ResourceType,SYS.Name,SYS.SMSUniqueIdentifier,SYS.ResourceDomainORWorkgroup,SYS.Client
from SMS_R_System as Sys where Sys.ResourceID not in (select SMS_R_System.ResourceID from SMS_R_System inner join
SMS_G_System_INSTALLED_SOFTWARE on SMS_G_System_INSTALLED_SOFTWARE.ResourceID =
SMS_R_System.ResourceID where SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like "%Computrace%")
```

66. All PCs without Symantec EndpointProtection 12.1.6867.6400 Installed

```
select SYS.ResourceID,SYS.ResourceType,SYS.Name,SYS.SMSUniqueIdentifier,SYS.ResourceDomainORWorkgroup,SYS.Client
from SMS_R_System as Sys where Sys.ResourceID not in (select SMS_R_System.ResourceID from SMS_R_System inner join
SMS_G_System_INSTALLED_SOFTWARE on SMS_G_System_INSTALLED_SOFTWARE.ResourceID =
SMS_R_System.ResourceID where SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like "%Symantec Endpoint
Protection%" and SMS_G_System_INSTALLED_SOFTWARE.ProductVersion like "12.1.6867.6400")
```

67. All PCs without SCCM Client CU3 Installed

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where ResourceID not in (select
ResourceID from SMS_R_System where ClientVersion >= "5.00.8239.1403")
```

68. All PCs without Microsoft OneDrive 17.3.6386.0412 Installed

```
select SYS.ResourceID, SYS.ResourceType, SYS.Name, SYS.SMSUniqueIdentifier, SYS.ResourceDomainORWorkgroup, SYS.Client
from SMS_R_System as Sys where Sys.ResourceId not in (select SMS_R_System.ResourceId from SMS_R_System inner join
SMS_G_System_INSTALLED_SOFTWARE on SMS_G_System_INSTALLED_SOFTWARE.ResourceID =
SMS_R_System.ResourceId where SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like "%Microsoft%OneDrive%" and
SMS_G_System_INSTALLED_SOFTWARE.ProductVersion = "17.3.6386.0412")
```

69. All PCs without Microsoft Silverlight 5.1.41212.0 Installed

```
select SYS.ResourceID, SYS.ResourceType, SYS.Name, SYS.SMSUniqueIdentifier, SYS.ResourceDomainORWorkgroup, SYS.Client
from SMS_R_System as Sys where Sys.ResourceId not in (select SMS_R_System.ResourceId from SMS_R_System inner join
SMS_G_System_INSTALLED_SOFTWARE on SMS_G_System_INSTALLED_SOFTWARE.ResourceID =
SMS_R_System.ResourceId where SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like "%Microsoft%Silverlight%" and
SMS_G_System_INSTALLED_SOFTWARE.ProductVersion < "5.1.4%")
```

70. All PCs without Bit9 Agent 7.2.2.1119 Installed

```
select SYS.ResourceID, SYS.ResourceType, SYS.Name, SYS.SMSUniqueIdentifier, SYS.ResourceDomainORWorkgroup, SYS.Client
from SMS_R_System as Sys where Sys.ResourceId not in (select SMS_R_SYSTEM.ResourceID from SMS_R_System inner join
SMS_G_System_INSTALLED_SOFTWARE on SMS_G_System_INSTALLED_SOFTWARE.ResourceID =
SMS_R_System.ResourceId where SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like "%Bit9%Agent%")
```

71. All Assigned Systems

```
select
SMS_R_SYSTEM.ResourceID, SMS_R_SYSTEM.ResourceType, SMS_R_SYSTEM.Name, SMS_R_SYSTEM.SMSUniqueIdentifier, SM
S_R_SYSTEM.ResourceDomainORWorkgroup, SMS_R_SYSTEM.Client from SMS_R_System where ResourceId in (select
SMS_R_System.ResourceId from SMS_R_System where SMSAssignedSites is not NULL)
```

72. All Not Assigned Systems

```
select
SMS_R_SYSTEM.ResourceID, SMS_R_SYSTEM.ResourceType, SMS_R_SYSTEM.Name, SMS_R_SYSTEM.SMSUniqueIdentifier, SM
S_R_SYSTEM.ResourceDomainORWorkgroup, SMS_R_SYSTEM.Client from SMS_R_System where ResourceId not in (select
SMS_R_System.ResourceId from SMS_R_System where SMSAssignedSites is not NULL)
```

73. All Client Systems

```
select
SMS_R_SYSTEM.ResourceID, SMS_R_SYSTEM.ResourceType, SMS_R_SYSTEM.Name, SMS_R_SYSTEM.SMSUniqueIdentifier, SM
S_R_SYSTEM.ResourceDomainORWorkgroup, SMS_R_SYSTEM.Client from SMS_R_System where ResourceId in (SELECT
SMS_R_System.ResourceID FROM SMS_R_System where Client = 1)
```

74. All No Client Systems

```
select
SMS_R_SYSTEM.ResourceID, SMS_R_SYSTEM.ResourceType, SMS_R_SYSTEM.Name, SMS_R_SYSTEM.SMSUniqueIdentifier, SM
S_R_SYSTEM.ResourceDomainORWorkgroup, SMS_R_SYSTEM.Client from SMS_R_System where ResourceId not in (SELECT
SMS_R_System.ResourceID FROM SMS_R_System where Client = 1)
```

75. All Not Obsolete Systems

```
select
SMS_R_SYSTEM.ResourceID, SMS_R_SYSTEM.ResourceType, SMS_R_SYSTEM.Name, SMS_R_SYSTEM.SMSUniqueIdentifier, SM
S_R_SYSTEM.ResourceDomainORWorkgroup, SMS_R_SYSTEM.Client from SMS_R_System where ResourceId not in (select
SMS_R_System.ResourceID from SMS_R_System where Obsolete = 1)
```

76. All Obsolete Systems

```
select
SMS_R_SYSTEM.ResourceID, SMS_R_SYSTEM.ResourceType, SMS_R_SYSTEM.Name, SMS_R_SYSTEM.SMSUniqueIdentifier, SM
S_R_SYSTEM.ResourceDomainORWorkgroup, SMS_R_SYSTEM.Client from SMS_R_System where ResourceId in (select
SMS_R_System.ResourceID from SMS_R_System where Obsolete = 1)
```

77.All Approved Systems

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_CM_RES_COLL_SMS00001 on SMS_CM_RES_COLL_SMS00001.ResourceId = SMS_R_System.ResourceId where
SMS_CM_RES_COLL_SMS00001.IsApproved <> '0'
```

78.All Not Approved Systems

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_CM_RES_COLL_SMS00001 on SMS_CM_RES_COLL_SMS00001.ResourceId = SMS_R_System.ResourceId where
SMS_CM_RES_COLL_SMS00001.IsApproved <> '1'
```

79.All Active Systems

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_CH_ClientSummary on SMS_G_System_CH_ClientSummary.ResourceId = SMS_R_System.ResourceId where
SMS_G_System_CH_ClientSummary.ClientActiveStatus = 1 and SMS_R_System.Client = 1 and SMS_R_System.Obsolete = 0 and
SMS_R_System.Active = 1
```

80.All Inactive Systems

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_CH_ClientSummary on SMS_G_System_CH_ClientSummary.ResourceId = SMS_R_System.ResourceId where
SMS_G_System_CH_ClientSummary.ClientActiveStatus = 0 and SMS_R_System.Client = 1 and SMS_R_System.Obsolete = 0
```

81.All PCs Heartbeat DDR Current within 23 Days

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where ResourceId in (select
ResourceId from SMS_R_System where AgentName in ("Heartbeat Discovery") and DATEDIFF(day,AgentTime,GetDate())<23)
```

82.All PCs Heartbeat DDR Not Current within 23 Days

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where ResourceId not in (select
ResourceId from SMS_R_System where AgentName in ("Heartbeat Discovery") and DATEDIFF(day,AgentTime,GetDate())<23)
```

83.All PCs Hardware Inventory Current within 23 Days

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where ResourceId in (select
SMS_R_System.ResourceID from SMS_R_System inner join SMS_G_System_WORKSTATION_STATUS on
SMS_G_System_WORKSTATION_STATUS.ResourceID = SMS_R_System.ResourceId where
DATEDIFF(dd,SMS_G_System_WORKSTATION_STATUS.LastHardwareScan,GetDate()) < 23)
```

84.All PCs Hardware Inventory Not Current within 23 Days

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where ResourceId not in (select
SMS_R_System.ResourceID from SMS_R_System inner join SMS_G_System_WORKSTATION_STATUS on
SMS_G_System_WORKSTATION_STATUS.ResourceID = SMS_R_System.ResourceId where
DATEDIFF(dd,SMS_G_System_WORKSTATION_STATUS.LastHardwareScan,GetDate()) < 23)
```

85. All PCs Software Inventory Current within 23 Days

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where ResourceId in (select
ResourceID from SMS_R_System inner join SMS_G_System_LastSoftwareScan on SMS_G_System_LastSoftwareScan.ResourceID =
SMS_R_System.ResourceId where DATEDIFF(dd,SMS_G_System_LastSoftwareScan.LastScanDate,GetDate()) < 23 )
```

86. All PCs Software Inventory Not Current within 23 Days

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where ResourceId not in (select
ResourceID from SMS_R_System inner join SMS_G_System_LastSoftwareScan on SMS_G_System_LastSoftwareScan.ResourceID =
SMS_R_System.ResourceId where DATEDIFF(dd,SMS_G_System_LastSoftwareScan.LastScanDate,GetDate()) < 23 )
```

87. All PCs Physical Memory Current Reported

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where ResourceId in (select
SMS_R_System.ResourceID from SMS_R_System inner join SMS_G_System_X86_PC_MEMORY on
SMS_G_System_X86_PC_MEMORY.ResourceID = SMS_R_System.ResourceId where
SMS_G_System_X86_PC_MEMORY.TotalPhysicalMemory is not NULL )
```

88. All PCs Physical Memory Not Current Reported

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where ResourceId not in (select
SMS_R_System.ResourceID from SMS_R_System inner join SMS_G_System_X86_PC_MEMORY on
SMS_G_System_X86_PC_MEMORY.ResourceID = SMS_R_System.ResourceId where
SMS_G_System_X86_PC_MEMORY.TotalPhysicalMemory is not NULL )
```

89. All PCs SCCM 2012 R2 SP1 is Installed

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where ResourceId in (select
ResourceID from SMS_R_System where ClientVersion >= "5.00.8239.1000")
```

90. All PCs SCCM 2012 R2 SP1 is Not Installed

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SM
S_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System where ResourceId not in (select
ResourceID from SMS_R_System where ClientVersion >= "5.00.8239.1000")
```

91. All PCs with Office 365 2013 Application Installed

```
select SMS_R_System.ResourceId from SMS_R_System inner join SMS_G_System_INSTALLED_SOFTWARE on
SMS_G_System_INSTALLED_SOFTWARE.ResourceID = SMS_R_System.ResourceId where
SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like "Microsoft Office 365 ProPlus%" and
SMS_G_System_INSTALLED_SOFTWARE.ProductVersion like "15.0%"
```

92. All PCs without Office 365 2013 Application Installed

```
select Sys.ResourceId, Sys.ResourceType, Sys.Name, Sys.SMSUniqueIdentifier, Sys.ResourceDomainORWorkgroup, Sys.Client from
SMS_R_System as Sys where Sys.ResourceId not in (select SMS_R_SYSTEM.ResourceID from SMS_R_System inner join
SMS_G_System_INSTALLED_SOFTWARE on SMS_G_System_INSTALLED_SOFTWARE.ResourceID =
SMS_R_System.ResourceId where SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like "Microsoft Office 365
ProPlus%" and SMS_G_System_INSTALLED_SOFTWARE.ProductVersion like "15.0%")
```

93. All PCs offline 60+ Days

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceID = SMS_R_System.ResourceID
where SMS_G_System_COMPUTER_SYSTEM.Name in (select SMS_R_System.Name from SMS_R_System inner join
SMS_G_System_WORKSTATION_STATUS on SMS_G_System_WORKSTATION_STATUS.ResourceID =
SMS_R_System.ResourceID where SMS_G_System_WORKSTATION_STATUS.LastHardwareScan <= DateAdd(dd,-60,GetDate()))
```

94. All PCs with a heartbeat within last 30 days

```
select SMS_R_System.ResourceID, SMS_R_System.ResourceType, SMS_R_System.Name, SMS_R_System.SMSUniqueIdentifier,
SMS_R_System.ResourceDomainORWorkgroup, SMS_R_System.Client, SMS_R_System.MACAddresses from SMS_R_System
inner join SMS_G_System_COMPUTER_SYSTEM on SMS_G_System_COMPUTER_SYSTEM.ResourceID =
SMS_R_System.ResourceID where SMS_G_System_COMPUTER_SYSTEM.Name in (select SMS_R_System.Name from
SMS_R_System inner join SMS_G_System_WORKSTATION_STATUS on SMS_G_System_WORKSTATION_STATUS.ResourceID =
SMS_R_System.ResourceID where SMS_G_System_WORKSTATION_STATUS.LastHardwareScan >= DateAdd(dd,-30,GetDate()))
and SMS_R_System.OperatingSystemNameandVersion like "% Workstation%"
```

95. All PCs without a heartbeat within last 60 days

```
select SMS_R_System.NetbiosName, SMS_G_System_SYSTEM_CONSOLE_USAGE.TopConsoleUser,
SMS_R_System.ADSiteName from SMS_R_System inner join SMS_G_System_SYSTEM_CONSOLE_USAGE on
SMS_G_System_SYSTEM_CONSOLE_USAGE.ResourceID = SMS_R_System.ResourceID where SMS_R_System.Name in (select
Name from SMS_R_System where ((DATEDIFF(day, SMS_R_SYSTEM.AgentTime, getdate()) >=60) and AgentName = "Heartbeat
Discovery")) order by SMS_R_System.ADSiteName
```

96. All PCs with Adobe Creative Cloud Design Standard 2015 Application Installed

```
select distinct SMS_R_System.ResourceID, SMS_R_System.ResourceType, SMS_R_System.Name,
SMS_R_System.SMSUniqueIdentifier, SMS_R_System.ResourceDomainORWorkgroup, SMS_R_System.Client from SMS_R_System
inner join SMS_G_System_INSTALLED_SOFTWARE on SMS_G_System_INSTALLED_SOFTWARE.ResourceID =
SMS_R_System.ResourceID where SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like "%CC-2015 Design Standard
x64%"
```

97. All PCs with BitLocker Encrypted

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_ENCRYPTABLE_VOLUME on SMS_G_System_ENCRYPTABLE_VOLUME.ResourceID =
SMS_R_System.ResourceID where SMS_G_System_ENCRYPTABLE_VOLUME.ProtectionStatus = 1
```

98. All PCs with Cisco AnyconnectSecureMobilityClient 4.2.02075 Installed

```
select SMS_R_System.ResourceID from SMS_R_System inner join SMS_G_System_INSTALLED_SOFTWARE on
SMS_G_System_INSTALLED_SOFTWARE.ResourceID = SMS_R_System.ResourceID where
SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like "Cisco%Anyconnect%Secure Mobility Client%" and
SMS_G_System_INSTALLED_SOFTWARE.ProductVersion < "4.2.02075"
```

99. All PCs with SEP Application Installed

```
select
SMS_R_SYSTEM.ResourceID,SMS_R_SYSTEM.ResourceType,SMS_R_SYSTEM.Name,SMS_R_SYSTEM.SMSUniqueIdentifier,SMS_R_SYSTEM.ResourceDomainORWorkgroup,SMS_R_SYSTEM.Client from SMS_R_System inner join
SMS_G_System_INSTALLED_SOFTWARE on SMS_G_System_INSTALLED_SOFTWARE.ResourceID =
SMS_R_System.ResourceID where SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like "%Symantec Endpoint
Protection%"
```

100. All PCs without SEP Application Installed

```
select Sys.ResourceId, Sys.ResourceType, Sys.Name, Sys.SMSUniqueIdentifier, Sys.ResourceDomainORWorkgroup, Sys.Client from  
SMS_R_System as Sys where Sys.ResourceId not in (select SMS_R_SYSTEM.ResourceID from SMS_R_System inner join  
SMS_G_System_INSTALLED_SOFTWARE on SMS_G_System_INSTALLED_SOFTWARE.ResourceID =  
SMS_R_System.ResourceId where SMS_G_System_INSTALLED_SOFTWARE.ARPDisplayName like "%Symantec Endpoint  
Protection%")
```