SAP HANA-Optimized BI Content

Generated on: 2026-10-23 10:28:00 GMT+0000

BI Content 7.57 | 7.57 SP33

Public

Original content: https://help.sap.com/docs/BI_CONTENT_757/c644067f89c74ff38da2b9f765be6cce?locale=en-US&state=PRODUCTION&version=7.57.33

Warning

This document has been generated from SAP Help Portal and is an incomplete version of the official SAP product documentation. The information included in custom documentation may not reflect the arrangement of topics in SAP Help Portal, and may be missing important aspects and/or correlations to other topics. For this reason, it is not for production use.

For more information, please visit https://help.sap.com/docs/disclaimer.

SAP HANA-Optimized BI Content

Use

SAP HANA-optimized BI Content combines enterprise data warehouse capabilities of SAP NetWeaver BW running on SAP HANA with explorative and interactive real-time analytics using the SAP HANA in-memory database. The new data model follows the recommendations for the layered scalable architecture LSA++, which is optimized for BW running on SAP HANA.

For more information about the layered scalable architecture optimized for BW on HANA, see **http://help.sap.com SAP NetWeaver SAP NetWeaver Platform Application Help SAP NetWeaver Library: Funtion-Oriented View Business Warehouse Data Warehousing The Data Warehouse Concept Layer Architecture of a Data Warehouses with SAP HANA Database (LSA++)**.

Prerequisites

Business Function/Switch

- To use SAP HANA-optimized BI content, you need to run your BW system on a SAP HANA database.
- To activate SAP HANA-optimized BI content, you need to turn on the Business Function “SAP HANA-optimized BW Content” (`/IMO/BWCONTENT`) in transaction SFW5.

  For detailed information about the Business Function “SAP HANA-optimized BI Content” (`/IMO/BWCONTENT`) see SAP HANA-optimized BW Content (Reversible)

  For more information about activating Business Functions, go to the SAP Help Portal at http://help.sap.com and search for **Switching On Business Functions**.

Note

SAP strongly recommends activating the Enterprise Business Function “SAP HANA-optimized BW Content” (`/IMO/BWCONTENT`) instead of the formerly delivered Industry Business Function “SAP HANA-optimized BW Content” (`/IMO/BW_CONTENT`). Therefore please apply BI CONTENT 7.37 SP16, 7.47 SP16, 7.57 SP9 or higher before activation of the Business Function.

The Enterprise Business Function “SAP HANA-optimized BW Content” (`/IMO/BWCONTENT`) replaces the formerly delivered Industry Business Function “SAP HANA-optimized BW Content” (`/IMO/BW_CONTENT`), as only one Industry Business Function can be active. For further details please see SAP Note 2257232.

Source System ID

Before you load data into the BW DataStore objects for SAP HANA-optimized content, you need to maintain the source system ID.

The two-digit source system ID (`0GN_R3_SSY`) is added to the BW DataStore objects for SAP HANA-optimized content. It is used to fill source system-dependent objects, such as consolidated InfoObjects (for example, `0GN_CUSTOM`), and allows you to determine the system from which the data was loaded.

Procedure

1. Open the Data Warehousing Workbench and choose **RSA1 Tools Asgnmnt of Srce Syst. to Srce Syst. ID**.
2. Enter the relevant values in the **Source System ID** column.

You can also use transaction SE16 to check that the two-digit source system ID has been defined in table RSSOURSYSTEM for your system and landscape.

Structure

LSA++ Aligned Data Model

The SAP HANA-optimized BI Content follows the LSA++ recommendations. The data model currently provides the following features:

- Three-layer approach to the enterprise data warehouse
  - The data is acquired in the **open operational data store layer**. The PSA serves as the historical data foundation. No transformations or aggregations are defined in this layer.

    > **Note**
    > BI Content DSOs are provided for this layer if the data is loaded further into multiple EDW Core Layer DSOs. The structure of the open operational data store layer DSOs reflects the structure of the connected DataSources.

  - The data is then harmonized and transformed to the **EDW core layer**. The DataSource and the DSOs in the EDW core layer are connected by an InfoSource. No transformation logic is applied between the open operational data store layer and the InfoSource. All harmonization and transformation logic is applied between the InfoSource(s) and the EDW core DSO(s).

    > **Note**
    > You can connect multiple sources of the open operational data store layer with the SAP HANA-optimized BI Content data flow without losing the predefined EDW transformations. This can be helpful if you need to connect multiple source systems.

    InfoCubes are no longer required for SAP HANA-optimized BI content. They are replaced by in-memory-optimized DataStore objects, which can be used for reporting.

  - A corporate memory layer is provided to contain the complete history of the loaded data. It is used as a source for reconstructions without the need to access the sources again. The corporate memory is filled independently of the EDW core layer's update.

  - A **virtual data mart layer** is used for reporting. InfoProviders that reside in this layer do not contain any data. Instead, they describe which data is accessed, and how it is displayed semantically to the end user.

    CompositeProviders are used as InfoProviders in this virtual data mart layer and access the data from DataStore objects. Depending on the use case, also data from SAP HANA information models is read and might be mixed with staged data in BW.

    All BI Content BEx Queries are deployed on top of the CompositeProviders.

- Date of last update

  The InfoObject **Last Update Date** 0UPD_DATE is available for all DataStore objects. You can use this information to identify the last update date for any particular data record. It supports the data load process, and enables selective lookups or rebuilds.

- Naming conventions

  The following naming conventions for the new SAP HANA-optimized Business Content are used throughout the data model:

Layer	InfoObject	Technical Name	Example
Open operational data store layer	DataStore object	/IMO/O_<*InfoArea*>nn	/IMO/O_PUR11
EDW core layer	InfoSource	/IMO/<*InfoArea*>_ISnn	/IMO/PUR_IS11 **Note** The long description of the InfoSource contains the technical name of the corresponding DataSource. For example: **MM-PUR: Purchase Data Item (2LIS_02_ITM)**
	DataStore object	/IMO/D_<*InfoArea*>nn	/IMO/D_PUR11
Corporate memory layer	DataStore object	/IMO/CM<*InfoArea*>nn	/IMO/CMPUR11
Virtual data mart layer	CompositeProvider	/IMO/V_<*InfoArea*>nn	/IMO/V_PUR01

Note

Product Cost Forecast and Simulation is not using the new BW artifacts (CompositeProvider, DataStore object (advanced)) yet.

Consolidated InfoObjects

The SAP HANA-optimized BI Content provides consolidated InfoObjects in its data model, where applicable.

SAP BW uses consolidated InfoObjects to integrate and harmonize information from different SAP components in a standardized (consolidated) data model (for example, 0MATERIAL from SAP ERP, and 0CRM_PROD from SAP CRM).

The consolidated InfoObjects can store information about duplicates in the master data, and therefore enable consolidated reporting using a group ID.

Note

If you use multiple source systems, you need to adapt the delivered business content to your specific system landscape setup (for example, by adding the source system ID to the key of each BW DSO).

For more information about consolidated InfoObjects, go to the SAP Help Portal at http://help.sap.com and search for **Consolidated InfoObjects for BP, Product and Product Category**.

More Information

For documentation updates relating to SAP HANA-optimized BI content, see SAP Note 1817520: **Collective Note: SAP HANA-Optimized BI Content**.