

# Rajalakshmi Engineering College

Name: subhashri bala  
Email: 240801337@rajalakshmi.edu.in  
Roll no: 2116240801337  
Phone: 7418182298  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_COD\_Question 2

Attempt : 2  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Arun is learning about data structures and algorithms. He needs your help in solving a specific problem related to a singly linked list.

Your task is to implement a program to delete a node at a given position. If the position is valid, the program should perform the deletion; otherwise, it should display an appropriate message.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of elements in the linked list.

The second line consists of N space-separated elements of the linked list.

The third line consists of an integer x, representing the position to delete.

Position starts from 1.

### **Output Format**

The output prints space-separated integers, representing the updated linked list after deleting the element at the given position.

If the position is not valid, print "Invalid position. Deletion not possible."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

8 2 3 1 7

2

Output: 8 3 1 7

### **Answer**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
void insert(int);
```

```
void display_List();
```

```
void deleteNode(int);
```

```
struct node {
```

```
    int data;
```

```
    struct node* next;
```

```
} *head = NULL, *tail = NULL;
```

```
void insert(int value)
```

```
{
```

```
    struct node* newNode = (struct node*)malloc(sizeof(struct node));
```

```
    newNode->data = value;
```

```
    newNode->next = NULL;
```

```
    if (head == NULL)
```

```
    {
```

```
        head = newNode;
```

```
    }
```

```

else
{
    struct node* temp = head;
    while (temp->next != NULL)
    {
        temp = temp->next;
    }
    temp->next = newNode;
}
}
void display_List()
{
    struct node* temp = head;
    if(temp == NULL)
    {
        printf("\n");
        return;
    }
    while(temp != NULL)
    {
        printf("%d ",temp->data);
        if(temp->next != NULL)
        {
            printf(" ");
        }
        temp = temp->next;
    }
    printf("\n");
}
void deleteNode(int position)
{
    if (head == NULL)
    {
        printf("Invalid position. Deletion not possible.\n");
        return;
    }
    struct node* temp = head;
    if (position == 1)
    {
        head = temp->next;
        free(temp);
        display_List();
    }
}

```

```

        return;
    }
    for(int i=1; temp != NULL && i < position - 1; i++)
    {
        temp = temp->next;
    }
    if(temp == NULL || temp->next == NULL)
    {
        printf("Invalid position. Deletion not possible.\n");
        return;
    }
    struct node* next = temp->next->next;
    free(temp->next);
    temp->next = next;
    display_List();
}

int main() {
    int num_elements, element, pos_to_delete;

    scanf("%d", &num_elements);

    for (int i = 0; i < num_elements; i++) {
        scanf("%d", &element);
        insert(element);
    }

    scanf("%d", &pos_to_delete);

    deleteNode(pos_to_delete);

    return 0;
}

```

**Status :** Correct

**Marks :** 10/10