

# Thresholding Bandits with Augmented UCB

Subhojyoti Mukherjee

Roll No: CS15S300

Guide: Dr. Balaraman Ravindran

Co-Guide: Dr. Nandan Sudarsanam

IIT Madras

July 14, 2017

# Overview

- 1 Stochastic Multi-Armed Bandit Problem
- 2 Problem Definition
- 3 Contribution
- 4 Previous Works
- 5 AugUCB
- 6 Theoretical Analysis
- 7 Experiments
- 8 Conclusion
- 9 References

# Stochastic Multi-Armed Bandit Problem (SMAB)

- The thresholding bandit problem falls under the broad area of stochastic multi-armed bandit problem.

# Stochastic Multi-Armed Bandit Problem (SMAB)

- The thresholding bandit problem falls under the broad area of stochastic multi-armed bandit problem.
- A finite set of actions or arms belonging to set  $A$  such that  $|A| = K$ .

# Stochastic Multi-Armed Bandit Problem (SMAB)

- The thresholding bandit problem falls under the broad area of stochastic multi-armed bandit problem.
- A finite set of actions or arms belonging to set  $A$  such that  $|A| = K$ .
- The rewards for each of the arms are identical and independent random variables drawn from distribution specific to the arm.

# Stochastic Multi-Armed Bandit Problem (SMAB)

- The thresholding bandit problem falls under the broad area of stochastic multi-armed bandit problem.
- A finite set of actions or arms belonging to set  $A$  such that  $|A| = K$ .
- The rewards for each of the arms are identical and independent random variables drawn from distribution specific to the arm.
- The learner does not know the mean  $r_i, \forall i \in A$  of the distribution or the variance  $\sigma_i^2$ .

# Stochastic Multi-Armed Bandit Problem (SMAB)

- The distributions for each of the arms are fixed throughout the time horizon denoted by  $T$ .

# Stochastic Multi-Armed Bandit Problem (SMAB)

- The distributions for each of the arms are fixed throughout the time horizon denoted by  $T$ .
- The estimated reward  $\hat{r}_i = \frac{1}{n_i} \sum_{z=1}^{n_i} X_{i,z}$ .



# Stochastic Multi-Armed Bandit Problem (SMAB)

- The distributions for each of the arms are fixed throughout the time horizon denoted by  $T$ .
- The estimated reward  $\hat{r}_i = \frac{1}{n_i} \sum_{z=1}^{n_i} X_{i,z}$ .
- Due to the uncertainty in  $\hat{r}_i$  we have carefully conduct exploration.

# Problem Definition of TBP

- Primary aim: Identify the arms whose mean of the reward distribution ( $r_i$ ) is above a particular threshold  $\tau$  given as input.

# Problem Definition of TBP

- Primary aim: Identify the arms whose mean of the reward distribution ( $r_i$ ) is above a particular threshold  $\tau$  given as input.
- Condition: This has to be achieved within  $T$  timesteps of exploration and this is termed as a fixed-budget problem.

# Problem Definition of TBP

- Primary aim: Identify the arms whose mean of the reward distribution ( $r_i$ ) is above a particular threshold  $\tau$  given as input.
- Condition: This has to be achieved within  $T$  timesteps of exploration and this is termed as a fixed-budget problem.
- At the end of the given  $T$  timesteps the learner must recommend a set of arms which (according to it) are the arms having reward mean above  $\tau$ .

# Problem Definition of TBP

- We define the set  $S_\tau = \{i \in \mathcal{A} : r_i \geq \tau\}$ .

# Problem Definition of TBP

- We define the set  $S_\tau = \{i \in \mathcal{A} : r_i \geq \tau\}$ .
- $S_\tau^c$  denote the complement of  $S_\tau$ , i.e.,  $S_\tau^c = \{i \in \mathcal{A} : r_i < \tau\}$ .

# Problem Definition of TBP

- We define the set  $S_\tau = \{i \in \mathcal{A} : r_i \geq \tau\}$ .
- $S_\tau^c$  denote the complement of  $S_\tau$ , i.e.,  $S_\tau^c = \{i \in \mathcal{A} : r_i < \tau\}$ .
- Let  $\hat{S}_\tau$  denote the recommendation of a learning algorithm after  $T$  time units of exploration, while  $\hat{S}_\tau^c$  denotes its complement.

# Problem Definition of TBP

- We define the set  $S_\tau = \{i \in \mathcal{A} : r_i \geq \tau\}$ .
- $S_\tau^c$  denote the complement of  $S_\tau$ , i.e.,  $S_\tau^c = \{i \in \mathcal{A} : r_i < \tau\}$ .
- Let  $\hat{S}_\tau$  denote the recommendation of a learning algorithm after  $T$  time units of exploration, while  $\hat{S}_\tau^c$  denotes its complement.
- The goal of the learning agent is to minimize the expected loss:

$$\mathbb{E}[\mathcal{L}(T)] = \mathbb{P}\left( \underbrace{\{S_\tau \cap \hat{S}_\tau^c \neq \emptyset\}}_{\text{Rejected good arms}} \cup \underbrace{\{\hat{S}_\tau \cap S_\tau^c \neq \emptyset\}}_{\text{Accepted bad arms}} \right)$$



# Challenges in the TBP Settings

- Closer arms' mean to the threshold  $\Rightarrow$  harder is to discriminate.

# Challenges in the TBP Settings

- Closer arms' mean to the threshold  $\Rightarrow$  harder is to discriminate.
- Lesser the budget  $\Rightarrow$  harder the problem.

# Challenges in the TBP Settings

- Closer arms' mean to the threshold  $\Rightarrow$  harder is to discriminate.
- Lesser the budget  $\Rightarrow$  harder the problem.
- Higher variance of the arms'  $\Rightarrow$  harder the problem.

- Selecting the best channels (out of several existing channels) for mobile communications in a very short duration whose qualities are above an acceptable threshold (see [Audibert and Bubeck(2010)]).

- Selecting the best channels (out of several existing channels) for mobile communications in a very short duration whose qualities are above an acceptable threshold (see [Audibert and Bubeck(2010)]).
- Selecting a small set of best workers (out of a very large pool of workers) whose productivity is above a threshold.

- Selecting the best channels (out of several existing channels) for mobile communications in a very short duration whose qualities are above an acceptable threshold (see [Audibert and Bubeck(2010)]).
- Selecting a small set of best workers (out of a very large pool of workers) whose productivity is above a threshold.
- In anomaly detection and classification (see Locatelli et al. (2016)).

- We propose the Augmented UCB (AugUCB) [Mukherjee et al. (2017)] algorithm for the fixed-budget TBP setting.

# Contributions

- We propose the Augmented UCB (AugUCB) [Mukherjee et al. (2017)] algorithm for the fixed-budget TBP setting.
- AugUCB takes into account the empirical variances of the arms along with mean estimates.



# Contributions

- We propose the Augmented UCB (AugUCB) [Mukherjee et al. (2017)] algorithm for the fixed-budget TBP setting.
- AugUCB takes into account the empirical variances of the arms along with mean estimates.
- It is the first variance-based arm elimination algorithm for the considered TBP settings.

- We propose the Augmented UCB (AugUCB) [Mukherjee et al. (2017)] algorithm for the fixed-budget TBP setting.
- AugUCB takes into account the empirical variances of the arms along with mean estimates.
- It is the first variance-based arm elimination algorithm for the considered TBP settings.
- It addresses an open problem discussed in [Auer and Ortner(2010)] of designing an algorithm that can eliminate arms based on variance estimates.

- We propose the Augmented UCB (AugUCB) [Mukherjee et al. (2017)] algorithm for the fixed-budget TBP setting.
- AugUCB takes into account the empirical variances of the arms along with mean estimates.
- It is the first variance-based arm elimination algorithm for the considered TBP settings.
- It addresses an open problem discussed in [Auer and Ortner(2010)] of designing an algorithm that can eliminate arms based on variance estimates.
- We also define a new problem complexity which uses empirical variance estimates along with arm's mean for giving the theoretical bound.

# The Upper Confidence Bound (UCB) Approach

- Since there is an initial uncertainty in the estimated mean ( $\hat{r}_i$ ) introduce a confidence interval term  $c_i$ .



# The Upper Confidence Bound (UCB) Approach

- Since there is an initial uncertainty in the estimated mean ( $\hat{r}_i$ ) introduce a confidence interval term  $c_i$ .
- $c_i$  ensures that the arm  $i$  is properly explored and is gradually reduced with time as one pulls the arm  $i$  more.


# The Upper Confidence Bound (UCB) Approach

- Since there is an initial uncertainty in the estimated mean ( $\hat{r}_i$ ) introduce a confidence interval term  $c_i$ .
- $c_i$  ensures that the arm  $i$  is properly explored and is gradually reduced with time as one pulls the arm  $i$  more.
- At every timestep pull arm that has the maximum value of  $\hat{r}_i + c_i$  and this will ensure that proper exploration is done.

# The UCB Approach




# Approach of UCB-Improved (UCB-Imp)





# Intuition of UCB-Improved (UCB-Imp)

Arm Elimination:  $\hat{r}_i + c_m < \hat{r}_{max} - c_m$



# APT Approach

- The Anytime Parameter Free (APT) [Locatelli et al. (2016)] algorithm was proposed for TBP setting in ICML 2016.

# APT Approach

- The Anytime Parameter Free (APT) [Locatelli et al. (2016)] algorithm was proposed for TBP setting in ICML 2016.
- This algorithm uses only mean estimation to find the  $S_T$ .

# APT Approach

- The Anytime Parameter Free (APT) [Locatelli et al. (2016)] algorithm was proposed for TBP setting in ICML 2016.
- This algorithm uses only mean estimation to find the  $S_T$ .
- Theoretically they proved this algorithm to be almost optimal when only mean estimation is used as a metric of comparison.

# APT Approach

- The Anytime Parameter Free (APT) [Locatelli et al. (2016)] algorithm was proposed for TBP setting in ICML 2016.
- This algorithm uses only mean estimation to find the  $S_\tau$ .
- Theoretically they proved this algorithm to be almost optimal when only mean estimation is used as a metric of comparison.
- Empirically it outperformed other state-of-the-art algorithms which were modified to perform in the TBP setting.

---

## Algorithm 1 APT

---

**Input:** Time horizon  $T$ , threshold  $\tau$ , tolerance factor  $\epsilon \geq 0$

Pull each arm once

**for**  $t = K + 1, \dots, T$  **do**


    Pull arm  $j \in \arg \min_{i \in A} \left\{ (|\hat{r}_i - \tau| + \epsilon) \sqrt{n_i} \right\}$  and observe the reward for arm  $j$ .

**end for**

**Output:**  $\hat{S}_\tau = \{i : \hat{r}_i \geq \tau\}$ .


---

# Intuition of APT



# AugUCB algorithm (Intuition, Arm pulling)

- Like UCB-Imp, AugUCB also divides the time budget  $T$  into rounds.
- At every timestep we pull arm  $j$  s.t.  $j \in \arg \min_{i \in B_m} \left\{ |\hat{r}_i - \tau| - 2s_i \right\}$  (like APT).






# AugUCB algorithm (Intuition, Arm Elimination)


- It is risky to eliminate arm  $i$  while  $\hat{r}_i$  is inside *Margin*.
- Confidence interval  $s_i$  will make sure arm  $i$  is not eliminated while inside Margin with a high probability.

Arm Elimination:  $\hat{r}_i + 2s_i < \tau$  or  $\hat{r}_i - 2s_i > \tau$




# AugUCB algorithm (Intuition, Arm Elimination)


Arm Elimination:  $\hat{r}_i + 2s_i < \tau$  or  $\hat{r}_i - 2s_i > \tau$



# AugUCB algorithm



# AugUCB parameter initialization



# Parameter initialization

- We define  $\ell_0 = \left\lceil \frac{2\psi_0 \log(T\epsilon_0)}{\epsilon_0} \right\rceil$  as the budget allocated to each arm in a round.


# Parameter initialization

- We define  $\ell_0 = \left\lceil \frac{2\psi_0 \log(T\epsilon_0)}{\epsilon_0} \right\rceil$  as the budget allocated to each arm in a round.
- The first round gets divided into  $N_0 = K\ell_0$  timesteps.

# Parameter initialization

- We define  $\ell_0 = \left\lceil \frac{2\psi_0 \log(T_{\epsilon_0})}{\epsilon_0} \right\rceil$  as the budget allocated to each arm in a round.
- The first round gets divided into  $N_0 = K\ell_0$  timesteps.
- We define a large exploration regulatory factor  $\psi_0 = \frac{T_{\epsilon_0}}{128 \left( \log(\frac{3}{16} K \log K) \right)^2}$  which controls exploration.

# AugUCB arm pull





# Arm pull

- We pull the arm that minimizes  $j \in \arg \min_{i \in B_m} \left\{ |\hat{r}_i - \tau| - 2s_i \right\}$

# Arm pull

- We pull the arm that minimizes  $j \in \arg \min_{i \in B_m} \left\{ |\hat{r}_i - \tau| - 2s_i \right\}$
- We define the confidence interval  $s_i = \sqrt{\frac{\rho \psi_m(\hat{v}_i + 1) \log(T \epsilon_m)}{4n_i}}$ .


# Arm pull

- We pull the arm that minimizes  $j \in \arg \min_{i \in B_m} \left\{ |\hat{r}_i - \tau| - 2s_i \right\}$
- We define the confidence interval  $s_i = \sqrt{\frac{\rho \psi_m(\hat{v}_i + 1) \log(T \epsilon_m)}{4n_i}}$ .
- $s_i$  decreases with more  $n_i$  and  $\psi_m$  and  $\rho$  ensures that it decreases at a correct rate.

# Arm pull

- We pull the arm that minimizes  $j \in \arg \min_{i \in B_m} \left\{ |\hat{r}_i - \tau| - 2s_i \right\}$
- We define the confidence interval  $s_i = \sqrt{\frac{\rho \psi_m(\hat{v}_i + 1) \log(T \epsilon_m)}{4n_i}}$ .
- $s_i$  decreases with more  $n_i$  and  $\psi_m$  and  $\rho$  ensures that it decreases at a correct rate.
- Note that  $\hat{v}_i$  estimated variance in  $s_i$  makes the algorithm pull the arm which shows more variance.

# AugUCB arm elimination



# Arm elimination

- Arm elimination condition is checked at every timestep.

# Arm elimination


- Arm elimination condition is checked at every timestep.
- It eliminated arm which are above or below margin.

# Arm elimination

- Arm elimination condition is checked at every timestep.
- It eliminated arm which are above or below margin.
- Re-allocates the remaining budget for surviving arms.



# AugUCB parameter reset



# AugUCB parameter reset

- Reduce the exploration factor as time progresses.

# AugUCB parameter reset

- Reduce the exploration factor as time progresses.
- Recalculate the budget for each surviving arms.

# AugUCB parameter reset

- Reduce the exploration factor as time progresses.
- Recalculate the budget for each surviving arms.
- Recalculate the length of each round on the number of surviving arms.

# Problem Complexity

- We must delve into the notion of hardness which come from the general pure exploration bandit literature.

# Problem Complexity

- We must delve into the notion of hardness which come from the general pure exploration bandit literature.
- We define  $H_1 = \sum_{i=1}^K \frac{1}{\Delta_i^2}$  and  $H_2 = \min_{i \in \mathcal{A}} \frac{i}{\Delta_{(i)}^2}$  where  $\Delta_{(i)}$  is an increasing ordering of  $\Delta_i$ .

# Problem Complexity

- We must delve into the notion of hardness which come from the general pure exploration bandit literature.
- We define  $H_1 = \sum_{i=1}^K \frac{1}{\Delta_i^2}$  and  $H_2 = \min_{i \in \mathcal{A}} \frac{i}{\Delta_{(i)}^2}$  where  $\Delta_{(i)}$  is an increasing ordering of  $\Delta_i$ .
- The relationship between  $H_1$  and  $H_2$  can be derived as,

$$H_2 \leq H_1 \leq \log(2K)H_2$$

# Problem Complexity

- For a variance aware algorithm we define  $H_{\sigma,1}$  ( as in Gabillon et al. (2011)) that incorporates reward variances into its expression as:

$$H_{\sigma,1} = \sum_{i=1}^K \frac{\sigma_i + \sqrt{\sigma_i^2 + (16/3)\Delta_i}}{\Delta_i^2}.$$



# Problem Complexity

- For a variance aware algorithm we define  $H_{\sigma,1}$  ( as in Gabillon et al. (2011)) that incorporates reward variances into its expression as:

$$H_{\sigma,1} = \sum_{i=1}^K \frac{\sigma_i + \sqrt{\sigma_i^2 + (16/3)\Delta_i}}{\Delta_i^2}.$$

- Finally, analogous to  $H_2$ , we introduce  $H_{\sigma,2}$ , such that  $H_{\sigma,2} = \max_{i \in \mathcal{A}} \frac{i}{\tilde{\Delta}_{(i)}^2}$ , where  $\tilde{\Delta}_i^2 = \frac{\Delta_i^2}{\sigma_i + \sqrt{\sigma_i^2 + (16/3)\Delta_i}}$ ,  $(\tilde{\Delta}_{(i)})$  is an increasing ordering of  $(\tilde{\Delta}_i)$ .

# Problem Complexity

- For a variance aware algorithm we define  $H_{\sigma,1}$  ( as in Gabillon et al. (2011)) that incorporates reward variances into its expression as:

$$H_{\sigma,1} = \sum_{i=1}^K \frac{\sigma_i + \sqrt{\sigma_i^2 + (16/3)\Delta_i}}{\Delta_i^2}.$$

- Finally, analogous to  $H_2$ , we introduce  $H_{\sigma,2}$ , such that  $H_{\sigma,2} = \max_{i \in \mathcal{A}} \frac{i}{\tilde{\Delta}_{(i)}^2}$ , where  $\tilde{\Delta}_i^2 = \frac{\Delta_i^2}{\sigma_i + \sqrt{\sigma_i^2 + (16/3)\Delta_i}}$ ,  $(\tilde{\Delta}_{(i)})$  is an increasing ordering of  $(\tilde{\Delta}_i)$ .
- From [Audibert and Bubeck(2010)], we can show that

$$H_{\sigma,2} \leq H_{\sigma,1} \leq \log(2K)H_{\sigma,2}.$$

# Problem Complexity

- For a variance aware algorithm we define  $H_{\sigma,1}$  ( as in Gabillon et al. (2011)) that incorporates reward variances into its expression as:

$$H_{\sigma,1} = \sum_{i=1}^K \frac{\sigma_i + \sqrt{\sigma_i^2 + (16/3)\Delta_i}}{\Delta_i^2}.$$

- Finally, analogous to  $H_2$ , we introduce  $H_{\sigma,2}$ , such that  $H_{\sigma,2} = \max_{i \in \mathcal{A}} \frac{i}{\tilde{\Delta}_{(i)}^2}$ , where  $\tilde{\Delta}_i^2 = \frac{\Delta_i^2}{\sigma_i + \sqrt{\sigma_i^2 + (16/3)\Delta_i}}$ ,  $(\tilde{\Delta}_{(i)})$  is an increasing ordering of  $(\tilde{\Delta}_i)$ .
- From [Audibert and Bubeck(2010)], we can show that

$$H_{\sigma,2} \leq H_{\sigma,1} \leq \log(2K)H_{\sigma,2}.$$

- Note that  $H_1$ ,  $H_2$  and  $H_{\sigma,1}$ ,  $H_{\sigma,2}$  are not directly comparable to each other except in a special case when variances and gaps  $(\Delta_i)$  are very low we can say that  $H_{\sigma,1} < H_1$ .

# Expected Loss of AugUCB

## Theorem

For  $K \geq 4$  and  $\rho = 1/3$ , the expected loss of the AugUCB algorithm is given by,


$$\mathbb{E}[\mathcal{L}(T)] \leq 2KT \exp \left( - \frac{T}{4096 \log(K \log K) H_{\sigma,2}} \right).$$

Table: AugUCB vs. State of the art

Algorithm	Upper Bound on Expected Loss
AugUCB	$\exp \left( - \frac{T}{4096 \log(K \log K) H_{\sigma,2}} + \log(2KT) \right)$
UCBEV	$\exp \left( - \frac{1}{512} \frac{T-2K}{H_{\sigma,1}} + \log(6KT) \right)$
APT	$\exp \left( - \frac{T}{64H_1} + 2 \log((\log(T) + 1)K) \right)$
CSAR	$\exp \left( - \frac{T-K}{72 \log(K) H_{CSAR,2}} + 2 \log(K) \right)$

# Sketch of the proof

Arm Elimination:  $\hat{r}_i + 2s_i < \tau$  or  $\hat{r}_i - 2s_i > \tau$



# Finally, experiment!!!

- We compare with APT, AugUCB, UCBE, UCBEV, CSAR, UA.

# Finally, experiment!!!

- We compare with APT, AugUCB, UCBE, UCBEV, CSAR, UA.
- Note that UCBE and UCBEV require access to  $H_1$  and  $H_{\sigma,1}$  as input and hence not implementable in real life.
- By access we mean that an oracle supplies them the  $H_1$  or  $H_{\sigma,1}$ . They do not have access to individual means and variances.

# Finally, experiment!!!

- We compare with APT, AugUCB, UCBE, UCBEV, CSAR, UA.
- Note that UCBE and UCBEV require access to  $H_1$  and  $H_{\sigma,1}$  as input and hence not implementable in real life.
- By access we mean that an oracle supplies them the  $H_1$  or  $H_{\sigma,1}$ . They do not have access to individual means and variances.
- APT, AugUCB, CSAR, UA do not require access to  $H_1$  or  $H_{\sigma,1}$ .



# Finally, experiment!!!

- We compare with APT, AugUCB, UCBE, UCBEV, CSAR, UA.
- Note that UCBE and UCBEV require access to  $H_1$  and  $H_{\sigma,1}$  as input and hence not implementable in real life.
- By access we mean that an oracle supplies them the  $H_1$  or  $H_{\sigma,1}$ . They do not have access to individual means and variances.
- APT, AugUCB, CSAR, UA do not require access to  $H_1$  or  $H_{\sigma,1}$ .
- UCBE, UCBEV, CSAR and UA come from the pure exploration lineage and are modified suitably to perform in TBP setting.

# Experimental Setup

- This setup involves Gaussian reward distributions with  $K = 100$ ,  $T = 10000$  and  $\tau = 0.5$  with the reward means set in two groups.


# Experimental Setup

- This setup involves Gaussian reward distributions with  $K = 100$ ,  $T = 10000$  and  $\tau = 0.5$  with the reward means set in two groups.
- The first 10 arms partitioned into two groups; the respective means are  $r_{1:5} = 0.45$ ,  $r_{6:10} = 0.55$ .


# Experimental Setup

- This setup involves Gaussian reward distributions with  $K = 100$ ,  $T = 10000$  and  $\tau = 0.5$  with the reward means set in two groups.
- The first 10 arms partitioned into two groups; the respective means are  $r_{1:5} = 0.45$ ,  $r_{6:10} = 0.55$ .
- The means of arms  $i = 11 : 100$  are chosen same as  $r_{11:100} = 0.4$ .
- Variances are set as  $\sigma_{1:5}^2 = 0.3$  and  $\sigma_{6:10}^2 = 0.8$ ;  $\sigma_{11:100}^2$  are independently and uniformly chosen in the interval  $[0.2, 0.3]$ .

# Experimental Results



(a) Expt-1: Two Group Setting (Advance)



(b) Expt-2: Two Group Setting (Advance)

# Conclusion

- We proposed the AugUCB algorithm for the fixed budget TBP which uses variance estimation and arm elimination to give an improved theoretical and experimental guarantees than APT.
- This work has been accepted in the proceedings of IJCAI 2017.

# Conclusion

- We proposed the AugUCB algorithm for the fixed budget TBP which uses variance estimation and arm elimination to give an improved theoretical and experimental guarantees than APT.
- This work has been accepted in the proceedings of IJCAI 2017.
- Further studies are required to establish a lower bound on the expected loss of AugUCB.

# Conclusion

- We proposed the AugUCB algorithm for the fixed budget TBP which uses variance estimation and arm elimination to give an improved theoretical and experimental guarantees than APT.
- This work has been accepted in the proceedings of IJCAI 2017.
- Further studies are required to establish a lower bound on the expected loss of AugUCB.
- A more detailed analysis of the non-uniform arm selection and parameter selection is also required.



# References I



Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári.  
Improved algorithms for linear stochastic bandits.  
*In Advances in Neural Information Processing Systems*, pages  
2312–2320, 2011.



Jacob D Abernethy, Kareem Amin, and Ruihao Zhu.  
Threshold bandits, with and without censored feedback.  
*In Advances In Neural Information Processing Systems*, pages  
4889–4897, 2016.



Shipra Agrawal and Navin Goyal.  
Analysis of thompson sampling for the multi-armed bandit  
problem.  
*arXiv preprint arXiv:1111.1797*, 2011.

# References II



Jean-Yves Audibert and Sébastien Bubeck.

Minimax policies for adversarial and stochastic bandits.

In *COLT*, pages 217–226, 2009.



Jean-Yves Audibert and Sébastien Bubeck.

Best arm identification in multi-armed bandits.

In *COLT-23th Conference on Learning Theory-2010*, pages 13–p, 2010.



Jean-Yves Audibert, Rémi Munos, and Csaba Szepesvári.

Exploration–exploitation tradeoff using variance estimates in multi-armed bandits.

*Theoretical Computer Science*, 410(19):1876–1902, 2009.

# References III



Peter Auer and Ronald Ortner.

Ucb revisited: Improved regret bounds for the stochastic multi-armed bandit problem.

*Periodica Mathematica Hungarica*, 61(1-2):55–65, 2010.



Peter Auer, Nicolo Cesa-Bianchi, and Paul Fischer.

Finite-time analysis of the multiarmed bandit problem.

*Machine learning*, 47(2-3):235–256, 2002a.



Peter Auer, Nicolo Cesa-Bianchi, Yoav Freund, and Robert E Schapire.

The nonstochastic multiarmed bandit problem.

*SIAM Journal on Computing*, 32(1):48–77, 2002b.

# References IV



Dimitri P Bertsekas and John N Tsitsiklis.

Neuro-dynamic programming (optimization and neural computation series, 3).

*Athena Scientific*, 7:15–23, 1996.



Sébastien Bubeck and Nicolo Cesa-Bianchi.

Regret analysis of stochastic and nonstochastic multi-armed bandit problems.

*arXiv preprint arXiv:1204.5721*, 2012.



Sébastien Bubeck, Rémi Munos, and Gilles Stoltz.

Pure exploration in finitely-armed and continuous-armed bandits.

*Theoretical Computer Science*, 412(19):1832–1852, 2011.



Sébastien Bubeck, Nicolo Cesa-Bianchi, and Gábor Lugosi.

Bandits with heavy tail.

*arXiv preprint arXiv:1209.1727*, 2012.

# References V



Sébastien Bubeck, Vianney Perchet, and Philippe Rigollet.  
Bounded regret in stochastic multi-armed bandits.  
*arXiv preprint arXiv:1302.1611*, 2013a.



Sébastien Bubeck, Tengyao Wang, and Nitin Viswanathan.  
Multiple identifications in multi-armed bandits.  
In *ICML (1)*, pages 258–265, 2013b.



Olivier Cappe, Aurelien Garivier, and Emilie Kaufmann.  
pymabandits, 2012.  
<http://mloss.org/software/view/415/>.



Shouyuan Chen, Tian Lin, Irwin King, Michael R Lyu, and Wei Chen.  
Combinatorial pure exploration of multi-armed bandits.  
In *Advances in Neural Information Processing Systems*, pages 379–387, 2014.

# References VI



Eyal Even-Dar, Shie Mannor, and Yishay Mansour.

Action elimination and stopping conditions for the multi-armed bandit and reinforcement learning problems.

*The Journal of Machine Learning Research*, 7:1079–1105, 2006.



Jerome Friedman, Trevor Hastie, and Robert Tibshirani.

*The elements of statistical learning*, volume 1.

Springer series in statistics Springer, Berlin, 2001.



Victor Gabillon, Mohammad Ghavamzadeh, Alessandro Lazaric, and Sébastien Bubeck.

Multi-bandit best arm identification.

In *Advances in Neural Information Processing Systems*, pages 2222–2230, 2011.

# References VII



Victor Gabillon, Mohammad Ghavamzadeh, and Alessandro Lazaric.

Best arm identification: A unified approach to fixed budget and fixed confidence.

*In Advances in Neural Information Processing Systems*, pages 3212–3220, 2012.



Aurélien Garivier and Olivier Cappé.

The kl-ucb algorithm for bounded stochastic bandits and beyond.  
*arXiv preprint arXiv:1102.2490*, 2011.



Mohammad Ghavamzadeh, Shie Mannor, Joelle Pineau, Aviv Tamar, et al.

*Bayesian reinforcement learning: a survey*.  
World Scientific, 2015.

# References VIII



Junya Honda and Akimichi Takemura.

An asymptotically optimal bandit algorithm for bounded support models.

In *COLT*, pages 67–79. Citeseer, 2010.



Kevin Jamieson and Robert Nowak.

Best-arm identification algorithms for multi-armed bandits in the fixed confidence setting.

In *Information Sciences and Systems (CISS), 2014 48th Annual Conference on*, pages 1–6. IEEE, 2014.



Shivaram Kalyanakrishnan, Ambuj Tewari, Peter Auer, and Peter Stone.

Pac subset selection in stochastic multi-armed bandits.

In *Proceedings of the 29th International Conference on Machine Learning (ICML-12)*, pages 655–662, 2012.



# References IX



Tze Leung Lai and Herbert Robbins.

Asymptotically efficient adaptive allocation rules.

*Advances in applied mathematics*, 6(1):4–22, 1985.



Tor Lattimore.

Optimally confident ucb: Improved regret for finite-armed bandits.

*arXiv preprint arXiv:1507.07880*, 2015.



Yun-Ching Liu and Yoshimasa Tsuruoka.

Modification of improved upper confidence bounds for regulating exploration in monte-carlo tree search.

*Theoretical Computer Science*, 2016.



Andrea Locatelli, Maurilio Gutzeit, and Alexandra Carpentier.

An optimal algorithm for the thresholding bandit problem.

*arXiv preprint arXiv:1605.08671*, 2016.

# References X



Shie Mannor and John N Tsitsiklis.

The sample complexity of exploration in the multi-armed bandit problem.

*Journal of Machine Learning Research*, 5(Jun):623–648, 2004.



Subhojyoti Mukherjee, K. P. Naveen, Nandan Sudarsanam, and Balaraman Ravindran.

Thresholding bandits with augmented UCB.

*CoRR*, abs/1704.02281, 2017.

URL <http://arxiv.org/abs/1704.02281>.



Vianney Perchet, Philippe Rigollet, Sylvain Chassang, and Erik Snowberg.

Batched bandit problems.

*arXiv preprint arXiv:1505.00369*, 2015.

# References XI



Herbert Robbins.

Some aspects of the sequential design of experiments.

In *Herbert Robbins Selected Papers*, pages 169–177. Springer, 1952.



Richard S Sutton and Andrew G Barto.

*Reinforcement learning: An introduction*.

MIT press, 1998.



William R Thompson.

On the likelihood that one unknown probability exceeds another in view of the evidence of two samples.

*Biometrika*, pages 285–294, 1933.



David Tolpin and Solomon Eyal Shimony.

Mcts based on simple regret.

In *AAAI*, 2012.

# Thank You