

# Thresholding Bandits with Augmented UCB

Subhojyoti Mukherjee

IIT Madras

July 12, 2017

# Overview

- 1 Introduction
- 2 Stochastic Multi-Armed Bandit Problem
- 3 Problem Definition
- 4 Contribution
- 5 Previous Works
- 6 AugUCB
- 7 Theoretical Analysis
- 8 Experiments
- 9 Conclusion
- 10 References

# Introduction to bandits

- The bandit problem is a sequential decision making process where at each timestep we have to choose one action or arm from a set of arms.

# Introduction to bandits

- The bandit problem is a sequential decision making process where at each timestep we have to choose one action or arm from a set of arms.
- There is a specific reward distribution attached to each arm. After pulling an arm we receive a reward (without delay) from the reward distribution specific to the arm.

# Introduction to bandits

- The bandit problem is a sequential decision making process where at each timestep we have to choose one action or arm from a set of arms.
- There is a specific reward distribution attached to each arm. After pulling an arm we receive a reward (without delay) from the reward distribution specific to the arm.
- After (say) pulling each arm once, we are presented with an *exploration-exploitation* trade-off, that is whether to continue to pull the arm for which we have observed the highest estimated reward till now (exploitation) or to explore a new arm (exploration).

# Introduction to bandits

- The bandit problem is a sequential decision making process where at each timestep we have to choose one action or arm from a set of arms.
- There is a specific reward distribution attached to each arm. After pulling an arm we receive a reward (without delay) from the reward distribution specific to the arm.
- After (say) pulling each arm once, we are presented with an *exploration-exploitation* trade-off, that is whether to continue to pull the arm for which we have observed the highest estimated reward till now (exploitation) or to explore a new arm (exploration).
- If we become too greedy and always exploit, we may miss the chance of actually finding the optimal arm and get stuck with a sub-optimal arm.

# Stochastic Multi-Armed Bandit Problem (SMAB)

- The thresholding bandit problem falls under the broad area of stochastic multi-armed bandit problem.

# Stochastic Multi-Armed Bandit Problem (SMAB)

- The thresholding bandit problem falls under the broad area of stochastic multi-armed bandit problem.
- In SMAB problem, we are presented with a finite set of actions or arms.



# Stochastic Multi-Armed Bandit Problem (SMAB)

- The thresholding bandit problem falls under the broad area of stochastic multi-armed bandit problem.
- In SMAB problem, we are presented with a finite set of actions or arms.
- The rewards for each of the arms are identical and independent random variables drawn from distribution specific to the arm.

# Stochastic Multi-Armed Bandit Problem (SMAB)

- The thresholding bandit problem falls under the broad area of stochastic multi-armed bandit problem.
- In SMAB problem, we are presented with a finite set of actions or arms.
- The rewards for each of the arms are identical and independent random variables drawn from distribution specific to the arm.
- The learner does not know the mean of the distributions, denoted by  $r_i, \forall i \in A$  and the variance denoted by  $\sigma_i^2$ .

# Stochastic Multi-Armed Bandit Problem (SMAB)

- The thresholding bandit problem falls under the broad area of stochastic multi-armed bandit problem.
- In SMAB problem, we are presented with a finite set of actions or arms.
- The rewards for each of the arms are identical and independent random variables drawn from distribution specific to the arm.
- The learner does not know the mean of the distributions, denoted by  $r_i, \forall i \in A$  and the variance denoted by  $\sigma_i^2$ .
- The distributions for each of the arms are fixed throughout the time horizon denoted by  $T$ .

# Problem Definition

- The primary aim in the thresholding bandit problem (TBP) is to identify the arms whose mean of the reward distribution is above a particular threshold  $\tau$  given as input.

# Problem Definition

- The primary aim in the thresholding bandit problem (TBP) is to identify the arms whose mean of the reward distribution is above a particular threshold  $\tau$  given as input.
- The above goal has to be achieved within  $T$  timesteps of exploration and this is termed as a fixed-budget problem.

# Problem Definition

- The primary aim in the thresholding bandit problem (TBP) is to identify the arms whose mean of the reward distribution is above a particular threshold  $\tau$  given as input.
- The above goal has to be achieved within  $T$  timesteps of exploration and this is termed as a fixed-budget problem.
- At the end of the given  $T$  timesteps the learner must recommend a set of arms which (according to it) are the arms having reward mean above  $\tau$ .

# Problem Definition

- We define the set  $S_\tau = \{i \in \mathcal{A} : r_i \geq \tau\}$ .

# Problem Definition

- We define the set  $S_\tau = \{i \in \mathcal{A} : r_i \geq \tau\}$ .
- $S_\tau^c$  denote the complement of  $S_\tau$ , i.e.,  $S_\tau^c = \{i \in \mathcal{A} : r_i < \tau\}$ .



# Problem Definition

- We define the set  $S_\tau = \{i \in \mathcal{A} : r_i \geq \tau\}$ .
- $S_\tau^c$  denote the complement of  $S_\tau$ , i.e.,  $S_\tau^c = \{i \in \mathcal{A} : r_i < \tau\}$ .
- Let  $\hat{S}_\tau$  denote the recommendation of a learning algorithm after  $T$  time units of exploration, while  $\hat{S}_\tau^c$  denotes its complement.

# Problem Definition

- We define the set  $S_\tau = \{i \in \mathcal{A} : r_i \geq \tau\}$ .
- $S_\tau^c$  denote the complement of  $S_\tau$ , i.e.,  $S_\tau^c = \{i \in \mathcal{A} : r_i < \tau\}$ .
- Let  $\hat{S}_\tau$  denote the recommendation of a learning algorithm after  $T$  time units of exploration, while  $\hat{S}_\tau^c$  denotes its complement.
- The performance of the learning agent is measured by the accuracy with which it can classify the arms into  $S_\tau$  and  $S_\tau^c$  after time horizon  $T$ . Equivalently, the *loss*  $\mathcal{L}(T)$  is defined as

$$\mathcal{L}(T) = \mathbb{I}(\{S_\tau \cap \hat{S}_\tau^c \neq \emptyset\} \cup \{\hat{S}_\tau \cap S_\tau^c \neq \emptyset\}).$$

- The goal of the learning agent is to minimize the expected loss:

$$\mathbb{E}[\mathcal{L}(T)] = \mathbb{P}(\{S_\tau \cap \hat{S}_\tau^c \neq \emptyset\} \cup \{\hat{S}_\tau \cap S_\tau^c \neq \emptyset\}).$$

# Some practical applications

- Selecting the best channels (out of several existing channels) for mobile communications in a very short duration whose qualities are above an acceptable threshold (see [Audibert and Bubeck(2010)]).

# Some practical applications

- Selecting the best channels (out of several existing channels) for mobile communications in a very short duration whose qualities are above an acceptable threshold (see [Audibert and Bubeck(2010)]).
- Selecting a small set of best workers (out of a very large pool of workers) whose productivity is above a threshold.

# Some practical applications

- Selecting the best channels (out of several existing channels) for mobile communications in a very short duration whose qualities are above an acceptable threshold (see [Audibert and Bubeck(2010)]).
- Selecting a small set of best workers (out of a very large pool of workers) whose productivity is above a threshold.
- In anomaly detection and classification (see Locatelli et al. (2016)).

- We propose the Augmented UCB (AugUCB) [Mukherjee et al. (2017)] algorithm for the fixed-budget TBP setting.

- We propose the Augmented UCB (AugUCB) [Mukherjee et al. (2017)] algorithm for the fixed-budget TBP setting.
- AugUCB takes into account the empirical variances of the arms along with mean estimates.

- We propose the Augmented UCB (AugUCB) [Mukherjee et al. (2017)] algorithm for the fixed-budget TBP setting.
- AugUCB takes into account the empirical variances of the arms along with mean estimates.
- It is the first variance-based arm elimination algorithm for the considered TBP settings.



- We propose the Augmented UCB (AugUCB) [Mukherjee et al. (2017)] algorithm for the fixed-budget TBP setting.
- AugUCB takes into account the empirical variances of the arms along with mean estimates.
- It is the first variance-based arm elimination algorithm for the considered TBP settings.
- It address an open problem discussed in [Auer and Ortner(2010)] of designing an algorithm that can eliminate arms based on variance estimates.

- We propose the Augmented UCB (AugUCB) [Mukherjee et al. (2017)] algorithm for the fixed-budget TBP setting.
- AugUCB takes into account the empirical variances of the arms along with mean estimates.
- It is the first variance-based arm elimination algorithm for the considered TBP settings.
- It address an open problem discussed in [Auer and Ortner(2010)] of designing an algorithm that can eliminate arms based on variance estimates.
- It is the first algorithm on the larger pure exploration setting which uses empirical variance estimates along with arm elimination with a new problem complexity.

- The Anytime Parameter Free (APT) [Locatelli et al. (2016)] algorithm was proposed for TBP setting in ICML 2016.

# Previous Works

- The Anytime Parameter Free (APT) [Locatelli et al. (2016)] algorithm was proposed for TBP setting in ICML 2016.
- This algorithm uses only mean estimation to find the  $S_{\tau}$ .

- The Anytime Parameter Free (APT) [Locatelli et al. (2016)] algorithm was proposed for TBP setting in ICML 2016.
- This algorithm uses only mean estimation to find the  $S_T$ .
- Theoretically they proved this algorithm to be almost optimal when only mean estimation is used as a metric of comparison.

- The Anytime Parameter Free (APT) [Locatelli et al. (2016)] algorithm was proposed for TBP setting in ICML 2016.
- This algorithm uses only mean estimation to find the  $S_\tau$ .
- Theoretically they proved this algorithm to be almost optimal when only mean estimation is used as a metric of comparison.
- Empirically it outperformed other state-of-the-art algorithms which were modified to perform in the TBP setting.

---

## Algorithm 1 APT

---

- 1: **Input:** Time horizon  $T$ , threshold  $\tau$ , tolerance factor  $\epsilon \geq 0$
  - 2: Pull each arm once
  - 3:
  - 4: **for**  $t = K + 1, \dots, T$  **do**
  - 5:     Pull arm  $j \in \arg \min_{i \in A} \left\{ (|\hat{r}_i - \tau| + \epsilon) \sqrt{n_i} \right\}$  and observe the reward for arm  $j$ .
  - 6: **end for**
  - 7: **Output:**  $\hat{S}_\tau = \{i : \hat{r}_i \geq \tau\}$ .
-

# Previous Works (Pure Exploration)

- The TBP problem also falls within the larger area called the Pure Exploration problem.



# Previous Works (Pure Exploration)

- The TBP problem also falls within the larger area called the Pure Exploration problem.
- In pure exploration problems the learner has to output a set of recommendations either with high confidence (fixed confidence) or after a specified number of rounds (fixed budget).

# Previous Works (Pure Exploration)

- The TBP problem also falls within the larger area called the Pure Exploration problem.
- In pure exploration problems the learner has to output a set of recommendations either with high confidence (fixed confidence) or after a specified number of rounds (fixed budget).
- Our considered TBP is a fixed budget pure exploration problem.

# Previous Works (Pure Exploration)

- The TBP problem also falls within the larger area called the Pure Exploration problem.
- In pure exploration problems the learner has to output a set of recommendations either with high confidence (fixed confidence) or after a specified number of rounds (fixed budget).
- Our considered TBP is a fixed budget pure exploration problem.
- Both APT and AugUCB reuses several ideas from Pure exploration problem.

# Previous Works (Diagram)




Figure: TBP place within SMAB and Pure exploration

# Approach of UCB-Improved (UCB-Imp)

- There is a strong relation between UCB-Imp [Auer and Ortner(2010)] and AugUCB where the former is used to find *a single optimal arm as quickly as possible*.

# Approach of UCB-Improved (UCB-Imp)

- There is a strong relation between UCB-Imp [Auer and Ortner(2010)] and AugUCB where the former is used to find *a single optimal arm as quickly as possible*.
- The basic idea of UCB-Improved is to divide the horizon into phases or rounds and initialize parameters.

# Approach of UCB-Improved (UCB-Imp)

- There is a strong relation between UCB-Imp [Auer and Ortner(2010)] and AugUCB where the former is used to find *a single optimal arm as quickly as possible*.
- The basic idea of UCB-Improved is to divide the horizon into phases or rounds and initialize parameters.
- Pull all surviving arms equal number of times during a round.

# Approach of UCB-Improved (UCB-Imp)

- There is a strong relation between UCB-Imp [Auer and Ortner(2010)] and AugUCB where the former is used to find *a single optimal arm as quickly as possible*.
- The basic idea of UCB-Improved is to divide the horizon into phases or rounds and initialize parameters.
- Pull all surviving arms equal number of times during a round.
- At the end of the round eliminate some sub-optimal arms (as judged by learner) based on elimination criteria.



# Approach of UCB-Improved (UCB-Imp)

- There is a strong relation between UCB-Imp [Auer and Ortner(2010)] and AugUCB where the former is used to find *a single optimal arm as quickly as possible*.
- The basic idea of UCB-Improved is to divide the horizon into phases or rounds and initialize parameters.
- Pull all surviving arms equal number of times during a round.
- At the end of the round eliminate some sub-optimal arms (as judged by learner) based on elimination criteria.
- Reset parameters and proceed to next round.

# UCB-Improved ([Auer and Ortner(2010)])

---

## Algorithm 2 UCB-Improved

---

- 1: **Input:** Time horizon  $T$
  - 2: **Initialization:** Set  $B_0 := A$  and  $\epsilon_0 := 1$ .
  - 3: **for**  $m = 0, 1, \dots, \lfloor \frac{1}{2} \log_2 \frac{T}{e} \rfloor$  **do**
  - 4:     Pull each arm in  $B_m$ ,  $n_m = \left\lceil \frac{2 \log(T \epsilon_m^2)}{\epsilon_m} \right\rceil$  number of times.
  - 5:     ***Arm Elimination***
  - 6:     For each  $i \in B_m$ , delete arm  $i$  from  $B_m$  if,
$$\hat{r}_i + \sqrt{\frac{\log(T \epsilon_m^2)}{2n_m}} < \max_{j \in B_m} \left\{ \hat{r}_j - \sqrt{\frac{\log(T \epsilon_m^2)}{2n_m}} \right\}$$
  - 7:
  - 8:     Set  $\epsilon_{m+1} := \frac{\epsilon_m}{2}$ , Set  $B_{m+1} := B_m$
  - 9:     Stop if  $|B_m| = 1$  and pull  $i \in B_m$  till  $T$  is reached.
  - 10: **end for**
-

# Some technical details of UCB-Improved

- We do not know the true means  $r_i, \forall i \in A$  of the distributions so we estimate it by the  $\hat{r}_i$  by initializing it from 1.

# Some technical details of UCB-Improved

- We do not know the true means  $r_i, \forall i \in A$  of the distributions so we estimate it by the  $\hat{r}_i$  by initializing it from 1.
- All rewards are assumed to be bounded between  $[0, 1]$  and so  $\Delta_i = (r^* - r_i) \in [0, 1], \forall i \in A$  as well.

# Some technical details of UCB-Improved


- We do not know the true means  $r_i, \forall i \in A$  of the distributions so we estimate it by the  $\hat{r}_i$  by initializing it from 1.
- All rewards are assumed to be bounded between  $[0, 1]$  and so  $\Delta_i = (r^* - r_i) \in [0, 1], \forall i \in A$  as well.
- UCB-Improved has fixed confidence interval  $c_m = \sqrt{\frac{\log(T \epsilon_m^2)}{2n_m}}$  for all arms in a particular round.

# Some technical details of UCB-Improved

- We do not know the true means  $r_i, \forall i \in A$  of the distributions so we estimate it by the  $\hat{r}_i$  by initializing it from 1.
- All rewards are assumed to be bounded between  $[0, 1]$  and so  $\Delta_i = (r^* - r_i) \in [0, 1], \forall i \in A$  as well.
- UCB-Improved has fixed confidence interval  $c_m = \sqrt{\frac{\log(T\epsilon_m^2)}{2n_m}}$  for all arms in a particular round.
- $c_m$  ensures that whenever  $\epsilon_m < \frac{\Delta_i}{2}$  in the  $m$ -th round, the arm  $i$  gets eliminated.

# AugUCB algorithm (Intuition)

- We define  $\Delta_i = |r_i - \tau|$ .
- It is risky to eliminate arm  $i$  while  $\hat{r}_i$  is inside *Margin*.
- Confidence interval  $s_i$  will make sure arm  $i$  is not eliminated while inside Margin with a high probability.



# AugUCB algorithm

- Like UCB-Imp, AugUCB also divides the time budget  $T$  into rounds.



# AugUCB algorithm

- Like UCB-Imp, AugUCB also divides the time budget  $T$  into rounds.
- A crucial difference is that in every round instead of pulling all the arms equal number of times we pull the arm that minimizes  $j \in \arg \min_{i \in B_m} \left\{ |\hat{r}_i - \tau| - 2s_i \right\}$  (like APT).

# AugUCB algorithm

- Like UCB-Imp, AugUCB also divides the time budget  $T$  into rounds.
- A crucial difference is that in every round instead of pulling all the arms equal number of times we pull the arm that minimizes  $j \in \arg \min_{i \in B_m} \left\{ |\hat{r}_i - \tau| - 2s_i \right\}$  (like APT).
- At every timestep now we run the arm elimination check to eliminate sub-optimal arms.

# AugUCB algorithm

- Like UCB-Imp, AugUCB also divides the time budget  $T$  into rounds.
- A crucial difference is that in every round instead of pulling all the arms equal number of times we pull the arm that minimizes  $j \in \arg \min_{i \in B_m} \left\{ |\hat{r}_i - \tau| - 2s_i \right\}$  (like APT).
- At every timestep now we run the arm elimination check to eliminate sub-optimal arms.
- At the end of the phase we reset the parameters.

# AugUCB algorithm

- Like UCB-Imp, AugUCB also divides the time budget  $T$  into rounds.
- A crucial difference is that in every round instead of pulling all the arms equal number of times we pull the arm that minimizes  $j \in \arg \min_{i \in B_m} \left\{ |\hat{r}_i - \tau| - 2s_i \right\}$  (like APT).
- At every timestep now we run the arm elimination check to eliminate sub-optimal arms.
- At the end of the phase we reset the parameters.
- Note that the length of the phase, the exploration parameters and the confidence interval term  $s_i = \sqrt{\frac{\rho \psi_m(\hat{v}_i + 1) \log(T \epsilon_m)}{4n_i}}$  are set through detailed theoretical analysis.

# AugUCB algorithm I

**Input:** Time budget  $T$ ; parameter  $\rho$ ; threshold  $\tau$

**Initialization:**  $B_0 = \mathcal{A}$ ;  $m = 0$ ;  $\epsilon_0 = 1$ ;

$$M = \left\lfloor \frac{1}{2} \log_2 \frac{T}{e} \right\rfloor; \quad \psi_0 = \frac{T\epsilon_0}{128 \left( \log\left(\frac{3}{16} K \log K\right) \right)^2};$$

$$\ell_0 = \left\lceil \frac{2\psi_0 \log(T\epsilon_0)}{\epsilon_0} \right\rceil; \quad N_0 = K\ell_0$$

Pull each arm once

**for**  $t = K + 1, \dots, T$  **do**

Pull arm  $j \in \arg \min_{i \in B_m} \left\{ |\hat{r}_i - \tau| - 2s_i \right\}$

**for**  $i \in B_m$  **do**

**if**  $(\hat{r}_i + s_i < \tau - s_i)$  or  $(\hat{r}_i - s_i > \tau + s_i)$  **then**

$B_m \leftarrow B_m \setminus \{i\}$  (Arm deletion)

**end if**

**end for**

**if**  $t \geq N_m$  and  $m \leq M$  **then**

**Reset Parameters**

$$\epsilon_{m+1} \leftarrow \frac{\epsilon_m}{2}$$

$$B_{m+1} \leftarrow B_m$$

$$\psi_{m+1} \leftarrow \frac{T_{\epsilon_{m+1}}}{128(\log(\frac{3}{16} K \log K))^2}$$

$$\ell_{m+1} \leftarrow \left\lceil \frac{2\psi_{m+1} \log(T_{\epsilon_{m+1}})}{\epsilon_{m+1}} \right\rceil$$

$$N_{m+1} \leftarrow t + |B_{m+1}| \ell_{m+1}$$

$$m \leftarrow m + 1$$

**end if**

**end for**

**Output:**  $\hat{S}_\tau = \{i : \hat{r}_i \geq \tau\}.$

# Problem Complexity

- We must delve into the notion of hardness which come from the general pure exploration bandit literature.

# Problem Complexity

- We must delve into the notion of hardness which come from the general pure exploration bandit literature.
- We define  $H_1 = \sum_{i=1}^K \frac{1}{\Delta_i^2}$  and  $H_2 = \min_{i \in \mathcal{A}} \frac{i}{\Delta_{(i)}^2}$  where  $\Delta_{(i)}$  is an increasing ordering of  $\Delta_i$ .



# Problem Complexity

- We must delve into the notion of hardness which come from the general pure exploration bandit literature.
- We define  $H_1 = \sum_{i=1}^K \frac{1}{\Delta_i^2}$  and  $H_2 = \min_{i \in \mathcal{A}} \frac{i}{\Delta_{(i)}^2}$  where  $\Delta_{(i)}$  is an increasing ordering of  $\Delta_i$ .
- The relationship between  $H_1$  and  $H_2$  can be derived as,

$$H_2 \leq H_1 \leq \log(2K)H_2$$

# Problem Complexity

- For a variance aware algorithm we define  $H_{\sigma,1}$  ( as in Gabillon et al. (2011)) that incorporates reward variances into its expression as:

$$H_{\sigma,1} = \sum_{i=1}^K \frac{\sigma_i + \sqrt{\sigma_i^2 + (16/3)\Delta_i}}{\Delta_i^2}.$$

# Problem Complexity

- For a variance aware algorithm we define  $H_{\sigma,1}$  ( as in Gabillon et al. (2011)) that incorporates reward variances into its expression as:

$$H_{\sigma,1} = \sum_{i=1}^K \frac{\sigma_i + \sqrt{\sigma_i^2 + (16/3)\Delta_i}}{\Delta_i^2}.$$

- Finally, analogous to  $H_2$ , we introduce  $H_{\sigma,2}$ , such that  $H_{\sigma,2} = \max_{i \in \mathcal{A}} \frac{i}{\tilde{\Delta}_{(i)}^2}$ , where  $\tilde{\Delta}_i^2 = \frac{\Delta_i^2}{\sigma_i + \sqrt{\sigma_i^2 + (16/3)\Delta_i}}$ ,  $(\tilde{\Delta}_{(i)})$  is an increasing ordering of  $(\tilde{\Delta}_i)$ .

# Problem Complexity

- For a variance aware algorithm we define  $H_{\sigma,1}$  ( as in Gabillon et al. (2011)) that incorporates reward variances into its expression as:

$$H_{\sigma,1} = \sum_{i=1}^K \frac{\sigma_i + \sqrt{\sigma_i^2 + (16/3)\Delta_i}}{\Delta_i^2}.$$

- Finally, analogous to  $H_2$ , we introduce  $H_{\sigma,2}$ , such that  $H_{\sigma,2} = \max_{i \in \mathcal{A}} \frac{i}{\tilde{\Delta}_{(i)}^2}$ , where  $\tilde{\Delta}_i^2 = \frac{\Delta_i^2}{\sigma_i + \sqrt{\sigma_i^2 + (16/3)\Delta_i}}$ ,  $(\tilde{\Delta}_{(i)})$  is an increasing ordering of  $(\tilde{\Delta}_i)$ .
- From [Audibert and Bubeck(2010)], we can show that

$$H_{\sigma,2} \leq H_{\sigma,1} \leq \log(2K)H_{\sigma,2}.$$

# Problem Complexity

- For a variance aware algorithm we define  $H_{\sigma,1}$  ( as in Gabillon et al. (2011)) that incorporates reward variances into its expression as:

$$H_{\sigma,1} = \sum_{i=1}^K \frac{\sigma_i + \sqrt{\sigma_i^2 + (16/3)\Delta_i}}{\Delta_i^2}.$$

- Finally, analogous to  $H_2$ , we introduce  $H_{\sigma,2}$ , such that  $H_{\sigma,2} = \max_{i \in \mathcal{A}} \frac{i}{\tilde{\Delta}_{(i)}^2}$ , where  $\tilde{\Delta}_i^2 = \frac{\Delta_i^2}{\sigma_i + \sqrt{\sigma_i^2 + (16/3)\Delta_i}}$ ,  $(\tilde{\Delta}_{(i)})$  is an increasing ordering of  $(\tilde{\Delta}_i)$ .
- From [Audibert and Bubeck(2010)], we can show that

$$H_{\sigma,2} \leq H_{\sigma,1} \leq \log(2K)H_{\sigma,2}.$$

- Note that  $H_1$ ,  $H_2$  and  $H_{\sigma,1}$ ,  $H_{\sigma,2}$  are not directly comparable to each other except in a special case when variances are very low we can say that  $H_{\sigma,1} < H_1$ .

# Expected Loss of AugUCB

## Theorem

For  $K \geq 4$  and  $\rho = 1/3$ , the expected loss of the AugUCB algorithm is given by,

$$\mathbb{E}[\mathcal{L}(T)] \leq 2KT \exp \left( - \frac{T}{4096 \log(K \log K) H_{\sigma,2}} \right).$$

Table: AugUCB vs. State of the art

Algorithm	Upper Bound on Expected Loss
AugUCB	$\exp \left( - \frac{T}{4096 \log(K \log K) H_{\sigma,2}} + \log(2KT) \right)$
UCBEV	$\exp \left( - \frac{1}{512} \frac{T-2K}{H_{\sigma,1}} + \log(6KT) \right)$
APT	$\exp \left( - \frac{T}{64H_1} + 2 \log((\log(T) + 1)K) \right)$
CSAR	$\exp \left( - \frac{T-K}{72 \log(K) H_{CSAR,2}} + 2 \log(K) \right)$

# Concentration Bounds

- Let  $X_1, \dots, X_n$  be random variables with common support  $[0, 1]$  and such that  $E[X_t | X_1, \dots, X_{t-1}] = r_i$ . Let  $\hat{r}_i = \frac{X_1 + \dots + X_n}{n}$ . Then for all  $c \geq 0$ ,

$$\mathbb{P}\{\hat{r}_i \geq r_i + c\} \leq \exp(-2c^2 n)$$

$$\mathbb{P}\{\hat{r}_i \leq r_i - c\} \leq \exp(-2c^2 n)$$

# Concentration Bounds

- Let  $X_1, \dots, X_n$  be random variables with common support  $[0, 1]$  and such that  $E[X_t | X_1, \dots, X_{t-1}] = r_i$ . Let  $\hat{r}_i = \frac{X_1 + \dots + X_n}{n}$ . Then for all  $c \geq 0$ ,

$$\mathbb{P}\{\hat{r}_i \geq r_i + c\} \leq \exp(-2c^2 n)$$

$$\mathbb{P}\{\hat{r}_i \leq r_i - c\} \leq \exp(-2c^2 n)$$

- Along with the above information if we know that  $\text{Var}[X_t | X_1, \dots, X_{t-1}] = \sigma_i^2$  then Bernstein inequality gives us,

$$\mathbb{P}\{\hat{r}_i \geq r_i + c\} \leq \exp\left(-\frac{c^2 n}{2\sigma_i^2 + \frac{2c}{3}}\right)$$

$$\mathbb{P}\{\hat{r}_i \leq r_i - c\} \leq \exp\left(-\frac{c^2 n}{2\sigma_i^2 + \frac{2c}{3}}\right)$$



# Sketch of the proof

- The proof comprises of two modules. In the first module we investigate the necessary conditions for arm elimination within a specified number of rounds, which is motivated by the technique in UCB-Imp.

# Sketch of the proof

- The proof comprises of two modules. In the first module we investigate the necessary conditions for arm elimination within a specified number of rounds, which is motivated by the technique in UCB-Imp.
- We bound the arm-elimination probability by Bernstein inequality (as in Audibert et al. (2009)) rather than the Chernoff-Hoeffding bounds (used in UCB-Imp).

# Sketch of the proof

- The proof comprises of two modules. In the first module we investigate the necessary conditions for arm elimination within a specified number of rounds, which is motivated by the technique in UCB-Imp.
- We bound the arm-elimination probability by Bernstein inequality (as in Audibert et al. (2009)) rather than the Chernoff-Hoeffding bounds (used in UCB-Imp).
- In the second module, we define a favourable event that will yield an upper bound on the expected loss and use union bound and module-1 (on the arm elimination probability) to derive the result through a series of simplifications.

# Finally, experiment!!!

- We experiment with APT, AugUCB, UCBE, UCBEV, CSAR, UA.

# Finally, experiment!!!

- We experiment with APT, AugUCB, UCBE, UCBEV, CSAR, UA.
- Note that UCBE and UCBEV require access to  $H_1$  and  $H_{\sigma,1}$  as input and hence not implementable in real life.
- By access we mean that an oracle supplies them the  $H_1$  or  $H_{\sigma,1}$ . They do not have access to individual means and variances.

# Finally, experiment!!!

- We experiment with APT, AugUCB, UCBE, UCBEV, CSAR, UA.
- Note that UCBE and UCBEV require access to  $H_1$  and  $H_{\sigma,1}$  as input and hence not implementable in real life.
- By access we mean that an oracle supplies them the  $H_1$  or  $H_{\sigma,1}$ . They do not have access to individual means and variances.
- APT, AugUCB, CSAR, UA do not require access to  $H_1$  or  $H_{\sigma,1}$ .

# Finally, experiment!!!

- We experiment with APT, AugUCB, UCBE, UCBEV, CSAR, UA.
- Note that UCBE and UCBEV require access to  $H_1$  and  $H_{\sigma,1}$  as input and hence not implementable in real life.
- By access we mean that an oracle supplies them the  $H_1$  or  $H_{\sigma,1}$ . They do not have access to individual means and variances.
- APT, AugUCB, CSAR, UA do not require access to  $H_1$  or  $H_{\sigma,1}$ .
- UCBE, UCBEV, CSAR and UA come from the pure exploration lineage and are modified suitably to perform in TBP setting.

# Experimental Setup

- This setup involves Gaussian reward distributions with  $K = 100$ ,  $T = 10000$  and  $\tau = 0.5$  with the reward means set in two groups.




# Experimental Setup

- This setup involves Gaussian reward distributions with  $K = 100$ ,  $T = 10000$  and  $\tau = 0.5$  with the reward means set in two groups.
- The first 10 arms partitioned into two groups; the respective means are  $r_{1:5} = 0.45$ ,  $r_{6:10} = 0.55$ .


# Experimental Setup

- This setup involves Gaussian reward distributions with  $K = 100$ ,  $T = 10000$  and  $\tau = 0.5$  with the reward means set in two groups.
- The first 10 arms partitioned into two groups; the respective means are  $r_{1:5} = 0.45$ ,  $r_{6:10} = 0.55$ .
- The means of arms  $i = 11 : 100$  are chosen same as  $r_{11:100} = 0.4$ .
- Variances are set as  $\sigma_{1:5}^2 = 0.3$  and  $\sigma_{6:10}^2 = 0.8$ ;  $\sigma_{11:100}^2$  are independently and uniformly chosen in the interval  $[0.2, 0.3]$ .

# Experimental Result



(a) Expt-1: Two Group Setting (Advance)



(b) Expt-2: Two Group Setting (Advance)

# Conclusion

- We proposed the AugUCB algorithm for the fixed budget TBP setting which has an improved theoretical and experimental guarantees than APT.

# Conclusion

- We proposed the AugUCB algorithm for the fixed budget TBP setting which has an improved theoretical and experimental guarantees than APT.
- Further studies are required to establish a lower bound on the expected loss of AugUCB.

# Conclusion

- We proposed the AugUCB algorithm for the fixed budget TBP setting which has an improved theoretical and experimental guarantees than APT.
- Further studies are required to establish a lower bound on the expected loss of AugUCB.
- A more detailed analysis of the non-uniform arm selection and parameter selection is also required.

- We have proposed a very similar algorithm as in AugUCB for the SMAB problem with more detailed study of non-uniform arm selection and parameter selection.

- We have proposed a very similar algorithm as in AugUCB for the SMAB problem with more detailed study of non-uniform arm selection and parameter selection.
- Termed as Efficient UCBV, we are preparing for submission for AAAI 2018.



# Future direction in MS

- We have proposed a very similar algorithm as in AugUCB for the SMAB problem with more detailed study of non-uniform arm selection and parameter selection.
- Termed as Efficient UCBV, we are preparing for submission for AAAI 2018.
- I am going to INRIA, SequeL Lab, Lille, France for a three month internship starting from 1st September under Dr. Odalric Maillard.

Any Questions?

# References I



Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári.  
Improved algorithms for linear stochastic bandits.  
*In Advances in Neural Information Processing Systems*, pages  
2312–2320, 2011.



Jacob D Abernethy, Kareem Amin, and Ruihao Zhu.  
Threshold bandits, with and without censored feedback.  
*In Advances In Neural Information Processing Systems*, pages  
4889–4897, 2016.



Shipra Agrawal and Navin Goyal.  
Analysis of thompson sampling for the multi-armed bandit  
problem.  
*arXiv preprint arXiv:1111.1797*, 2011.

# References II



Jean-Yves Audibert and Sébastien Bubeck.

Minimax policies for adversarial and stochastic bandits.

In *COLT*, pages 217–226, 2009.



Jean-Yves Audibert and Sébastien Bubeck.

Best arm identification in multi-armed bandits.

In *COLT-23th Conference on Learning Theory-2010*, pages 13–p, 2010.



Jean-Yves Audibert, Rémi Munos, and Csaba Szepesvári.

Exploration–exploitation tradeoff using variance estimates in multi-armed bandits.

*Theoretical Computer Science*, 410(19):1876–1902, 2009.

# References III



Peter Auer and Ronald Ortner.

Ucb revisited: Improved regret bounds for the stochastic multi-armed bandit problem.

*Periodica Mathematica Hungarica*, 61(1-2):55–65, 2010.



Peter Auer, Nicolo Cesa-Bianchi, and Paul Fischer.

Finite-time analysis of the multiarmed bandit problem.

*Machine learning*, 47(2-3):235–256, 2002a.



Peter Auer, Nicolo Cesa-Bianchi, Yoav Freund, and Robert E Schapire.

The nonstochastic multiarmed bandit problem.

*SIAM Journal on Computing*, 32(1):48–77, 2002b.

# References IV



Dimitri P Bertsekas and John N Tsitsiklis.

Neuro-dynamic programming (optimization and neural computation series, 3).

*Athena Scientific*, 7:15–23, 1996.



Sébastien Bubeck and Nicolo Cesa-Bianchi.

Regret analysis of stochastic and nonstochastic multi-armed bandit problems.

*arXiv preprint arXiv:1204.5721*, 2012.



Sébastien Bubeck, Rémi Munos, and Gilles Stoltz.

Pure exploration in finitely-armed and continuous-armed bandits.

*Theoretical Computer Science*, 412(19):1832–1852, 2011.



Sébastien Bubeck, Nicolo Cesa-Bianchi, and Gábor Lugosi.

Bandits with heavy tail.

*arXiv preprint arXiv:1209.1727*, 2012.

# References V



Sébastien Bubeck, Vianney Perchet, and Philippe Rigollet.  
Bounded regret in stochastic multi-armed bandits.  
*arXiv preprint arXiv:1302.1611*, 2013a.



Sébastien Bubeck, Tengyao Wang, and Nitin Viswanathan.  
Multiple identifications in multi-armed bandits.  
In *ICML (1)*, pages 258–265, 2013b.



Olivier Cappe, Aurelien Garivier, and Emilie Kaufmann.  
pymabandits, 2012.  
<http://mloss.org/software/view/415/>.



Shouyuan Chen, Tian Lin, Irwin King, Michael R Lyu, and Wei Chen.  
Combinatorial pure exploration of multi-armed bandits.  
In *Advances in Neural Information Processing Systems*, pages 379–387, 2014.

# References VI



Eyal Even-Dar, Shie Mannor, and Yishay Mansour.

Action elimination and stopping conditions for the multi-armed bandit and reinforcement learning problems.

*The Journal of Machine Learning Research*, 7:1079–1105, 2006.



Jerome Friedman, Trevor Hastie, and Robert Tibshirani.

*The elements of statistical learning*, volume 1.

Springer series in statistics Springer, Berlin, 2001.



Victor Gabillon, Mohammad Ghavamzadeh, Alessandro Lazaric, and Sébastien Bubeck.

Multi-bandit best arm identification.

In *Advances in Neural Information Processing Systems*, pages 2222–2230, 2011.



# References VII



Victor Gabillon, Mohammad Ghavamzadeh, and Alessandro Lazaric.

Best arm identification: A unified approach to fixed budget and fixed confidence.

*In Advances in Neural Information Processing Systems*, pages 3212–3220, 2012.



Aurélien Garivier and Olivier Cappé.

The kl-ucb algorithm for bounded stochastic bandits and beyond.  
*arXiv preprint arXiv:1102.2490*, 2011.



Mohammad Ghavamzadeh, Shie Mannor, Joelle Pineau, Aviv Tamar, et al.

*Bayesian reinforcement learning: a survey*.  
World Scientific, 2015.

# References VIII



Junya Honda and Akimichi Takemura.

An asymptotically optimal bandit algorithm for bounded support models.

In *COLT*, pages 67–79. Citeseer, 2010.



Kevin Jamieson and Robert Nowak.

Best-arm identification algorithms for multi-armed bandits in the fixed confidence setting.

In *Information Sciences and Systems (CISS), 2014 48th Annual Conference on*, pages 1–6. IEEE, 2014.



Shivaram Kalyanakrishnan, Ambuj Tewari, Peter Auer, and Peter Stone.

Pac subset selection in stochastic multi-armed bandits.

In *Proceedings of the 29th International Conference on Machine Learning (ICML-12)*, pages 655–662, 2012.

# References IX



Tze Leung Lai and Herbert Robbins.

Asymptotically efficient adaptive allocation rules.

*Advances in applied mathematics*, 6(1):4–22, 1985.



Tor Lattimore.

Optimally confident ucb: Improved regret for finite-armed bandits.

*arXiv preprint arXiv:1507.07880*, 2015.



Yun-Ching Liu and Yoshimasa Tsuruoka.

Modification of improved upper confidence bounds for regulating exploration in monte-carlo tree search.

*Theoretical Computer Science*, 2016.



Andrea Locatelli, Maurilio Gutzeit, and Alexandra Carpentier.

An optimal algorithm for the thresholding bandit problem.

*arXiv preprint arXiv:1605.08671*, 2016.

# References X



Shie Mannor and John N Tsitsiklis.

The sample complexity of exploration in the multi-armed bandit problem.

*Journal of Machine Learning Research*, 5(Jun):623–648, 2004.



Subhojyoti Mukherjee, K. P. Naveen, Nandan Sudarsanam, and Balaraman Ravindran.

Thresholding bandits with augmented UCB.

*CoRR*, abs/1704.02281, 2017.

URL <http://arxiv.org/abs/1704.02281>.



Vianney Perchet, Philippe Rigollet, Sylvain Chassang, and Erik Snowberg.

Batched bandit problems.

*arXiv preprint arXiv:1505.00369*, 2015.

# References XI



Herbert Robbins.

Some aspects of the sequential design of experiments.

In *Herbert Robbins Selected Papers*, pages 169–177. Springer, 1952.



Richard S Sutton and Andrew G Barto.

*Reinforcement learning: An introduction*.

MIT press, 1998.



William R Thompson.

On the likelihood that one unknown probability exceeds another in view of the evidence of two samples.

*Biometrika*, pages 285–294, 1933.



David Tolpin and Solomon Eyal Shimony.

Mcts based on simple regret.

In *AAAI*, 2012.

# Thank You