

Advanced Neuro-Granular Architectures for Affective Computing: A Comprehensive Research Plan

Dr. Manan Kumar Gupta

Dr. Abhijit Bhattacharya

Topic: Natural Language Processing for Social Network Data Analysis

Abstract

This document outlines a rigorous research plan for developing novel mood and emotion detection systems using social media data (Reddit, Twitter/X). It proposes a "Neuro-Granular" approach, integrating Deep Learning with Fuzzy Logic and Rough Set Theory to handle the linguistic vagueness and label uncertainty inherent in user-generated content. Five novel methodologies are detailed, including mathematical derivations for differentiable Rough Set layers, Fuzzy-LSTMs, and Sequential Pattern Mining integrated networks.

Contents

1	Introductory Theoretical Framework	3
1.1	Introduction	3
1.2	Theoretical Underpinnings: The Convergence of Symbolic and Connectionist AI	3
1.2.1	The Limitations of Pure Connectionism	3
1.2.2	The Role of Granular Computing	4
1.3	Scope and Objectives	4
2	Research Problem Identification	4
2.1	Research Problem 1 (RP1): Feature Redundancy and High Dimensionality in Raw Text	4
2.2	Research Problem 2 (RP2): Modeling Sequential Emotional Dynamics	5
2.3	Research Problem 3 (RP3): Handling Linguistic Vagueness and Overlapping Classes	5
2.4	Research Problem 4 (RP4): Uncertainty in Graph-Based Social Context	5
3	Comprehensive Data Pipeline: From Collection to Tensors	5
3.1	Data Sources and Collection Strategy	5
3.1.1	Reddit Data Scraping	5
3.1.2	Twitter (X) Data Scraping	6
3.2	Advanced Preprocessing Pipeline	6
3.3	Labeling and Ground Truth Generation	6
4	Novel Methodologies: Theoretical Derivation and Implementation	6
4.1	Method 1: Differentiable Rough Set Attribute Reduction Network (DRSAR-Net)	6
4.1.1	Theoretical Background	7
4.1.2	Mathematical Derivation	7
4.1.3	Neural Network Architecture	7
4.2	Method 2: Fuzzy Logic-Augmented Recurrent Neural Network (FL-RNN)	7
4.2.1	Mathematical Implementation: The Fuzzy Gate	8
4.3	Method 3: Sequential Pattern Mining Integrated Convolutional Network (SPM-CN)	8

4.3.1	Phase 1: Sequential Pattern Mining (SPM)	8
4.3.2	Phase 2: Pattern-to-Image Transformation	8
4.3.3	Phase 3: Convolutional Neural Network (CNN)	8
4.4	Method 4: Hybrid BERT-Fuzzy Inference System (BERT-FIS)	8
4.4.1	Mathematical Implementation: Differentiable Type-2 Fuzzy Layer	9
4.5	Method 5: Graph-Based Emotion Propagation Network	9
4.5.1	Rough Granulation Message Passing	9
5	Algorithmic Implementation Details	9
6	Experimental Evaluation Protocol	9

1 Introductory Theoretical Framework

1.1 Introduction

The digital era has transformed social media platforms into the world's largest repositories of human emotional expression. Platforms like Reddit and Twitter (now X) generate millions of textual data points daily, offering an unmediated stream of public sentiment, individual mood states, and collective emotional reactions to global events. The analysis of this data—Mood and Emotion Detection—has transitioned from a niche academic pursuit to a critical capability for mental health monitoring, crisis management, brand sentiment analysis, and sociological research. However, the computational modeling of human emotion remains fraught with challenges that traditional Deep Learning (DL) architectures struggle to address effectively.

While Deep Learning, particularly through Convolutional Neural Networks (CNNs), Recurrent Neural Networks (RNNs), and Transformer-based Large Language Models (LLMs), has achieved state-of-the-art (SOTA) performance in many Natural Language Processing (NLP) tasks, it fundamentally operates on a connectionist paradigm. This paradigm excels at statistical pattern recognition but often fails to capture the *semantics of uncertainty* inherent in emotional expression. Human emotion is not a discrete, crisp state; it is vague, overlapping, and highly context-dependent. A phrase like "I'm shaking" could indicate fear, excitement, or physical coldness. Standard softmax classification layers force such inputs into mutually exclusive categories, losing the crucial "boundary information" that defines the ambiguity of the state.

This research plan proposes a paradigm shift toward **Neuro-Granular Computing**, a hybrid methodology that integrates the representational power of Deep Learning with the reasoning capabilities of **Granular Computing (GrC)**—specifically **Fuzzy Logic** and **Rough Set Theory (RST)**. Fuzzy Logic provides a rigorous mathematical framework for modeling vagueness (partial truth), while Rough Set Theory offers tools for handling indiscernibility and granulometry of data [1, 2, 3]. By embedding these logic-driven layers directly into differentiable neural architectures, we aim to construct systems that are not only more accurate but also more interpretable and robust to the noisy, unstructured nature of social media text.

1.2 Theoretical Underpinnings: The Convergence of Symbolic and Connectionist AI

The core hypothesis driving this research is that the combination of symbolic uncertainty modeling (Fuzzy/Rough) and connectionist feature learning (Deep Learning) yields a "synergistic intelligence" capable of resolving the limitations of either approach in isolation.

1.2.1 The Limitations of Pure Connectionism

Deep learning models, while powerful, operate as "black boxes." They learn dense vector representations (embeddings) that map inputs to outputs via non-linear transformations. However, they lack explicit mechanisms for handling:

1. **Label Uncertainty:** Social media labels are often noisy or subjective. A post labeled "sad" by one annotator might be labeled "nostalgic" by another. Standard cross-entropy loss assumes a single ground truth, penalizing valid alternative interpretations [4, 5].
2. **Linguistic Ambiguity:** Words have fuzzy boundaries. The distinction between "annoyed" and "angry" is a matter of degree, not a binary switch. DL models typically use crisp activation functions (ReLU) that do not inherently model this gradation [3, 6].
3. **Data Sparsity and Dimensionality:** Text data is high-dimensional. Identifying the minimal subset of features (reducts) that preserve information is computationally expensive.

DL models often rely on massive parameter sets to overcome this, leading to overfitting on smaller, specific emotion datasets [7, 8].

1.2.2 The Role of Granular Computing

Granular Computing (GrC) deals with representing information in the form of aggregates, or "granules."

- **Fuzzy Logic:** Introduced by Zadeh, Fuzzy Logic extends classical Boolean logic to allow for partial membership. In the context of emotion detection, it allows a tweet to belong to the set of "Sad tweets" with membership $\mu = 0.8$ and "Angry tweets" with $\mu = 0.3$. This models the *vagueness* of the emotional content [1, 9].
- **Rough Set Theory:** Introduced by Pawlak, RST handles *indiscernibility*. It defines a set not by a crisp boundary, but by a Lower Approximation (objects certainly belonging to the set) and an Upper Approximation (objects possibly belonging to the set). The region between these approximations is the Boundary Region. This is mathematically ideal for handling the *inconsistency* in social media labeling [2, 10, 11].

1.3 Scope and Objectives

This report details a complete research roadmap for developing five novel Neuro-Granular architectures.

- **Objective 1:** To design a robust data collection and preprocessing pipeline capable of harvesting and normalizing noisy data from Reddit and Twitter.
- **Objective 2:** To mathematically derive and implement three novel emotion detection architectures *without* the use of pretrained models, forcing the learning of features from scratch using hybrid GrC-DL techniques.
- **Objective 3:** To derive and implement two novel architectures *utilizing* pretrained models (e.g., BERT), enhancing their transfer learning capabilities with fuzzy and rough set layers.
- **Objective 4:** To validate these methods using rigorous statistical frameworks, moving beyond simple accuracy metrics to evaluate robustness and interpretability.

2 Research Problem Identification

2.1 Research Problem 1 (RP1): Feature Redundancy and High Dimensionality in Raw Text

Social media text, when converted to vector space (e.g., TF-IDF or One-Hot Encoding), results in massive sparsity. Most features (words) are irrelevant or redundant for emotion classification. Traditional feature selection methods (Filter/Wrapper) are discrete and cannot be easily integrated into the backpropagation of a neural network.

- **Solution Pathway:** We need a *differentiable* feature selection mechanism based on Rough Set Theory that can learn feature importance weights as part of the neural network training process [12, 13].

2.2 Research Problem 2 (RP2): Modeling Sequential Emotional Dynamics

Emotions in text are often constructed through sequences of events or shifts in tone (e.g., "I was worried, but then I felt relieved"). Standard RNNs capture dependencies but do not explicitly mine "frequent emotional patterns." Data mining techniques like Sequential Pattern Mining (SPM) excel at finding these frequent substructures but are typically disjoint from the classification model.

- **Solution Pathway:** Integrating SPM-detected patterns as explicit input channels into a Convolutional LSTM architecture to combine symbolic pattern discovery with sequential learning [14, 15].

2.3 Research Problem 3 (RP3): Handling Linguistic Vagueness and Overlapping Classes

Current multi-label classification approaches often treat classes as independent binary decisions (Sigmoid cross-entropy). They fail to model the *logical relationships* and *fuzzy overlap* between emotions (e.g., Anger often co-occurs with Disgust).

- **Solution Pathway:** Implementing a Fuzzy Inference System (FIS) as the final classification layer, where "rules" are learned to map semantic features to fuzzy emotion sets [6, 16].

2.4 Research Problem 4 (RP4): Uncertainty in Graph-Based Social Context

Social context (who replies to whom) is a strong predictor of emotion (homophily). However, social links are noisy. Not every reply indicates emotional agreement; some indicate conflict. Standard Graph Neural Networks (GNNs) aggregate all neighbors equally or via attention, which may not sufficiently distinguish between "certain" and "uncertain" influences.

- **Solution Pathway:** Using Rough Set Granulation within a GNN to split neighbors into "Lower Approximation" (consistent influence) and "Boundary Region" (uncertain influence) for differential aggregation [17, 18].

3 Comprehensive Data Pipeline: From Collection to Tensors

3.1 Data Sources and Collection Strategy

We will target two primary platforms, Reddit and Twitter (X), due to their distinct communication styles.

3.1.1 Reddit Data Scraping

- **Tooling:** We will utilize the Python Reddit API Wrapper (PRAW) for real-time data and the Pushshift API for historical archives.
- **Target Subreddits:**
 - *High Arousal/Negative:* r/Anger, r/Anxiety, r/politics.
 - *Low Arousal/Negative:* r/Depression, r/Sadness, r/OffMyChest.
 - *High Arousal/Positive:* r/Happy, r/CongratsLikeImFive, r/UpliftingNews.
 - *Neutral/Mixed:* r/AskReddit, r/CasualConversation.

- **Attributes:** `submission_id`, `title`, `selftext` (body), `author_flair`, `upvote_ratio`, `comments` (forest structure), `timestamp`.
- **Volume:** Target of 500,000 posts and 2,000,000 associated comments.

3.1.2 Twitter (X) Data Scraping

- **Tooling:** Tweepy (accessing X API v2 Enterprise or Academic Research track) or SNScrape.
- **Sampling Strategy:**
 - *Keyword-based:* Using emotional anchors (e.g., "I feel sad", "so happy", "furious").
 - *Event-based:* targeting specific timestamps around polarizing events.
- **Attributes:** `tweet_id`, `text`, `created_at`, `retweet_count`, `reply_to_status_id`, `user_description`.

3.2 Advanced Preprocessing Pipeline

1. **Emoji Identification and Substitution:** Emojis are dense emotional carriers. We will map emojis to textual descriptors using the `emoji` library (e.g., 🤔 → [loudly_crying_face]) [19].
2. **Slang and Abbreviation Normalization:** Mapping social media shorthand (e.g., "idk", "smh", "af") to standard English.
3. **Entity Masking:** Named Entity Recognition (NER) will be used to mask entities with [PER], [ORG], [LOC] tokens to prevent bias.
4. **Tokenization:**
 - For Methods 1-3: `nltk.tokenize.TweetTokenizer`.
 - For Methods 4-5: WordPiece (BERT) or BPE (RoBERTa).

3.3 Labeling and Ground Truth Generation

1. **Distant Supervision:** Using hashtags (#sad, #joy) and emojis as weak labels.
2. **Existing Corpora Integration:** GoEmotions (Reddit), SemEval-2018 Task 1 (E-c), and ISEAR.
3. **Active Learning (Gold Standard):** A subset of 10,000 samples will be manually annotated. We will use the **McNemar's Test** to ensure inter-annotator agreement is statistically significant.

4 Novel Methodologies: Theoretical Derivation and Implementation

4.1 Method 1: Differentiable Rough Set Attribute Reduction Network (DRSAR-Net)

Constraint: No Pretrained Models.

Core Innovation: A differentiable layer that performs Rough Set Attribute Reduction (feature selection) via backpropagation.

4.1.1 Theoretical Background

Classical Rough Set Attribute Reduction seeks a "reduct"—a minimal subset of attributes $B \subseteq A$ that preserves the dependency $\gamma_B(D)$ of the decision attribute D [7, 12]. The dependency is defined as:

$$\gamma_B(D) = \frac{|\text{POS}_B(D)|}{|U|}$$

where $\text{POS}_B(D) = \bigcup_{X \in U/D} \underline{B}X$.

4.1.2 Mathematical Derivation

Step 1: Learnable Feature Weights. Let the input be a batch of feature vectors $X \in \mathbb{R}^{N \times M}$. We introduce a weight vector $w \in \mathbb{R}^M$ passed through a sigmoid function to ensure $w_j \in [0, 1]$.

Step 2: Differentiable Indiscernibility Relation. Instead of a crisp equivalence relation, we define a fuzzy similarity matrix $R \in \mathbb{R}^{N \times N}$ based on the weighted Euclidean distance:

$$d_{ij}(w) = \sqrt{\sum_{k=1}^M w_k^2 (x_{ik} - x_{jk})^2}$$

$$R_{ij}(w) = \exp\left(-\frac{d_{ij}(w)^2}{2\sigma^2}\right)$$

Step 3: Soft Lower Approximation. Let C_c be the set of indices of samples belonging to class c . The membership of sample x_i to the lower approximation of class c ($\underline{B}C_c$) is determined by how dissimilar it is to all objects *not* in class c . In classical RST: $x_i \in \underline{B}C_c \iff \forall x_j \notin C_c, (x_i, x_j) \notin \text{IND}(B)$. In our differentiable framework, we use the **SoftMin** operator:

$$\mu_{\underline{B}C_c}(x_i) = 1 - \max_{j \notin C_c} (R_{ij})$$

Using the smooth maximum approximation:

$$\max_{j \notin C_c} (R_{ij}) \approx \frac{\sum_{j \notin C_c} R_{ij} e^{\alpha R_{ij}}}{\sum_{j \notin C_c} e^{\alpha R_{ij}}}$$

Step 4: Dependency Loss. The Rough Set Dependency Loss $\mathcal{L}_{RS}$ aims to maximize the dependency degree γ .

$$\gamma = \frac{1}{N} \sum_{c \in \text{Classes}} \sum_{i \in C_c} \mu_{\underline{B}C_c}(x_i)$$

$$\mathcal{L}_{RS} = 1 - \gamma$$

4.1.3 Neural Network Architecture

- **Total Loss Function:** $\mathcal{L}_{Total} = \mathcal{L}_{CrossEntropy} + \lambda_1 \mathcal{L}_{RS} + \lambda_2 \|w\|_1$

4.2 Method 2: Fuzzy Logic-Augmented Recurrent Neural Network (FL-RNN)

Constraint: No Pretrained Models.

4.2.1 Mathematical Implementation: The Fuzzy Gate

Let x_t be the input word embedding and h_{t-1} be the previous hidden state. The linear projection is:

$$z_t = W_x x_t + W_h h_{t-1} + b$$

Fuzzification Layer: Instead of a sigmoid activation, z_t is passed through a bank of K Gaussian membership functions (MFs) for each neuron j .

$$\mu_{jk}(z_{tj}) = \exp\left(-\frac{(z_{tj} - c_{jk})^2}{2\sigma_{jk}^2}\right)$$

Rule Application (Fuzzy Inference): We use the Takagi-Sugeno-Kang (TSK) zero-order model. The output of the fuzzy gate g_{tj} is the weighted average of the rule consequents q_{jk} :

$$g_{tj} = \frac{\sum_{k=1}^K \mu_{jk}(z_{tj}) \cdot q_{jk}}{\sum_{k=1}^K \mu_{jk}(z_{tj})}$$

RNN Update with Fuzzy Gates:

$$h_t = (1 - g_t) \odot h_{t-1} + g_t \odot \tanh(W_c x_t)$$

4.3 Method 3: Sequential Pattern Mining Integrated Convolutional Network (SPM-CN)

Constraint: No Pretrained Models.

4.3.1 Phase 1: Sequential Pattern Mining (SPM)

We use the **PrefixSpan** algorithm to find frequent emotional subsequences. We select the top K patterns based on Information Gain [14, 15].

4.3.2 Phase 2: Pattern-to-Image Transformation

We transform each document D_i into a binary matrix (Pattern Image) $M_i \in \{0, 1\}^{L \times K}$.

$$M_i[t, k] = 1 \text{ if pattern } p_k \text{ ends at position } t \text{ in } D_i$$

4.3.3 Phase 3: Convolutional Neural Network (CNN)

We apply 1D Convolutions along the time axis with filters of size $3 \times K$.

4.4 Method 4: Hybrid BERT-Fuzzy Inference System (BERT-FIS)

Constraint: Pretrained Model Allowed.

4.4.1 Mathematical Implementation: Differentiable Type-2 Fuzzy Layer

Step 1: BERT Encoding. $e_{BERT} = \text{BERT}(S) \in \mathbb{R}^{768}$.

Step 2: Interval Type-2 Fuzzification. For each dimension x_i , we define Upper ($\bar{\mu}$) and Lower ($\underline{\mu}$) membership functions.

$$\bar{\mu}_{ij}(x_i) = \exp\left(-\frac{(x_i - c_{ij})^2}{2\sigma_{ij}^2}\right), \quad \underline{\mu}_{ij}(x_i) = \exp\left(-\frac{(x_i - c_{ij})^2}{2\sigma_{ij}^2}\right)$$

Step 3: Rule Computation. The firing strength is an interval $[\underline{f}_k, \bar{f}_k]$ computed using the product t-norm.

$$\bar{f}_k = \prod_i \bar{\mu}_{ij}(x_i), \quad \underline{f}_k = \prod_i \underline{\mu}_{ij}(x_i)$$

Step 4: Type-Reduction and Defuzzification.

$$y = \frac{\sum_k \bar{f}_k \theta_k + \sum_k \underline{f}_k \theta_k}{\sum_k \bar{f}_k + \sum_k \underline{f}_k}$$

4.5 Method 5: Graph-Based Emotion Propagation Network

Constraint: Pretrained Model Allowed.

4.5.1 Rough Granulation Message Passing

We separate neighbors $N(v)$ into Lower Approximation $\underline{N}(v)$ (consistent) and Boundary Region $BND(v)$ (conflicting/uncertain) [18].

$$h_{\underline{N}} = \text{AGGREGATE}(\{h_u^{(l)} \mid u \in \underline{N}(v)\})$$

$$h_{BND} = \text{AGGREGATE}(\{h_u^{(l)} \mid u \in BND(v)\})$$

$$h_v^{(l+1)} = \sigma(W_{low} \cdot h_{\underline{N}} + W_{bnd} \cdot h_{BND} + W_{self} \cdot h_v^{(l)})$$

5 Algorithmic Implementation Details

- **Optimizer:** AdamW (Weight Decay 0.01).
- **Loss Function:** Focal Loss: $FL(p_t) = -\alpha_t(1 - p_t)^\gamma \log(p_t)$.
- **Environment:** PyTorch, Hugging Face Transformers, NVIDIA A100.

6 Experimental Evaluation Protocol

- **Metrics:** Micro/Macro F1-Score, Jaccard Index ($J(Y, \hat{Y}) = \frac{|Y \cap \hat{Y}|}{|Y \cup \hat{Y}|}$), Roughness Index.
- **Statistical Significance:** Friedman Test followed by Nemenyi Post-hoc Test; McNemar's Test for pairwise comparison [23].

References

- [1] Zadeh, L. A. (1965). Fuzzy sets. *Information and Control*, 8(3), 338-353.
- [2] Pawlak, Z. (1982). Rough sets. *International Journal of Computer and Information Sciences*, 11(5), 341-356.
- [3] Yao, Y. (2013). Granular computing and sequential three-way decisions. *International Conference on Rough Sets and Knowledge Technology*, 16-27.
- [4] Wang, Y., et al. (2019). Modeling uncertainty in emotion classification: A fuzzy logic approach. *IEEE Transactions on Affective Computing*.
- [5] Zhang, L., et al. (2020). Deep learning for sentiment analysis: A survey. *WIREs Data Mining and Knowledge Discovery*, 8(4).
- [6] Cambria, E., et al. (2017). Sentiment analysis is a big suitcase. *IEEE Intelligent Systems*, 32(6), 74-80.
- [7] Jensen, R., & Shen, Q. (2004). Semantics-preserving dimensionality reduction: Rough and fuzzy-rough set-based feature selection. *IEEE Transactions on Knowledge and Data Engineering*, 16(12), 1457-1471.
- [8] Aggarwal, C. C., & Zhai, C. (2012). *Mining Text Data*. Springer Science & Business Media.
- [9] Zadeh, L. A. (1996). Fuzzy logic = computing with words. *IEEE Transactions on Fuzzy Systems*, 4(2), 103-111.
- [10] Pawlak, Z. (1991). *Rough Sets: Theoretical Aspects of Reasoning about Data*. Kluwer Academic Publishers.
- [11] Yao, Y. Y. (1998). Generalized rough set models. *Rough Sets in Knowledge Discovery*, 1, 286-318.
- [12] Tsang, E. C., et al. (2008). Attributes reduction using fuzzy rough sets. *IEEE Transactions on Fuzzy Systems*, 16(5), 1130-1141.
- [13] Chen, D., et al. (2011). A rough set-based feature selection method for high-dimensional data. *Knowledge-Based Systems*, 24(8), 1263-1272.
- [14] Pei, J., et al. (2001). PrefixSpan: Mining sequential patterns efficiently by prefix-projected pattern growth. *Proceedings of ICDE 2001*, 215-224.
- [15] Fournier-Viger, P., et al. (2016). The SPMF open-source data mining library version 2. *ECML PKDD*, 36-40.
- [16] Jang, J. S. (1993). ANFIS: Adaptive-network-based fuzzy inference system. *IEEE Transactions on Systems, Man, and Cybernetics*, 23(3), 665-685.
- [17] Kipf, T. N., & Welling, M. (2017). Semi-supervised classification with graph convolutional networks. *ICLR 2017*.
- [18] Zhao, J., et al. (2021). Fuzzy-rough graph neural networks. *IEEE Transactions on Fuzzy Systems*.
- [19] Barbieri, F., et al. (2020). TweetEval: Unified benchmark and comparative evaluation for tweet classification. *Findings of EMNLP 2020*.
- [20] Devlin, J., et al. (2019). BERT: Pre-training of deep bidirectional transformers for language understanding. *NAACL-HLT 2019*.

- [21] Liu, Y., et al. (2019). RoBERTa: A robustly optimized BERT pretraining approach. *arXiv preprint arXiv:1907.11692*.
- [22] Velickovic, P., et al. (2018). Graph attention networks. *ICLR 2018*.
- [23] Dietterich, T. G. (1998). Approximate statistical tests for comparing supervised classification learning algorithms. *Neural Computation*, 10(7), 1895-1923.