```html
<!-- define that it is an HTML5 document -->
<!DOCTYPE html>
<!-- <html> tag as the main cardboard box that holds everything on a
webpage. -->
<html lang="en">

<!-- <head> tag contains meta information about the document -->

<head>
    <!-- <meta> tags define metadata about the HTML document -->
    <meta charset="UTF-8">

    <!-- <meta> tag for responsive design -->
    <meta name="viewport" content="width=device-width, initial-
scale=1.0">

    <!-- <meta> tag for website description -->
    <meta name="description" content="Website Description">

    <!-- <meta> tag for keywords -->
    <meta name="keywords" content="HTML,CSS,JavaScript">

    <!-- <meta> tag for author -->
    <meta name="author" content="Your Name">

    <!-- <title> tag defines the title of the document -->
    <title>Document</title>

    <!-- <link> tag for favicon -->
    <link rel="icon" href="favicon.ico">

    <!-- <link> tag for stylesheet -->
    <link rel="stylesheet" href="style.css">
    <link rel="shortcut icon" href="favicon.ico" type="image/x-icon">

</head>

<!-- Body tags -->

<body>
    <!-- Heading Tags - block-level elements -->
    <h1>Hello, World!</h1>
    <h2>This is a subheading.</h2>
    <h3>This is a smaller subheading.</h3>
    <h4>This is an even smaller subheading.</h4>
    <h5>This is a very small subheading.</h5>
    <h6>This is the smallest subheading.</h6>
```

```html
<!-- Paragraph Tag - block-level element -->
<p>This is a paragraph.</p>

<!-- Div Tag - block-level element -->
<div>This is a div element.</div>

<!-- Span Tag - inline-level element -->
<span>This is a span element.</span>
<span>This is a span element 2.</span>

<!-- span inside div -->
<div>this is a div element
    <span>This is a span element.</span>
</div>

<!-- div inside span -->
<span>this is a span tag
    <div>This is a div tag</div>
</span>

<!-- Anchor (Link) Tags -->
<a href="https://google.com" target="_blank">Google</a>

<!-- <a> tag for About page -->
<a href="aloo.html" >Aloo</a>

<!-- <a> tag for phone number -->
<a href="tel:9876543210">Call</a>

<!-- <a> tag for email -->
<a href="mailto:test@gmail.com">Email</a>

<br>
<!-- Text Formatting Tags -->

<!-- <i> tag for italic text -->
<i>This is italic text.</i>
<!-- <b> tag for bold text -->
<b>This is bold text.</b>
<!-- <u> tag for underlined text -->
<u>This is underlined text.</u>
<!-- <em> tag for emphasized text -->
<em>This is emphasized text.</em>
<!-- <s> tag for strikethrough text -->
<s>This is strikethrough text.</s>
<!-- <strong> tag for strong text -->
<strong>This is strong text.</strong>
<!-- <mark> tag for marked text -->
```

```
    <mark>This is marked text.</mark>
    <!-- <small> tag for small text -->
    <small>This is small text.</small>
    <!-- <big> tag for big text -->
    <big>This is big text.</big>

    <br>
    <!-- Image Tag -->
    <img src="" alt="Nature" width="300">


    <!-- Ordered List -->
    <ol type="A">
        <!-- List Items -->
        <li>HTML</li>
        <li>CSS</li>
    </ol>

    <!-- Unordered List -->
    <ul style="list-style: circle;">
        <li>HTML</li>
        <li>CSS</li>
    </ul>


    <!-- Audio and Video Tags -->
    <audio controls>
        <!-- Audio source -->
        <source src="song.mp3">
    </audio>

    <video controls width="250">
        <!-- Video source -->
        <source src="video.mp4" type="video/mp4">
    </video>

    <!-- Iframe Tag -->

<iframe width="560" height="315"
src="https://www.youtube.com/embed/LRNdGU0UlG4?si=HGDF4MGrdYHYJe8n"
title="YouTube video player" frameborder="0" allow="accelerometer;
autoplay; clipboard-write; encrypted-media; gyroscope; picture-in-
picture; web-share" referrerpolicy="strict-origin-when-cross-origin"
allowfullscreen></iframe>


    <!-- Textarea Tag -->
    <textarea rows="4" cols="5">
        This is a textarea.
```

```
    </textarea>



<br>
    <!-- Input & Label Tags -->
    <label for="name">Name:</label>
    <input type="text" id="name" name="username" placeholder="Enter your
name" required>
<br>
    <label for="email">Email:</label>
    <input type="email" id="email" name="useremail" placeholder="Enter
your email" required>
<br>
    <!-- readonly inputs -->
    <label for="city">City:</label>
    <input type="text" id="city" name="city" value="India" readonly>
<br>
    <!-- disabled inputs -->
    <label for="country">Country:</label>
    <input type="text" id="country" name="country" value="India"
disabled>
<br>
    <!-- Password Input -->
    <label for="password">Password:</label>
    <input type="password" id="password" name="password"
placeholder="Enter your password" required>
<br>
    <!-- Number Input -->
    <label for="age">Age:</label>
    <input type="number" id="age" name="age" min="1" max="100">
<br>
    <!-- Telephone Input -->
    <label for="phone">Phone:</label>
    <input type="tel" id="phone" name="phone" placeholder="Enter your
phone number">
<br>
    <!-- URL Input -->
    <label for="website">Website:</label>
    <input type="url" id="website" name="website" placeholder="Enter your
website URL">
<br>
    <!-- Search Input -->
    <label for="query">Search:</label>
    <input type="search" id="query" name="query" placeholder="Search...">
<br>
    <!-- Date Input -->
    <label for="birthdate">Birth Date:</label>
    <input type="date" id="birthdate" name="birthdate">
```

```
<br>
    <!-- Time Input -->
    <label for="appointment">Appointment Time:</label>
    <input type="time" id="appointment" name="appointment">
<br>
    <!-- Datetime Local Input -->
    <label for="datetime">Datetime:</label>
    <input type="datetime-local" id="datetime" name="datetime">
<br>
    <!-- Month Input -->
    <label for="month">Month:</label>
    <input type="month" id="month" name="month">
<br>
    <!-- Week Input -->
    <label for="week">Week:</label>
    <input type="week" id="week" name="week">
<br>
    <!-- Color Input -->
    <label for="color">Color:</label>
    <input type="color" id="color" name="color">
<br>
    <!-- Range Input -->
    <label for="volume">Volume:</label>
    <input type="range" id="volume" name="volume" min="0" max="100">
<br>
    <!-- Checkbox Form -->
    <!--  -->
    <form action="/action_page.php">
        <input type="checkbox" id="vehicle1" name="vehicle1"
value="Bike">
        <label for="vehicle1"> I have a bike</label><br>
        <input type="checkbox" id="vehicle2" name="vehicle2" value="Car">
        <label for="vehicle2"> I have a car</label><br>
        <input type="checkbox" id="vehicle3" name="vehicle3"
value="Boat">
        <label for="vehicle3"> I have a boat</label><br><br>
        <input type="submit" value="Submit">
    </form>

    <!-- Radio Button Form -->
    <!-- action=" "  --   It tells the browser where to send the form
data when submitted.
    In this case, clicking submit sends the user's input to the
/action_page.php script on your server for processing. -->
    <form action="/action_page.php">
        <p>Please select your favorite Web language:</p>
        <input type="radio" id="html" name="fav_language" value="HTML">
        <label for="html">Male</label><br>
```

```
        <input type="radio" id="css" name="fav_language" value="CSS">
        <label for="css">Female</label><br>
        <input type="radio" id="javascript" name="fav_language"
value="JavaScript">
        <label for="javascript">Other</label>

        <!-- produces a line break in text -->
        <br>

        <!-- link break + write horizontal line -->
        <hr>

        <!-- another radio button using numbers -->
        <p>Please select your age:</p>
        <input type="radio" id="age1" name="age" value="30">
        <label for="age1">0 - 30</label><br>
        <input type="radio" id="age2" name="age" value="60">
        <label for="age2">31 - 60</label><br>
        <input type="radio" id="age3" name="age" value="100">
        <label for="age3">61 - 100</label><br><br>
        <input type="submit" value="Submit">
    </form>

    <!-- File Input -->
    <label for="file-upload">Upload File:</label>
    <input type="file" id="file-upload" name="file-upload">

    <!-- Submit Button -->
    <input type="submit" id="submit-btn" value="Register">

    <!-- Reset Button -->
    <input type="reset" id="reset-btn" value="Reset">

    <!-- Standard Button -->
    <input type="button" id="custom-btn" value="Click">

    <!-- Image Button -->
    <input type="image" id="image-btn" src="submit.png" alt="Submit">


    <!-- Table Tag -->
    <table border="1">

        <!-- Table row -->
        <tr>
            <!-- Table headers -->
            <th>Name</th>
            <th>Age</th>
            <th>City</th>
```

```
            <th>class</th>
        </tr>

        <tr>
            <!-- Table data -->
            <td>Hritik</td>
            <td>24</td>
            <td>Delhi</td>
            <td>12</td>
        </tr>

        <tr>
            <td>Sneha</td>
            <td>23</td>
            <td>Lucknow</td>
            <td>11</td>
        </tr>
        <tr>
            <td>Sneha</td>
            <td>23</td>
            <td>Lucknow</td>
        </tr>

    </table>

    <!-- Marquee Tag -->
    <marquee direction="right" scrollamount="5" behavior="scroll"
width="100%" height="100px">
        <h2>Scrolling Text lorem ipsum dolor sit amet</h2>
    </marquee>

    <!-- Dropdown tags -->
    <label for="cars">Choose a car:</label>
    <!-- select tag : used to create a dropdown list -->
    <select name="cars" id="cars">
        <!-- option tag : used to create a dropdown option -->
        <option value="volvo">Volvo</option>
        <option value="saab">Saab</option>
        <option value="mercedes">Mercedes</option>
        <option value="audi">Audi</option>
    </select>

    <!-- some more important tags - you should know-->

    <!-- Header - block-level element -->
    <header>
        <h1>My Website</h1>
    </header>
```

```
    <!-- Navigation - block-level element -->
     <!-- The <nav> tag is used to define navigation links in a document.
-->
    <nav>
        <ul>
            <li><a href="index.html">Home</a></li>
            <li><a href="about.html">About</a></li>
            <li><a href="contact.html">Contact</a></li>
        </ul>
    </nav>

    <!-- Main Content - block-level element -->
     <!-- The <main> tag is used to define the main content of a
document. -->
    <main>
        <!-- Section - block-level element -->
         <!-- The <section> tag is used to define sections in a document.
-->
        <section>
            <h2>Welcome to My Website</h2>
            <p>This is a simple paragraph.</p>
        </section>
    </main>

    <!-- Footer - block-level element -->
     <!-- The <footer> tag is used for the bottom section of a webpage or
a piece of content. -->
    <footer>
        <p>&copy; 2024 My Website. All rights reserved.</p>
    </footer>

    <!-- Aside - block-level element -->
     <!-- The <aside> tag is used for extra information that is not part
of the main story.Think of it like a "side-bar" or a "fun fact" or "ads"
box in a textbook.  -->
    <aside>
        <h2>Related Links</h2>
        <ul>
            <li><a href="https://www.w3schools.com/html/">HTML
Tutorial</a></li>
            <li><a href="https://www.w3schools.com/css/">CSS
Tutorial</a></li>
            <li><a href="https://www.w3schools.com/js/">JavaScript
Tutorial</a></li>
        </ul>
    </aside>
```

```
    <!-- Comments - used to add comments in HTML code using ctrl+/ -->
    <!-- This is a simple comment -->

    <!-- Script Tag -->
    <script src="script.js"></script>
</body>

</html>
```