
Ex. No: 2 **Date: 20.08.24**

Register No.: 230701347 **Name: Subramani A**

Finding Time Complexity of Algorithms

2.a. Finding Complexity using Counter Method

Aim: Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;    int s =1;

    while(s <= n)
    {
         i++;
         s += i;
     }
}
```

Note: No need of counter increment for declarations and scanf() and printf() statements. count variable

Input:

A positive Integer n

Output:

Print the value of the counter variable

Algorithm:

void function(int n){

set count = 0

set i = 1

increment count by 1


```
    set s = 1
    increment count by 1

    while (s <=n){
        increment count by 1
        increment i by 1
        increment count by 1
        set s = s + i
        increment count by 1
     }
    increment count by 1
    print count
}
```

Program:

```
#include<stdio.h>
void function(int n)
{
    int count=0;
    int i=1;
    count++;
    int s=1;
    count++;
    while(s<=n)
    {
        i++;
        count++;
        s+=i;
        count++;
        count++;
    }
```


```
    count++;
    printf("%d",count);
}


int main()
{
    int num;
    scanf("%d",&num);
    function(num);
}
```

Output:

	Input	Expected	Got	
✔	9	12	12	✔
✔	4	9	9	✔

Passed all tests! ✔

2.b. Finding Complexity using Counter Method

Aim: Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and printf() statements. count variable

Input:

A positive Integer n

Output:

Print the value of the counter variable

Algorithm:

```
void func(int n){
   initialize count to 0
   if n = 1{
      increment count by 1
      print "*"
   }
   else{
      increment count by 1
```

```
    // outer loop from 1 to n
    for each i from 1 to n{
        increment count by 1

        // inner loop from 1 to n
        for each j from 1 to n {
            increment count by 1

            // simulate print statements with count increments
            increment count by 1  // first simulated printf("*")
            increment count by 1  // second simulated printf("*")

            // exit inner loop immediately
            increment count by 1  // break statement
        }
        increment count by 1
    }
    increment count by 1
  }
   print count
}
```

Program:

```
#include<stdio.h>
void func(int n)
{   int count=0;
   if(n==1)
   { count++;
```

```
      printf("*");
    }
    else
    {count++;
     for(int i=1; i<=n; i++)
     { count++;
       for(int j=1; j<=n; j++)
       {  count++;
          //printf("*");
          count++;
          //printf("*");
          count++;
          break;
       }
       count++;
     }
     count++;
   }
   printf("%d",count);
}



int main(){
     int n;
     scanf("%d",&n);
     func(n);
}
```

Output:

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔
✔	143	717	717	✔

2.c. Finding Complexity using Counter Method

Aim: Convert the following algorithm into a program and find its time complexity using counter method.

```
 Factor(num) {
 {
    for (i = 1; i <= num;++i)
    {
     if (num % i== 0)
        {
          printf("%d ", i);
        }
     }
  }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:
A positive Integer n
Output:
Print the value of the counter variable

Algorithm:

function Factor(num) {

initialize count to 0

// loop from 1 to num

for each i from 1 to num {

increment count by 1

// check if i is a factor of num

if num modulo i equals 0 {

increment count by 1

// simulate printing i (e.g., printf("%d ", i);)

}

```
        increment count by 1  // end of inner if-statement
    }

    increment count by 1  // after loop completion

    print count
}
```

Program:

```
#include<stdio.h>
void Factor(int num)
{   int count=0;
    for (int i = 1; i <= num;++i)
    {
        count++;
        if (num % i== 0)
        {
            count++;
            //printf("%d ", i);
        }
        count++;
    }
    count++;
    printf("%d",count);
}

int main(){
    int n;
    scanf("%d",&n);
    Factor(n);
```


}

Output:

	Input	Expected	Got	
✔	12	31	31	✔
✔	25	54	54	✔
✔	4	12	12	✔

2.d. Finding Complexity using Counter Method

Aim: Convert the following algorithm into a program and find its timecomplexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and printf() statements. count variable

Input:
A positive Integer n
Output:
Print the value of the counter variable

Algorithm:

function(n) {

initialize count to 0

initialize c to 0

increment count by 1

// outer loop: i goes from n/2 to n-1

for each i from n/2 to n-1 {

increment count by 1

// middle loop: j starts at 1 and doubles each iteration until j < n

for each j starting from 1 and doubling each time (j = 2 * j) until j < n {

increment count by 1

// inner loop: k starts at 1 and doubles each iteration until k < n

```
        for each k starting from 1 and doubling each time (k = k * 2) until k < n {
            increment count by 1
            increment c by 1
            increment count by 1
        }

        increment count by 1  // after inner loop ends
    }

    increment count by 1  // after middle loop ends
  }

  increment count by 1  // after outer loop ends

  print count
}
```

Program:

```
#include<stdio.h>
void function(int n)
{
  int count=0;
  int c= 0;
  count++;
  for(int i=n/2; i<n; i++){
    count++;
    for(int j=1; j<n; j = 2 * j){
      count++;
      for(int k=1; k<n; k = k * 2){
        count++;
```

```
            c++;
            count++;
          }
          count++;
       }
       count++;
   }
   count++;
   printf("%d",count);
}
int main(){
   int n;
   scanf("%d",&n);
   function(n);
}
```

Output:

	Input	Expected	Got	
✔	4	30	30	✔
✔	10	212	212	✔

2.e. Finding Complexity using Counter Method

Aim: Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev = 0, remainder;
   while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and printf() statements. count variable

Input:
A positive Integer n
Output:
Print the value of the counter variable

Algorithm:

function reverse(n) {

initialize count to 0

initialize rev to 0

initialize remainder

increment count by 1 // for initialization

// loop until n is not equal to 0

while n is not equal to 0 {

increment count by 1 // start of loop

remainder = n modulo 10

increment count by 1 // after calculating remainder

```
        rev = rev * 10 + remainder
        increment count by 1  // after updating rev

        n = n divided by 10
        increment count by 1  // after updating n
    }

    increment count by 1  // after loop ends

    // simulate printing rev (e.g., print(rev))
    increment count by 1  // for print statement

    print count
}
```

Program:

```
#include<stdio.h>
void reverse(int n)
{
   int count=0;
    int rev = 0, remainder;
   count++;
   while (n != 0)
    {
        count++;
        remainder = n % 10;
        count++;
        rev = rev * 10 + remainder;
        count++;
```

```
        n/= 10;
        count++;

    }
    count++;
//print(rev);
count++;
printf("%d",count);
}

int main(){
    int n;
    scanf("%d",&n);
    reverse(n);
}
```

Output:

	Input	Expected	Got	
✔	12	11	11	✔
✔	1234	19	19	✔