

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Superscript Text Example</title>
</head>
<body>
<p>The following word uses a <sup>superscript</sup> typeface.</p>
</body>
</html>
```

This will produce the following result:

The following word uses a ^{superscript} typeface.

Subscript Text

The content of a **_{...}** element is written in subscript; the font size used is the same as the characters surrounding it, but is displayed half a character's height beneath the other characters.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Subscript Text Example</title>
</head>
<body>
<p>The following word uses a <sub>subscript</sub> typeface.</p>
</body>
</html>
```

This will produce the following result:

The following word uses a _{subscript} typeface.

Inserted Text

Anything that appears within `<ins>...</ins>` element is displayed as inserted text.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Inserted Text Example</title>
</head>
<body>
<p>I want to drink <del>cola</del> <ins>wine</ins></p>
</body>
</html>
```

This will produce the following result:

I want to drink ~~cola~~ wine

Deleted Text

Anything that appears within `<del>...</del>` element, is displayed as deleted text.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Deleted Text Example</title>
</head>
<body>
<p>I want to drink <del>cola</del> <ins>wine</ins></p>
</body>
</html>
```

This will produce the following result:

I want to drink ~~cola~~ wine

Larger Text

The content of the **<big>...</big>** element is displayed one font size larger than the rest of the text surrounding it as shown below:

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Larger Text Example</title>
</head>
<body>
<p>The following word uses a <big>big</big> typeface.</p>
</body>
</html>
```

This will produce the following result:

The following word uses a **big** typeface.

Smaller Text

The content of the **<small>...</small>** element is displayed one font size smaller than the rest of the text surrounding it as shown below:

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Smaller Text Example</title>
</head>
<body>
<p>The following word uses a <small>small</small> typeface.</p>
</body>
```

```
</html>
```

This will produce the following result:

The following word uses a small typeface.

Grouping Content

The **<div>** and **** elements allow you to group together several elements to create sections or subsections of a page.

For example, you might want to put all of the footnotes on a page within a `<div>` element to indicate that all of the elements within that `<div>` element relate to the footnotes. You might then attach a style to this `<div>` element so that they appear using a special set of style rules.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Div Tag Example</title>
</head>
<body>
<div id="menu" align="middle" >
<a href="/index.htm">HOME</a> |
<a href="/about/contact_us.htm">CONTACT</a> |
<a href="/about/index.htm">ABOUT</a>
</div>

<div id="content" align="left" bgcolor="white">
<h5>Content Articles</h5>
<p>Actual content goes here.....</p>
</div>
</body>
</html>
```

This will produce the following result:

[HOME](#) | [CONTACT](#) | [ABOUT](#)

CONTENT ARTICLES

Actual content goes here.....

The `<span>` element, on the other hand, can be used to group inline elements only. So, if you have a part of a sentence or paragraph which you want to group together, you could use the `<span>` element as follows

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Span Tag Example</title>
</head>
<body>
<p>This is the example of <span style="color:green">span tag</span> and the <span
style="color:red">div tag</span> alongwith CSS</p>
</body>
</html>
```

This will produce the following result:

This is the example of span tag and the div tag along with CSS

These tags are commonly used with CSS to allow you to attach a style to a section of a page.

6. HTML – PHRASE TAGS

The phrase tags have been designed for specific purposes, though they are displayed in a similar way as other basic tags like ****, *<i>*, **<pre>**, and **<tt>**, you have seen in previous chapter. This chapter will take you through all the important phrase tags, so let's start seeing them one by one.

Emphasized Text

Anything that appears within **...** element is displayed as emphasized text.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Emphasized Text Example</title>
</head>
<body>
<p>The following word uses a <em>emphasized</em> typeface.</p>
</body>
</html>
```

This will produce the following result:

The following word uses an *emphasized* typeface.

Marked Text

Anything that appears with-in **<mark>...</mark>** element, is displayed as marked with yellow ink.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Marked Text Example</title>
```

```

</head>
<body>
<p>The following word has been <mark>marked</mark> with yellow</p>
</body>
</html>

```

This will produce the following result:

The following word has been marked with yellow.

Strong Text

Anything that appears within **...** element is displayed as important text.

Example

```

<!DOCTYPE html>
<html>
<head>
<title>Strong Text Example</title>
</head>
<body>
<p>The following word uses a <strong>strong</strong> typeface.</p>
</body>
</html>

```

This will produce the following result:

The following word uses a **strong** typeface.

Text Abbreviation

You can abbreviate a text by putting it inside opening **<abbr>** and closing **</abbr>** tags. If present, the title attribute must contain this full description and nothing else.

Example

```

<!DOCTYPE html>
<html>
<head>

```

```
<title>Text Abbreviation</title>
</head>
<body>
<p>My best friend's name is <abbr title="Abhishek">Abhy</abbr>.</p>
</body>
</html>
```

This will produce the following result:

My best friend's name is Abhy.

Acronym Element

The **<acronym>** element allows you to indicate that the text between `<acronym>` and `</acronym>` tags is an acronym.

At present, the major browsers do not change the appearance of the content of the `<acronym>` element.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Acronym Example</title>
</head>
<body>
<p>This chapter covers marking up text in <acronym>XHTML</acronym>.</p>
</body>
</html>
```

This will produce the following result:

This chapter covers marking up text in XHTML.

Text Direction

The **<bdo>...</bdo>** element stands for Bi-Directional Override and it is used to override the current text direction.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Text Direction Example</title>
</head>
<body>
<p>This text will go left to right.</p>
<p><bdo dir="rtl">This text will go right to left.</bdo></p>
</body>
</html>
```

This will produce the following result:

This text will go left to right.

This text will go right to left.

Special Terms

The **<dfn>...</dfn>** element (or HTML Definition Element) allows you to specify that you are introducing a special term. It's usage is similar to italic words in the midst of a paragraph.

Typically, you would use the `<dfn>` element the first time you introduce a key term. Most recent browsers render the content of a `<dfn>` element in an italic font.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Special Terms Example</title>
</head>
<body>
<p>The following word is a <dfn>special</dfn> term.</p>
</body>
</html>
```

This will produce the following result:

The following word is a *special* term.

Quoting Text

When you want to quote a passage from another source, you should put it in between **<blockquote>...</blockquote>** tags.

Text inside a `<blockquote>` element is usually indented from the left and right edges of the surrounding text, and sometimes uses an italicized font.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Blockquote Example</title>
</head>
<body>
<p>The following description of XHTML is taken from the W3C Web site:</p>

<blockquote>XHTML 1.0 is the W3C's first Recommendation for XHTML, following on
from earlier work on HTML 4.01, HTML 4.0, HTML 3.2 and HTML 2.0.</blockquote>
</body>
</html>
```

This will produce the following result:

The following description of XHTML is taken from the W3C Web site:

```
XHTML 1.0 is the W3C's first Recommendation for XHTML, following on from earlier
work on HTML 4.01, HTML 4.0, HTML 3.2 and HTML 2.0.
```

Short Quotations

The **<q>...</q>** element is used when you want to add a double quote within a sentence.

Example

```
<!DOCTYPE html>
<html>
<head>
```

```
<title>Double Quote Example</title>
</head>
<body>
<p>Amit is in Spain, <q>I think I am wrong</q>.</p>
</body>
</html>
```

This will produce the following result:

Amit is in Spain, I think I am wrong.

Text Citations

If you are quoting a text, you can indicate the source placing it between an opening **<cite>** tag and closing **</cite>** tag

As you would expect in a print publication, the content of the `<cite>` element is rendered in italicized text by default.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Citations Example</title>
</head>
<body>
<p>This HTML tutorial is derived from <cite>W3 Standard for HTML</cite>.</p>
</body>
</html>
```

This will produce the following result:

This HTML tutorial is derived from *W3 Standard for HTML*.

Computer Code

Any programming code to appear on a Web page should be placed inside **<code>...</code>** tags. Usually the content of the `<code>` element is presented in a monospaced font, just like the code in most programming books.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Computer Code Example</title>
</head>
<body>
<p>Regular text. <code>This is code.</code> Regular text.</p>
</body>
</html>
```

This will produce the following result:

Regular text. `This is code.` Regular text.

Keyboard Text

When you are talking about computers, if you want to tell a reader to enter some text, you can use the **<kbd>...</kbd>** element to indicate what should be typed in, as in this example.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Keyboard Text Example</title>
</head>
<body>
<p>Regular text. <kbd>This is inside kbd element</kbd> Regular text.</p>
</body>
</html>
```

This will produce the following result:

Regular text. `This is inside kbd element` Regular text.

Programming Variables

This element is usually used in conjunction with the **<pre>** and **<code>** elements to indicate that the content of that element is a variable.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Variable Text Example</title>
</head>
<body>
<p><code>document.write("<var>user-name</var>")</code></p>
</body>
</html>
```

This will produce the following result:

```
document.write("user-name")
```

Program Output

The **<samp>...</samp>** element indicates sample output from a program, and script etc. Again, it is mainly used when documenting programming or coding concepts.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Program Output Example</title>
</head>
<body>
<p>Result produced by the program is <samp>Hello World!</samp></p>
</body>
</html>
```

This will produce the following result:

Result produced by the program is Hello World!

Address Text

The **<address>...</address>** element is used to contain any address.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Address Example</title>
</head>
<body>
<address>388A, Road No 22, Jubilee Hills - Hyderabad</address>
</body>
</html>
```

This will produce the following result:

388A, Road No 22, Jubilee Hills - Hyderabad

7. HTML – META TAGS

HTML lets you specify metadata - additional important information about a document in a variety of ways. The META elements can be used to include name/value pairs describing properties of the HTML document, such as author, expiry date, a list of keywords, document author etc.

The **<meta>** tag is used to provide such additional information. This tag is an empty element and so does not have a closing tag but it carries information within its attributes.

You can include one or more meta tags in your document based on what information you want to keep in your document but in general, meta tags do not impact physical appearance of the document so from appearance point of view, it does not matter if you include them or not.

Adding Meta Tags to Your Documents

You can add metadata to your web pages by placing <meta> tags inside the header of the document which is represented by **<head>** and **</head>** tags. A meta tag can have following attributes in addition to core attributes:

Attribute	Description
Name	Name for the property. Can be anything. Examples include, keywords, description, author, revised, generator etc.
content	Specifies the property's value.
scheme	Specifies a scheme to interpret the property's value (as declared in the content attribute).
http-equiv	Used for http response message headers. For example, http-equiv can be used to refresh the page or to set a cookie. Values include content-type, expires, refresh and set-cookie.

Specifying Keywords

You can use <meta> tag to specify important keywords related to the document and later these keywords are used by the search engines while indexing your webpage for searching purpose.

Example

Following is an example, where we are adding HTML, Meta Tags, Metadata as important keywords about the document.

```
<!DOCTYPE html>
<html>
<head>
<title>Meta Tags Example</title>
<meta name="keywords" content="HTML, Meta Tags, Metadata" />
</head>
<body>
<p>Hello HTML5!</p>
</body>
</html>
```

This will produce the following result:

```
Hello HTML5!
```

Document Description

You can use <meta> tag to give a short description about the document. This again can be used by various search engines while indexing your webpage for searching purpose.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Meta Tags Example</title>
<meta name="keywords" content="HTML, Meta Tags, Metadata" />
<meta name="description" content="Learning about Meta Tags." />
</head>
<body>
<p>Hello HTML5!</p>
</body>
</html>
```


Document Revision Date

You can use <meta> tag to give information about when last time the document was updated. This information can be used by various web browsers while refreshing your webpage.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>Meta Tags Example</title>
<meta name="keywords" content="HTML, Meta Tags, Metadata" />
<meta name="description" content="Learning about Meta Tags." />
<meta name="revised" content="Tutorialspoint, 3/7/2014" />
</head>
<body>
<p>Hello HTML5!</p>
</body>
</html>
```

Document Refreshing

A <meta> tag can be used to specify a duration after which your web page will keep refreshing automatically.

Example

If you want your page keep refreshing after every 5 seconds then use the following syntax.

```
<!DOCTYPE html>
<html>
<head>
<title>Meta Tags Example</title>
<meta name="keywords" content="HTML, Meta Tags, Metadata" />
<meta name="description" content="Learning about Meta Tags." />
<meta name="revised" content="Tutorialspoint, 3/7/2014" />
<meta http-equiv="refresh" content="5" />
```

```
</head>
<body>
<p>Hello HTML5!</p>
</body>
</html>
```

Page Redirection

You can use <meta> tag to redirect your page to any other webpage. You can also specify a duration if you want to redirect the page after a certain number of seconds.

Example

Following is an example of redirecting current page to another page after 5 seconds. If you want to redirect page immediately then do not specify *content* attribute.

```
<!DOCTYPE html>
<html>
<head>
<title>Meta Tags Example</title>
<meta name="keywords" content="HTML, Meta Tags, Metadata" />
<meta name="description" content="Learning about Meta Tags." />
<meta name="revised" content="Tutorialspoint, 3/7/2014" />
<meta http-equiv="refresh" content="5; url=http://www.tutorialspoint.com" />
</head>
<body>
<p>Hello HTML5!</p>
</body>
</html>
```

Setting Cookies

Cookies are data, stored in small text files on your computer and it is exchanged between web browser and web server to keep track of various information based on your web application need.

You can use <meta> tag to store cookies on client side and later this information can be used by the Web Server to track a site visitor.

Example

Following is an example of redirecting current page to another page after 5 seconds. If you want to redirect page immediately then do not specify *content* attribute.

```
<!DOCTYPE html>
<html>
<head>
<title>Meta Tags Example</title>
<meta name="keywords" content="HTML, Meta Tags, Metadata" />
<meta name="description" content="Learning about Meta Tags." />
<meta name="revised" content="Tutorialspoint, 3/7/2014" />
```