DESIGN SYSTEM AUDIT · READ-ONLY FINDINGS

Numero — Design System Audit

No redesign proposed. This documents what exists today, with file references, so decisions can be made deliberately.

Headline finding: there are three parallel design systems in this codebase, and the one actually rendered to users (`loshu.tsx` + `components/numerology/*`) uses none of the other two consistently. A documented spec (`DESIGN.md`) and a Tailwind token layer (`tailwind.config.js` + `globals.css`) both exist, but most components bypass both and hardcode raw hex values and pixel numbers inline.

0. What's actually running

`app/page.tsx` renders `loshu.tsx`'s default export directly — that 429-line file is the entire app shell (mode/language toggles, both person forms, calculate button, results). It imports and composes components from `components/numerology/*` and `components/forms/PersonForm.tsx`.

Separately, `components/ui/` (Card, Button, Badge, Input) is a small Tailwind-variant component kit — but it's used in exactly **one** place in the whole app: `DriverConductorCard.tsx` imports `Card` but never renders it (dead import — the component builds its own `<div>` instead). `PersonForm.tsx` imports `Input` and `Button` but also never uses them — it hand-rolls its own `<input>` / `<button>` with inline styles instead. So the `ui/` kit is effectively unused dead code today.

Third, `DESIGN.md` at the repo root is a detailed, well-written token spec (colors, type scale, spacing, shadows, component recipes) — but it reads as aspirational documentation, not a build artifact: its "Cosmic Void" gradient (`#0f0720 → #1a0a3d → #0a1628`) matches `globals.css`'s `--gradient-cosmic`, but almost none of its other tokens (e.g. `secondary: #f59e0b` named "warning," font sizes, the `card-padding: 14px` unit) are referenced by class name or variable anywhere in the components read.

1. Colors

Not centralized. Three independent color definitions exist and disagree with each other:

- `tailwind.config.js` — `solar-500: #a855f7` (!) is actually purple, mislabeled "solar," while `leaf-500: #00f5d4` is cyan, not green. `terra-500/600` are pink (`#f472b6` / `#f15bb5`).
- `globals.css` CSS variables — a *different* palette: `--color-solar-500: #f59e0b` (actually gold, as the name implies), `--color-leaf-500: #10b981` (actually green), `--color-terra-500: #bfa094` (an earth tone, not pink). These variables are what `loshu.tsx` actually consumes (`var(--color-mystic-500)` , etc.).
- `DESIGN.md` — a third set again (`secondary: #f59e0b` , `tertiary: #10b981`), roughly matching `globals.css` but with different naming (primary/secondary/tertiary vs. solar/leaf/mystic).

So `bg-solar-500` (Tailwind class, resolves purple) and `var(--color-solar-500)` (CSS variable, resolves gold) are both live in the codebase and mean opposite colors depending on which system a component happens to reach for.

On top of that, most components skip both systems and hardcode hex literally in JS. Observed inline hex values, by rough semantic role:

- Purple/mystic: `#a855f7` , `#7c3aed` , `#c084fc` — used interchangeably as "the purple" across `LoShuGrid.tsx:17` , `NumerologyDashboard.tsx:35` , `PersonForm.tsx:56` , `ChatPanel.tsx:58,125` , `NarrativeCard.tsx:32` , `PersonalYearCard.tsx:19` . Near-duplicates of the same brand purple, never referencing one token.
- Green/success: `#4ade80` (`DriverConductorCard.tsx:17` , `PersonalYearCard.tsx:15`) vs. `#34d399` (`PartnershipScoreCard.tsx:96` , `PlaneBar.tsx:21`) — two different greens used for the same "positive/success" meaning, never reconciled.
- Amber/warning: `#f59e0b` (`PersonalYearCard.tsx:16`) vs. `#fbbf24` (`PartnershipScoreCard.tsx:96`) — same ambiguity.
- Red/error: `#f87171` appears consistently (`DriverConductorCard.tsx:19` , `PartnershipScoreCard.tsx:96` , `PersonalYearCard.tsx:17`) — the one color that's actually stable across files.
- Blue: `#60a5fa` (`DriverConductorCard.tsx:18` , `PlaneBar.tsx:19`).
- One-offs with no reuse: `#94a3b8` and `#c084fc` (both only in `PersonalYearCard.tsx`), `#f472b6` (only in `PlaneBar.tsx:20`).

Additionally, alpha-suffixed template strings like `${color}18` , `${color}44` , `${color}55` , `${color}66` , `${color}77` , `${color}88` appear directly in `DriverConductorCard.tsx` and `LoShuGrid.tsx` — opacity values chosen ad hoc per call site rather than as a defined alpha scale, even though `DESIGN.md` documents a clean text-alpha scale (90/70/50/40/30/20/10%) that isn't actually followed for anything but body text.

Recommendation flag (no action taken): pick one naming system, one hex per role, and delete the other two before any visual work — right now "solar" and "leaf" are landmines because their meaning flips between files.

2. Spacing

`DESIGN.md` documents a real 4px-based scale (4/8/16/24/32/48, plus a `card-padding: 14px` exception). In practice, components mix Tailwind's default spacing scale with arbitrary bracket values freely. Distinct spacing values actually observed in the components read:

```
2px  ·  3px  ·  4px (gap-1)  ·  6px (p-1.5)  ·  7px  ·  8px (gap-2 / p-2)  ·  10px (p-2.5)  ·  11px  ·  12px  ·
 14px (p-3.5, "card-padding")  ·  16px (p-4 / gap-4)  ·  20px  ·  24px (p-6 / gap-6)  ·  32px (p-8 / gap-8)  ·
 40px (mb-10 equivalents in gaps)  ·  48px (gap-12)
```

The dense info cards (`PlaneBar` , `PlanetDayCard` , `RemediesCard` , `HealthCard` , `DriverConductorCard`) consistently use Tailwind's `p-3.5` (14px) as the outer card padding — this one convention actually holds across ~5 files. But nested spacing inside those same cards is inconsistent: mb-1, mb-1.5, mb-2, mb-2.5, mb-3 all appear as "space below a label," with no visible rule for which one applies where (e.g. `DriverConductorCard.tsx` uses `mb-1` , `mb-1.5` , and `mb-2.5` for what look like the same kind of label-to-content gap in different spots).

The app shell in `loshu.tsx` is 100% inline `style={{}}` objects with raw px numbers (`padding:"20px 16px"` , `marginBottom:18` , `gap:8` , `borderRadius:10`) — it doesn't touch Tailwind spacing utilities at all, so the "4/8/16" rhythm documented in `DESIGN.md` is being applied by eye there, not by scale.

3. Typography

Google Fonts are loaded twice — once via `next/font/google` in `layout.tsx` (Orbitron, Inter, JetBrains Mono, exposed as CSS variables) and again via an `@import` URL in `globals.css:5` pulling the same three families from the Google Fonts CDN. Redundant, and the two loading paths could resolve to slightly different weight subsets.

`DESIGN.md` defines a clean 10-step type scale (display/headline-lg/md/title-lg/body-lg/md/sm/label-lg/md/sm/mono). None of the components read use these names. Instead, every text size is a raw Tailwind bracket value or inline px number, and the same visual "role" is styled differently depending on which file you're in:

- **Card micro-labels** ("DRIVER", "Missing", section eyebrows) appear at `9px` , `10px` , and `11px` across `DriverConductorCard.tsx` , `NumerologyDashboard.tsx` , `PlaneBar.tsx` , and `PlanetDayCard.tsx` — no single size for this repeated role.
- **Card titles**text-[12px] font-bold text-white/90 across `PlaneBar` , `PlanetDayCard` , `RemediesCard` , `HealthCard` — this one role is actually consistent.
- **Section headings** vary widely: `NumerologyDashboard.tsx:60` uses `text-xl font-bold` for a person-label heading, `PartnershipScoreCard.tsx:102` uses `text-2xl font-bold` for its card title, and the app's own `<h1>` in `loshu.tsx` is set inline at `fontSize:20,fontWeight:900` — three different sizes for what all read as top-level headings in their respective contexts.
- **Body/insight text** ranges from `text-[9px]` (health advice, remedies detail) to `text-sm` / `text-base` (the dashboard's "inline insight strip") with many intermediate stops (`10px` , `11px` , `12px` , `13px`) and no evident rule for which content gets which size.

The unused `components/ui/` kit does reference the documented type roles somewhat (`CardTitle` uses `font-retro text-lg font-bold`) — but since that kit isn't rendered anywhere, it doesn't help.

4. Radii & shadows

Radii: `rounded-organic` (1.25rem/20px, defined once in `tailwind.config.js`) is the one radius token that's genuinely reused — it appears in `PlaneBar` , `PlanetDayCard` , `RemediesCard` , `HealthCard` , `DriverConductorCard` , `NarrativeCard` , `PersonForm` . That's a real win. But it coexists with untokenized arbitrary radii on nearby elements in the same files: `rounded-xl` (12px), `rounded-2xl` / `rounded-3xl` (16/24px), and bracket values like `rounded-[32px]` in `ChatPanel.tsx:69` and `md:rounded-[32px]` — a one-off that duplicates the already-defined `rounded-bio` (2rem/32px) token instead of using it.

Shadows: `tailwind.config.js` defines three named glow shadows (`glow-solar` , `glow-leaf` , `glow-mystic`), each hardcoding its own rgba rather than deriving from a color variable, and `DESIGN.md` separately lists five (`glow-primary` , `glow-secondary` , `glow-tertiary` , `glow-mystic` , plus `card-elevated` , `chat-bubble` , `soft-lg`) with different rgba values again. In the components actually rendered, glow shadows are almost never referenced by class — they're written inline per component: `0 0 20px rgba(139,92,246,0.5)` (`PersonForm.tsx` / `ChatPanel.tsx` , purple), `0 0 10px rgba(168,85,247,0.4)` (`loshu.tsx` mode toggle), `0 0 16px ${color}55` (`DriverConductorCard.tsx` , parameterized). Same visual effect ("glowing purple halo"), at least four different literal rgba/alpha combinations.

5. Grid / layout

There's a genuine, consistently-applied layout idea in `NumerologyDashboard.tsx` : a `45%/55%` desktop split (`md:grid-cols-[45%_55%]`) collapsing to one column on mobile, with numbered comment blocks marking five sections (Hero, Insights, Action, Timeline, Interactive) — this is the closest thing to a documented layout system in the codebase and it's followed within that one file.

Outside that file, layout logic is ad hoc per component:

- `PartnershipScoreCard.tsx` uses its own `flex-col md:flex-row` + a separate `grid-cols-1 md:grid-cols-2` nested grid for its breakdown/synergy panels — a different column convention than the dashboard's `45/55` split it sits above.
- `ComplementaryCard.tsx:50` introduces a three-step responsive grid (`grid-cols-1 sm:grid-cols-2 lg:grid-cols-3`) not used anywhere else — the only place `sm:` / `lg:` grid breakpoints appear together in one rule.
- The app shell (`loshu.tsx`) uses plain flexbox with inline `gap` values for its toggle rows and form row, unrelated to any grid system below it.

Section ordering within the dashboard (Hero → Insights → Action → Timeline → floating Chat) is fixed and doesn't vary by mode (single vs. couple) except for the Partnership card being prepended in couple mode — that part is consistent.

6. Responsive behavior

Breakpoints used: only Tailwind's default `sm` (640px), `md` (768px), and `lg` (1024px) — no custom breakpoints defined in `tailwind.config.js` . Usage is inconsistent in which breakpoint a given component chooses to switch at:

- `LoShuGrid.tsx:45` scales cell size at `md:` (90px → 110px).
- `ChatPanel.tsx:69` switches its own width at `sm:` (full-width-minus-margin → fixed 350px) — a different breakpoint than the grid uses for its own size change, even though both are "does this get bigger on a wider screen" decisions.
- `ComplementaryCard.tsx:50` uses all three (`sm` , then `lg`) in a single grid rule, skipping `md` entirely — a step pattern not seen elsewhere.
- `NumerologyDashboard.tsx` standardizes on `md:` for every column/direction change in that one file (grid split, flex-row, order/col-start rules) — internally consistent, but again a different single breakpoint than `ChatPanel`'s `sm:` .

Likely mobile issues (from reading, not measured in a live viewport):

- `ChatPanel.tsx` is `fixed bottom-6 right-6` with `z-50` , permanently floating over content — on a small phone viewport with the dashboard's own content also using bottom padding via section gaps, there's no reserved safe-area at the bottom, so the last dashboard section (Timeline: PersonalYearCard/HealthCard) can end up partially covered by the open 350px-tall chat panel with no scroll-margin accounting for it.
- `PartnershipScoreCard.tsx`'s circular score gauge is a fixed `w-48 h-48` (192px) with no responsive size step at all — on narrow phones this is a large fixed-size circle next to text that does wrap, so the gauge doesn't scale down like `LoShuGrid`'s cells do.
- `DriverConductorCard.tsx`'s Driver/Conductor number tiles are fixed `w-[60px] h-[60px]` with no `md:` variant, unlike the Lo Shu grid cells right next to them in the same dashboard column, which do get a mobile→desktop size step — an inconsistency in whether "number tile" sizing responds to viewport.
- The app shell's top toggle row (mode + language pills) in `loshu.tsx` is a flat `display:flex` with inline `flex:2` / `flex:1` ratios and no breakpoint logic — it will always keep both pill groups side by side, even at very narrow widths, since it's plain inline flex rather than a Tailwind responsive class.

Summary table

Area	Centralized?	Notes
Colors	No	3 conflicting palettes (Tailwind config, CSS vars, DESIGN.md); most usage is raw inline hex
Spacing	Partial	14px card padding holds; internal gaps (1–3) inconsistent; app shell is all raw inline px
Typography	No	Documented 10-step scale in DESIGN.md unused; same roles sized differently per file
Radii	Partial	`rounded-organic` genuinely reused; several one-off arbitrary radii alongside it
Shadows	No	Named tokens exist twice (Tailwind + DESIGN.md); real usage is inline rgba, 4+ variants for "purple glow" alone
Grid/layout	Partial	Dashboard's 45/55 split is a real, followed system; other components layout independently
Responsive	Partial	Only default sm/md/lg used, but which breakpoint gates what varies per component; a few fixed-size elements don't respond at all

---

Scope: read `tailwind.config.js` , `globals.css` , `layout.tsx` , `DESIGN.md` , `loshu.tsx` , `components/ui/*` (Card, Button, Input, Badge), `components/forms/PersonForm.tsx` , and 10 of 12 files in `components/numerology/` (LoShuGrid, NumerologyDashboard, PartnershipScoreCard, ChatPanel, DriverConductorCard, PlaneBar, PlanetDayCard, RemediesCard, HealthCard; ComplementaryCard and NarrativeCard read partially via grep).

Not read: ArrowsPanel.tsx, PersonalYearCard.tsx (grepped only), RepetitionCard.tsx, `lib/numerology/*` (pure logic, no styling). No changes were made to any source file.