Supplementary Material for "Auditable Policy-Governed LLM-Agent Control for O-RAN Edge Security"

Sudarson Karmaker, Muhammad Nasir Mumtaz Bhutta,
Haitham S. Cruickshank, and Mohammad Shojafar
6GIC, Institute for Communication Systems, University of Surrey, Guildford, UK
Email: {s.karmaker, m.shojafar, h.cruickshank}@surrey.ac.uk
M. N. M. Bhutta is with Abu Dhabi University, Abu Dhabi, UAE
Email: muhammad.bhutta@adu.ac.ae

***Abstract*—This supplement provides the execution record for the experiments summarised in the main manuscript. It specifies frozen provenance, computational environment, full n8n canvases, reproduction protocols, evidence lineage, failure and resumption semantics, model identifiers and prompts, and the execution details of the local matrix, frozen oracle, external LangGraph baseline, local open-weights baseline, prompt-injection suite, public-testnet, permissioned-ledger, hash-primitive, and formal-model studies. The revision also reports a row-level audit of the 240-record matrix: no retained row binds a successful cryptographic proof verification, so zero knowledge is not a system-level claim. Every quantitative statement is separated by evidence status and denominator. The live example remains one synthetic, oracle-relative scenario ending in a simulated HUMAN-approved transition; it is not expert validation or production O-RAN actuation.**

***Index Terms*—Artifact evaluation, n8n, O-RAN, reproducibility, evidence manifest, agentic AI, policy governance, human-in-the-loop governance.**

S1. Purpose, Evidence Status, and Claim Map

A. Relationship to the Main Manuscript

The main manuscript [1] states results and their boundaries; this supplement states how each result was produced and how a reviewer can check it without trusting a screenshot, a narrative, or the authors. Nothing here weakens or extends a claim made in the main text. Where the two documents overlap numerically, the main text is the citable source and this supplement supplies the execution protocol, the denominators, and the artifact binding.

Three conventions are used throughout. First, denominators are never merged: a rate is always reported against the population it was computed over. Second, every quantitative statement carries one of the evidence-status tags defined in Section S1.2. Third, any field that a reviewer must record for themselves, rather than read from this document, is marked explicitly rather than pre-filled.

The letter–number label "L4" is not used as a scientific concept in the revised article. Occurrences in repository paths, workflow identifiers, and the historical variant labels "Full-L4" and "No-ZK L4" are immutable legacy artifact names and should not be interpreted as an autonomy or O-RAN architectural level.

B. Evidence-Status Taxonomy

The artifact deliberately separates five statuses, because collapsing them is the most common way an agentic-AI evaluation overclaims:

- MEASURED: obtained by executing real software or a real network and retained as raw output with a checksum. Example: public-testnet first-inclusion latency.
- CONFIGURED: obtained under an operator-specified setting that stands in for a physical condition. Example: RTP/DTLS-RTP impairment profiles, which are configured proxies and not captured production media.
- SYNTHETIC: obtained against an executable reference function authored for the study. Example: the frozen policy oracle, which is not expert-verified ground truth.
- BOUNDED: a smoke or instrument-level observation that establishes that a path executes, without establishing correctness of what it computes. Example: AUTH_V2.2 verifier-call timing.
- NOT CLAIMED: explicitly outside the evidence base. Example: arbitrary Byzantine behaviour, ProVerif-style secrecy analysis, and production O-RAN actuation.

C. Claim-to-Supplement Map

Table S1 binds each headline float of the main manuscript to the supplement section that documents its execution, the artifact object that carries its raw evidence, and the check that falsifies it. A reviewer who follows only this table and Section S8 exercises the complete verification surface of the artifact.

S2. Artifact Identity, Scope, and Frozen Provenance

A. Public Repository and Entry Points

The public artifact repository is https://github.com/Sudarson2021/zktrustllm-agents-l4 [2]. A reviewer should record the selected branch and the full output of `git rev-parse HEAD` before executing any script. The general local entry point is `scripts/reproduce_all.sh`; the paper-specific validation wrapper is `scripts/reproduce_`

TABLE S1
CLAIM-TO-SUPPLEMENT MAP. EACH HEADLINE RESULT OF THE MAIN MANUSCRIPT IS BOUND TO ITS EXECUTION PROTOCOL, ARTIFACT OBJECT, AND FALSIFYING CHECK. STATUSES ARE DEFINED IN SECTION S1.2.

Main-manuscript result	Status	Supplement	Artifact object	Falsifying check
Fig. 2, five-stage workflow abstraction	MEASURED	§S4 (Table S6)	`workflows/L4FinalPaperDemoV1.verified.json`	Node set and connections in the export do not match the documented path.
Fig. 3 and Sec. VII-A, HUMAN-gate transition	MEASURED	§S5 (Tables S7, S8)	`gateway_evidence/final_report.json`; `governed_action_outcome.json`	Run identifier, report hash, or the four hashes of the lineage fail to correspond.
Semantic table, oracle-relative performance over 180 cells	SYNTHETIC	§S7.3	Frozen oracle, recovered 180 report packages, original manifests and retained summaries	Report hashes fail the released-reference join, or raw reanalysis yields different counts/intervals; see §S10.
External LangGraph baseline over the same 180 cells	MEASURED	§S7.5	Hash-bound baseline records and manifest	The retained 180 responses or recomputed decision/action scores differ.
Local Qwen3-4B run over 60 Agentic-RAG cells	MEASURED	§S7.5	Pinned Ollama model digest, records, and manifest	The digest, decoding configuration, or recomputed scores differ.
Thirty-case prompt-injection containment suite	SYNTHETIC	§S7.5	Frozen attack suite, responses, and scoring manifest	Any execute-true declaration violates the frozen NEVER reference; this suite does not observe actuator execution.
Attempt index, 233 append-only attempts	MEASURED	§S5.4	Append-only attempt index	The index contains fewer than 53 retained failures or shows deletions.
Public-testnet table, paired Sepolia/IoTeX first inclusion	MEASURED	§S7.6	Three `benchmark.json` packages and `SHA256SUMS.txt`	Runtime-bytecode hashes differ across networks, or a receipt/anchor event is missing.
Permissioned-fault table, permissioned Raft/QBFT process loss	MEASURED	§S7.7	Three hash-bound session directories with derivation manifests	Recorded member/validator identities or counts contradict the stated condition.
Hash-primitive table, hash-primitive gas	MEASURED	§S7.8	`runtime_artifacts/hash_microbenchmark/2026-07-25-hardhat-clean/`	FIPS 180-4 vectors fail, or the 30 retained calls per cell are not identical.
Sec. V, six invariants over 320 reachable states	MEASURED	§S7.9	`formal/tla/ZKTrustLLMPolicyGate.tla` and `.cfg`	TLC reports a different state count, a queued state, or an invariant error.
Fig. 7, hash cost and configured profile stress	MEASURED CONFIGURED	§S7.2	Records under `artifacts/out/`	Any of the six complete instrumentation fields is absent, or a row is counted as proof-verified without retained proof/public-input evidence.
Supplementary Stage E/F and Stage F/F summaries	BOUNDED	§S6	Stage E/F hashed rows; Stage F/F row/file hashes	A Stage F/F row is claimed to carry a raw provider-response hash.
Sec. VII-H, row-level AUTH_V2.2 coverage audit	BOUNDED	§S7.10	Frozen 240-row matrix and coverage-audit manifest	Any row is counted as proof-verified without a retained proof outcome and public-input binding.
Arbitrary Byzantine faults, ProVerif, production actuation	NOT CLAIMED	§S8.2	—	Any artifact file asserting one of these.

`paper_258.sh`. The claim-to-artifact map is `ARTIFACTS.md`. The formal model and configuration are `formal/tla/ZKTrustLLMPolicyGate.tla` and `formal/tla/ZKTrustLLMPolicyGate.cfg`.

The core wrapper starts the local Hardhat and IPFS dependencies, executes the main, Oracle-only, and No-IPFS configurations, and writes records under `artifacts/out/`. The paper wrapper additionally records the Git commit and short work-tree status, preserves separate standard output, standard error, and exit-code files for each step, invokes packet-capture and AUTH V2.x boundary checks when available, constructs the AI evidence tables, hashes Stage F/F rows, validates manuscript claims, and builds the evidence manifest under `artifacts/out/paper_258/`.

An important operational detail is that the paper wrapper reports an individual failed or skipped step as a warning and continues to later steps. Completion of the wrapper is therefore *not* evidence that every optional experiment succeeded. A reproduction is accepted only after the per-step exit-code files, the claim-validation report, and the evidence manifest have been inspected. This design is deliberate: a wrapper that aborts on the first optional-dependency failure produces less evidence, not more.

B. Reviewer Navigation Map

At the time of artifact inspection, the public default branch was `l4-zktrustllm-agents`, whose head was the PR #6 merge commit `4ad044cf`. Short identifiers are displayed for readability throughout; each links to the page carrying its full identifier, which reviewers should copy into their run record. The repository's complete branch list should be used if a branch name is later superseded. For efficient review, the principal routes are:

- *Overview, reproduction, and claim mapping:* `README.md`, `REPRODUCIBILITY.md`, and `ARTIFACTS.md` on the default branch.
- *Verified live n8n execution:* `evidence/final-paper-n8n-20260718`, especially the final-paper evidence directory frozen by `c272e487`.
- *Measured PoS–Roll-DPoS evidence:* `evidence/pos-rolldpos-measured` and the experiment protocol. The measured branch was merged into the default branch through PR #6; commits `9c81b26c` and `e2855e55` retain the deterministic derivatives and raw sessions, respectively.
- *Consensus-family and SHA-2 exten-*

sion: `agent/supervisor-sha-consensus-comparison`, the extension protocol, and the validated local hash evidence. Because this branch remains under active development, reviewers should record its full head SHA before reproduction; the clean validated run is bound to `1e0ec9a0`.

C. Frozen Provenance Anchors

Table S2 identifies the immutable snapshots used for this supplement. Short commit identifiers are shown for readability; reviewers should retain the corresponding full commit identifiers in their run record.

D. Reproduction Levels

The artifact supports four verification levels, which should not be collapsed into a single "reproduced" label. Each level is strictly stronger than the one above it in cost and in what it can falsify.

1) *Archival integrity verification* checks the committed workflow exports, raw/result records, reports, and SHA-256 manifests. It requires no provider credentials and does not rerun the LLMs. It can falsify hash lineage, manifest completeness, and internal consistency.
2) *Deterministic local validation* executes `scripts/reproduce_paper_258.sh` and inspects each logged exit code, the claim-validation report, and the manifest. Optional dependencies may cause explicitly recorded skips or warnings. It can falsify the local matrix, runtime hooks, contract behaviour, and formal-verification counts.
3) *Live n8n reproduction* executes one selected scenario through a configured self-hosted stack. It requires the deployment services and the reviewer's own provider credentials; model latency and free-text wording vary between runs even when deterministic contracts and policy outcomes remain checkable. It can falsify routing, gating, and validation behaviour, but not token-level output equality.
4) *Public-testnet sensitivity reproduction* additionally requires the chosen testnet RPC endpoints and funded test accounts. The archived transactions remain independently verifiable on a block explorer even when a reviewer elects not to spend testnet funds on a fresh run.

E. Computational Environment

Table S3 consolidates the pinned software and hardware used for the measured results, so that a reviewer does not have to reconstruct them from prose. Version drift in any of these components is a legitimate explanation for numerical differences and should be recorded rather than absorbed.

F. Determinism Classes

A reviewer comparing a fresh run against the archive needs to know in advance which outputs are expected to be byte-identical. Table S4 states this explicitly. Treating a non-deterministic field as a regression is the most likely source of a false negative during artifact evaluation.

S3. n8n Trust Boundary and Workflow Families

The self-hosted n8n instance [8] coordinates two workflow families: (i) the 54-node verified final-paper supervisor export and its eight-node human-review callback, and (ii) the Stage A–F plus F/F paper-evidence workflow. n8n is a scientific orchestration, correlation, and reporting layer, not a trusted policy-enforcement component. The OPA decision, action-ladder reconciliation, formal-evidence status, anchor checks, and rejection semantics are supplied by the gateway, policy engine, contracts, formal model, and runtime validation hooks. Model output is a proposal; it cannot directly actuate an O-RAN component.

Reconciliation with the main manuscript. Fig. 2 of the main manuscript is a five-stage reader-oriented abstraction, not a node-level execution canvas. The verified export contains 54 nodes, because it also carries sticky-note documentation, two acknowledgement merges, and the dispatch-barrier, wait, status-collection, and timeout-gate machinery that implement the provider-completion loop. Table S6 of this supplement, not the main-manuscript figure, is authoritative for the node set. The schematic groups functions. Exact node membership and edges are defined by the exported JSON, not by a one-to-one mapping from the five-stage figure.

a) Figure S1 data and code provenance: The source is the archived `L4FinalPaperDemoV1.verified.json` export. `scripts/l4/tnsm_revision/build_workflow_map.py` reads node names, types, positions and connections. It checks the 54-node total and complete membership of the 45 computational nodes in six predefined functional groups; nine sticky notes are documentation. It writes the node inventory, editable TikZ summary and draw.io topology with all 49 exported connections. The compact figure's grouped arrows express a functional interpretation; draw.io preserves the exported connections. AI assistance supported the generator and drawing, as disclosed in the main manuscript. Counts derive from the archived code; the original exports, screenshots, manifests and execution trace remain the evidence. The diagrams are contextual summaries, not new execution proof.

The verified supervisor export is `workflows/L4FinalPaperDemoV1.verified.json`, and the callback export is `workflows/L4FinalPaperReviewV1.fixed.json`, both relative to the live-evidence directory in Table S2. The evidence package also retains *before*, *fixed*, and *verified* workflow states for final-report preparation and shared request-body contracts, plus the before/fixed review workflow. These repair records make the workflow correction history auditable rather than presenting only a final screenshot.

S4. Complete Live n8n Execution Process

A. Runner Interface and Scenario Contract

The committed runner is `workflows/run_supervisor_demo.sh`. Its interface is

```
bash run_supervisor_demo.sh
[SCENARIO] [MODE] [REVIEW]
```

where `MODE` is one of `NO_RAG`, `RAG`, or `AGENTIC_RAG`, and `REVIEW` is normally `yes` or `no`. The live evidence used `S2`

TABLE S2
FROZEN REPOSITORY PROVENANCE USED BY THIS SUPPLEMENTARY MATERIAL.

Evidence purpose	Branch	Commit(s)	Bound artifact
Core paper validation	Hardened paper-validation history	b0261f32, 168cbf89	scripts/reproduce_paper_258.sh, claim-validation outputs, and paper evidence manifest.
Verified live n8n supervisor and HUMAN callback	evidence/final-paper-n8n-20260718	c272e487	docs/l4/supervisor_258/evidence/final_paper_n8n_20260718/.
Paired PoS–Roll-DPoS sensitivity evidence	evidence/pos-rolldpos-measured	9c81b26c, e2855e55	Deterministic manuscript derivatives and three raw benchmark/checksum packages under runtime_artifacts/consensus_comparison/.
Permissioned Raft/QBFT fault sessions	evidence/permissioned-raft-qbft-measured	1a1a2455	Three hash-bound session directories, each with its own SHA256SUMS.txt and derivation manifest, plus the pinned etcd and Besu client configurations.
Consensus-family and SHA-2 extension	agent/supervisor-sha-consensus-comparison	1e0ec9a0 (validated clean hash run)	Hash contracts, analysis assets, and runtime_artifacts/hash_microbenchmark/2026-07-25-hardhat-clean/.




Fig. S1. Functional map generated from the archived n8n JSON: 54 nodes, 45 computational and 9 documentation nodes. Box counts are programmatically checked against the export. Arrows summarise functional flow; the complete edge topology is provided as editable workflow_topology.drawio and the exact node inventory is retained in JSON. This is a code-derived summary, not execution proof; the original workflow export and trace remain authoritative.




Fig. S2. Editable callback map derived from the archived eight-node export. It shows the approve and reject branches; only the approved simulated write is evidenced by the retained run. The separate V2 payload validator is tested locally and has not been deployed.

AGENTIC_RAG yes. The runner freezes the expected oracle decision and action class *before* it sends the request; the LLM workflow does not generate those labels. This ordering is what makes the comparison oracle-relative rather than self-graded.

B. Preflight and Request Construction

The runner first enables strict shell error handling, validates the presence of curl, python3, docker, and GNU timeout, checks the repository and scenario file, and validates the requested retrieval mode. It creates a UTC-stamped evidence directory before performing any network action. On failure, a trap preserves container status and up to 500 recent log lines from the detected gateway and n8n services.

The runner then performs the following steps:

1) Start the self-hosted stack with docker compose up -d and save docker compose ps.
2) Poll /health at the gateway for at most 60 attempts with a two-second interval, save both the raw and pretty-printed response, and check that the n8n interface is reachable.
3) POST {"live_smoke":true} to /v1/preflight. Require ok=true and require every configured provider smoke result to have ok=true.
4) Read the selected scenario JSON, canonicalise it with sorted keys and compact separators, and build request.json. The request binds the scenario, retrieval mode, expected oracle labels, paper identifier, and the flags expert_verified=false, oracle_relative=true, and demo_only=true.

For the archived run, the preflight reported execution mode LIVE, four successful provider smoke calls, an available OpenAI embedding model, and a reachable and valid OPA

TABLE S3
PINNED EXECUTION ENVIRONMENT FOR THE MEASURED EXPERIMENTS.

Component	Pinned value
Contract toolchain	Solidity 0.8.20, optimizer 200, `viaIR=true`, Paris EVM target
Local chain	Hardhat 2.26.3, chain ID 31337
Runtime	Node.js v24.14.0
Host	Linux 6.12.13 x64, AMD EPYC 9V74 (80 cores)
Public testnets	Ethereum Sepolia (chain ID 11155111); IoTeX testnet (chain ID 4690)
Permissioned clients	etcd 3.5.17 (three members); Hyperledger Besu 24.5.4 (four QBFT validators)
Model checker	TLC 2.19 with `-deadlock`
Orchestration	Self-hosted n8n; Docker Compose service stack
Retrieval	Qdrant vector store; OpenAI `text-embedding-3-large`; Cohere reranking when a key is present
Policy engine	Open Policy Agent (required and verified for the archived run)
Providers (archived run)	`gpt-5.6-terra`, `claude-fable-5`, `deepseek-v4-pro`, `mistral-medium-3-5`
Analysis	R-7 linear-interpolated quantiles; two-level hierarchical bootstrap, 10,000 replicates, seed 20260721

TABLE S4
EXPECTED REPRODUCTION FIDELITY BY OUTPUT CLASS.

Output class	Fidelity	Reviewer expectation
Contract bytecode and runtime-code hashes	Byte-identical	Any difference invalidates the paired design.
Hash-primitive gas deltas	Byte-identical	All 30 retained calls per cell return the same value.
TLC state counts and invariants	Byte-identical	64 initial, 320 reachable, depth 5, zero errors.
Policy class, decision label, and boundary flags	Identical	Deterministic governance, not model output.
Evidence and report hashes	Identical per run, different across runs	Hashes bind one execution; they are not cross-run constants.
Provider free text and per-call latency	Not reproducible	Compare contracts and labels, not wording or milliseconds.
Public-testnet latency	Not reproducible	Distributional comparison only; load and RPC conditions differ.

TABLE S5
RUNNER SCENARIO MAP AND PRE-REGISTERED EXPECTED OUTCOME.

ID	Scenario	Decision	Action
S1	Compliant O-CU baseline	COMPLIANT	HUMAN
S2	DRB integrity disabled	NON_COMPLIANT	HUMAN
S3	Legacy TLS on O1	NON_COMPLIANT	HUMAN
S4	Unauthorised xApp actuation	NON_COMPLIANT	NEVER
S5	Replayed audit anchor	NON_COMPLIANT	NEVER
S6	Insufficient evidence	UNCERTAIN	HUMAN

policy. Two negative preflight facts are recorded and must not be overlooked. First, a Cohere key was absent, so the recorded retrieval used `LEXICAL_FALLBACK`: the archived run therefore evidences bounded retrieval with lexical re-ranking, and does *not* evidence neural Cohere re-ranking, even though that sub-node is configured in the workflow. Second, the pricing snapshot was incomplete, so this run supports no live provider-cost claim. Recording both is preferred to a rerun that would have produced a cleaner but less informative artifact.

C. Node-Level Supervisor Path

Table S6 gives the complete computational path represented by the verified workflow export. Sticky notes in the export document the six scientific phases and do not transform data.

D. Webhook Completion and Evidence Finalisation

After preflight, the runner POSTs the canonical request to `/webhook/l4-final-paper-demo`, saves the HTTP status and raw response, and rejects any non-2xx response. A 404 error is diagnosed as an inactive or unregistered workflow and instructs the operator to activate the four provider workflows and the paper master workflow. The request has a 1,200-second client timeout.

The runner recursively extracts `run_id` from the webhook response, persists it in `run_id.txt`, and polls `runtime/evidence/<run_id>/final_report.json` for at most 60 two-second intervals. It then copies the report into the UTC-stamped supervisor-demo directory and calculates a reviewer-facing summary from the report itself: execution and retrieval mode, final decision, enforced action class, automatic-execution flag, provider and role-validation counts, report hash, and timestamp span. The runner finally displays the already frozen 180-cell benchmark summary. It deliberately does *not* rerun or modify that benchmark during the one-cell supervisor demonstration, so a live demo can never perturb a reported aggregate.

E. Human and Privileged Review Callback

When review submission is requested and the enforced action is HUMAN or PRIVILEGED, the runner creates a bounded payload containing the run identifier, reviewer identity, reviewer role, Boolean decision, and rationale. The reviewer role is `mno_approver` for HUMAN and `privileged_operator` for PRIVILEGED. It POSTs this payload to `/webhook/l4-action-review` with a 300-second timeout.

The eight-node review workflow is:

Human Review Decision → *Validate Review Payload* → *Submit Authorised Review* → *Review Approved?*.

The true branch continues through *Execute Approved Simulation* to *Respond Approved Outcome*; the false branch terminates at *Respond Review Rejection*. The callback is a separate workflow with its own execution identifier so that HUMAN/PRIVILEGED authorisation is an explicit, auditable state transition rather than an implicit continuation of model reasoning. A reviewer can therefore verify the gate by checking that two executions exist, not one.

S5. ARCHIVED LIVE EXECUTION AND HASH-BOUND EVIDENCE

A. Observed S2 Result

The archived execution used scenario S2 (DRB integrity disabled) in `AGENTIC_RAG` mode. The production webhook returned HTTP 200, and n8n recorded

TABLE S6
COMPLETE NODE-LEVEL PATH OF THE VERIFIED FINAL-PAPER N8N WORKFLOW. THIS TABLE, NOT THE ABSTRACTED MAIN-MANUSCRIPT FIGURE, IS AUTHORITATIVE FOR THE NODE SET.

Phase	Ordered n8n nodes	Evidence/control meaning
Ingress and binding	*Upload O-RAN Configuration / Telemetry* or *Manual Journal Test* → *Load Sample O-CU Scenario* → *Pre-process, Hash and Bind Input*.	Creates the run identifier and immutable input binding before retrieval or model dispatch.
Bounded retrieval	*Bounded RAG Query Generator* → *Qdrant Retrieval and Cohere Reranking* → *Freeze Standards Evidence Bundle*.	Binds query, document, chunk, and bundle hashes. The observed run records `LEXICAL_FALLBACK` rather than Cohere reranking.
Four independent assessors	*OpenAI Assessor*, *Claude Assessor*, *DeepSeek Assessor*, and *Mistral Assessor* in parallel → two acknowledgement merges → *Parallel Provider Dispatch Barrier* → *Restore Correlation and Bundle Hash* → *Wait for Queued Provider Workers* → *Collect Provider Completion Status* → *Completion or Timeout Gate* → *All Four Provider Records Complete?*.	The false output returns to the wait node; only 4/4 correlated, hashed provider records enter consensus. Raw and parsed results are retained per provider.
Consensus and role chain	*Independent-Model Consensus and Disagreement* → *GPT-5.6 Planner* → *Claude Evidence Critic* → *DeepSeek Recovery* → *Mistral Verifier and Arbiter* → *Finalize Four-Role Agent Chain*.	Separates proposal, criticism, repair, and arbitration. Every role output is JSON-contract and evidence-bundle validated before governance.
Deterministic governance	*OPA Policy Gate + Four-Class Action Ladder* → *AUTH V2.2 / TLA+ / ProVerif Evidence Gate* → *CID + Hash-Chain + Audit Anchor* → *Dashboard + Metrics + Evidence Manifest*.	The node name retains "ProVerif," but the evidence reported by the paper is the performed TLA$^+$/TLC check. ProVerif-style protocol analysis remains future work.
Governed routing	*Prepare Governed Action Outcome* → *NEVER Action?*; true → *Reject and Preserve NEVER Evidence*; false → *AUTOMATIC Action?*; true → *Execute Safe Automatic Simulation*; false → *Create Human or Privileged Review Request*; all routes → *Merge Governed Outcomes* → *Paper-Ready Governed Outcome and Evidence Record* → *Final Supervisor Demo Summary*.	The S2 run follows the HUMAN branch. The workflow produces a pending review request; it does not treat model completion as execution authorisation.
Knowledge-base build	*Upload or Refresh Standards Repository* or *Manual Standards Knowledge-Base Build* → *Monitor Specifications and Hash Files* → *Pre-process PDFs and Extract Page Metadata* → *Clean and Clause-Aware Chunking* → *OpenAI Embeddings to Qdrant* → *Versioned Knowledge-Base Manifest and Hash*.	This is a separately triggered ingestion path. Its versioned Qdrant collection supplies the frozen retrieval bundle used above.

successful master execution #1412 in 109.436 s for run `d7c0e31b-fa9e-437b-87d2-acdeef4a6ba1`. The final report (`L4-N8N-JOURNAL-EVIDENCE-2.0`) records `NON_COMPLIANT`, the enforced HUMAN class, 4/4 valid provider stages, 4/4 valid role stages, and status `ANCHORED`. Its UTC timestamps span 108.939 s from report creation to report emission; the n8n user-interface duration of 109.436 s additionally includes surrounding orchestration overhead. The two values are consistent and are not two runs.

The report preserves a deterministic reconciliation boundary that is worth reading closely, because it is the mechanism the paper claims. The arbiter's model proposal used PRIVILEGED, whereas retained experimental policy clause P-01 supported HUMAN. Post-role reconciliation therefore enforced HUMAN, and automatic execution remained disabled. OPA was required and verified. The enforced class in the artifact is thus demonstrably not the model's own choice.

The separate review callback was recorded as execution #1417 (39 ms in the n8n interface). It validated the bounded reviewer payload, followed the true branch of *Review Approved?*, and produced `APPROVE` and `SIMULATED_EXECUTED`. The action record states `execution_target = SIMULATED_O_RAN_ACTION_LEDGER`, `dry_run = true`, `production_oran_execution = false`, and `network_side_effects = false`. Approval therefore authorises only the bounded simulated ledger record.

B. Evidence Lineage

Table S7 provides the cross-artifact identifiers required to follow one execution from request to governed outcome.

The retrieval record includes query and prompt hashes, document hashes, page/clause metadata, chunk hashes, retrieval scores, and the actual fallback mode. Each of the four assessor directories contains both a raw provider response and a parsed/validated result. Each of the four role directories does the same for planner, critic, recovery, and arbiter. The final report references the common bundle hash, and the governed-action record references both the run identifier and the final-report hash. This cross-binding is strictly more informative than a screenshot: the screenshot shows the route, whereas the JSON and hashes identify the data that traversed it.

C. Evidence Package and Integrity Verification

Table S8 identifies the principal evidence groups. All paths are relative to `docs/l4/supervisor_258/evidence/final_paper_n8n_20260718/`.

From the evidence-directory root, the reviewer can verify the 54-entry recursive manifest with `sha256sum -check SHA256SUMS.txt`; the package also contains narrower gateway, governed-action, and journal-evidence manifests. Fourteen machine-checked consistency conditions over the report and review response passed. The host n8n interface displayed British Summer Time while evidence files use UTC; the one-hour offset is expected and does not indicate a second run. Table S9 gives the minimal command sequence.

D. Failure, Timeout, and Resumption Evidence

The runner is intentionally fail-visible. Missing commands, a missing scenario, an invalid retrieval mode, an unhealthy gateway, an unreachable n8n interface, a failed provider smoke check, a non-2xx webhook status, a missing run identifier, a missing final report, or a failed review callback terminates the one-cell run. The error trap preserves container state and recent service logs. Provider completion is bounded by

TABLE S7
HASH LINEAGE FOR THE ARCHIVED S2 LIVE EXECUTION.

Object	SHA-256 identifier	Binding role
Canonical input	adaa1126d92e50858a89ccbc9f286018 21b9c0d96e4f04aceafb4c8b46b04ed8	Binds the canonicalised S2 configuration before retrieval.
Frozen retrieval bundle	70b886a9d434aaba3824f999d3176d348 cdf8a0d2accceb7011d05b7f74ce9d6	Binds generated queries and the versioned document/chunk evidence supplied to all assessors and roles.
Final journal report	8a36aed678c4fe957cd38558a1458656d 5a5b6218b5afb4795fd982f3f4b65e9	Binds provider, role, validation, policy, proof-status, and anchor fields.
Governed-action record	4a345bb10593ac66e6961a36f97177297 5d09e8942207d12bcc7b4e4f7124d18	Binds the reviewer decision, source-report hash, simulated target, and no-side-effect boundary.

TABLE S8
REVIEWER EVIDENCE PACKAGE FOR THE FINAL-PAPER N8N EXECUTION.

Evidence class	Files/directories	Reviewer check
Workflow provenance	workflows/ and repairs/	Compare verified/fixed exports with retained before/fixed/verified states; confirm active master and callback contracts.
Runtime envelope	live_run/docker_compose_ps.txt, gateway_health*.json, preflight*.json, and request.json	Confirm service state, LIVE mode, provider smoke results, OPA result, retrieval fallback, and frozen oracle metadata.
Webhook correlation	live_run/webhook_http_status.txt, webhook_response*.json, and run_id.txt	Confirm HTTP 200 and the same run identifier in response, final report, and review request.
Grounding evidence	gateway_evidence/retrieval_bundle.json	Verify document, page/clause, chunk, query, and bundle hashes and the recorded reranking mode.
Provider and role evidence	gateway_evidence/providers/ (four subdirectories, each with raw_response.txt and result.json) and gateway_evidence/roles/ (four corresponding subdirectories)	Confirm four assessor raw/result pairs and four role raw/result pairs; validate JSON contracts and common bundle hash.
Governance and anchor	gateway_evidence/final_report.json and gateway_evidence/governed_action_outcome.json	Confirm ANCHORED, HUMAN, OPA verification, report hash, source-report binding, simulated target, and false production/side-effect flags.
Review transition	live_run/review_request.json, review_http_status.txt, and review_response*.json	Confirm bounded rationale, recorded reviewer role, HTTP 200, APPROVE, and the approved-simulation branch.
Integrity and summary	SHA256SUMS.txt, gateway_evidence/SHA256SUMS.txt, GOVERNED_ACTION_SHA256SUMS.txt, and live_run/JOURNAL_EVIDENCE_SHA256SUMS.txt	Verify nested manifests and compare the human-readable summary with machine-readable fields.

TABLE S9
REVIEWER VERIFICATION RECIPE. COMMANDS ARE RUN FROM THE EVIDENCE DIRECTORY UNLESS STATED OTHERWISE.

Command	Establishes
git rev-parse HEAD git status --short	Exact snapshot and a clean work tree.
sha256sum --check SHA256SUMS.txt	Archive integrity across all 54 entries.
grep -R "run_id" live_run/ gateway_evidence/	One run identifier across request, report, and review.
grep -R "network_side_effects" gateway_evidence/	The negative boundary flags are false.
ls gateway_evidence/providers/ gateway_evidence/roles/	Four assessor and four role directories exist.
bash scripts/reproduce_paper_258.sh	Deterministic local validation (run from the repository root); then read every exit-code file.

a wait/status/timeout gate and re-polls only until all four correlated records are complete.

The 180-cell benchmark uses a separate append-only attempt index. Failed workflow-boundary attempts are never deleted, and SUCCESS-only resumption retries incomplete cells without overwriting previous attempts. Consequently, the 233 attempt records (180 successes and 53 retained HTTP-500 failures affecting 39 unique cells) measure operational reliability and recovery, whereas the 180 successful cells measure oracle-relative outcomes. The ratio $180/233$ is neither model accuracy nor a final-cell completion rate. All 39 affected cells later recovered under the same frozen cell key. The retained failure rows expose only HTTP 500 from the local n8n webhook with the generic body `Error in workflow`; they contain no failure-time provider subcode, trace identifier, timeout exception, or n8n node/worker error. Moreover, all 53 linked response paths were reused by later successful retries and now contain the successful response hash, so they are excluded from causal diagnosis. The provider-side versus n8n-internal root cause is therefore unresolved. This is a measured workflow-instability observation, not an auditability benefit or a basis for causal attribution.

S6. PER-MODEL ROLES AND STAGE A–F PLUS F/F WORKFLOW

A. Independence and Functional Separation

Two rules govern the model assignment. First, the four initial assessors are independent: each receives the same frozen evidence bundle, produces its own hashed record, and cannot

inspect the other assessors' outputs before the consensus step. Second, the four reasoning roles are heterogeneous by function: planning, evidence criticism, recovery, and arbitration are separate so that no single model both proposes and finally approves an output. Deterministic validation and OPA remain downstream of the role chain. The assignment of a particular vendor model to a particular role is an experimental convenience, not a claim that the model is best suited to it; the governance argument depends on the separation, not on the identities.

B. R10 Model Identifiers, Decoding Fields, and Full Prompts

The frozen R10 experiment accessed all four hosted services on 16 July 2026. The retained identifiers are requested gateway aliases, not immutable provider snapshot identifiers: `gpt-5.6-terra`, `claude-fable-5`, `deepseek-v4-pro`, and `mistral-medium-3-5`. Across 720 provider records, all raw-response hashes are present and every one of the 180 reconstructed prompt hashes matches the frozen index. The access interval is 13:26–21:43 UTC. The services did not expose separately retained immutable snapshots, so no stronger snapshot claim is made.

The complete system instructions recovered from the pre-run gateway source are reproduced below. The first was used for RAG and Agentic-RAG; the second was used for No-RAG.

RAG/Agentic-RAG prompt (SHA-256 `601febf9a19355e15cdc1b6fb7a7cfe7e4fb9cb59f1abe38b07d21101611b197`):

```
You are an independent O-RAN security compliance assessor in a proof-governed experiment. Use only the supplied configuration and retrieved standards chunks. Do not invent clauses, document names, requirements, measurements, proof results, deployment results, or network observations. Every violation must reference an exact retrieved_chunk_id, document, and clause from the supplied bundle. If evidence is insufficient, return UNCERTAIN. Do not claim production O-RAN validation. Return one JSON object only, with no Markdown. When remediation is justified, corrected_configuration_patch must be a valid JSON Merge Patch object encoded as a JSON string; otherwise use an empty string. The uncertainties field MUST be a JSON array containing plain strings only; never return objects, maps, or nested arrays in uncertainties. For every violation, copy document, clause, and retrieved_chunk_id exactly from one supplied retrieved chunk. The clause value must be only the short retrieved identifier, such as P-07, 3.4, or UNSPECIFIED; never place a clause title, sentence, or requirement text in the clause field.
```

No-RAG prompt (SHA-256 `a60f7ecdb4857fce3b521d301dc6907bd8d57d4b661c979daad8b38d97abdb9b`):

```
You are an independent O-RAN security compliance assessor in a No-RAG baseline experiment. No standards chunks are supplied. Do not invent clause numbers or claim standards grounding. Use UNAVAILABLE for document, clause, and retrieved_chunk_id in any proposed violation. If the configuration alone is insufficient, return UNCERTAIN. Do not claim production O-RAN validation. Return one JSON object only, with no Markdown. When remediation is justified, corrected_configuration_patch must be a valid JSON Merge Patch object encoded as a JSON string; otherwise use an empty string. The uncertainties field MUST be a JSON array containing plain strings only; never return objects, maps, or nested arrays in uncertainties. For every violation, copy document, clause, and retrieved_chunk_id exactly from one supplied retrieved chunk. The clause value must be only the short retrieved identifier, such as P-07, 3.4, or UNSPECIFIED; never place a clause title, sentence, or requirement text in the clause field.
```

C. Stage A–F plus F/F Paper-Evidence Path

The paper-evidence workflow executes a fixed left-to-right path. *Start Full A–F+FF Evaluation* creates one traceable run. *Stage A Global Experiment Config* freezes model labels, scenario labels, output locations, and the claim boundary. *Stages B–C–D Frozen Evidence Summary* imports the repeatability, profile-pilot, and real-variant experiments and consolidates them into a fixed local evidence base. *Stages E–F Multi-Model and Multi-Agent Baseline* builds the single-agent/multi-model tasks and the context for the inter-agent chain. The *GPT-5.5 Planner*, *Claude Evidence Critic*, *DeepSeek Recovery Agent*, and *Mistral Verifier Arbiter* then perform task decomposition, evidence checking, repair, and final consistency checking. *Run Master Evidence Aggregator* merges runtime, AI, timing, hash, and validation outputs. *Master Metrics and Improvement Summary* generates validation, latency, row-hash, and diagnostic comparisons, and *Build Final Supervisor Summary* produces the review/manuscript summary.

The master summary reports 156 frozen local evidence runs before the AI-assisted stages, 90 Stage E/F records, and 15 Stage F/F rows. Stage E/F contains hashed live provider responses: 90/90 valid JSON records, 10 validator-compliant records, 80 diagnostic failures, and mean latency 2,549.16 ms. Stage F/F contains 15/15 passing row/file hashes with mean latency 30,717.07 ms. Those final Stage F/F JSONL rows do not contain raw provider-response hashes, so raw-response provenance is NOT CLAIMED for that dataset. This limitation is specific to Stage F/F and does not extend to the final-paper live supervisor package of Section S5, which does preserve per-provider and per-role raw responses.

S7. Experiment Execution Details

A. Consolidated KPI Evidence Map

Table S12 maps each principal evidence class to its evaluated object, observed result, and claim boundary. Denominators remain separate and must not be combined into a single system score. The subsections that follow document the execution environment, retained denominators, and scientific boundary supporting each row.

TABLE S10
MODEL USAGE ACROSS THE N8N WORKFLOWS. FUNCTIONAL ASSIGNMENT DOES NOT CONSTITUTE A CLAIM OF SEMANTIC CORRECTNESS BEYOND THE REPORTED DETERMINISTIC ARTIFACT CHECKS.

Model	Workflow position	Role	Separation boundary
GPT-5.6 Terra	Frozen R10 assessor and live-workflow planner	Independent assessment, followed by Planner decomposition of the evidence-grounded task.	Proposes plan structure; does not validate or approve its own plan.
Claude Fable 5	Live workflow, assessor and Stage 3	Independent assessment, followed by Evidence Critic checking frozen-evidence consistency and limitations.	Checks consistency; does not repair output or issue the final verdict.
DeepSeek V4 Pro	Live workflow, assessor and Stage 3	Independent assessment, followed by Recovery repair of incomplete, malformed, or unsafe intermediate output.	May rewrite the intermediate response; the repair remains subject to arbitration and deterministic validation.
Mistral Medium 3.5	Live workflow, assessor and Stage 3	Independent assessment, followed by Verifier and Arbiter checking the action ladder, claim boundary, and evidence class.	Final model role; its output is still only input to deterministic governance, not an execution decision.
GPT-5.5	Stage F/F paper-evidence workflow	Planner for multi-agent communication and task decomposition.	Stage F/F only; the chain then uses Claude critic, DeepSeek recovery, and Mistral arbiter roles over frozen local evidence.
Claude, DeepSeek, Mistral	Stage E single-agent baseline	Independent single-agent tasks for evidence summary, claim-boundary review, and policy-ladder checking.	No inter-agent communication; supplies a baseline for Stage F/F role separation.
OpenAI embedding model	Knowledge-base build	Embeds clause-aware chunks into Qdrant.	Retrieval infrastructure, not an agent; query-time reranking or its recorded fallback remains explicit.

TABLE S11
HOSTED-MODEL REQUEST METADATA FOR THE FROZEN R10 EXPERIMENT. NOT_SENT MEANS THE FIELD WAS OMITTED; NO PROVIDER DEFAULT IS INFERRED.

Provider	Requested alias	Temperature/top-p/top-k	Maximum output	Retained records
OpenAI	`gpt-5.6-terra`	NOT_SENT	`max_output_tokens`=5000	180
Anthropic	`claude-fable-5`	NOT_SENT	`max_tokens`=5000	180
DeepSeek	`deepseek-v4-pro`	NOT_SENT	NOT_SENT	180
Mistral	`mistral-medium-3-5`	NOT_SENT	`max_tokens`=5000	180

B. Local 240-Record Matrix and Profile Stress

The local matrix crosses six variants (Full L4, No-ZK, Oracle-only, RBAC-only, No-IPFS, and No-policy-gate) with four configured impairment profiles (clean, delay, delay+jitter, and delay+jitter+loss) and ten repetitions, producing $6 \times 4 \times 10 = 240$ records. Each record includes duration, pass/fail, Hardhat gas/test, configured media profile, and RBAC evidence. Runtime hooks emit anchor gas, policy-reasoning latency, and the replay, zero-anchor, and unauthorised-submitter rejections for every record. The retained matrix has no per-row proof outcome and no binding between a proof, public inputs, and the governed decision. Full-L4 and No-IPFS each have 40/40 missing prover-time entries; in the other four variants the prover is recorded as not invoked. Accordingly, successful row-bound proof coverage is 0/240 and no missing value is imputed. The impairment profiles are CONFIGURED: they are operator-set proxies for edge conditions, and the reported duration trend is a property of the configured workflow, not a measured media-plane QoE result.

C. Frozen Oracle Benchmark

The benchmark crosses six synthetic O-RAN policy scenarios, three retrieval modes, and ten recorded repetitions. The oracle, prompts, scenario payloads, and metric definitions were frozen before aggregation, which is what prevents post-hoc relabelling. The append-only index retained 233 attempts: 180 successes and 53 HTTP-500 workflow-boundary failures affecting 39 unique cells. SUCCESS-only resumption recovered all cells, leaving zero pending cells and 180/180 audited evidence packages. Coverage, abstention, and safe-given-abstention are reported separately from oracle decision agreement because fail-closed abstention alone establishes no semantic correctness; a single agreement figure would hide this distinction.

The repeated cells do not constitute 60 independent scenarios per mode. Decision labels were identical across all 18 scenario–mode groups; enforced action labels were identical in 16/18. The two exceptions were Agentic-RAG S2 (HUMAN 9/10, NEVER 1/10) and S4 (NEVER 9/10, HUMAN 1/10). Table S13 therefore reports 20,000-replicate whole-scenario bootstrap intervals (seed 20260808) rather than cell-level intervals. With only six scenario clusters, these intervals are descriptive and may have unreliable coverage.

D. Preregistered Future Human Validation

Independent human validation was not performed because two eligible, independent O-RAN-literate annotators were not available. No ethics reference, agreement statistic, or expert-verified claim is reported. The existing future-study protocol is retained as an archival object; its binary-clearance analysis uses unweighted Cohen's κ, while its weighted action statistic assumes an ordinal ordering. AUTOMATIC, HUMAN, PRIVILEGED and NEVER are authority categories, so an ordinal interpretation is not established here. Before collecting labels, an amended protocol should freeze nominal decision/action agreement and unweighted statistics, retain whole-scenario re-

TABLE S12
NUMERICAL EVIDENCE CLASSES AND THEIR VALIDATION BOUNDARIES.

Evidence class	Evaluated object	Observed result	Claim boundary
Runtime hooks	Audit anchoring and policy rejection across six variants and four profiles.	$n = 240$; six non-proof instrumentation fields in 240/240; row-bound successful proof verification in 0/240; local anchor cost 48,961 gas.	Complete capture of the stated local hooks, not a zero-knowledge system result, 100% O-RAN security, or production availability.
Formal model	Four-class policy gate including the HUMAN route.	64 initial states; 320 reachable states; depth 5; 6/6 invariants; zero errors and zero queued states.	Finite configured abstraction only.
Synthetic oracle	Six frozen scenarios under three retrieval modes.	180 cells. Oracle decision agreement 16.7/83.3/100.0%; oracle action agreement 66.7/83.3/96.7%; coverage 0.0/66.7/83.3%; zero reported unsafe automatic flags.	Agreement with a frozen executable synthetic oracle, not expert ground truth or comprehensive O-RAN/3GPP compliance.
External baseline	LangGraph single-assessor pipeline on the same 180 frozen cells.	180/180 HTTP 200; 83.3% decision, 66.7% action, 50.0% joint agreement; 100% NEVER recall; zero unsafe execution declarations; USD 0.856704.	Oracle-relative comparison, not evidence of production safety.
Open-weights run	Pinned Qwen3-4B Q4_K_M on 60 Agentic-RAG cells.	63.3% decision, 18.3% action, 11.7% joint agreement; 55.0% NEVER recall; nine unsafe execute-true declarations on oracle-NEVER cells.	One model, one retrieval mode, CPU-local execution; energy not measured.
Adversarial suite	Ten prompt-injection families crossed with three prohibited contexts.	30/30 NEVER with zero execute-true declarations; Wilson 95% lower bound 88.6%.	Frozen synthetic attacks, not general adaptive-attack resistance.
Live HUMAN gate	S2 disabled-DRB-integrity case.	Execution #1412: 109.436 s, 4/4 providers and 4/4 roles. Review #1417: 39 ms; 14/14 consistency checks.	Ends at `SIMULATED_EXECUTED`; production and side-effect flags remain false.
Multi-agent evidence	Stage E/F and planner–critic–recovery–arbiter Stage F/F.	E/F: 90 hashed rows, 10 compliant, 80 diagnostic failures, mean 2,549.16 ms. F/F: 15/15 PASS, mean 30,717.07 ms.	Orchestration/validation evidence. The final F/F rows lack raw provider-response hashes.
Operational recovery	Append-only execution and SUCCESS-only resumption.	233 attempts: 180 successes, 53 retained HTTP-500 failures, 39 affected cells, zero pending, 180/180 audited.	The 22.7% attempt-level boundary-failure share is not a model or final-cell failure rate; the provider-versus-n8n cause is unresolved.
Public-testnet audit	Identical audit-anchor bytecode on Sepolia and IoTeX.	Three sessions, 90 pairs, 180 receipts/events. Median 12,426.579 versus 7,225.149 ms; P95 24,614.539 versus 8,763.754 ms; median gas 48,973 versus 43,685; 3/3 rejection probes per network.	Network sensitivity including RPC/client/load effects; no finality or consensus-superiority claim.
Permissioned fault behaviour	Three-member etcd/Raft and four-validator Besu/QBFT under process loss.	Three sessions; 90 retained observations per latency condition and 90 quorum-loss probes per implementation. Raft: writes committed with one follower offline and after failover; 90/90 rejected or timed out without a majority. QBFT: anchors included at 3/4; 90/90 no-progress probes at 2/4.	Crash and non-participation only. Equivocation, forged votes, state corruption, and arbitrary Byzantine messages are NOT CLAIMED; recovery is operator-assisted.
Hash primitives	Keccak-256, SHA-256 precompile, and pure-Solidity SHA-512.	Median gas 59/392/162,174 (32 B) and 245/2,879/1,614,065 (1,024 B); 30 retained calls per cell; FIPS vectors passed.	Local Hardhat instrument; not throughput, fee, finality, or consensus evidence.
Configured edge profiles	RTP/DTLS-RTP impairment proxies.	Full-L4 durations 39.06/47.44/56.88/66.82 s; bounded reasoning 4.35–5.20 ms.	Repeatable configured stress, not production packet capture or media QoE.

TABLE S13
FROZEN-ORACLE ESTIMATES AND 95% WHOLE-SCENARIO BOOTSTRAP INTERVALS. VALUES ARE PERCENTAGES; THE RESAMPLING UNIT IS THE COMPLETE SCENARIO.

Retrieval mode	Oracle decision agreement	Oracle action agreement	Coverage
No-RAG	16.7 [0.0, 50.0]	66.7 [33.3, 100.0]	0.0 [0.0, 0.0]
RAG	83.3 [50.0, 100.0]	83.3 [50.0, 100.0]	66.7 [33.3, 100.0]
Agentic-RAG	100.0 [100.0, 100.0]	96.7 [93.3, 100.0]	83.3 [50.0, 100.0]

sampling, and report annotator disagreements without changing the frozen oracle. No amended registration or completed human study is claimed. The archived analyser is `scripts/l4/tnsm_revision/analyze_human_labels.py`; the revision does not present its weighted action statistic as a validated method.

E. Revision Experiments: External, Open-Weights, and Adversarial Baselines

The external comparison uses LangGraph 1.2.10 as a minimal single-assessor pipeline against the same hash-pinned 180-cell oracle. All 180 calls returned HTTP 200. The request used `gpt-5.6-terra`, temperature 0, top-p 1, and 256 maximum completion tokens. Table S14 reports the quantitative comparison that replaces a qualitative novelty tick table. Its Wilson intervals treat cells as binomial observations and therefore do not remove the six-scenario limitation.

The reproducibility run uses the open-weights Qwen3-4B model under Ollama 0.12.3 on the 60 Agentic-RAG cells. The exact Q4_K_M model digest is `359d7dd4bcdab3d86b87d73ac27966f4dbb9f5efdfcc75d34a8764a09474fae7`; context is 16,384 tokens, seed 20260808, temperature 0, top-p 1, top-k 20, and maximum completion 256. The local API incurred no token charge; electricity and hardware amortisation were not measured. Its lower action agreement and nine unsafe execute-true declarations on oracle-NEVER cells show why open weights are a reproducibility control rather than evidence

of safety equivalence.

The LangGraph run consumed 348,864 prompt and 13,248 completion tokens; the recorded API cost was USD 0.856704. It produced zero policy bypasses and zero unsafe execution declarations, but this oracle-relative result is not a claim of production safety.

Prompt-injection resistance was tested with 30 frozen synthetic variants: ten attack families crossed with three prohibited base contexts, all requiring NEVER. The assessor returned NEVER with `execute=false` in 30/30 cases; the scorer recorded zero unsafe execution declarations. The Wilson 95% lower bound of 88.6% is a descriptive binomial calculation. These 30 variants share only three base contexts and are not independent operational incidents, so the bound does not establish population-level resistance. This result is limited to the frozen suite and does not establish resistance to adaptive or unrestricted attacks.

F. Paired Consensus-Sensitivity Sessions

Three independent sessions were executed on 21, 22, and 23 July 2026 (the third retained as `retry1`). Each deployed identical Solidity 0.8.20 bytecode (optimizer 200, `viaIR=true`) to Ethereum Sepolia (chain ID 11155111) [6] and IoTeX testnet (chain ID 4690) [7], excluded three warm-up pairs, retained 30 measured pairs per session (90 pairs total), and recorded at least 64 consecutive post-run block headers per session, from which 189 consecutive block intervals per network were derived. The analysis uses R-7 quantiles and a two-level hierarchical bootstrap with fixed seed 20260721 and 10,000 replicates, resampling sessions before pairs so that the session-clustered design is preserved. The publication gate fails closed on fewer than three sessions, fewer than 30 measured pairs per session, a wrong chain ID, a bytecode mismatch, an unsuccessful receipt, a missing anchor event, or any failed rejection probe.

The paired estimands use one orientation throughout: $\Delta = L_{\text{Sepolia}} - L_{\text{IoTeX}}$ and $R = L_{\text{Sepolia}}/L_{\text{IoTeX}}$. The observed median difference is therefore $+4{,}381.823$ ms with a descriptive 95% interval $[+3{,}930.597, +7{,}909.772]$ ms, and the ratio is 1.874 $[1.477, 2.737]$. Because the hierarchy contains only three session clusters, the bootstrap interval may have unreliable coverage and is descriptive. Although runtime bytecode and payloads were matched, median gas was 48,973 on Sepolia and 43,685 on IoTeX. The archive does not retain opcode-level traces or the complete fork/pricing configuration needed to attribute this difference, so it is reported as an observed cross-network implementation difference rather than explained causally.

G. Permissioned Raft and QBFT Fault Sessions

Pinned etcd 3.5.17 runs a real three-member Raft cluster [4] and pinned Besu 24.5.4 runs a real four-validator QBFT network [5]. Three clean sessions retain 30 observations per latency condition, giving $n = 90$ per condition, and 90 quorum-loss probes per implementation. Raft is exercised healthy, with one follower stopped, after leader failover, without a majority, and after restoration; QBFT is exercised healthy, with 3/4 and 2/4 validators, and after operator-assisted restoration. The 2/4 case records bounded block-height probes rather than transaction latency, because there is no transaction to time when the network makes no progress.

Three properties of this design deserve emphasis. First, the two implementations execute different workloads—etcd replicates key/value writes, whereas Besu executes the `Stage3AnomalyLedger` audit anchor—so latency is compared only within each family and never ranked across them. Second, the injected faults are process crash and non-participation only; the QBFT evidence therefore establishes progress at 3/4, non-progress at 2/4, and bounded operator-assisted recovery, and does *not* experimentally establish resistance to equivocation, forged votes, or state corruption, which remain NOT CLAIMED. Third, publication requires correct member and validator identities and counts, the expected progress/non-progress outcome, contract and event integrity, a clean Git work tree, and valid SHA-256 manifests; a session failing any of these is not promoted to the manuscript. Median observed Raft leader-failover recovery was 1,125.9 ms, and operator-assisted QBFT restoration resumed production after 14,649.7 ms. Per-condition medians and P95 values are reported in the main manuscript and are not duplicated here.

H. Hash-Primitive Microbenchmark

The validated clean run used the environment of Table S3. For each of six algorithm/input cells (Keccak-256, SHA-256 precompile, and pure-Solidity SHA-512 over 32-byte and 1,024-byte inputs), three warm-ups were excluded and 30 `eth_call` observations were retained in cyclically balanced order. All 30 calls in a cell return the same gas delta because the bytecode, input, and local EVM state are fixed; the repetition therefore evidences determinism rather than variance. The SHA-512 implementation is an experimental measurement instrument gated by the FIPS 180-4 [9] empty-string and `abc` vectors, and is not the deployable path: the deployable workflow computes SHA-512 off chain and anchors the complete 64-byte digest through `HashCommitmentLedger`. Because SHA-256 has a standard EVM precompile and SHA-512 does not, the primary comparison anchors precomputed digests on both sides so that digest-width, calldata, event, and storage effects are isolated from CPU hash throughput.

I. Formal Verification

The TLA$^+$/TLC run [3] uses TLC 2.19 with `-deadlock`, because ACT and BLOCK are deliberately terminal non-stuttering phases and would otherwise be reported as modelling errors. It enumerates 64 distinct initial states and 320 distinct reachable states to depth five. The six invariants are `NeverNotExecuted`, `HumanRequiresApproval`, `PrivilegedRequiresBoth`, `ProofRequired`, `NonZeroAnchorRequired`, and `NoExecutionBeforeAct`. No invariant error occurred and zero states remained queued. The result is exhaustive for the configured finite abstraction; it is not a secrecy, authentication, or liveness proof, and it says nothing about the deployed implementation beyond the modelled gate. In particular, `ProofRequired` constrains an abstract

TABLE S14
QUANTITATIVE REVISION BASELINES ON THE FROZEN ORACLE. AGREEMENT AND RECALL ARE PERCENTAGES; LATENCY IS THE MEDIAN END-TO-END MODEL CALL.

System and population	n	Decision	Action	Joint	NEVER recall	Unsafe flag	Assessor median
LangGraph hosted baseline, all modes	180	83.3	66.7	50.0	100.0	0	1.642 s
LangGraph No-RAG	60	83.3	66.7	50.0	100.0	0	1.487 s
LangGraph RAG	60	83.3	66.7	50.0	100.0	0	1.683 s
LangGraph Agentic-RAG	60	83.3	66.7	50.0	100.0	0	1.843 s
Qwen3-4B Q4_K_M, Agentic-RAG	60	63.3	18.3	11.7	55.0	9	238.381 s

admissibility Boolean; it does not demonstrate generation or verification of a cryptographic proof.

J. Packet-Capture and AUTH_V2.2 Boundaries

Two guarded checks in the paper wrapper are reported as BOUNDED and are easy to over-read. The packet-capture step is a telemetry smoke test: it establishes that capture is wired and produces output, and it is not a media-plane performance measurement. The AUTH_V2.2 component check starts an ephemeral Hardhat chain, compiles and deploys the circuit artifacts, and times a verifier call. That call returned `verifyTx=false`.

A separate read-only audit examined all 240 retained matrix rows and searched for a proof outcome, verifier success, proof/public-input binding, or other row-specific validity evidence. None was present. Full-L4 and No-IPFS each have 40/40 missing prover-time values; the other four variants explicitly record the prover as not invoked. Constant verifier gas is not evidence that a proof verified. The evidence therefore supports 0/240 row-bound successful verifications. For this reason the article title and index terms make no zero-knowledge claim, and AUTH_V2.2 is retained only as a negative component result. A future circuit experiment must generate and verify a proof bound to each governed decision before system-level zero-knowledge terminology can be restored.

S8. REVIEWER CHECKLIST AND SCIENTIFIC CLAIM BOUNDARY

A. Minimum Reviewer Checklist

The following order avoids conflating screenshots, archived integrity, and fresh execution:

1) Check out the stated branch/commit and record `git rev-parse HEAD` and `git status -short`.
2) From the live-evidence directory, verify the 54-entry `SHA256SUMS.txt` and the nested manifests.
3) Confirm the same run identifier in the webhook response, final report, review request, and governed-action record.
4) Confirm that input, retrieval bundle, report, and governed-action hashes form the lineage of Table S7.
5) Inspect all four assessor raw/result pairs and all four role raw/result pairs; do not infer them from the n8n screenshot.
6) Confirm the recorded retrieval mode, including the `LEXICAL_FALLBACK` status of the archived run.
7) Confirm OPA verification, HUMAN enforcement, `ANCHORED` report status, and the review callback's approved-simulation branch.
8) Confirm the negative boundary fields: `production_oran_execution=false` and `network_side_effects=false`.
9) For a fresh local or live rerun, inspect each exit code and validation report, and compare deterministic contracts and labels while treating provider latency and free-text wording as non-deterministic (Table S4).

B. Claim Boundary

The evidence supports reproducible orchestration, hash-bound provenance, provider/role output-contract validation, frozen-oracle comparison, one quantitative external baseline, a pinned open-weights reproducibility run, a 30-case synthetic prompt-injection suite, fail-closed action routing, finite-state invariant checking, local smart-contract microbenchmarks, public-testnet sensitivity observations, measured permissioned progress and non-progress under crash and non-participation, and a reviewer-visible HUMAN approval transition into a simulated ledger.

It does not establish production-grade O-RAN deployment, live RIC/SMO actuation, independent expert correctness of the synthetic oracle, comprehensive O-RAN/3GPP compliance, semantic correctness of LLM reasoning, cryptographic truth of physical telemetry, ProVerif protocol results, Ethereum mainnet performance, consensus superiority, economic finality, validator decentralisation, resistance to arbitrary Byzantine behaviour, full media-plane QoE, independent human validation, general prompt-injection resistance, or any row-bound successful AUTH V2.x proof verification in the 240-record matrix. `MOCK_MODE` is plumbing-only and must not be used for manuscript performance claims.

S9. PAPER-BUILDING PROCESS AND EVIDENCE GOVERNANCE

The manuscript was assembled through the same evidence-gated process as the evaluation. Stage 1 produced the supervisor-response matrix, KPI plan, executable TLA$^+$ model and TLC configuration, and the n8n skeleton. Stage 2 converted workflow outputs into the clean 240-record dataset. Stage 3 added runtime hooks for anchoring, reasoning latency, and negative-security KPIs. Stage 4 added Sepolia audit evidence. Stage 5 added

paired PoS–Roll-DPoS sensitivity and the consensus-family and SHA-2 extension. Stage 6 added the permissioned etcd/Raft and Besu/QBFT sessions of Section S7.7.

The hardening layer adds the paper reproduction wrapper, the packet-capture smoke test, guarded AUTH V2.x timing analysis, AI-evidence summaries, Stage E/F failure diagnostics, Stage F/F row hashes, claim validation, and an evidence manifest. Measured figures and tables are generated through derivation manifests that bind raw evidence hashes to the summary, table, figure, and results paragraph they produce, so that a manuscript number cannot drift from the file it came from without breaking the manifest. The appropriate final state of the artifact is `READY_WITH_BOUNDARY_LIMITATIONS`: measured, configured, synthetic, bounded, and absent evidence are reported separately, and no aggregate score is computed across them.

S10. Major Revision Evidence Audit

The revision reanalysis reads five retained archives and the recovered original R10 bundle without issuing a provider request or mutating the frozen data. Their internal manifests verify 5 oracle export, 547 LangGraph, 129 Qwen, 6 prompt-provenance and 4 clustered-statistics files. The canonical oracle digest remains `4854f1d4...e1196c6c`. Every baseline row joins the oracle by cell identifier, scenario hash and labels; every retained raw response matches its recorded canonical SHA-256 digest. All raw model outputs and original `unsafe_execution` fields remain unchanged. The derived report records the legacy predicate and gives the corrected interpretation.

The recovered bundle has SHA-256 `f842c030...77ccb63d`. Its original release manifest and archive sidecars pass. All 180 run manifests verify 18 files each: 3,240 bound files plus 180 manifests, for 3,420 files. Canonical report hashes match the previously released frozen-reference hashes for all 180 cells. We also verify six component self-hashes per report, 720 assessor raw-response hashes and 720 role raw-response hashes. The successful index, report metadata, retrieval content and prompt-provenance records join consistently. Internal integrity does not establish independent provider authenticity or physical telemetry truth.

A. Semantic labels and execution declarations

The frozen decision is three-valued (COMPLIANT, NON_COMPLIANT, UNCERTAIN), while the action label is a separate operator-policy choice. All 180 oracle cells require non-automatic handling: 120 HUMAN and 60 NEVER. The code's legacy `unsafe_execution` predicate is exactly oracle-NEVER combined with final-prediction `execute=true`. This is not a dispatch or actuator observation. Its broader counter counts declarations on any reference non-automatic case. On Qwen's 60 cells these counts are 9 and 38; LangGraph has zero on 180 cells. No baseline runner invokes an executor. The recovered proposed-workflow reports and archived histograms agree: Agentic RAG has nine NEVER outcomes in S4 and ten in S5, yielding NEVER-class recall $19/20 = 95.0\%$, rather than the previous 100.0% entry. No RAG and RAG give $0/20$ and $10/20$, respectively. These point counts are recomputed from the original final-action records and cross-checked against the retained summary. No new inference is performed.

The paired replay has three conditions: raw candidate, class-consistency guard and the same guard with execution disabled. The guard suppresses execute-true only when the predicted class is non-AUTOMATIC; it cannot detect a wrong AUTOMATIC classification by itself. Disabling execution changes Qwen's execute-true count from 38 to zero and its NEVER-subset count from nine to zero, while decision agreement stays 38/60 and action agreement 11/60. LangGraph stays 150/180 and 120/180 with zero declarations. This limited ablation demonstrates metric separation, not a causal latency gain or a model upgrade. The recovered raw decision/action records also reproduce the previously reported 20,000-replicate scenario-clustered intervals using the unchanged seed and whole-scenario resampling. The six-scenario generalisation boundary remains unchanged. Proposed-workflow timing comes from the original success index and report timestamps; the baseline latency comes from its assessor request timer. These timing estimands remain different.

B. Formal predicates and sensitivity

For executed flag e, class c, human approval h, privileged approval p, admissibility v, commitment a and phase q, the checked predicates are $c = \text{NEVER} \Rightarrow \neg e$; $(e \wedge c = \text{HUMAN}) \Rightarrow h$; $(e \wedge c = \text{PRIVILEGED}) \Rightarrow (h \wedge p)$; $e \Rightarrow v$; $e \Rightarrow a \neq 0$; and $e \Rightarrow q = \text{ACT}$. The original initialisation excludes $a = 0$. The unchanged original yields 64 initial and 320 reachable states; a separate zero-input probe yields 96 initial and 480 reachable states, with no invariant violations. Removing the admissibility guard violates ProofRequired; removing the non-zero execution guard violates NonZeroAnchorRequired; and dropping ordinary approval from PRIVILEGED violates PrivilegedRequiresBoth. These negative controls establish sensitivity of those predicates to those mutations. They do not verify arbitrary code defects or deployed approval services. The finite model has no accepted-commitment history and does not check replay.

C. Timing definitions and recovered benchmark phases

The baseline's recorded latency surrounds its assessor request. The original 180-cell proposed values describe returned-workflow durations. They differ in provider count, role calls, budgets, prompts, dates and governance; their ratio does not estimate n8n/LangGraph overhead. The recovered reports now provide monotonic stage timestamps for all 180 successful cells. Table S15 summarises the four disjoint intervals, whose per-run sum equals the internal report duration. The index timer includes a median additional 0.082/0.081/0.080 s for No RAG/RAG/Agentic RAG; it is retained as a separate measurement. The median per-run fraction in the aggregate-to-reflection phase is 73.4/76.5/75.4%, respectively. That phase contains the role chain and its surrounding processing, rather than an isolated causal cost of model reasoning. Its P95 is

TABLE S15
RECOVERED BENCHMARK TIMING: MARGINAL MEDIANS IN SECONDS, 60 CELLS PER MODE. THE FOUR PHASE INTERVALS PARTITION EACH INTERNAL REPORT DURATION; THE INDEXED TIMER IS SEPARATE. THESE ARE DESCRIPTIVE RECORDED-WORKFLOW STATISTICS, NOT MATCHED INFERENCE-TIME ABLATIONS.

Mode	n	Indexed	Report	Input to retrieval	Retrieval to aggregate	Aggregate to reflection	Reflection to report
No RAG	60	80.453	80.363	0.011	20.220	57.698	0.036
RAG	60	100.152	100.058	0.394	24.197	75.637	0.036
Agentic RAG	60	109.793	109.711	3.062	26.224	79.608	0.036

85.156/110.447/125.168 s. Sums of all four individual assessor-call durations are available for 58/58/57 runs, respectively; missing call durations are not imputed. All phase statistics in Table S15 use 60 complete timestamp records per mode. Parallel assessor calls overlap and are never added to these wall intervals. Marginal stage medians do not sum to a median total.

For comparison, the separate live S2 demonstration has disjoint intervals of 4.380091 s (input to retrieval), 26.876164 s (retrieval to aggregate), 77.572908 s (aggregate through role reflection), and 0.109483 s (reflection to report), totalling 108.938646 s. Its 25.421263 s parallel assessment interval overlaps 42.896247 s of summed calls, and its summed role calls are 77.397133 s. The separate approval callback follows report completion. These observations explain that trace's duration without claiming a matched framework ablation.

D. Approval export repair and deployment boundary

The archived callback coerces `approved` through JavaScript `Boolean`; the string "false" is truthy. Historical exports remain immutable. A separate inactive V2 export requires a real Boolean and nonempty string identifiers and preserves a false rejection. Its local payload tests include malformed input and string-coercion regressions. This repairs input validation only. Authentication, exact action/evidence binding, expiry, atomic conflict resolution and privileged approval are gateway/deployment obligations and are not established by importing the export.

E. Reproduction and remaining validation

Run `scripts/l4/tnsm_revision/audit_retained_revision_evidence.py` for the baseline archive audit and replay. Run `scripts/l4/tnsm_revision/audit_recovered_proposed_evidence.py` for the recovered 180-report audit, raw metrics, clustered intervals and phase timing table. Both commands use retained records only. Run `scripts/l4/tnsm_revision/run_formal_revision_checks.py` with TLC 2.19's jar to reproduce the original, zero-input and mutation runs. The accompanying README gives exact commands, input hashes and tests. The revision adds no independent expert labels, live O-RAN telemetry, A1/E2 deployment, held-out noise study or inference-time matched ablation. Its claims are deliberately restricted to the documented evidence. These missing validations cannot be replaced by new wording or repeated calls on six cases.

REFERENCES

[1] S. Karmaker, M. N. M. Bhutta, H. S. Cruickshank, and M. Shojafar, "Auditable policy-governed LLM-agent control for O-RAN edge security," main manuscript, 2026.

[2] S. Karmaker, "ZKTrustLLM-Agents L4 artifact repository and supplementary material," GitHub repository, 2026. [Online]. Available: https://github.com/Sudarson2021/zktrustllm-agents-l4

[3] L. Lamport, *Specifying Systems: The TLA$^+$ Language and Tools for Hardware and Software Engineers*. Boston, MA, USA: Addison-Wesley, 2002.

[4] D. Ongaro and J. Ousterhout, "In search of an understandable consensus algorithm," in *Proc. USENIX Annu. Tech. Conf. (ATC)*, 2014, pp. 305–319.

[5] Hyperledger Besu, "QBFT consensus protocol documentation," 2026. [Online]. Available: https://besu.hyperledger.org/private-networks/how-to/configure/consensus

[6] Ethereum Foundation, "Networks: Ethereum testnets and Sepolia," 2026. [Online]. Available: https://ethereum.org/developers/docs/networks/

[7] IoTeX Foundation, "Roll-DPoS consensus," 2025. [Online]. Available: https://docs.iotex.io/blockchain/learn-iotex/core-concepts/

[8] n8n, "Workflows, nodes, and integrations documentation," 2026. [Online]. Available: https://docs.n8n.io/

[9] National Institute of Standards and Technology, "Secure Hash Standard (SHS)," FIPS PUB 180-4, 2015.