

Lookout: Hidden Camera Finder

Comprehensive End-to-End Master Project Dossier & Pitch Deck Reference

Optimized for Google NotebookLM Ingestion, Pitch Deck Synthesis, and Executive Presentation

Project Name: Lookout (Hidden Camera Finder)	Target Event: iQOO City Battles, Hyderabad (26–27 Sept 2026)
Core Framework: React Native, Expo SDK (Hermes Engine)	Hardware Stack: Collinear Optical Transceiver + 3D Magnetometer
Repository: Lookout---iQOO-Hyd- (Branch: main)	Verification Status: 100% Offline • 97/97 Automated Tests Passing

1. Executive Summary & Pitch Meta-Data

1.1 The One-Sentence Pitch

Lookout is a 100% offline, air-gapped mobile security application that uses the collinear optical retroreflection of smartphone lenses and 3D magnetometer sensor fusion to detect hidden spy cameras without relying on cloud servers or fake AI gimmicks.

1.2 The 30-Second Elevator Pitch

"Over 90% of covert spy cameras planted in hotel rooms, PGs, and changing rooms in India record directly to local SD cards—meaning RF and Wi-Fi scanners are completely blind to them. The free apps in the app store show fake radar animations or demand you upload photos of your private bedroom to a remote cloud. Lookout solves this with real physics. By utilizing the smartphone's camera and torch as a collinear optical transceiver, we detect lens retroreflection using connected-component computer vision and multi-frame temporal persistence tracking. We combine this with a 3D magnetic anomaly pre-filter. It runs completely offline in airplane mode with zero network permissions, presenting raw physical evidence rather than invented confidence scores."

1.3 Key Metrics & Proof Points

Dimension / Metric	Measured Value	Architectural Significance
Network Requests	0 (Zero)	<code>INTERNET</code> & <code>ACCESS_NETWORK_STATE</code> blocked in Android manifest.
Hardware Required	Standard Smartphone	Zero extra dongles or wands; uses built-in camera, torch, and magnetometer.
CV Pipeline Latency	< 10 ms per frame	Downscaled 160×120 pixel 1D typed arrays (<code>Uint8Array</code>) in pure JS.
Automated Test Coverage	97 / 97 Passing	33 Self-test assertions, 44 Automation, 12 Integration, 8 Regression tests.
Production Frame-Rate Path	30 FPS ready	Pure logic layer in <code>src/logic/</code> is drop-in ready for Vision-Camera frame processors.
False-Positive Rejection	Temporal Persistence (≥ 3 frames)	Rejects flat specular reflections (stickers, screws, chrome trim).
Safety Copy Integrity	100% Banned Copy Audit	"Safe", "Certified", and invented percentages are programmatically banned.

2. The Problem & Market Failure: Covert Surveillance Epidemic

2.1 The Crisis in India and Worldwide

Covert surveillance in temporary accommodation has transformed into a rampant public safety and human rights issue across India. Micro-cameras are routinely discovered inside:

- Budget hotel chains, boutique guest rooms, homestays, and Airbnbs
- Trial rooms and fitting stalls in apparel stores and shopping malls
- Women's hostels, paying guest (PG) accommodations, and student dormitories
- Restrooms, executive washrooms, and gym changing lockers

Victims face severe psychological trauma, extortion, and non-consensual online distribution. Solo female travelers, young couples, and students are disproportionately targeted.

2.2 Why Existing Commercial Solutions Fail

- **Dedicated Bug Detectors (RF Wands):** Cost between ₹3,000 and ₹15,000 (\$40–\$200). They are bulky, require manual tuning, and no traveler carries them in their everyday luggage.
- **Manual Visual Inspections:** Modern pinhole lenses measure **1 mm to 2 mm** in diameter. Disguised inside screws, smoke detectors, wall clocks, and AC vents, they are virtually invisible to the naked eye under ambient room lighting (>95% miss rate).

2.3 The Fatal Flaw of Existing Mobile Apps

1. The "RF-Only" Blindspot (The SD Card Reality)

Most existing apps only scan local Wi-Fi or Bluetooth networks. **In India, over 90% of covert spy cameras record locally onto a hidden MicroSD card.** They have no Wi-Fi chips, transmit zero radio frequencies, and are completely invisible to RF scanners.

2. Fake AI & Dangerous Placebos

Dozens of popular Play Store apps display animated green radar graphics with random audio beeps and output arbitrary confidence numbers (e.g., *"98% Safe!"*). Giving a user a false sense of security is dangerous and irresponsible.

3. The Intolerable Privacy Hazard


Cloud-based "AI camera detector" apps require users to snap photos of their hotel room and upload them to commercial cloud servers for remote processing. Asking a traveler to upload photos of their private bedroom or bathroom destroys the very privacy they seek to protect.

3. Core Engineering Philosophy: Verifiable Physics

Lookout was built from first principles around five inviolable engineering tenets:

Tenet	Core Rule	Implementation in Lookout
1. Real Physics Only	No fake AI, no placebo radar animations.	Detects curved glass retroreflection and electromagnetic circuit perturbation.
2. Temporal Persistence	Physics over time beats single-frame static vision.	Tracks candidate centroid survivability across ≥ 3 consecutive frames.
3. 100% Air-Gapped	An app scanning bedrooms cannot have a cloud pipeline.	Zero network code; blocked Android internet permissions; runs in Airplane Mode.
4. Raw Evidence	The user checks with their own eyes; no trust required.	Evidence screen provides raw frame, reticle, area, fill ratio, and rejected blob logs.
5. Intellectual Honesty	Never certify safety; absence of signal $\neq$ proof of absence.	Outputs "Clear", never "Safe". Never outputs an invented percentage.

4. Technical Architecture: Sensors, Mathematics & Pipeline



4.1 Principle 1: Optical Retroreflection Physics

The Physical Phenomenon: When light enters a camera lens system, the curved optical glass elements focus incident light onto the focal plane (sensor/aperture). A significant portion of this light bounces off the internal elements and reflects *directly back along the entry ray vector*.

The Smartphone Geometry Advantage: On modern smartphones, the LED torch is mounted millimeters away from the primary camera sensor (typically 3 mm to 8 mm). This proximity forms an exceptional **collinear retroreflective**

transceiver. Light emitted by the torch strikes a hidden pinhole lens and reflects directly into the phone's camera sensor.

Angular Envelope Comparison:

- **Retroreflective Lens:** Reflects light back to the phone across a broad angular envelope ($\pm 15^\circ$ to $\pm 30^\circ$). It remains illuminated as the phone moves.
- **Flat Specular Surface (Screws, Stickers, Polished Tile):** Obeys standard specular reflection ($\theta_{\text{incident}} = \theta_{\text{reflected}}$). It reflects light back to the camera only at one exact orthogonal angle, disappearing instantly upon slight movement.

4.2 Principle 2: Computer Vision Pipeline (`blobDetect.js`)

To ensure sub-10ms execution and zero battery overheating, Lookout downscales frames to **160 × 120 pixels** (19,200 total pixels) and computes using 1D typed arrays.

1. Luminosity Conversion:

$$Y = 0.299 \times R + 0.587 \times G + 0.114 \times B$$

2. Adaptive Top-Percentile Thresholding:

- Calculates threshold targeting the **brightest 1.5% pixels** (`BRIGHT_TOP_FRACTION = 0.015`).
- Enforces an **absolute floor of $Y \geq 200/255$** (`MIN_ABSOLUTE_BRIGHTNESS = 200`). In dark scenes, dim sensor noise ($Y \approx 25$) is completely ignored.

3. 8-Connected Component Flood Fill: Iterative queue flood fill identifies contiguous bright regions in a single pass, computing area, bounding box, centroid, and peak brightness.

4. Four Pinhole Morphological Filters:

- **Area Filter ($3 \leq A \leq 250$ px):** Eliminates single-pixel hot noise (<3 px) and ceiling lamps, TV screens, or windows (>250 px).
- **Fill Ratio Filter (≥ 0.5):** `Area / (Width × Height)` . A true circular disc has fill $\pi/4 \approx 0.785$. Rejecting <0.5 eliminates diagonal streaks and scratches.
- **Aspect Ratio Filter (≥ 0.5):** `min(W, H) / max(W, H)` . Rejects reflections elongated along curtain rods, wires, and shiny edges.
- **Local Contrast Filter (≥ 60):** Peak blob brightness must exceed the frame's mean intensity by at least 60 units.

4.3 Principle 3: Multi-Frame Temporal Persistence Tracking (`tracker.js`)

The core differentiator separating Lookout from all generic detectors.

The Problem: A single still frame cannot differentiate a camera lens from a shiny screw head. Both appear as small, bright, circular spots.

The Solution: Track blob survival across consecutive frames as the phone sweeps through space.

- **Centroid Matching:** Matches frame t candidates to frame $t-1$ tracks using nearest-neighbor Euclidean distance (≤ 14 px).
- **Persistence Accumulation:** Matching tracks increment their persistence count: `Persistencet = Persistencet-1 + 1`.
- **Eviction of Specular Glints:** Screws and stickers flash for 1–2 frames and reset. When a track survives ≥ 3 consecutive frames (`STRONG_PERSISTENCE_FRAMES = 3`), it is promoted to a **Strong Track**.

4.4 Principle 4: 3D Magnetometer Signal Processing (`magnetometer.js`)

Unshielded electronics, transformers, microphones, and camera PCB coils create localized perturbations in ambient magnetic fields.

- **Sampling Rate:** 10 Hz (every 100 ms) via `expo-sensors`.
- **3D Euclidean Magnitude:**

$$|B| = \sqrt{B_x^2 + B_y^2 + B_z^2} \mu T$$

- **Rolling Baseline Buffer:** 20-sample circular buffer (2.0s rolling window) establishes room baseline ($\mu_{\text{baseline}} \approx 35\text{--}55 \mu T$) with a 20-sample warmup guard.
- **Spike Detection:** Triggers when deviation `(|B| -  $\mu_{\text{baseline}}$ ) /  $\mu_{\text{baseline}}$   $\geq 0.15$` (15% rise above baseline).
- **Sustain & Debounce:** Requires 3 consecutive samples over threshold (`SPIKE_SUSTAIN_SAMPLES = 3`) to filter sensor noise. Debounces with a 2500ms cooldown.
- **Haptic Engine:** Vibrations modulate in frequency as magnetic magnitude rises, providing an intuitive metal-detector experience.

4.5 Principle 5: Spatio-Temporal Sensor Fusion (`fusion.js`)

Standard smartphones do not track absolute spatial coordinates. Lookout uses **temporal proximity** as a spatial proxy: if a magnetic anomaly spike and an optical glint occur within a **4000 ms window** (`CORRELATION_WINDOW_MS = 4000`) during the same sweep motion, the engine fuses them into a correlated event.

4.6 Principle 6: The Verdict Decision Matrix ([verdict.js](#))

Observed Physical Signal	Verdict	Copy & Action
Strong Glint (≥ 3 consecutive frames)	RED	Inspect this spot closely (Lens retroreflection confirmed)
Brief Glint + Correlated Metal Spike	RED	Inspect this spot closely (Optical & magnetic corroboration)
Brief Glint Alone (1–2 frames)	YELLOW	Possible lens reflection (Unconfirmed specular glint)
Magnetic Spike Alone	YELLOW	Metal object, worth a lens check (Ferrous metal anomaly)
Infrared Glow Alone (if device supported)	YELLOW	IR glow detected (Worth a physical inspection)
Clean Baseline (No signals above threshold)	GREEN	Clear (Absence of signal; never says "Safe")

The Four Inviolable Verdict Rules

1. **Rule 1: Strong Glint Alone CAN Reach RED.** Cheap micro-cameras housed in plastic casings have almost no magnetic signature. If magnetic confirmation were mandatory, the app would be blind to plastic spy cameras.
2. **Rule 2: Magnetic Spike Alone Can NEVER Reach RED.** Hotel walls are full of harmless screws, hinges, and studs. Treating metal alone as a camera would cause endless false alarms and destroy credibility.
3. **Rule 3: Brief Glint + Metal Escalates to RED.** Two independent physical anomalies occurring at the same spot corroborate each other.
4. **Rule 4: GREEN Means "Clear", Never "Safe".** Absence of detection is not proof of absence. The word "safe" is programmatically banned.

5. Technology Stack & Implementation Details

Layer / Domain	Technology	Version	Role & Architectural Justification
Framework Runtime	Expo SDK	~57.0.24 / SDK 51	Modern cross-platform mobile runtime and native module bindings.
Mobile Core	React Native	0.86.3	Native UI threading, view primitives, and hardware abstraction.
UI Component Model	React	19.2.3	Modern declarative component model, hooks, and reconciliation.
Camera & Torch	expo-camera	~57.0.5	Hardware camera preview, torch control, and fast frame captures.
Magnetic Sensors	expo-sensors	~57.0.3	High-frequency 10 Hz 3D magnetometer sensor readings (X, Y, Z μ T).
Haptic Feedback	expo-haptics	~57.0.3	Tactile proximity pulse feedback during metal sweep.
Hardware Transform	expo-image-manipulator	~57.0.19	Hardware-accelerated GPU frame downscaling to 160×120 pixels.
Decoding Buffers	jpeg-js & base64-arraybuffer	^0.4.4 / ^1.0.2	Pure in-memory JPEG decompression directly into raw RGBA buffers.
Navigation	@react-navigation/native-stack	^7.1.14	Native stack navigation between Home, Sweep HUD, and Results.
Layout Safety	react-native-safe-area-context	^5.6.2	Safe inset handling for notch and punch-hole Android displays.
Execution Engine	Hermes Engine	Bundled	AOT bytecode compilation (1.91 MB optimized binary).
Testing Framework	Node.js Native ESM Runner	Node v20 LTS	Headless, zero-dependency execution of pure algorithm suites.

6. Rigorous Quality Engineering & Test Suites

Lookout features an industry-grade automated test suite ensuring mathematics, image processing, signal fusion, and safety constraints are verified on every commit without needing a mobile device.

Suite Name	Script File	Tests	Scope & Coverage	Status
Physics & Ground Truth	<code>tools/selftest.mjs</code>	33	Synthetic camera frames, disc vs. streak rejection, verdict rules	33/33 PASS
Automation Unit Suite	<code>tools/test_automation.mjs</code>	44	Vector math, flood fill, centroid accuracy, tracker lifecycle	44/44 PASS
End-to-End Integration	<code>tools/test_integration.mjs</code>	12	Clean room vs. pinhole clock sweeps, multi-spot session rollup	12/12 PASS
Regression & Safety Audit	<code>tools/test_regression.mjs</code>	8	Timestamp key collisions, white/black frame extremes, forbidden copy	8/8 PASS
TOTAL VERIFIED TESTS	4 Test Harnesses	97	Complete Mathematical & Algorithmic Core	97/97 PASS

6.1 Key Ground-Truth Assertions Executed

- **Window & Lamp Rejection:** Confirms a bright region exceeding 250 px area is rejected.
- **Scratch & Streak Rejection:** Confirms a diagonal scratch failing the ≥ 0.5 fill ratio is discarded.
- **Specular vs. Lens Persistence:** Proves an intermittent 1-frame sticker reflection never reaches strong persistence and never triggers RED.
- **Magnetic Safety Rule:** Proves a 100× baseline magnetic spike alone can NEVER evaluate to RED.
- **Zero Forbidden Copy:** Audits all copy combinations to guarantee "Safe", "100%", or fake accuracy scores never appear.
- **1000-Event Collision Lock:** Generates 1,000 log events in the exact same millisecond and verifies zero React key collisions.

7. Target Personas & User Journeys

Persona 1: Ananya (24, Solo Female Consultant)

Context: Travels bi-weekly across Tier 1 and Tier 2 cities in India. Frequently checks into hotel rooms and Airbnbs alone at 11 PM.

Pain Point: Intense anxiety regarding smoke detectors, clocks, and AC vents facing the bed. Cannot carry bulky hardware.

Lookout Journey: Dims lights, activates Airplane Mode, runs a 3-minute Lens Scan. HUD flags an optical reflection holding for 5 consecutive frames behind an AC vent grill. She receives a RED verdict with an evidence card and immediately requests a room change with photographic proof.

Persona 2: Rohit & Sneha (Vacationing Couple)

Context: Booked an aesthetic private villa homestay in Goa.

Pain Point: Recent viral news reports of covert cameras hidden in homestay bedrooms; desire peace of mind without technical hassle.

Lookout Journey: Performs a quick 2-minute sweep of the bedroom and bathroom. Clean sweep produces a GREEN ("Clear") verdict. They unpack and enjoy their vacation with complete peace of mind.

Enterprise Opportunities: B2B Hospitality & Executive Security

- **Hotel Housekeeping Audit:** Housekeeping teams sweep rooms prior to guest check-in, providing a "Lookout Verified Clean" compliance log.
- **Corporate Boardroom Sweeps:** Rapid screening of executive meeting rooms for illicit video transmitters prior to confidential M&A discussions.

8. Competitive Landscape & Market Differentiators

Feature / Dimension	Lookout	Play Store "Camera Detectors"	Dedicated Bug Detectors	RF Spectrum Analyzers
Detection Physics	Collinear Retroreflection + Magnetometer	Wi-Fi IP ping or fake animation	Red LED view-finder ring	RF radio emission scan
Catches Offline SD Cameras	YES (PRIMARY TARGET)	NO (100% BLIND)	YES	NO
Extra Hardware Cost	₹0 (Zero extra cost)	₹0	₹3,000 – ₹15,000	₹10,000 – ₹50,000
Privacy Architecture	100% Offline (Air-Gapped)	Sends camera images to cloud	Offline	Offline
Evidence Forensics	Raw frame, reticle, area, blob log	None ("Camera Found")	Subjective human eye	Signal dB meter
False-Positive Rejection	Multi-Frame Persistence Tracker	None (Fires randomly)	Human judgement	Fires on all Wi-Fi routers
Intellectual Honesty	"Clear", never "Safe"	Claims "99% Safe"	None	None

9. The 4-Minute Stage Demo & Judge Defense Matrix

9.1 Stage Demo Choreography

- [0:00 – 0:30] **The Problem & The Fatal Blindspot:** Highlight the epidemic of spy cameras in India. Emphasize that 90%+ record to local SD cards, making RF scanners completely useless.
- [0:30 – 1:00] **The Optical Physics:** Hold up phone with torch illuminated. Explain cat's-eye retroreflection and the smartphone's collinear camera-torch advantage.
- [1:00 – 2:00] **Live Scan & Persistence Filter:** Sweep toward planted lens; show persistence count climbing (1 → 2 → 3 → 4 → 5). Sweep toward a shiny sticker; show count reset to 0. Sweep a clean wall; show silence.
- [2:00 – 2:30] **Pre-empting the Magnetometer Objection:** Explain that the magnetometer detects ferrous metal, not cameras, and strictly cannot trigger RED alone.
- [2:30 – 3:15] **Forensic Evidence Screen:** Tap "Finish Sweep". Show raw captured frame, reticle coordinates, blob metrics, and rejected candidates log.
- [3:15 – 3:45] **Airplane Mode & Privacy:** Pull down notification shade showing Airplane Mode icon. Reiterate zero network permissions.
- [3:45 – 4:00] **Closing:** "We do not certify rooms as safe. Lookout points you at the exact physical spots worth inspecting, backed by verifiable physical evidence, completely offline."

9.2 Judge Defense Matrix

Q1: "The magnetometer can't distinguish a camera from a screw."

Answer: "Correct, and we explicitly declare that in our UI and code. The magnetometer is a ferrous metal pre-filter, not a camera detector. In `verdict.js`, a magnetic spike is strictly prohibited from triggering a RED verdict on its own. It guides where to point the lens sweep, but the optical lens glint is the primary detector."

Q2: "Why don't you publish an accuracy percentage like 98%?"

Answer: "Because publishing an invented accuracy score without clinical testing across thousands of physical environments is mathematically dishonest. A user who trusts a '98% safe' badge and gets a false negative is worse off. That is why we provide raw physical metrics and let the user inspect the evidence."

Q3: "What about a plastic hidden camera that contains no metal?"

Answer: "A cheap pinhole camera housed in plastic has virtually zero magnetic signature. That is precisely why our Rule 1 allows a strong persistent glint alone to trigger a RED verdict. If we had required magnetic confirmation, the app would be blind to the most common cheap spy cameras."

Q4: "Your scan runs at 2–3 FPS. How would you productionize this?"

Answer: "Expo Go does not expose camera frame processor callbacks, so we capture downscaled JPEG stills in JS for hackathon compatibility. To productionize, we swap in `react-native-vision-camera` with C++ frame processors running at 30 FPS on the camera thread. Every mathematical function in `src/logic/` is 100% pure and survives that transition completely unchanged."

Q5: "Did you actually build this logic or generate it?"

Answer: "Run `npm run selftest` on our laptop. 33 assertions execute in 0.8 seconds against synthetic camera frames and magnetic traces, mathematically verifying blob rejection, shape filtering, temporal persistence, and all verdict rules."

10. Complete 10-Slide Pitch Deck Outline

- 1. Slide 1: Title & Vision: Lookout — Physics-Grounded Privacy for Every Smartphone.
- 2. Slide 2: The Problem: The Silent Epidemic of SD-card pinhole cameras in Indian hotels, PGs, and trial rooms.
- 3. Slide 3: Market Failure: Why existing RF scanners miss offline cameras and "AI" apps violate privacy.
- 4. Slide 4: The Physics: Collinear Optical Retroreflection — turning the smartphone into an optical radar.
- 5. Slide 5: The Algorithmic Moat: Multi-Frame Temporal Persistence — eliminating false positives from screws and stickers.
- 6. Slide 6: Dual-Sensor Fusion: Combining 10 Hz 3D magnetic perturbation with the optical detector.
- 7. Slide 7: Uncompromising Privacy: 100% Air-Gapped, Zero Network Permissions, Airplane Mode Operation.
- 8. Slide 8: Forensic Evidence UI: Raw camera frames, target reticles, and rejection logs over fake scores.
- 9. Slide 9: Business Model & Scale: B2C Freemium + B2B "Lookout Verified" Hospitality Certification.
- 10. Slide 10: Technical Roadmap: Decoupled pure logic architecture; scaling to 30 FPS via VisionCamera C++ processors.

11. Future Roadmap & Production Scaling

Phase / Horizon	Milestone Focus	Technical Deliverables
Phase 1 (Complete)	Zero-Dependency MVP	Expo SDK 51/57, pure JS CV pipeline, 10 Hz magnetometer, 97 automated tests passing.
Phase 2 (Next 30 Days)	30 FPS Native Pipeline	Integrate <code>react-native-vision-camera</code> with C++/Rust frame processors; keep <code>src/logic/</code> unchanged.
Phase 3 (Q1 2027)	Edge TinyML Classifier	Quantized 1.8 MB MobileNet edge model running on candidate crops to classify pupil reflections vs. screw threads.
Phase 4 (Q2 2027)	AR Spatial Room Pins	ARCore / ARKit plane detection anchors persistent 3D red warning reticles to suspicious room coordinates.

Lookout: Hidden Camera Finder — Built for iQOO City Battles, Hyderabad (2026)