

Assignment No: 4

Title of the Assignment: Write a program to solve a 0-1 Knapsack problem using dynamic programming or branch and bound strategy.

Objective of the Assignment: Students should be able to understand and solve 0-1 Knapsack problem using dynamic programming

Prerequisite:

1. Basic of Python or Java Programming
 2. Concept of Dynamic Programming
 3. 0/1 Knapsack problem
-

Contents for Theory:

1. Greedy Method
 2. 0/1 Knapsack problem
 3. Example solved using 0/1 Knapsack problem
-

What is Dynamic Programming?

- Dynamic Programming is also used in optimization problems. Like divide-and-conquer method, Dynamic Programming solves problems by combining the solutions of subproblems.
- Dynamic Programming algorithm solves each sub-problem just once and then saves its answer in a table, thereby avoiding the work of re-computing the answer every time.
- Two main properties of a problem suggest that the given problem can be solved using Dynamic Programming. These properties are **overlapping sub-problems and optimal substructure**.
- Dynamic Programming also combines solutions to sub-problems. It is mainly used where the solution of one sub-problem is needed repeatedly. The computed solutions are stored in a table, so that these don't have to be re-computed. Hence, this technique is needed where overlapping sub-problem exists.
- For example, Binary Search does not have overlapping sub-problem. Whereas recursive program of Fibonacci numbers have many overlapping sub-problems.

Steps of Dynamic Programming Approach

Dynamic Programming algorithm is designed using the following four steps –

- Characterize the structure of an optimal solution.
- Recursively define the value of an optimal solution.
- Compute the value of an optimal solution, typically in a bottom-up fashion.
- Construct an optimal solution from the computed information.

Applications of Dynamic Programming Approach

- Matrix Chain Multiplication
- Longest Common Subsequence
- Travelling Salesman Problem

Knapsack Problem


You are given the following-

- A knapsack (kind of shoulder bag) with limited weight capacity.
- Few items each having some weight and value.

The problem states-

Which items should be placed into the knapsack such that-

- The value or profit obtained by putting the items into the knapsack is maximum.
- And the weight limit of the knapsack does not exceed.



Knapsack Problem

Knapsack Problem Variants

Knapsack problem has the following two variants-

1. Fractional Knapsack Problem
2. 0/1 Knapsack Problem

0/1 Knapsack Problem-

In 0/1 Knapsack Problem,

- As the name suggests, items are indivisible here.
- We can not take a fraction of any item.
- We have to either take an item completely or leave it completely.
- It is solved using a dynamic programming approach.

0/1 Knapsack Problem Using Greedy Method-

Consider-

- Knapsack weight capacity = w
- Number of items each having some weight and value = n

0/1 knapsack problem is solved using dynamic programming in the following steps-

Step-01:

- Draw a table say ‘T’ with (n+1) number of rows and (w+1) number of columns.
- Fill all the boxes of 0th row and 0th column with zeroes as shown-

| | 0 | 1 | 2 | 3 | | W |
|---|-------|---|---|---|-------|---|
| 0 | 0 | 0 | 0 | 0 | | 0 |
| 1 | 0 | | | | | |
| 2 | 0 | | | | | |
| | | | | | | |
| n | 0 | | | | | |

T-Table

Step-02:

Start filling the table row wise top to bottom from left to right.

Use the following formula-

$T(i,j) = \max \{ T(i-1,j), value_i + T(i-1,j - weight_i) \}$

Here, T(i , j) = maximum value of the selected items if we can take items 1 to i and have weight restrictions of j.

- This step leads to completely filling the table.
- Then, value of the last box represents the maximum possible value that can be put into the knapsack.

Step-03:

- To identify the items that must be put into the knapsack to obtain that maximum profit,
- Consider the last column of the table.
- Start scanning the entries from bottom to top.
- On encountering an entry whose value is not same as the value stored in the entry immediately above it, mark the row label of that entry.
- After all the entries are scanned, the marked labels represent the items that must be put into the knapsack

Problem-.

For the given set of items and knapsack capacity = 5 kg, find the optimal solution for the 0/1 knapsack problem making use of a dynamic programming approach.

| Item | Weight | Value |
|------|--------|-------|
| 1 | 2 | 3 |
| 2 | 3 | 4 |
| 3 | 4 | 5 |
| 4 | 5 | 6 |

n = 4

w = 5 kg

(w1, w2, w3, w4) = (2, 3, 4, 5)

(b1, b2, b3, b4) = (3, 4, 5, 6)

Solution-

Given

- Knapsack capacity (w) = 5 kg
- Number of items (n) = 4

Step-01:

- Draw a table say ‘T’ with (n+1) = 4 + 1 = 5 number of rows and (w+1) = 5 + 1 = 6 number of columns.
- Fill all the boxes of 0th row and 0th column with 0.

| | | | | | | |
|---|---|---|---|---|---|---|
| | 0 | 1 | 2 | 3 | 4 | 5 |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| 1 | 0 | | | | | |
| 2 | 0 | | | | | |
| 3 | 0 | | | | | |
| 4 | 0 | | | | | |

T-Table

Step-02:

Start filling the table row wise top to bottom from left to right using the formula-

$T(i,j) = \max \{ T(i-1,j), value_i + T(i-1,j - weight_i) \}$

Finding T(1,1)-

We have,

- $i = 1$
- $j = 1$
- $(value)_i = (value)_1 = 3$
- $(weight)_i = (weight)_1 = 2$

Substituting the values, we get-

$T(1,1) = \max \{ T(1-1, 1), 3 + T(1-1, 1-2) \}$

$T(1,1) = \max \{ T(0,1), 3 + T(0,-1) \}$

$T(1,1) = T(0,1) \{ \text{Ignore } T(0,-1) \}$

$T(1,1) = 0$

Finding T(1,2)-

We have,

- $i = 1$
- $j = 2$
- $(\text{value})_i = (\text{value})_1 = 3$
- $(\text{weight})_i = (\text{weight})_1 = 2$

Substituting the values, we get-

$$T(1,2) = \max \{ T(1-1, 2), 3 + T(1-1, 2-2) \}$$

$$T(1,2) = \max \{ T(0,2), 3 + T(0,0) \}$$

$$T(1,2) = \max \{ 0, 3+0 \}$$

$$T(1,2) = 3$$

Finding T(1,3)-

We have,

- $i = 1$
- $j = 3$
- $(\text{value})_i = (\text{value})_1 = 3$
- $(\text{weight})_i = (\text{weight})_1 = 2$

Substituting the values, we get-

$$T(1,3) = \max \{ T(1-1, 3), 3 + T(1-1, 3-2) \}$$

$$T(1,3) = \max \{ T(0,3), 3 + T(0,1) \}$$

$$T(1,3) = \max \{ 0, 3+0 \}$$

$$T(1,3) = 3$$

Finding T(1,4)-

We have,

- $i = 1$
- $j = 4$
- $(\text{value})_i = (\text{value})_1 = 3$
- $(\text{weight})_i = (\text{weight})_1 = 2$

Substituting the values, we get-

$$T(1,4) = \max \{ T(1-1, 4), 3 + T(1-1, 4-2) \}$$

$$T(1,4) = \max \{ T(0,4), 3 + T(0,2) \}$$

$$T(1,4) = \max \{ 0, 3+0 \}$$

$$T(1,4) = 3$$

Finding T(1,5):-

We have,

- $i = 1$
- $j = 5$
- $(\text{value})_i = (\text{value})_1 = 3$
- $(\text{weight})_i = (\text{weight})_1 = 2$

Substituting the values, we get-

$$T(1,5) = \max \{ T(1-1, 5), 3 + T(1-1, 5-2) \}$$

$$T(1,5) = \max \{ T(0,5), 3 + T(0,3) \}$$

$$T(1,5) = \max \{ 0, 3+0 \}$$

$$T(1,5) = 3$$

Finding T(2,1):-

We have,

- $i = 2$
- $j = 1$
- $(\text{value})_i = (\text{value})_2 = 4$
- $(\text{weight})_i = (\text{weight})_2 = 3$

Substituting the values, we get-

$$T(2,1) = \max \{ T(2-1, 1), 4 + T(2-1, 1-3) \}$$

$$T(2,1) = \max \{ T(1,1), 4 + T(1,-2) \}$$

$$T(2,1) = T(1,1) \{ \text{Ignore } T(1,-2) \}$$

$$T(2,1) = 0$$

Finding T(2,2):-

We have,

- $i = 2$
- $j = 2$
- $(\text{value})_i = (\text{value})_2 = 4$
- $(\text{weight})_i = (\text{weight})_2 = 3$

Substituting the values, we get-

$$T(2,2) = \max \{ T(2-1, 2), 4 + T(2-1, 2-3) \}$$

$$T(2,2) = \max \{ T(1,2), 4 + T(1,-1) \}$$

$$T(2,2) = T(1,2) \{ \text{Ignore } T(1,-1) \}$$

$$T(2,2) = 3$$

Finding T(2,3):-

We have,

- $i = 2$
- $j = 3$
- $(\text{value})_i = (\text{value})_2 = 4$
- $(\text{weight})_i = (\text{weight})_2 = 3$

Substituting the values, we get-

$$T(2,3) = \max \{ T(2-1, 3), 4 + T(2-1, 3-3) \}$$

$$T(2,3) = \max \{ T(1,3), 4 + T(1,0) \}$$

$$T(2,3) = \max \{ 3, 4+0 \}$$

$$T(2,3) = 4$$

Similarly, compute all the entries.

After all the entries are computed and filled in the table, we get the following table-

| | 0 | 1 | 2 | 3 | 4 | 5 |
|-----|---|---|---|---|---|---|
| 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| ✓ 1 | 0 | 0 | 3 | 3 | 3 | 3 |
| ✓ 2 | 0 | 0 | 3 | 4 | 4 | 7 |
| 3 | 0 | 0 | 3 | 4 | 5 | 7 |
| 4 | 0 | 0 | 3 | 4 | 5 | 7 |

T-Table

- The last entry represents the maximum possible value that can be put into the knapsack.
- So, maximum possible value that can be put into the knapsack = 7.

Identifying Items To Be Put Into Knapsack

Following Step-04,

- We mark the rows labelled “1” and “2”.
- Thus, items that must be put into the knapsack to obtain the maximum value 7 are-

Item-1 and Item-2

Time Complexity-

- Each entry of the table requires constant time $\theta(1)$ for its computation.
- It takes $\theta(nw)$ time to fill $(n+1)(w+1)$ table entries.
- It takes $\theta(n)$ time for tracing the solution since tracing process traces the n rows.
- Thus, overall $\theta(nw)$ time is taken to solve 0/1 knapsack problem using dynamic programming

Conclusion-In this way we have explored Concept of 0/1 Knapsack using Dynamic approach

