

Ex. No.: 6

DSA

Date:

Aim:

To implement Digital Signature Algorithm (DSA) using C.

Algorithm:

- Get the prime number p and its divisor q from the user.
- Get the value of h from the user.
- Compute the value of g .
- Get the private key x_a from the user.
- Compute the user's public key y .
- Get the per-message secret key k and hash value of message M .
- Compute the value of z using g , k & p
- Compute $z \% q$ to get the value of r
- Compute the multiplicative inverse.
- Compute the value of s .
- Print the signature (r, s) .

Program Code:

```
#include
<stdio.h>
#include
<math.h>
int power(int,unsigned int,int);
int
multiplicativeInverse(int,int,int);
int main()
{
    int p,q,h,g,r,s,t,x,y,z,k,inv,hash;

    printf("\nEnter prime number p and enter q prime divisor of (p-1):
"); scanf("%d %d",&p,&q);
    printf("\nEnter h such that it greater than 1 and less than (p-1):
"); scanf("%d",&h);

    //Compute
    g t = (p-
    1)/q;
    g = power(h,t,p);
```

```

printf("\nEnter user's private key such that it is greater than 0 and less than q :
"); scanf("%d",&x);

//Computer user's public
key y = power(g,x,p);
printf("\nEnter user's per-message secret key k such that it is greater than 0 and less than q :
"); scanf("%d",&k);
printf("\nEnter the hash(M) value : ");
scanf("%d",&hash);

//Signing. Compute r and s
pair z = power(g,k,p);
r = z % q;
inv =
multiplicativeInverse(k,q,p); s =
inv * (hash + x * r) % q;

//Display
printf("\n*****Computed Values*****");
printf("\ng = %d",g);
printf("\ny = %d",y);
printf("\nGenerated Signature Sender = (%d, %d) \n",r,s);
}

```

```

int power(int x, unsigned int y, int p)
{
    int res = 1;    // Initialize result
    x = x % p; // Update x if it is more than or equal to p

    while (y > 0)

    {
        // If y is odd, multiply x
        with result if (y & 1)
        res = (res * x) % p;

        // y must be even now
        y = y >> 1;    // y =
        y/2 x = (x * x) % p;
    }
    return res;
}

```

```

int multiplicativeInverse(int a, int b, int n)
{
    int sum,x,y;
    for(y=0;y<n;y++)

```

```

    {
        for(x=0;x<n;x++)
        {
            sum = a * x + b * (-
            y); if(sum == 1)
                return x;
        }
    }
}

```

Output:

```

student : bash — Konsole
File Edit View Bookmarks Settings Help
[student@localhost ~]$ vi dsa.c
[student@localhost ~]$ gcc dsa.c
dsa.c: In function 'main':
dsa.c:22:13: error: 'k' undeclared (first use in this function)
scanf("%d",&k);
            ^
dsa.c:22:13: note: each undeclared identifier is reported only once for each function it appears in
dsa.c:33:1: error: expected ';' before 'printf'
printf("\n generated signature sender=(%d,%d)\n",r,s);
^
[student@localhost ~]$ vi dsa.c
[student@localhost ~]$ gcc dsa.c
dsa.c: In function 'main':
dsa.c:33:1: error: expected ';' before 'printf'
printf("\n generated signature sender=(%d,%d)\n",r,s);
^
[student@localhost ~]$ vi dsa.c
[student@localhost ~]$ gcc dsa.c
[student@localhost ~]$ ./a.out
Enter number p and enter the number q prime divisor of(p-1):1279 71

Enter h such that it greater than 1 and less than (p-1):3

Enter user's private key such that it is greater than 0 and less than q:15

Enter user's message secret key k such that it is greater than q:10

Enter hash(M) value:123

+++++++computed values+++++++
g=1157
y=851
generated signature sender=(32,39)
[student@localhost ~]$

```

Result: