## Rajalakshmi Engineering College

Name: Sudiksha S

Email: 241801278@rajalakshmi.edu.in

Roll no: 241801278 Phone: 9677276373

Branch: REC

Department: I AI & DS FD

Batch: 2028

Degree: B.E - AI & DS



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

REC\_DS using C\_Week 2\_COD\_Question 5

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

### 1. Problem Statement

Ashwin is tasked with developing a simple application to manage a list of items in a shop inventory using a doubly linked list. Each item in the inventory has a unique identification number. The application should allow users to perform the following operations:

Create a List of Items: Initialize the inventory with a given number of items. Each item will be assigned a unique number provided by the user and insert the elements at end of the list.

Delete an Item: Remove an item from the inventory at a specific position.

Display the Inventory: Show the list of items before and after deletion.

If the position provided for deletion is invalid (e.g., out of range), it should

display an error message.

# Input Format

The first line contains an integer n, representing the number of items to be initially entered into the inventory.

The second line contains n integers, each representing the unique identification number of an item separated by spaces.

The third line contains an integer p, representing the position of the item to be deleted from the inventory.

### **Output Format**

The first line of output prints "Data entered in the list:" followed by the data values of each node in the doubly linked list before deletion.

If p is an invalid position, the output prints "Invalid position. Try again."

If p is a valid position, the output prints "After deletion the new list:" followed by the data values of each node in the doubly linked list after deletion.

Refer to the sample output for the formatting specifications.

### Sample Test Case

Input: 4 1 2 3 4

5

Output: Data entered in the list:

node 1 : 1 node 2 : 2 node 3 : 3 node 4 : 4

Invalid position. Try again.

#### Answer

#include<stdio.h> #include<stdlib.h> typedef struct node

```
int data;
      struct node*next;
      struct node*prev;
    }node;
    typedef struct linkedlist
      node*head;
      node*tail;
    }linkedlist;
    void initlist(linkedlist*list)
      list->head=NULL;
      list->tail=NULL;
void insertend(linkedlist*list,int data)
      node*newnode=(node*)malloc(sizeof(node));
      newnode->data=data;
      newnode->next=NULL;
      newnode->prev=list->tail;
      if(list->tail!=NULL)
        list->tail->next=newnode;
      list->tail=newnode;
                                                     24,801218
      if(list->head==NULL)
        list->head=newnode;
    void deleteposition(linkedlist*list,int position)
      if(position<1)
        printf("Invalid position.Try again.\n");
        return;
      node*current=list->head;
                                                     241801218
while(current!=NULL)
```

```
if(count==position)
{

if(cur
                                                        241801218
            if(current->prev!=NULL)
              current->prev->next=current->next;
            else
              list->head=current->next;
            if(current->next!=NULL)
              current->next->prev=current->prev;
                                                        24,80,1218
            else
              list->tail=current->prev;
            free(current);
            return;
          current=current->next;
          count++;
       }
       printf("Invalid position.Try again.\n");
                                                        24,180,12,18
     void display(linkedlist*list)
       node*current=list->head;
       int count=1;
       while(current!=NULL)
          printf(" node %d : %d\n",count,current->data);
          current=current->next;
          count++;
       }
     int main()
                                                        241801218
scanf("%d",&n);
int items<sup>[p].</sup>
```

```
24,80,218
                                                    24,80,1218
        scanf("%d",&items[i]);
       for(int i=0;i<n;i++)
24,307
       scanf("%d",&p);
       linkedlist inventory;
       initlist(&inventory);
       for(int i=0;i<n;i++)
         insertend(&inventory,items[i]);
       printf("Data entered in the list:\n");
       display(&inventory);
                                                                               24,801218
                                                    241801218
if(p>=1&&p<=n)
       deleteposition(&inventory,p);
         printf("\nAfter deletion the new list:\n");
         display(&inventory);
       return 0;
    }
```

Status: Correct Marks: 10/10

24,801278

241801218

24,801218

24/80/2/18

24,80,278

241801218

241801218

241801218