



CRFQ No. : 1000459858

TENDER TITLE - Procurement of Mooring Hawsers for Single Point Mooring system at BPCL Crude oil terminal Vadinar (Gujarat)

SPECIFICATIONS & SCOPE OF SUPPLY OF THE MOORING HAWSERS

Sl. No.	Description		Specification
1	Circumference	:	14" (14 inch)
2	Length	:	175 (±5) ft.
3	Minimum New Wet Breaking Strength (NWBS)	:	271 tons
4	Construction	:	Single Leg Hawser, Double Braided Nylon Rope (2 in 1) construction and provision for inserting Bell Mouth Thimble. (spliced ends)
5	Material	:	100 % Nylon (Braided nylon core with braided nylon sheath)
6	Linear Density	:	7.9 to 8.1 kg/m
7	Color of Rope	:	Natural White
8	Rope Cover	:	Rope length 100% encapsulated with Polyurethane Elastomer.
9	Float Type for Hawser	:	Rope to be supplied and fastened with lace-on floats to provide buoyancy for floating in sea.
10	Buoyancy for Hawser Floats	:	Adequate reserve buoyancy for supporting hawser in sea water
11	Applicable standards	:	OCIMF 2000 "Guidelines for Purchasing and Testing of SPM Hawsers".
12	Thimble Type (Both Ends)	:	SPM Type Hawser Bell Mouth Thimble reusable type.
13	Thimble Size	:	For 14" rope size or appropriate to size of Hawser & to fit 130 Tons heavy duty 'D' shackle.
14	Thimble Material	:	Thimble Body – Galvanized with stainless steel roller.
15	Service life of Mooring hawser		12 months continuous operations or 100 number Tanker operations.



CRFQ No. : 1000459858

TENDER TITLE - Procurement of Mooring Hawser for Single Point Mooring system at BPCL Crude oil terminal Vadinar (Gujarat)

Note:

1. Bell Mouth Thimble shall fit with 130 tons Heavy Duty 'D' Shackle with pin Ø 114 mm and inside length of 480 mm. Dimension of Heavy-duty shackle is below:

Bow Diameter	100 MM
Pin Diameter	114 MM
Jaw Width	280 MM
Inside Length	480 MM
Pin Inserting Dia.	235 MM

2. Vendors shall supply the mooring hawsers tied with lace on floats as per buoyancy requirement.

Scope of Supply:

1. Vendor has to quote against the material as per the specification & scope of supply.
2. Mooring Hawser encapsulated cast thimble shall be certified by Third Party Surveyor – ABS only and the third-party inspection certificate from ABS shall be sent prior to shipment.
3. Delivery Period shall be within 180 days up to COT Vadinar for Indian bidders and Nhava sheva port (Indian port) for foreign bidder.
4. Detailed drawings along with technical details of the offered hawser shall be sent along with the offer for evaluation. Performance Tests shall be carried out as per standard procedures of OCIMF 2000 "Guidelines for Purchasing and Testing of SPM Hawsers".
5. Mooring Hawser shall comply with the latest OCIMF Standards (OCIMF 2000 or later).
6. Specification of lace on floats and its number/ quantity suitable for providing buoyancy to the hawsers shall be specified.
7. Details of the company, quality management systems, ISO certificates, etc. should be attached to the offer.