

2. Implement transmission of ping messages/trace route over a network topology consisting of 6 nodes and find the number of packets dropped due to congestion.

```
set ns [ new Simulator ]
set nf [ open 2. nam w ]
$ns namtrace-all $nf
set tf [ open 2. tr w ]
$ns trace-all $tf

set n0 [$ns node]
set n1 [$ns node]
set n2 [$ns node]
set n3 [$ns node]
set n4 [$ns node]
set n5 [$ns node]

$n4 shape box

$ns duplex-link $n0 $n4 1005Mb 1ms DropTail
$ns duplex-link $n1 $n4 50Mb 1ms DropTail
$ns duplex-link $n2 $n4 2000Mb 1ms DropTail
$ns duplex-link $n3 $n4 200Mb 1ms DropTail
$ns duplex-link $n4 $n5 1Mb 1ms DropTail

set p1 [new Agent/Ping]
$ns attach-agent $n0 $p1
$p1 set packetSize_ 50000
$p1 set interval_ 0.0001

set p2 [new Agent/Ping]
$ns attach-agent $n1 $p2

set p3 [new Agent/Ping]
$ns attach-agent $n2 $p3
$p3 set packetSize_ 30000
$p3 set interval_ 0.00001

set p4 [new Agent/Ping]
$ns attach-agent $n3 $p4

set p5 [new Agent/Ping]
$ns attach-agent $n5 $p5

$ns queue-limit $n0 $n4 5
$ns queue-limit $n2 $n4 3
$ns queue-limit $n4 $n5 2

Agent/Ping instproc recv {from rtt} {
    $self instvar node_
    puts "node($node_ id) received answer from $from with round trip time $rtt msec"
}

$ns connect $p1 $p5
$ns connect $p3 $p4
proc finish { } {
    global ns nf tf
```



```
$ns flush-trace
close $nf
close $tf
exec nam 2. nam &
exit 0
}
```

```
$ns at 0.1 "$p1 send"
$ns at 0.2 "$p1 send"
$ns at 0.3 "$p1 send"
$ns at 0.4 "$p1 send"
$ns at 0.5 "$p1 send"
$ns at 0.6 "$p1 send"
$ns at 0.7 "$p1 send"
$ns at 0.8 "$p1 send"
$ns at 0.9 "$p1 send"
$ns at 1.0 "$p1 send"
$ns at 1.1 "$p1 send"
$ns at 1.2 "$p1 send"
$ns at 1.3 "$p1 send"
$ns at 1.4 "$p1 send"
$ns at 1.5 "$p1 send"
$ns at 1.6 "$p1 send"
$ns at 1.7 "$p1 send"
$ns at 1.8 "$p1 send"
$ns at 1.9 "$p1 send"
$ns at 2.0 "$p1 send"
$ns at 2.1 "$p1 send"
$ns at 2.2 "$p1 send"
$ns at 2.3 "$p1 send"
$ns at 2.4 "$p1 send"
$ns at 2.5 "$p1 send"
$ns at 2.6 "$p1 send"
$ns at 2.7 "$p1 send"
$ns at 2.8 "$p1 send"
$ns at 2.9 "$p1 send"
$ns at 0.1 "$p3 send"
$ns at 0.2 "$p3 send"
$ns at 0.3 "$p3 send"
$ns at 0.4 "$p3 send"
$ns at 0.5 "$p3 send"
$ns at 0.6 "$p3 send"
$ns at 0.7 "$p3 send"
$ns at 0.8 "$p3 send"
$ns at 0.9 "$p3 send"
$ns at 1.0 "$p3 send"
$ns at 1.1 "$p3 send"
$ns at 1.2 "$p3 send"
$ns at 1.3 "$p3 send"
$ns at 1.4 "$p3 send"
$ns at 1.5 "$p3 send"
$ns at 1.6 "$p3 send"
$ns at 1.7 "$p3 send"
$ns at 1.8 "$p3 send"
$ns at 1.9 "$p3 send"
$ns at 2.0 "$p3 send"
$ns at 2.1 "$p3 send"
```



```
$ns at 2.2 "$p3 send"  
$ns at 2.3 "$p3 send"  
$ns at 2.4 "$p3 send"  
$ns at 2.5 "$p3 send"  
$ns at 2.6 "$p3 send"  
$ns at 2.7 "$p3 send"  
$ns at 2.8 "$p3 send"  
$ns at 2.9 "$p3 send"  
$ns at 3.0 "finish"  
$ns run
```

AWK file:

```
BEGIN{  
  drop=0;  
}  
{  
  if($1=="d")  
  {  
    drop++;  
  }  
}  
END{  
  printf("Total number of %s packets dropped due to congestion =%d\n", $5, drop);  
}
```

