

Add the following configuration to your pom.xml :

```
<plugin>
<groupId>org.apache.maven.plugins</groupId>
<artifactId>maven-jar-plugin</artifactId>
<version>3.2.0</version>
<configuration>
<archive>
<manifestEntries>
<Main-Class>com.example.Main</Main-Class>
</manifestEntries>
</archive>
</configuration>
</plugin>
```

Create a Main Class:

In your src/main/java directory, create a package with name org.example and create a class with a main method. For example, create a Main.java under org.example :

```
package org.example;
public class Main {
    public static void main(String args[])
    {
        System.out.println("Hello World");
        System.out.println("Hello welcome to devops labs");
    }
}
```

\$mvn clean package

\$ java -jar .\target\project_name.jar

Maven site & deploy Commands

```
<plugin>
<groupId>org.apache.maven.plugins</groupId>
<artifactId>maven-site-plugin</artifactId>
<version>3.12.1</version> <!-- Use latest version -->
</plugin>
```

\$mvn site

Create a folder in some drive with the name **mkdir D:\my-local-maven-repo**

```
<distributionManagement>
<repository>
<id>local-repo</id>
<url>file:///D:/my-local-maven-repo</url>
</repository>
</distributionManagement>
```

Write the above code in between </build> and </project>

\$mvn deploy