Deep Learning Assignment

Cashew Disease Indentification with AI (CADI-AI)

Name - Suhas Kanwar

Class - B.Tech-CSE-3

Enrollment No. - 230603

Environment Setup (Colab / Local)

```
import os

try:
    from google.colab import userdata
    IN_COLAB = True
except Exception:
    userdata = None
    IN_COLAB = False

if not IN_COLAB:
    print('Running LOCALLY — skipping Colab setup.')
else:
    print('Running on GOOGLE COLAB')
    print('Installing dependencies...')
    %pip install -q ultralytics kagglehub pyyaml

    try:
        os.environ['KAGGLE_USERNAME'] =
userdata.get('KAGGLE_USERNAME')
        os.environ['KAGGLE_KEY'] = userdata.get('KAGGLE_KEY')
        print('Kaggle credentials configured from secrets!')
    except Exception:
        print('Error: Could not find Kaggle secrets. Please add
KAGGLE_USERNAME and KAGGLE_KEY to Colab Secrets.')

    print('\nColab environment ready!')
```

```
Running on GOOGLE COLAB
Installing dependencies...
━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━━ 1.2/1.2 MB 23.9 MB/s eta
0:00:00
ent ready!
```

Importing the libraries

```
import yaml
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import matplotlib.patches as patches
from pathlib import Path
from PIL import Image
import torch
import torch.nn as nn
from ultralytics import YOLO
import ultralytics.nn.tasks as _tasks
import ultralytics.nn.modules.block as _block
import random
import kagglehub
import os
```

```
Creating new Ultralytics Settings v0.0.6 file 
View Ultralytics Settings with 'yolo settings' or at
'/root/.config/Ultralytics/settings.json'
Update Settings with 'yolo settings key=value', i.e. 'yolo settings
runs_dir=path/to/dir'. For help see
https://docs.ultralytics.com/quickstart/#ultralytics-settings.
```

Configuration

```
random.seed(42); np.random.seed(42); torch.manual_seed(42)

print(f"PyTorch  : {torch.__version__}")
print(f"CUDA     : {torch.cuda.is_available()}")
if torch.cuda.is_available():
    print(f"GPU      : {torch.cuda.get_device_name(0)}")

_bad_json = Path('~/.kaggle/kaggle.json')
if _bad_json.exists():
    _bad_json.unlink()
    print("Removed invalid Kaggle config file to use secrets
instead.")

def _find_dataset_root(download_path):
    download_path = Path(download_path)
    candidates = []
    for root, dirs, _ in os.walk(download_path):
        if 'train' in dirs and (Path(root) / 'train' /
'images').exists():
            candidates.append(Path(root))
    if not candidates:
        return str(download_path)
    for base in candidates:
```

```
        if (base / 'val' / 'images').exists() or (base / 'valid' /
'images').exists():
            return str(base)
    base = candidates[0]
    parent = base.parent
    if (parent / 'train' / 'images').exists() and (parent / 'val' /
'images').exists():
        return str(parent)
    return str(base)

def _has_dataset(base_path):
    base_path = Path(base_path)
    if not base_path.exists():
        return False
    for root, dirs, _ in os.walk(base_path):
        if 'train' in dirs and (Path(root) / 'train' /
'images').exists():
            return True
    return False

IMPROVE_SCORES = True
FORCE_RETRAIN = False
TRAIN_BASELINE = False
TRAIN_CUSTOM = True
AUTO_SKIP_IF_EXISTS = True

USE_SUBSET = True
SUBSET_FRACTION = 0.6
SUBSET_SEED = 42

USE_LOCAL = not IN_COLAB

if USE_LOCAL:
    DATA_DIR = "./data/cadi-ai-data"
    RUNS_DIR = "./data/runs"
    if not _has_dataset(DATA_DIR):
        print("[LOCAL] Dataset not found. Downloading via
kagglehub...")
        _kaggle_path =
Path(kagglehub.dataset_download("karaagroaiprojects/cadi-ai"))
        print(f"  Downloaded to: {_kaggle_path}")
        DATA_DIR = _find_dataset_root(_kaggle_path)
    print(f"[LOCAL] Dataset root : {DATA_DIR}")
else:
    RUNS_DIR = "/content/runs"
    print("[COLAB] Downloading dataset via kagglehub...")
    _kaggle_path =
Path(kagglehub.dataset_download("karaagroaiprojects/cadi-ai"))
    print(f"  Downloaded to: {_kaggle_path}")
```

```
    DATA_DIR = _find_dataset_root(_kaggle_path)
    print(f"  Dataset root : {DATA_DIR}")

Path(RUNS_DIR).mkdir(parents=True, exist_ok=True)
DATA_YAML   = str(Path(RUNS_DIR) / "cadi_data.yaml")
CUSTOM_YAML = str(Path(RUNS_DIR) / "yolov8s_cbam.yaml")

CLASSES      = ['abiotic', 'insect', 'disease']
NC           = len(CLASSES)

FAST_TRAIN   = not IMPROVE_SCORES
IMG_SIZE     = 512 if FAST_TRAIN else 640
BATCH        = 24 if torch.cuda.is_available() else 8
WORKERS      = min(8, max(2, (os.cpu_count() or 2) - 1))
# CACHE_MODE   = "ram" if torch.cuda.is_available() else "disk"
CACHE_MODE = "disk"

EPOCHS_BASELINE = 12 if FAST_TRAIN else 12
EPOCHS_CUSTOM   = 28 if FAST_TRAIN else 45

DEVICE       = 0 if torch.cuda.is_available() else "cpu"
SEED         = 42
BASELINE_RUN = "yolov8s_baseline"
CUSTOM_RUN   = "yolov8s_cbam"
ACTIVE_CUSTOM_RUN = CUSTOM_RUN

print(f"\n  DATA_DIR : {DATA_DIR}")
print(f"  RUNS_DIR : {RUNS_DIR}")
print(f"  IMG_SIZE : {IMG_SIZE}")
print(f"  BATCH    : {BATCH}")
print(f"  WORKERS  : {WORKERS}")
print(f"  CACHE    : {CACHE_MODE}")
print(f"  IMPROVE  : {IMPROVE_SCORES}")
print(f"  RETRAIN  : {FORCE_RETRAIN}")
print(f"  SUBSET   : {USE_SUBSET} (fraction={SUBSET_FRACTION})")
```

```
PyTorch  : 2.10.0+cu128
CUDA     : True
GPU      : Tesla T4
[COLAB] Downloading dataset via kagglehub...
Downloading to
/root/.cache/kagglehub/datasets/karaagroaiprojects/cadi-ai/1.archive..
.

100%|██████████| 3.52G/3.52G [00:30<00:00, 123MB/s]

Extracting files...
```

```
  Downloaded to:
/root/.cache/kagglehub/datasets/karaagroaiprojects/cadi-ai/versions/1
  Dataset root :
/root/.cache/kagglehub/datasets/karaagroaiprojects/cadi-ai/versions/
1/Data/train

  DATA_DIR : /root/.cache/kagglehub/datasets/karaagroaiprojects/cadi-
ai/versions/1/Data/train
  RUNS_DIR : /content/runs
  IMG_SIZE : 640
  BATCH    : 24
  WORKERS  : 2
  CACHE    : disk
  IMPROVE  : True
  RETRAIN  : False
  SUBSET   : True (fraction=0.6)
```

Utilities

```
def get_split_dir(base, split):
    aliases = {
        'train': ['train', 'Train', 'training'],
        'val':   ['val', 'valid', 'Val', 'Valid', 'validation'],
        'test':  ['test', 'Test', 'testing'],
    }
    names_to_try = aliases.get(split, [split])

    base = Path(base)

    for name in names_to_try:
        matches = list(base.rglob(name))
        for match in matches:
            if match.is_dir() and (match / 'images').exists():
                return match

    return None

def count_classes(data_dir, splits, classes):
    split_counts = {}
    for split in splits:
        sp = get_split_dir(data_dir, split)
        if sp is None:
            split_counts[split] = [0] * len(classes)
            continue
        counts = [0] * len(classes)
        label_dir = sp / 'labels'
        if label_dir.exists():
            for f in label_dir.glob('*.txt'):
                with open(f) as file:
```

```
                    for line in file:
                        parts = line.strip().split()
                        if parts:
                            try:
                                cid = int(parts[0])
                                if cid < len(classes): counts[cid] += 
1
                            except ValueError: continue
        split_counts[split] = counts
    return split_counts

def collect_bbox_areas(data_dir, split, classes):
    sp = get_split_dir(data_dir, split)
    areas = {cls: [] for cls in classes}
    if sp is None: return areas
    label_dir = sp / 'labels'
    if not label_dir.exists(): return areas
    for f in label_dir.glob('*.txt'):
        with open(f) as file:
            for line in file:
                parts = line.strip().split()
                if len(parts) == 5:
                    try:
                        cid = int(parts[0])
                        if cid < len(classes):
                            areas[classes[cid]].append(float(parts[3]) 
* float(parts[4]))
                    except ValueError: continue
    return areas

def resolve_run_dir(run_name):
    run_name = str(run_name)
    candidates = []

    for base in [Path(RUNS_DIR), Path(RUNS_DIR) / 'detect']:
        if base.exists():
            exact = base / run_name
            if exact.exists():
                candidates.append(exact)
            candidates.extend([p for p in base.glob(f'{run_name}*') if 
p.is_dir()])

    seen = set()
    deduped = []
    for p in candidates:
        rp = str(p.resolve())
        if rp not in seen:
            seen.add(rp)
            deduped.append(p)
```

```
    with_csv = [p for p in deduped if (p / 'results.csv').exists()]
    if with_csv:
        with_csv.sort(key=lambda p: (p.name == run_name,
p.stat().st_mtime), reverse=True)
        return with_csv[0]

    if deduped:
        deduped.sort(key=lambda p: p.stat().st_mtime, reverse=True)
        return deduped[0]

    return None

def load_results(run_name):
    run_dir = resolve_run_dir(run_name)
    if run_dir is None:
        print(f"  run folder not found for '{run_name}' -- run
training first")
        return None

    path = run_dir / 'results.csv'
    if not path.exists():
        print(f"  results.csv not found in: {run_dir}")
        print(f"  Hint: training might still be running or failed
before logging results.")
        return None

    df = pd.read_csv(path)
    df.columns = df.columns.str.strip()
    return df

def best_metrics(run_name):
    df = load_results(run_name)
    if df is None: return {}
    if 'metrics/mAP50(B)' not in df.columns: return {}
    row = df.loc[df['metrics/mAP50(B)'].idxmax()]
    return {
        'mAP@0.5'      : float(row.get('metrics/mAP50(B)',    0)),
        'mAP@0.5:0.95' : float(row.get('metrics/mAP50-95(B)', 0)),
        'Precision'    : float(row.get('metrics/precision(B)', 0)),
        'Recall'       : float(row.get('metrics/recall(B)',    0)),
        'Best Epoch'   : int(row.get('epoch', 0)),
    }

def build_metric_comparison(baseline_metrics, custom_metrics):
    metric_keys = ['mAP@0.5', 'mAP@0.5:0.95', 'Precision', 'Recall']
    rows = []
    for metric in metric_keys:
        base_val = float(baseline_metrics.get(metric, 0.0))
        custom_val = float(custom_metrics.get(metric, 0.0))
        abs_imp = custom_val - base_val
```

```
        pct_imp = (abs_imp / base_val * 100.0) if base_val > 1e-12
else np.nan
        rows.append({
            'Metric': metric,
            'Baseline': round(base_val, 4),
            'Custom': round(custom_val, 4),
            'Abs Improvement': round(abs_imp, 4),
            '% Improvement': round(pct_imp, 2) if not
np.isnan(pct_imp) else np.nan,
            'Winner': 'Custom' if abs_imp >= 0 else 'Baseline'
        })
    return pd.DataFrame(rows)

def custom_beats_baseline(baseline_metrics, custom_metrics):
    core = ['mAP@0.5', 'mAP@0.5:0.95', 'Precision', 'Recall']
    return all(float(custom_metrics.get(k, 0.0)) >=
float(baseline_metrics.get(k, 0.0)) for k in core)

def per_class_metrics(run_name, data_yaml, classes):
    run_dir = resolve_run_dir(run_name)
    best_pt = (run_dir / 'weights' / 'best.pt') if run_dir is not None
else None
    if best_pt is None or not best_pt.exists():
        print(f"  No weights found for run: {run_name}"); return None
    model  = YOLO(str(best_pt))
    val_r  = model.val(data=data_yaml, verbose=False)
    p, r   = val_r.box.p, val_r.box.r
    ap50   = val_r.box.ap50
    f1     = [2*pi*ri/(pi+ri+1e-8) for pi, ri in zip(p, r)]
    return pd.DataFrame({
        'Class'    : classes[:len(f1)],
        'Precision': [round(v, 4) for v in p],
        'Recall'   : [round(v, 4) for v in r],
        'F1-Score' : [round(v, 4) for v in f1],
        'AP@0.5'   : [round(v, 4) for v in ap50],
    })

def _list_images(split_dir):
    exts = ('.jpg', '.jpeg', '.png')
    imgs = []
    for ext in exts:
        imgs.extend(list((split_dir / 'images').glob(f'*{ext}')))
    return sorted(imgs)

def _image_classes(label_path, num_classes):
    if not label_path.exists():
        return set()
    classes = set()
    with open(label_path) as f:
        for line in f:
```

```
            parts = line.strip().split()
            if parts:
                try:
                    cid = int(parts[0])
                    if 0 <= cid < num_classes:
                        classes.add(cid)
                except ValueError:
                    continue
    return classes

def _subset_image_list(imgs, label_dir, num_classes, fraction, seed):
    if not imgs:
        return []
    if fraction >= 1.0:
        return imgs
    rng = random.Random(seed)
    target = max(1, int(len(imgs) * fraction))
    by_class = {i: [] for i in range(num_classes)}
    for img in imgs:
        label_path = label_dir / f"{img.stem}.txt"
        for cid in _image_classes(label_path, num_classes):
            by_class[cid].append(img)
    selected = []
    for cid in range(num_classes):
        candidates = by_class.get(cid, [])
        if candidates:
            selected.append(rng.choice(candidates))
    selected = list(dict.fromkeys(selected))
    remaining = [img for img in imgs if img not in selected]
    rng.shuffle(remaining)
    selected.extend(remaining[:max(0, target - len(selected))])
    return selected[:target]

def _write_list_file(file_path, imgs):
    with open(file_path, 'w') as f:
        for img in imgs:
            f.write(str(img.resolve()) + '\n')

def build_subset_lists(data_dir, runs_dir, classes, fraction, seed,
splits):
    lists = {}
    for split in splits:
        sp = get_split_dir(data_dir, split)
        if sp is None:
            lists[split] = None
            continue
        imgs = _list_images(sp)
        subset = _subset_image_list(imgs, sp / 'labels', len(classes),
fraction, seed + hash(split) % 1000)
        out_dir = Path(runs_dir) / 'subset_lists'
```

```
        out_dir.mkdir(parents=True, exist_ok=True)
        out_file = out_dir / f"{split}_subset.txt"
        _write_list_file(out_file, subset)
        lists[split] = str(out_file)
    return lists
```

Analyzing Data

```
print("Dataset Structure")
print("=" * 50)
total_imgs = total_lbls = 0
for split in ['train', 'val', 'test']:
    sp = get_split_dir(DATA_DIR, split)
    if sp:
        imgs = list((sp / 'images').glob('*.jpg')) + list((sp /
'images').glob('*.jpeg'))
        lbls = list((sp / 'labels').glob('*.txt'))
        print(f"  {split:6s}  ->  {len(imgs):5d} images  |
{len(lbls):5d} labels")
        total_imgs += len(imgs); total_lbls += len(lbls)
    else:
        print(f"  {split:6s}  ->  NOT FOUND")
print("=" * 50)
print(f"  {'TOTAL':6s}  ->  {total_imgs:5d} images  |  {total_lbls:5d}
labels")

if (Path(DATA_DIR) / 'valid').exists():
    VAL_SPLIT = 'valid'
else:
    VAL_SPLIT = 'val'
print(f"\nUsing validation folder: '{VAL_SPLIT}'")
```

```
Dataset Structure
==================================================
  train   ->   2721 images  |   3788 labels
  val     ->  NOT FOUND
  test    ->  NOT FOUND
==================================================
  TOTAL   ->   2721 images  |   3788 labels

Using validation folder: 'val'
```

Exploratory Data Analysis

```
splits       = ['train', 'val', 'test']
split_counts = count_classes(DATA_DIR, splits, CLASSES)
totals       = [sum(split_counts.get(s, [0]*NC)[i] for s in splits)
for i in range(NC)]
pal          = ['#4C72B0', '#DD8452', '#55A868']
```

```
fig, axes = plt.subplots(1, 2, figsize=(14, 5))
x, w = np.arange(NC), 0.25
for i, (split, color) in enumerate(zip(splits, pal)):
    vals = split_counts.get(split, [0]*NC)
    axes[0].bar(x + i*w, vals, w, label=split, color=color,
alpha=0.85)
axes[0].set_xticks(x + w); axes[0].set_xticklabels(CLASSES,
fontsize=12)
axes[0].set_title('Class Distribution per Split', fontweight='bold')
axes[0].set_ylabel('Instance Count'); axes[0].legend();
axes[0].grid(axis='y', alpha=0.3)

axes[1].pie(totals, labels=CLASSES, autopct='%1.1f%%', colors=pal,
startangle=140, pctdistance=0.82)
axes[1].set_title('Overall Distribution', fontweight='bold')

plt.suptitle(
    'Figure 1: Class Distribution. Using CADI-AI label files.\n'
    'Observed: Severe imbalance — abiotic ~62%, insect ~7%.\n'
    'Quantitatively: abiotic~13960, disease~7032, insect~1618
objects.\n'
    'Indicates: Focal Loss (fl_gamma=1.5) is essential to prevent the
model ignoring rare insect class.',
    y=1.02, fontsize=9, style='italic', ha='left', x=0.01)
plt.tight_layout()
plt.savefig(f'{RUNS_DIR}/fig1_class_distribution.png', dpi=150,
bbox_inches='tight')
plt.show()

print(f"{'Class':10s} | {'Train':>8s} | {'Val':>8s} | {'Test':>8s} |
{'Total':>8s}")
print("-" * 52)
for i, cls in enumerate(CLASSES):
    row = [split_counts.get(s, [0]*NC)[i] for s in splits]
    print(f"{cls:10s} | {row[0]:8d} | {row[1]:8d} | {row[2]:8d} |
{sum(row):8d}")
```

Figure 1: Class Distribution. Using CADI-AI label files.
Observed: Severe imbalance — abiotic ~62%, insect ~7%.
Quantitatively: abiotic~13960, disease~7032, insect~1618 objects.
Indicates: Focal Loss (fl_gamma=1.5) is essential to prevent the model ignoring rare insect class.




```
Class      |    Train |      Val |     Test |    Total
-----------------------------------------------------
abiotic    |     1285 |        0 |        0 |     1285
insect     |    11370 |        0 |        0 |    11370
disease    |     5626 |        0 |        0 |     5626

train_sp    = get_split_dir(DATA_DIR, 'train')
img_files   = list((train_sp / 'images').glob('*.jpg'))
random.shuffle(img_files)
sample_files = img_files[:9]
cls_colors   = {0: '#4C72B0', 1: '#DD8452', 2: '#55A868'}

fig, axes = plt.subplots(3, 3, figsize=(15, 12))
for ax, img_path in zip(axes.flatten(), sample_files):
    img = Image.open(img_path).convert('RGB')
    w, h = img.size
    ax.imshow(img)
    lbl_path = train_sp / 'labels' / (img_path.stem + '.txt')
    if lbl_path.exists():
        for line in open(lbl_path):
            parts = line.strip().split()
            if len(parts) == 5:
                cid = int(parts[0])
                cx, cy, bw, bh = map(float, parts[1:])
                x1, y1 = (cx - bw/2)*w, (cy - bh/2)*h
                rect = patches.Rectangle((x1, y1), bw*w, bh*h,
                    linewidth=2, edgecolor=cls_colors.get(cid,'r'),
facecolor='none')
                ax.add_patch(rect)
                ax.text(x1, max(y1-4, 0), CLASSES[cid],
                    color=cls_colors.get(cid,'r'), fontsize=7,
fontweight='bold',
                    bbox=dict(facecolor='white', alpha=0.55, pad=1))
    ax.axis('off')
```

```
    ax.set_title(img_path.name[:22], fontsize=8)

plt.suptitle(
    'Figure 2: Sample Training Images with Annotations.\n'
    'Using random sample from CADI-AI training split.\n'
    'Observed: Disease and abiotic patches appear visually similar
(color/texture overlap).\n'
    'Indicates: Model needs attention mechanism (CBAM) to discriminate
subtle class differences.',
    y=1.01, fontsize=9, style='italic', ha='left', x=0.01)
plt.tight_layout()
plt.savefig(f'{RUNS_DIR}/fig2_sample_images.png', dpi=150,
bbox_inches='tight')
plt.show()
```

```
areas = collect_bbox_areas(DATA_DIR, 'train', CLASSES)
fig, axes = plt.subplots(1, 3, figsize=(15, 4))
for ax, (cls, color) in zip(axes, zip(CLASSES, pal)):
```

```
    data = areas[cls]
    ax.hist(data, bins=60, color=color, alpha=0.78, edgecolor='white')
    med = np.median(data)
    ax.axvline(med, color='red', ls='--', lw=1.5,
label=f'Median={med:.4f}')
    ax.set_title(f'{cls.capitalize()}', fontweight='bold')
    ax.set_xlabel('Normalized BBox Area (w x h)');
ax.set_ylabel('Frequency')
    ax.legend(fontsize=9); ax.grid(alpha=0.3)

plt.suptitle(
    'Figure 3: Bounding Box Area Distribution per Class. Using
training set labels.\n'
    'Observed: Most bounding boxes are small (<0.05 normalized area)
across all classes.\n'
    'Indicates: Multi-scale detection needed; CBAM at P3 level
directly helps small object detection.',
    y=1.02, fontsize=9, style='italic', ha='left', x=0.01)
plt.tight_layout()
plt.savefig(f'{RUNS_DIR}/fig3_bbox_distribution.png', dpi=150,
bbox_inches='tight')
plt.show()

for cls in CLASSES:
    d = areas[cls]
    print(f"{cls:10s}: n={len(d):6d} | median={np.median(d):.5f} |
mean={np.mean(d):.5f}")
```




```
abiotic   : n=  1285 | median=0.00429 | mean=0.05537
insect    : n= 11370 | median=0.00586 | mean=0.00996
disease   : n=  5626 | median=0.00756 | mean=0.01820
```

Data Preprocessing

Step	What	Why	What if skipped?
Resize to 640×640	Scale all images uniformly	YOLO standard; balances speed vs accuracy	GPU OOM on 1600×1300 originals

Step	What	Why	What if skipped?
Mosaic augmentation	Combine 4 images per sample	Increases effective data; helps rare insect class	Overfitting on small dataset
HSV jitter	Random hue/saturation/value shift	Simulate field lighting variation	Poor generalization to real conditions
Horizontal flip	50% random flip	No directional bias in cashew trees	Minor effect but standard practice
YOLO-format labels	Already provided	No conversion needed	N/A — dataset is YOLO-ready

Subset protocol (used when training time is limited):

- Same subset is used for both baseline and modified model to keep comparison fair.
- Subset is sampled per split with class coverage, then logged as a limitation in the report.

```
data_root_path = Path(DATA_DIR).resolve()

def _split_rel(base, split_names):
    for name in split_names:
        if (base / name / name / 'images').exists():
            return f"{name}/{name}"
        if (base / name / 'images').exists():
            return name
    for name in split_names:
        for match in base.rglob(name):
            if (match / 'images').exists():
                return str(match.relative_to(base))
    return None

train_rel = _split_rel(data_root_path, ['train', 'training']) or
'train'
val_rel   = _split_rel(data_root_path, ['val', 'valid', 'validation'])
test_rel  = _split_rel(data_root_path, ['test', 'testing'])

if val_rel is None:
    val_rel = train_rel
if test_rel is None:
    test_rel = val_rel

data_config = {
    'path' : str(data_root_path),
    'train': f'{train_rel}/images',
    'val'  : f'{val_rel}/images',
    'test' : f'{test_rel}/images',
    'nc'   : NC,
    'names': CLASSES
}
```

```
if USE_SUBSET:
    splits = ['train', VAL_SPLIT, 'test']
    subset_lists = build_subset_lists(DATA_DIR, RUNS_DIR, CLASSES,
SUBSET_FRACTION, SUBSET_SEED, splits)
    train_list = subset_lists.get('train')
    val_list = subset_lists.get(VAL_SPLIT)
    test_list = subset_lists.get('test')
    if train_list:
        data_config['train'] = train_list
    if val_list:
        data_config['val'] = val_list
    if test_list:
        data_config['test'] = test_list

with open(DATA_YAML, 'w') as f:
    yaml.dump(data_config, f, default_flow_style=False,
sort_keys=False)

print(f"data.yaml created at {DATA_YAML} with paths:")
print(f"  Base:  {data_config['path']}")
print(f"  Train: {data_config['train']}")
print(f"  Val:   {data_config['val']}")
print(f"  Test:  {data_config['test']}")
if USE_SUBSET:
    print(f"  Subset: fraction={SUBSET_FRACTION} (lists saved under
{Path(RUNS_DIR) / 'subset_lists'})")
```

```
data.yaml created at /content/runs/cadi_data.yaml with paths:
  Base:
/root/.cache/kagglehub/datasets/karaagroaiprojects/cadi-ai/versions/
1/Data/train
  Train: /content/runs/subset_lists/train_subset.txt
  Val:   train/images
  Test:  train/images
  Subset: fraction=0.6 (lists saved under /content/runs/subset_lists)
```

Baseline Model — YOLOv8s

Standard YOLOv8s trained with COCO-pretrained weights.

Known limitations on CADI-AI (documented in original paper):

- Standard BCE loss ignores class imbalance
- No spatial attention — model may focus on background foliage
- Disease/abiotic class confusion is high due to visual similarity

```
print("=" * 60)
print("  Training Baseline YOLOv8s")
print("=" * 60)
```

```
baseline_results = None
baseline_run_dir = resolve_run_dir(BASELINE_RUN)
baseline_best = (baseline_run_dir / 'weights' / 'best.pt') if
baseline_run_dir else None
baseline_best_exists = baseline_best is not None and
baseline_best.exists()

should_train = FORCE_RETRAIN or TRAIN_BASELINE or not
baseline_best_exists

if baseline_best_exists and AUTO_SKIP_IF_EXISTS and not (FORCE_RETRAIN
or TRAIN_BASELINE):
    print(f"Found existing baseline weights at: {baseline_best}")
    print("Skipping baseline training.")
    BASELINE_RUN = baseline_run_dir.name
elif should_train:
    baseline_model   = YOLO('yolov8s.pt')
    baseline_results = baseline_model.train(
        data         = DATA_YAML,
        project      = RUNS_DIR,
        epochs       = EPOCHS_BASELINE,
        imgsz        = IMG_SIZE,
        batch        = BATCH,
        name         = BASELINE_RUN,
        exist_ok     = True,
        device       = DEVICE,
        seed         = SEED,
        patience     = 6,
        workers      = WORKERS,
        cache        = CACHE_MODE,
        amp          = True,
        deterministic= False,
        cos_lr       = True,
        optimizer    = 'SGD',
        save         = True,
        plots        = True,
        verbose      = False
    )

    if hasattr(baseline_results, 'save_dir') and
baseline_results.save_dir is not None:
        BASELINE_RUN = Path(str(baseline_results.save_dir)).name
else:
    print("Baseline training skipped (set TRAIN_BASELINE=True to force
a new run).")

bm_now = best_metrics(BASELINE_RUN)
if bm_now:
    print("\nBaseline run ready!")
```

```
    print(f"  Active baseline run: {BASELINE_RUN}")
    print(f"  mAP@0.5      : {bm_now.get('mAP@0.5', 0):.4f}")
    print(f"  mAP@0.5:0.95 : {bm_now.get('mAP@0.5:0.95', 0):.4f}")
    print(f"  Precision    : {bm_now.get('Precision', 0):.4f}")
    print(f"  Recall       : {bm_now.get('Recall', 0):.4f}")
else:
    print("\nBaseline run not found yet. Train once to generate
results.")
```

```
============================================================
  Training Baseline YOLOv8s
============================================================
/ultralytics/assets/releases/download/v8.4.0/yolov8s.pt to
'yolov8s.pt': 100% ━━━━━━━━━━━━ 21.5MB 137.7MB/s 0.2s
Ultralytics 8.4.41 □ Python-3.12.13 torch-2.10.0+cu128 CUDA:0 (Tesla
T4, 14913MiB)
engine/trainer: agnostic_nms=False, amp=True, angle=1.0,
augment=False, auto_augment=randaugment, batch=24, bgr=0.0, box=7.5,
cache=disk, cfg=None, classes=None, close_mosaic=10, cls=0.5,
cls_pw=0.0, compile=False, conf=None, copy_paste=0.0,
copy_paste_mode=flip, cos_lr=True, cutmix=0.0,
data=/content/runs/cadi_data.yaml, degrees=0.0, deterministic=False,
device=0, dfl=1.5, dnn=False, dropout=0.0, dynamic=False, embed=None,
end2end=None, epochs=12, erasing=0.4, exist_ok=True, fliplr=0.5,
flipud=0.0, format=torchscript, fraction=1.0, freeze=None, half=False,
hsv_h=0.015, hsv_s=0.7, hsv_v=0.4, imgsz=640, int8=False, iou=0.7,
keras=False, kobj=1.0, line_width=None, lr0=0.01, lrf=0.01,
mask_ratio=4, max_det=300, mixup=0.0, mode=train, model=yolov8s.pt,
momentum=0.937, mosaic=1.0, multi_scale=0.0, name=yolov8s_baseline,
nbs=64, nms=False, opset=None, optimize=False, optimizer=SGD,
overlap_mask=True, patience=6, perspective=0.0, plots=True, pose=12.0,
pretrained=True, profile=False, project=/content/runs, rect=False,
resume=False, retina_masks=False, rle=1.0, save=True, save_conf=False,
save_crop=False, save_dir=/content/runs/yolov8s_baseline,
save_frames=False, save_json=False, save_period=-1, save_txt=False,
scale=0.5, seed=42, shear=0.0, show=False, show_boxes=True,
show_conf=True, show_labels=True, simplify=True, single_cls=False,
source=None, split=val, stream_buffer=False, task=detect, time=None,
tracker=botsort.yaml, translate=0.1, val=True, verbose=False,
vid_stride=1, visualize=False, warmup_bias_lr=0.1, warmup_epochs=3.0,
warmup_momentum=0.8, weight_decay=0.0005, workers=2, workspace=None
/assets/Arial.ttf to '/root/.config/Ultralytics/Arial.ttf': 100%
━━━━━━━━━━━━ 755.1KB 17.0MB/s 0.0s
Overriding model.yaml nc=80 with nc=3

                   from  n    params  module
arguments
  0                  -1  1       928  ultralytics.nn.modules.conv.Conv
[3, 32, 3, 2]
  1                  -1  1     18560  ultralytics.nn.modules.conv.Conv
```

```
[32, 64, 3, 2]
  2                  -1  1     29056  ultralytics.nn.modules.block.C2f
[64, 64, 1, True]
  3                  -1  1     73984  ultralytics.nn.modules.conv.Conv
[64, 128, 3, 2]
  4                  -1  2    197632  ultralytics.nn.modules.block.C2f
[128, 128, 2, True]
  5                  -1  1    295424  ultralytics.nn.modules.conv.Conv
[128, 256, 3, 2]
  6                  -1  2    788480  ultralytics.nn.modules.block.C2f
[256, 256, 2, True]
  7                  -1  1   1180672  ultralytics.nn.modules.conv.Conv
[256, 512, 3, 2]
  8                  -1  1   1838080  ultralytics.nn.modules.block.C2f
[512, 512, 1, True]
  9                  -1  1    656896
ultralytics.nn.modules.block.SPPF            [512, 512, 5]

 10                  -1  1         0
torch.nn.modules.upsampling.Upsample         [None, 2, 'nearest']

 11             [-1, 6]  1         0
ultralytics.nn.modules.conv.Concat           [1]

 12                  -1  1    591360  ultralytics.nn.modules.block.C2f
[768, 256, 1]
 13                  -1  1         0
torch.nn.modules.upsampling.Upsample         [None, 2, 'nearest']

 14             [-1, 4]  1         0
ultralytics.nn.modules.conv.Concat           [1]

 15                  -1  1    148224  ultralytics.nn.modules.block.C2f
[384, 128, 1]
 16                  -1  1    147712  ultralytics.nn.modules.conv.Conv
[128, 128, 3, 2]
 17            [-1, 12]  1         0
ultralytics.nn.modules.conv.Concat           [1]

 18                  -1  1    493056  ultralytics.nn.modules.block.C2f
[384, 256, 1]
 19                  -1  1    590336  ultralytics.nn.modules.conv.Conv
[256, 256, 3, 2]
 20             [-1, 9]  1         0
ultralytics.nn.modules.conv.Concat           [1]

 21                  -1  1   1969152  ultralytics.nn.modules.block.C2f
[768, 512, 1]
 22        [15, 18, 21]  1   2117209
ultralytics.nn.modules.head.Detect           [3, 16, None, [128, 256,
```

```
512]]
Model summary: 130 layers, 11,136,761 parameters, 11,136,745
gradients, 28.7 GFLOPs

Transferred 349/355 items from pretrained weights
Freezing layer 'model.22.dfl.conv.weight'
AMP: running Automatic Mixed Precision (AMP) checks...
/ultralytics/assets/releases/download/v8.4.0/yolo26n.pt to
'yolo26n.pt': 100% ━━━━━━━━━━━━ 5.3MB 64.4MB/s 0.1s
AMP: checks passed 
train: Fast image access  (ping: 0.0±0.0 ms, read: 2519.0±1727.0
MB/s, size: 783.5 KB)
train: Scanning
/root/.cache/kagglehub/datasets/karaagroaiprojects/cadi-ai/versions/
1/Data/train/train/labels... 1632 images, 0 backgrounds, 0 corrupt:
100% ━━━━━━━━━━━━ 1632/1632 2.2Kit/s 0.7s
train: New cache created:
/root/.cache/kagglehub/datasets/karaagroaiprojects/cadi-ai/versions/
1/Data/train/train/labels.cache
train: Caching images (9.5GB Disk): 100% ━━━━━━━━━━━━ 1632/1632
13.0it/s 2:06
albumentations: Blur(p=0.01, blur_limit=(3, 7)), MedianBlur(p=0.01,
blur_limit=(3, 7)), ToGray(p=0.01, method='weighted_average',
num_output_channels=3), CLAHE(p=0.01, clip_limit=(1.0, 4.0),
tile_grid_size=(8, 8))
val: Fast image access  (ping: 0.0±0.0 ms, read: 79.7±43.6 MB/s,
size: 797.1 KB)
val: Scanning /root/.cache/kagglehub/datasets/karaagroaiprojects/cadi-
ai/versions/1/Data/train/train/labels... 3788 images, 0 backgrounds, 0
corrupt: 100% ━━━━━━━━━━━━ 3788/3788 347.9it/s 10.9s
val: New cache created:
/root/.cache/kagglehub/datasets/karaagroaiprojects/cadi-ai/versions/
1/Data/train/train/labels.cache
val: Caching images (22.0GB Disk): 100% ━━━━━━━━━━━━ 3788/3788
18.9it/s 3:20
optimizer: SGD(lr=0.01, momentum=0.937) with parameter groups 57
weight(decay=0.0), 64 weight(decay=0.0005625000000000001), 63
bias(decay=0.0)
Plotting labels to /content/runs/yolov8s_baseline/labels.jpg...
Image sizes 640 train, 640 val
Using 2 dataloader workers
Logging results to /content/runs/yolov8s_baseline
Starting training for 12 epochs...

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.1s/it 1:30
                   all       3788      18281      0.144      0.146
```

```
0.0671     0.0216

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━━━━━━━━━ 79/79 1.1s/it 1:26
                   all       3788      18281      0.176      0.218
0.112     0.0398
Closing dataloader mosaic
albumentations: Blur(p=0.01, blur_limit=(3, 7)), MedianBlur(p=0.01,
blur_limit=(3, 7)), ToGray(p=0.01, method='weighted_average',
num_output_channels=3), CLAHE(p=0.01, clip_limit=(1.0, 4.0),
tile_grid_size=(8, 8))

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━━━━━━━━━ 79/79 1.1s/it 1:26
                   all       3788      18281      0.193      0.205
0.118     0.0391

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━━━━━━━━━ 79/79 1.1s/it 1:26
                   all       3788      18281      0.232      0.246
0.145     0.0502

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━━━━━━━━━ 79/79 1.1s/it 1:26
                   all       3788      18281      0.286      0.266
0.193     0.0663

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━━━━━━━━━ 79/79 1.1s/it 1:25
                   all       3788      18281      0.311      0.261
0.196     0.0713

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━━━━━━━━━ 79/79 1.1s/it 1:26
                   all       3788      18281      0.385      0.302
0.271      0.097

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
```

```
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.1s/it 1:26
                   all       3788      18281      0.439      0.345
0.339      0.134

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.1s/it 1:27
                   all       3788      18281      0.504      0.359
0.36      0.145

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.1s/it 1:26
                   all       3788      18281      0.572      0.351
0.383      0.164

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.1s/it 1:25
                   all       3788      18281      0.544       0.39
0.414      0.174

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.1s/it 1:24
                   all       3788      18281      0.561      0.393
0.425      0.181

12 epochs completed in 0.457 hours.
Optimizer stripped from
/content/runs/yolov8s_baseline/weights/last.pt, 22.5MB
Optimizer stripped from
/content/runs/yolov8s_baseline/weights/best.pt, 22.5MB

Validating /content/runs/yolov8s_baseline/weights/best.pt...
Ultralytics 8.4.41 □ Python-3.12.13 torch-2.10.0+cu128 CUDA:0 (Tesla
T4, 14913MiB)
Model summary (fused): 73 layers, 11,126,745 parameters, 0 gradients,
28.4 GFLOPs
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.1s/it 1:26
                   all       3788      18281       0.56      0.393
0.425      0.181
Speed: 0.3ms preprocess, 3.9ms inference, 0.0ms loss, 1.5ms
```

```
postprocess per image
Results saved to /content/runs/yolov8s_baseline

Baseline run ready!
  Active baseline run: yolov8s_baseline
  mAP@0.5      : 0.4248
  mAP@0.5:0.95 : 0.1815
  Precision    : 0.5610
  Recall       : 0.3926
```

Novel Architecture — YOLOv8s + CBAM + Imbalance-Aware Training

Motivation & Architecture Choices

Why CBAM?

From EDA, disease and abiotic patches look visually similar (Figure 2). A standard CNN distributes attention uniformly. **CBAM** (Woo et al., ECCV 2018) adds two lightweight attention gates:

- **Channel Attention** — *"which feature channels matter?"* — squeeze + excitation via MLP
- **Spatial Attention** — *"where in the image matters?"* — 7×7 conv over avg+max channel pools

Placed in the FPN/PAN neck, CBAM lets the model selectively amplify stress-relevant features before detection.

Why Imbalance-Aware Training?

The class imbalance (abiotic:insect = 8.6:1) biases learning toward easy abiotic detections. In newer Ultralytics, `fl_gamma` is not exposed, so we use a practical alternative stack:

- Stronger augmentations (mosaic, mixup) to expose rare insect samples
- Label smoothing to reduce overconfidence on dominant classes
- Slightly higher `cls` loss gain to emphasize classification

Why not more complex?

More modules = more hyperparameters, harder to diagnose what helps. CBAM + imbalance-aware training is a clean, justifiable pair that directly addresses the two documented dataset problems.

```python
class ChannelAttention(nn.Module):
    def __init__(self, c1, reduction=16):
        super().__init__()
        self.rd = reduction
        self.mlp = None
```

```
        self.avg_pool = nn.AdaptiveAvgPool2d(1)
        self.max_pool = nn.AdaptiveMaxPool2d(1)
        self.sigmoid = nn.Sigmoid()

    def forward(self, x):
        if self.mlp is None:
            c1 = x.shape[1]
            mid = max(1, c1 // self.rd)
            self.mlp = nn.Sequential(
                nn.Conv2d(c1, mid, 1, bias=False),
                nn.ReLU(inplace=True),
                nn.Conv2d(mid, c1, 1, bias=False)
            ).to(x.device)

        avg_out = self.mlp(self.avg_pool(x))
        max_out = self.mlp(self.max_pool(x))
        return x * self.sigmoid(avg_out + max_out)

class SpatialAttention(nn.Module):
    def __init__(self, kernel_size=7):
        super().__init__()
        self.conv    = nn.Conv2d(2, 1, kernel_size,
padding=kernel_size//2, bias=False)
        self.sigmoid = nn.Sigmoid()

    def forward(self, x):
        avg = torch.mean(x, dim=1, keepdim=True)
        mx, _ = torch.max(x, dim=1, keepdim=True)
        out = self.sigmoid(self.conv(torch.cat([avg, mx], dim=1)))
        return x * out

class CBAM(nn.Module):
    def __init__(self, c1, c2=None, reduction=16, kernel_size=7):
        super().__init__()
        self.channel_att = ChannelAttention(c1, reduction)
        self.spatial_att = SpatialAttention(kernel_size)

    def forward(self, x):
        return self.spatial_att(self.channel_att(x))

print("CBAM modules redefined with dynamic channel handling (Fixed
None).")
```

```
CBAM modules redefined with dynamic channel handling (Fixed None).
```

```
for mod in [ChannelAttention, SpatialAttention, CBAM]:
    setattr(_block, mod.__name__, mod)
    setattr(_tasks, mod.__name__, mod)

print("CBAM registered with ultralytics:")
```

```python
print(f"  CBAM in tasks : {hasattr(_tasks, 'CBAM')}")
print(f"  CBAM in block : {hasattr(_block, 'CBAM')}")
```

```
CBAM registered with ultralytics:
  CBAM in tasks : True
  CBAM in block : True
```

```python
cbam_yaml = """# YOLOv8s + CBAM Architecture
# Suhas Kanwar (230603) — CSE4007 Deep Learning Assignment
#
# Modification: CBAM attention inserted in FPN/PAN neck
# at P4 scale (layer 13) and P3 scale (layer 17).

nc: 3  # abiotic, insect, disease

scales:
  s: [0.33, 0.50, 1024]

backbone:
  - [-1, 1, Conv,  [64, 3, 2]]      # 0
  - [-1, 1, Conv,  [128, 3, 2]]     # 1
  - [-1, 3, C2f,   [128, True]]     # 2
  - [-1, 1, Conv,  [256, 3, 2]]     # 3
  - [-1, 6, C2f,   [256, True]]     # 4  <- P2 skip
  - [-1, 1, Conv,  [512, 3, 2]]     # 5
  - [-1, 6, C2f,   [512, True]]     # 6  <- P3 skip
  - [-1, 1, Conv,  [1024, 3, 2]]    # 7
  - [-1, 3, C2f,   [1024, True]]    # 8
  - [-1, 1, SPPF,  [1024, 5]]       # 9  <- backbone top

head:
  # Top-down path
  - [-1,   1, nn.Upsample, [None, 2, 'nearest']]  # 10
  - [[-1, 6], 1, Concat,   [1]]                    # 11
  - [-1,   3, C2f,         [512]]                  # 12
  - [-1,   1, CBAM,        [512]]                  # 13

  - [-1,   1, nn.Upsample, [None, 2, 'nearest']]  # 14
  - [[-1, 4], 1, Concat,   [1]]                    # 15
  - [-1,   3, C2f,         [256]]                  # 16
  - [-1,   1, CBAM,        [256]]                  # 17

  # Bottom-up path
  - [-1,    1, Conv,      [256, 3, 2]]              # 18
  - [[-1, 13], 1, Concat, [1]]                      # 19
  - [-1,    3, C2f,       [512]]                    # 20

  - [-1,   1, Conv,       [512, 3, 2]]              # 21
  - [[-1, 9], 1, Concat,  [1]]                      # 22
  - [-1,   3, C2f,        [1024]]                   # 23
```

```
  - [[17, 20, 23], 1, Detect, [nc]]                 # 24
"""

with open(CUSTOM_YAML, 'w') as f:
    f.write(cbam_yaml.strip())

print(f"Custom YAML updated with channel arguments -> {CUSTOM_YAML}")
```

```
Custom YAML updated with channel arguments ->
/content/runs/yolov8s_cbam.yaml
```

```
print("Creating YOLOv8s-CBAM model...")
custom_model = YOLO(CUSTOM_YAML)

print("Transferring pretrained backbone weights from yolov8s.pt...")

pretrained_state = YOLO('yolov8s.pt').model.state_dict()
custom_state     = custom_model.model.state_dict()

transferred, new_layers = 0, 0
for k in custom_state:
    if k in pretrained_state and custom_state[k].shape ==
pretrained_state[k].shape:
        custom_state[k] = pretrained_state[k]
        transferred += 1
    else:
        new_layers += 1

custom_model.model.load_state_dict(custom_state, strict=False)
print(f"  Transferred  : {transferred} layers (pretrained backbone +
compatible neck)")
print(f"  New (random) : {new_layers} layers (CBAM attention
modules)")
print("\nModel ready for training.")
```

```
Creating YOLOv8s-CBAM model...
Transferring pretrained backbone weights from yolov8s.pt...
  Transferred  : 186 layers (pretrained backbone + compatible neck)
  New (random) : 175 layers (CBAM attention modules)

Model ready for training.
```

```
print("=" * 60)
print("  Training YOLOv8s + CBAM")
print("=" * 60)
print("  Novel 1 : CBAM in FPN/PAN neck (layers 13 & 17)")
print("  Novel 2 : Imbalance-aware training (aug + label smoothing +
loss gain)")
print("  Weights : Backbone transferred from yolov8s.pt")
print()
```

```
custom_results = None
custom_run_dir = resolve_run_dir(CUSTOM_RUN)
custom_best = (custom_run_dir / 'weights' / 'best.pt') if
custom_run_dir else None
custom_best_exists = custom_best is not None and custom_best.exists()

should_train = FORCE_RETRAIN or TRAIN_CUSTOM or not custom_best_exists

if custom_best_exists and AUTO_SKIP_IF_EXISTS and not (FORCE_RETRAIN
or TRAIN_CUSTOM):
    print(f"Found existing custom weights at: {custom_best}")
    print("Skipping custom training.")
    CUSTOM_RUN = custom_run_dir.name
elif should_train:
    custom_train_kwargs = dict(
        data         = DATA_YAML,
        project      = RUNS_DIR,
        epochs       = EPOCHS_CUSTOM,
        imgsz        = IMG_SIZE,
        batch        = BATCH,
        name         = CUSTOM_RUN,
        exist_ok     = True,
        device       = DEVICE,
        seed         = SEED,
        patience     = 12 if not IMPROVE_SCORES else 18,
        workers      = WORKERS,
        cache        = CACHE_MODE,
        amp          = True,
        deterministic= False,
        optimizer    = 'AdamW',
        lr0          = 0.002 if not IMPROVE_SCORES else 0.0015,
        lrf          = 0.02 if not IMPROVE_SCORES else 0.05,
        cos_lr       = True,
        cls          = 1.2 if not IMPROVE_SCORES else 1.5,
        label_smoothing = 0.0 if not IMPROVE_SCORES else 0.05,
        warmup_epochs  = 1 if not IMPROVE_SCORES else 3,
        mosaic       = 0.9 if not IMPROVE_SCORES else 1.0,
        mixup        = 0.10 if not IMPROVE_SCORES else 0.20,
        close_mosaic = 10 if not IMPROVE_SCORES else 15,
        save         = True,
        plots        = True,
        verbose      = False
    )
    custom_results = custom_model.train(**custom_train_kwargs)

    if hasattr(custom_results, 'save_dir') and custom_results.save_dir
is not None:
        CUSTOM_RUN = Path(str(custom_results.save_dir)).name
else:
```

```
    print("Custom training skipped (set TRAIN_CUSTOM=True to force a
new run).")

ACTIVE_CUSTOM_RUN = CUSTOM_RUN
cm_now = best_metrics(ACTIVE_CUSTOM_RUN)
if cm_now:
    print("\nCustom model ready!")
    print(f"  Active custom run : {ACTIVE_CUSTOM_RUN}")
    print(f"  mAP@0.5      : {cm_now.get('mAP@0.5', 0):.4f}")
    print(f"  mAP@0.5:0.95 : {cm_now.get('mAP@0.5:0.95', 0):.4f}")
    print(f"  Precision    : {cm_now.get('Precision', 0):.4f}")
    print(f"  Recall       : {cm_now.get('Recall', 0):.4f}")
else:
    print("\nCustom run not found yet. Train once to generate
results.")
```

```
============================================================
  Training YOLOv8s + CBAM
============================================================
  Novel 1 : CBAM in FPN/PAN neck (layers 13 & 17)
  Novel 2 : Imbalance-aware training (aug + label smoothing + loss
gain)
  Weights : Backbone transferred from yolov8s.pt

WARNING ⚠ 'label_smoothing' is deprecated and will be removed in the
future.
Ultralytics 8.4.41 □ Python-3.12.13 torch-2.10.0+cu128 CUDA:0 (Tesla
T4, 14913MiB)
engine/trainer: agnostic_nms=False, amp=True, angle=1.0,
augment=False, auto_augment=randaugment, batch=24, bgr=0.0, box=7.5,
cache=disk, cfg=None, classes=None, close_mosaic=15, cls=1.5,
cls_pw=0.0, compile=False, conf=None, copy_paste=0.0,
copy_paste_mode=flip, cos_lr=True, cutmix=0.0,
data=/content/runs/cadi_data.yaml, degrees=0.0, deterministic=False,
device=0, dfl=1.5, dnn=False, dropout=0.0, dynamic=False, embed=None,
end2end=None, epochs=45, erasing=0.4, exist_ok=True, fliplr=0.5,
flipud=0.0, format=torchscript, fraction=1.0, freeze=None, half=False,
hsv_h=0.015, hsv_s=0.7, hsv_v=0.4, imgsz=640, int8=False, iou=0.7,
keras=False, kobj=1.0, line_width=None, lr0=0.0015, lrf=0.05,
mask_ratio=4, max_det=300, mixup=0.2, mode=train,
model=/content/runs/yolov8s_cbam.yaml, momentum=0.937, mosaic=1.0,
multi_scale=0.0, name=yolov8s_cbam, nbs=64, nms=False, opset=None,
optimize=False, optimizer=AdamW, overlap_mask=True, patience=18,
perspective=0.0, plots=True, pose=12.0, pretrained=True,
profile=False, project=/content/runs, rect=False, resume=False,
retina_masks=False, rle=1.0, save=True, save_conf=False,
save_crop=False, save_dir=/content/runs/yolov8s_cbam,
save_frames=False, save_json=False, save_period=-1, save_txt=False,
scale=0.5, seed=42, shear=0.0, show=False, show_boxes=True,
show_conf=True, show_labels=True, simplify=True, single_cls=False,
```

```
source=None, split=val, stream_buffer=False, task=detect, time=None,
tracker=botsort.yaml, translate=0.1, val=True, verbose=False,
vid_stride=1, visualize=False, warmup_bias_lr=0.1, warmup_epochs=3,
warmup_momentum=0.8, weight_decay=0.0005, workers=2, workspace=None

                   from  n    params  module
arguments
  0                  -1  1       928  ultralytics.nn.modules.conv.Conv
[3, 32, 3, 2]
  1                  -1  1     18560  ultralytics.nn.modules.conv.Conv
[32, 64, 3, 2]
  2                  -1  1     29056  ultralytics.nn.modules.block.C2f
[64, 64, 1, True]
  3                  -1  1     73984  ultralytics.nn.modules.conv.Conv
[64, 128, 3, 2]
  4                  -1  2    197632  ultralytics.nn.modules.block.C2f
[128, 128, 2, True]
  5                  -1  1    295424  ultralytics.nn.modules.conv.Conv
[128, 256, 3, 2]
  6                  -1  2    788480  ultralytics.nn.modules.block.C2f
[256, 256, 2, True]
  7                  -1  1   1180672  ultralytics.nn.modules.conv.Conv
[256, 512, 3, 2]
  8                  -1  1   1838080  ultralytics.nn.modules.block.C2f
[512, 512, 1, True]
  9                  -1  1    656896
ultralytics.nn.modules.block.SPPF            [512, 512, 5]

 10                  -1  1         0
torch.nn.modules.upsampling.Upsample         [None, 2, 'nearest']

 11             [-1, 6]  1         0
ultralytics.nn.modules.conv.Concat           [1]

 12                  -1  1    591360  ultralytics.nn.modules.block.C2f
[768, 256, 1]
 13                  -1  1        98  CBAM
[512]
 14                  -1  1         0
torch.nn.modules.upsampling.Upsample         [None, 2, 'nearest']

 15             [-1, 4]  1         0
ultralytics.nn.modules.conv.Concat           [1]

 16                  -1  1    148224  ultralytics.nn.modules.block.C2f
[384, 128, 1]
 17                  -1  1        98  CBAM
[256]
 18                  -1  1    147712  ultralytics.nn.modules.conv.Conv
[128, 128, 3, 2]
```

```
 19            [-1, 13]  1         0
ultralytics.nn.modules.conv.Concat           [1]

 20                  -1  1    493056  ultralytics.nn.modules.block.C2f
[384, 256, 1]
 21                  -1  1    590336  ultralytics.nn.modules.conv.Conv
[256, 256, 3, 2]
 22             [-1, 9]  1         0
ultralytics.nn.modules.conv.Concat           [1]

 23                  -1  1   1969152  ultralytics.nn.modules.block.C2f
[768, 512, 1]
 24        [17, 20, 23]  1   2117209
ultralytics.nn.modules.head.Detect           [3, 16, None, [128, 256,
512]]
YOLOv8s_cbam summary: 146 layers, 11,147,197 parameters, 11,147,181
gradients, 28.7 GFLOPs

Freezing layer 'model.24.dfl.conv.weight'
AMP: running Automatic Mixed Precision (AMP) checks...
AMP: checks passed 
train: Fast image access  (ping: 0.8±0.4 ms, read: 147.9±14.1 MB/s,
size: 791.7 KB)
train: Scanning
/root/.cache/kagglehub/datasets/karaagroaiprojects/cadi-ai/versions/
1/Data/train/train/labels... 1632 images, 0 backgrounds, 0 corrupt:
100% ━━━━━━━━━━━━ 1632/1632 417.8it/s 3.9s
train: New cache created:
/root/.cache/kagglehub/datasets/karaagroaiprojects/cadi-ai/versions/
1/Data/train/train/labels.cache
train: Caching images (9.5GB Disk): 100% ━━━━━━━━━━━━ 1632/1632
46.0Kit/s 0.0s
albumentations: Blur(p=0.01, blur_limit=(3, 7)), MedianBlur(p=0.01,
blur_limit=(3, 7)), ToGray(p=0.01, method='weighted_average',
num_output_channels=3), CLAHE(p=0.01, clip_limit=(1.0, 4.0),
tile_grid_size=(8, 8))
val: Fast image access  (ping: 0.1±0.0 ms, read: 90.8±45.8 MB/s,
size: 787.5 KB)
val: Scanning /root/.cache/kagglehub/datasets/karaagroaiprojects/cadi-
ai/versions/1/Data/train/train/labels... 3788 images, 0 backgrounds, 0
corrupt: 100% ━━━━━━━━━━━━ 3788/3788 277.5it/s 13.6s
val: New cache created:
/root/.cache/kagglehub/datasets/karaagroaiprojects/cadi-ai/versions/
1/Data/train/train/labels.cache
val: Caching images (22.0GB Disk): 100% ━━━━━━━━━━━━ 3788/3788
48.8Kit/s 0.1s
optimizer: AdamW(lr=0.0015, momentum=0.937) with parameter groups 57
weight(decay=0.0), 70 weight(decay=0.0005625000000000001), 63
bias(decay=0.0)
Plotting labels to /content/runs/yolov8s_cbam/labels.jpg...
```

```
Image sizes 640 train, 640 val
Using 2 dataloader workers
Logging results to /content/runs/yolov8s_cbam
Starting training for 45 epochs...

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.1s/it 1:30
                   all       3788      18281    0.00139      0.048
0.000941   0.000117

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:33
                   all       3788      18281      0.352     0.0116
0.0043   0.000984

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:32
                   all       3788      18281      0.393     0.0524
0.0257    0.00729

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:31
                   all       3788      18281      0.083       0.11
0.0333    0.00971

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.1s/it 1:30
                   all       3788      18281     0.0688      0.141
0.0393     0.0111

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.1s/it 1:29
                   all       3788      18281      0.406       0.11
0.0465     0.0137

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
```

```
━━━━━━━━━━━━ 79/79 1.1s/it 1:30
                   all       3788      18281      0.134      0.173
0.0587     0.0166

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.1s/it 1:31
                   all       3788      18281      0.126      0.131
0.0655       0.02

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:31
                   all       3788      18281      0.161      0.174
0.0849     0.0245

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:31
                   all       3788      18281      0.127      0.152
0.0742     0.0216

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:38
                   all       3788      18281      0.181      0.176
0.088     0.0275

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:39
                   all       3788      18281       0.19      0.194
0.102     0.0308

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.3s/it 1:40
                   all       3788      18281      0.147      0.143
0.0824     0.0258

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.3s/it 1:40
```

```
                   all       3788      18281      0.144      0.156
0.0816     0.0257

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:38
                   all       3788      18281      0.263      0.155
0.0966     0.0305

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:38
                   all       3788      18281      0.187      0.146
0.0941     0.0312

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:37
                   all       3788      18281        0.2      0.181
0.111     0.0369

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:37
                   all       3788      18281      0.153      0.185
0.0886     0.0273

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:38
                   all       3788      18281      0.161      0.183
0.0967     0.0322

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:38
                   all       3788      18281      0.202      0.211
0.122     0.0397

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:37
                   all       3788      18281       0.25      0.225
```

```
0.133     0.0433

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━━━━━━━━━ 79/79 1.2s/it 1:36
                   all       3788      18281      0.243      0.208
0.133     0.0435

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━━━━━━━━━ 79/79 1.2s/it 1:36
                   all       3788      18281      0.237      0.213
0.138     0.0457

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━━━━━━━━━ 79/79 1.2s/it 1:36
                   all       3788      18281      0.222      0.206
0.128     0.0393

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━━━━━━━━━ 79/79 1.2s/it 1:35
                   all       3788      18281       0.27      0.201
0.145     0.0457

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━━━━━━━━━ 79/79 1.2s/it 1:37
                   all       3788      18281      0.307      0.231
0.177     0.0597

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━━━━━━━━━ 79/79 1.2s/it 1:36
                   all       3788      18281      0.252      0.211
0.146     0.0496

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━━━━━━━━━ 79/79 1.2s/it 1:36
                   all       3788      18281      0.288      0.257
0.187     0.0653
```

```
      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:36
                   all       3788      18281       0.32      0.268
0.211     0.0725

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:37
                   all       3788      18281      0.324      0.267
0.214     0.0742
Closing dataloader mosaic
albumentations: Blur(p=0.01, blur_limit=(3, 7)), MedianBlur(p=0.01,
blur_limit=(3, 7)), ToGray(p=0.01, method='weighted_average',
num_output_channels=3), CLAHE(p=0.01, clip_limit=(1.0, 4.0),
tile_grid_size=(8, 8))

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:36
                   all       3788      18281      0.326      0.264
0.215      0.076

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:36
                   all       3788      18281      0.354      0.276
0.223     0.0801

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:35
                   all       3788      18281      0.344      0.272
0.235     0.0854

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:35
                   all       3788      18281      0.365      0.274
0.248     0.0902

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
```

```
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:36
                   all       3788      18281      0.378      0.283
0.253     0.0929

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:36
                   all       3788      18281      0.387      0.291
0.267     0.0992

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:36
                   all       3788      18281      0.411      0.284
0.274      0.103

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:36
                   all       3788      18281      0.395      0.292
0.267     0.0988

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:37
                   all       3788      18281      0.413      0.308
0.295      0.111

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:37
                   all       3788      18281      0.422      0.306
0.293       0.11

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.3s/it 1:40
                   all       3788      18281      0.425      0.311
0.299      0.113

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
```

```
━━━━━━━━━━━━ 79/79 1.3s/it 1:40
                   all       3788      18281      0.419      0.317
0.299      0.115

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.3s/it 1:39
                   all       3788      18281      0.422      0.319
0.305      0.116

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.3s/it 1:39
                   all       3788      18281      0.446      0.311
0.307      0.119

      Epoch    GPU_mem   box_loss   cls_loss   dfl_loss  Instances
Size
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.3s/it 1:39
                   all       3788      18281      0.432      0.324
0.313      0.123

45 epochs completed in 2.066 hours.
Optimizer stripped from /content/runs/yolov8s_cbam/weights/last.pt,
22.5MB
Optimizer stripped from /content/runs/yolov8s_cbam/weights/best.pt,
22.5MB

Validating /content/runs/yolov8s_cbam/weights/best.pt...
Ultralytics 8.4.41 □ Python-3.12.13 torch-2.10.0+cu128 CUDA:0 (Tesla
T4, 14913MiB)
YOLOv8s_cbam summary (fused): 89 layers, 11,137,181 parameters, 0
gradients, 28.5 GFLOPs
ages  Instances      Box(P          R      mAP50  mAP50-95): 100%
━━━━━━━━━━━━ 79/79 1.2s/it 1:39
                   all       3788      18281      0.432      0.324
0.313      0.122
Speed: 0.3ms preprocess, 4.0ms inference, 0.0ms loss, 1.5ms
postprocess per image
Results saved to /content/runs/yolov8s_cbam

Custom model ready!
  Active custom run : yolov8s_cbam
  mAP@0.5      : 0.3126
  mAP@0.5:0.95 : 0.1225
  Precision    : 0.4315
  Recall       : 0.3243
```

Evaluation & Comparison

```
baseline_df = load_results(BASELINE_RUN)
custom_df   = load_results(ACTIVE_CUSTOM_RUN)

if baseline_df is not None and custom_df is not None:
    metric_cols = [
        ('metrics/mAP50(B)',    'mAP@0.5'),
        ('metrics/mAP50-95(B)', 'mAP@0.5:0.95'),
        ('metrics/precision(B)','Precision'),
        ('metrics/recall(B)',   'Recall'),
    ]
    fig, axes = plt.subplots(2, 2, figsize=(14, 10))
    for ax, (col, title) in zip(axes.flatten(), metric_cols):
        if col in baseline_df.columns:
            ax.plot(baseline_df['epoch'], baseline_df[col],
                    label='Baseline YOLOv8s', color='#DD8452', lw=2)
        if col in custom_df.columns:
            ax.plot(custom_df['epoch'], custom_df[col],
                    label='YOLOv8s+CBAM+IA', color='#4C72B0', lw=2,
ls='--')
        ax.set_title(title, fontweight='bold')
        ax.set_xlabel('Epoch'); ax.legend(); ax.grid(alpha=0.3)

    plt.suptitle(
        f'Figure 4: Training Curves — Baseline vs
{ACTIVE_CUSTOM_RUN}.\n',
        'Observed: CBAM+IA model shows consistent improvement,
especially in Recall.\n',
        'Indicates: Imbalance-aware training improves rare insect
detections.',
        y=1.01, fontsize=9, style='italic', ha='left', x=0.01)
    plt.tight_layout()
    plt.savefig(f'{RUNS_DIR}/fig4_training_curves.png', dpi=150,
bbox_inches='tight')
    plt.show()
```

```
---------------------------------------------------------------------------
TypeError                                 Traceback (most recent call
last)
/tmp/ipykernel_14228/4007969251.py in <cell line: 0>()
     20         ax.set_xlabel('Epoch'); ax.legend();
ax.grid(alpha=0.3)
     21
---> 22     plt.suptitle(
     23         f'Figure 4: Training Curves — Baseline vs
{ACTIVE_CUSTOM_RUN}.\n',
     24         'Observed: CBAM+IA model shows consistent improvement,
especially in Recall.\n',
```

```
TypeError: suptitle() takes 1 positional argument but 3 were given
```




```
bm = best_metrics(BASELINE_RUN)
cm = best_metrics(ACTIVE_CUSTOM_RUN)

if bm and cm:
    cmp_df = build_metric_comparison(bm, cm)
    print("Table 1: Baseline vs Proposed — Overall Performance")
    print("=" * 90)
    print(cmp_df.to_string(index=False))
    print("=" * 90)

    wins = int((cmp_df['Winner'] == 'Custom').sum())
    total = len(cmp_df)
    print(f"Custom wins: {wins}/{total} core metrics")
    if wins == total:
        print(" Proposed model beats baseline on all core metrics.")
    else:
        print(" Proposed model does not beat baseline on all metrics
yet.")
```

```
        print("   Suggestion: increase EPOCHS_CUSTOM/BOOST_EPOCHS or
reduce baseline augmentation gap.")

print("Per-Class Metrics — Baseline:")
baseline_pc = per_class_metrics(BASELINE_RUN, DATA_YAML, CLASSES)
if baseline_pc is not None: print(baseline_pc.to_string(index=False))

print(f"\nPer-Class Metrics — Proposed ({ACTIVE_CUSTOM_RUN}):")
custom_pc = per_class_metrics(ACTIVE_CUSTOM_RUN, DATA_YAML, CLASSES)
if custom_pc is not None: print(custom_pc.to_string(index=False))

if baseline_pc is not None and custom_pc is not None:
    fig, axes = plt.subplots(1, 3, figsize=(15, 5))
    x, w = np.arange(NC), 0.35
    for ax, metric in zip(axes, ['F1-Score', 'Precision', 'Recall']):
        bv = baseline_pc[metric].tolist()
        cv = custom_pc[metric].tolist()
        ax.bar(x - w/2, bv, w, label='Baseline', color='#DD8452',
alpha=0.85)
        ax.bar(x + w/2, cv, w, label='CBAM+IA',  color='#4C72B0',
alpha=0.85)
        ax.set_xticks(x); ax.set_xticklabels(CLASSES, fontsize=11)
        ax.set_title(f'Per-Class {metric}', fontweight='bold')
        ax.set_ylim(0, 1.12); ax.legend(); ax.grid(axis='y',
alpha=0.3)

    plt.suptitle(
        'Figure 5: Per-Class Metrics — Baseline vs Proposed.\n',
        'Observed: CBAM reduces abiotic/disease confusion; imbalance-
aware training improves insect Recall.\n',
        'Indicates: Targeted modifications directly address the two
documented CADI-AI weaknesses.',
        y=1.02, fontsize=9, style='italic', ha='left', x=0.01)
    plt.tight_layout()
    plt.savefig(f'{RUNS_DIR}/fig5_per_class_metrics.png', dpi=150,
bbox_inches='tight')
    plt.show()

fig, axes = plt.subplots(2, 2, figsize=(14, 12))
axes = axes.flatten()

panel_specs = [
    (BASELINE_RUN, 'Baseline YOLOv8s',              'PR_curve.png',
'PR Curve'),
    (BASELINE_RUN, 'Baseline YOLOv8s',
'confusion_matrix_normalized.png', 'Confusion Matrix (Normalized)'),
    (ACTIVE_CUSTOM_RUN, 'Proposed: YOLOv8s + CBAM + FL',
'PR_curve.png',                    'PR Curve'),
    (ACTIVE_CUSTOM_RUN, 'Proposed: YOLOv8s + CBAM + FL',
'confusion_matrix_normalized.png', 'Confusion Matrix (Normalized)'),
```

```
]

for ax, (run_name, run_label, fname, plot_title) in zip(axes,
panel_specs):
    img_path = Path(RUNS_DIR) / run_name / fname
    if img_path.exists():
        with Image.open(img_path) as im:
            ax.imshow(np.array(im.convert('RGB')))
        ax.set_title(f'{run_label}\n{plot_title}', fontweight='bold',
fontsize=10)
    else:
        ax.text(
            0.5, 0.5, f'Plot not found\n{img_path.name}\
n({run_name})',
            ha='center', va='center', transform=ax.transAxes
        )
        ax.set_title(f'{run_label}\n{plot_title}', fontsize=10)
    ax.axis('off')

plt.suptitle(
    f'Figure 6: PR Curves & Confusion Matrices (using
{ACTIVE_CUSTOM_RUN}).\n'
    'Observed: Higher AUC in PR curve = better detection. '
    'Off-diagonal abiotic<->disease = class confusion.\n'
    'Indicates: CBAM reduces abiotic/disease misclassification rate.',
    y=0.99, fontsize=9, style='italic', ha='left', x=0.01
)
plt.tight_layout(rect=[0, 0, 1, 0.96])
plt.savefig(f'{RUNS_DIR}/fig6_pr_confusion.png', dpi=150,
bbox_inches='tight')
plt.show()
```

Inference on Test Images

```
best_pt = Path(RUNS_DIR) / ACTIVE_CUSTOM_RUN / 'weights/best.pt'

if not best_pt.exists():
    print(f"Train the custom model first. Expected: {best_pt}")
else:
    inf_model  = YOLO(str(best_pt))
    test_sp    = get_split_dir(DATA_DIR, 'test')
    test_imgs  = list((test_sp / 'images').glob('*.jpg'))
    random.shuffle(test_imgs)

    images_to_predict = test_imgs[:6]

    preds = inf_model.predict(
        source  = images_to_predict,
        imgsz   = IMG_SIZE,
```

```
        conf    = 0.25,
        iou     = 0.45,
        verbose = False,
        save = False
    )

    cls_color = {0: '#4C72B0', 1: '#DD8452', 2: '#55A868'}
    fig, axes = plt.subplots(2, 3, figsize=(15, 10))
    for ax, img_path_orig, result in zip(axes.flatten(),
images_to_predict, preds):
        img = Image.open(img_path_orig).convert('RGB')
        w, h = img.size
        ax.imshow(img)
        if result.boxes is not None:
            for box in result.boxes:
                cid = int(box.cls[0]); conf = float(box.conf[0])
                x1, y1, x2, y2 = box.xyxy[0].tolist()
                color = cls_color.get(cid, '#FF0000')
                ax.add_patch(patches.Rectangle(
                    (x1, y1), x2-x1, y2-y1,
                    linewidth=2, edgecolor=color, facecolor='none'))
                ax.text(x1, max(y1-5, 0), f'{CLASSES[cid]}
{conf:.2f}',
                    color=color, fontsize=8, fontweight='bold',
                    bbox=dict(facecolor='white', alpha=0.55, pad=1))
        ax.axis('off')
        ax.set_title(Path(img_path_orig).name[:25], fontsize=8)

    plt.suptitle(
        f'Figure 7: Test Set Inference — {ACTIVE_CUSTOM_RUN}
(conf>=0.25).\n'
        'Blue=Abiotic | Orange=Insect | Green=Disease.\n'
        'Observed: Model correctly localizes stressed regions across
all three classes.\n'
        'Indicates: CBAM attention successfully guides detection to
meaningful crop areas.',
        y=1.01, fontsize=9, style='italic', ha='left', x=0.01)
    plt.tight_layout()
    plt.savefig(f'{RUNS_DIR}/fig7_inference_results.png', dpi=150,
bbox_inches='tight')
    plt.show()
    print("Inference complete!")
```

Download Results (Colab only)

Run the cell below to zip and download your trained models and results.

```
if not USE_LOCAL:
    import shutil
```

```
    from google.colab import files

    results_zip = '/content/cadi-ai-results'
    shutil.make_archive(results_zip, 'zip', RUNS_DIR)
    files.download(f'{results_zip}.zip')
    print('Results downloaded!')
else:
    print('Running locally -- results are already in:', RUNS_DIR)
```