
CSS Basics

Ref: <https://www.w3schools.com/> and
other internet based tutorials

Ways of Adding CSS

- There are three ways of inserting a style sheet:
 - ❑ External CSS
 - ❑ Internal CSS
 - ❑ Inline CSS
-

External CSS

- With an external style sheet, you can change the look of an entire website by changing just one file!
- Each HTML page must include a reference to the external style sheet file inside the <link> element, inside the head section.

```
!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<link rel="stylesheet" type="text/css" href="mystyle.css">
```

```
</head>
```

```
<body>
```

```
<h1>This is a heading</h1>
```

```
<p>This is a paragraph.</p>
```

```
</body>
```

```
</html>
```

- An external style sheet can be written in any text editor, and must be saved with a .css extension.
- The external .css file should not contain any HTML tags.
- "mystyle.css" file looks like:

```
body {  
    background-color: lightblue;  
}  
  
h1 {  
    color: navy;  
    margin-left: 20px;  
}
```

Internal CSS

- An internal style sheet may be used if one single HTML page has a unique style.
- The internal style is defined inside the <style> element, inside the head section.

```
<!DOCTYPE html>
```

```
<html>
```

```
<head>
```

```
<style>
```

```
body {
```

```
    background-color: linen;
```

```
}
```

```
h1 {
```

```
    color: maroon; margin-left: 40px;
```

```
}
```

```
</style>
```

```
</head>
```

```
<body>
```

```
<h1>This is a heading</h1>
```

```
<p>This is a paragraph.</p>
```

```
</body> </html>
```

Inline CSS

- An inline style may be used to apply a unique style for a single element.
- To use inline styles, add the style attribute to the relevant element. The style attribute can contain any CSS property.

```
<!DOCTYPE html>
```

```
<html>
```

```
<body>
```

```
<h1 style="color:blue;text-align:center;">This is a heading</h1>
```

```
<p style="color:red;">This is a paragraph.</p>
```

```
</body>
```

```
</html>
```

Cascading Order

- What style will be used when there is more than one style specified for an HTML element?
- All the styles in a page will "cascade" into a new "virtual" style sheet by the following rules, where number one has the highest priority:
 1. Inline style (inside an HTML element)
 2. External and internal style sheets (in the head section)
 3. Browser default
- So, an inline style has the highest priority, and will override external and internal styles and browser defaults.

CSS Backgrounds

- The CSS background properties are used to define the background effects for elements.
 - CSS background properties:
 - background-color
 - background-image
 - background-attachment
 - background-position
-

CSS Backgrounds

- The background image for a page can be set like this:

```
body {  
    background-image: url("paper.gif");  
}
```

- To repeat an image vertically, set background-repeat: repeat-y;
- CSS background-repeat: no-repeat

```
body {  
    background-image: url("img_tree.png");  
    background-repeat: no-repeat;  
}
```

- In the example above, the background image is placed in the same place as the text. We want to change the position of the image, so that it does not disturb the text too much.

- background-position property is used to specify the position of the background image.

■ CSS background - Shorthand property

- To shorten the code, it is also possible to specify all the background properties in one single property. This is called a shorthand property.
- The shorthand property for background is background.
- Example
- Use the shorthand property to set all the background properties in one declaration:
- `body {`
- `background: #fddddd url("img_tree.png") no-repeat fixed right top;`
- `}`
- When using the shorthand property the order of the property values is:
- background-color
- background-image
- background-repeat
- ~~background-attachment~~
- background-position

All CSS Background Properties

Property	Description
<u>background</u>	Sets all the background properties in one declaration
<u>background-attachment</u>	Sets whether a background image is fixed or scrolls with the rest of the page
<u>background-color</u>	Sets the background color of an element
<u>background-image</u>	Sets the background image for an element
<u>background-position</u>	Sets the starting position of a background image
<u>background-repeat</u>	Sets how a background image will be repeated
<u>background-size</u>	Specifies the size of the background image(s)