

Command	Purpose
hostname	Displays the name of the current machine.
sudo /home/cloudera/cloudera-manager --express --force	Starts/configures Cloudera Manager in express mode.
service hadoop-hdfs-namenode restart	Restarts the HDFS NameNode service.
hadoop fs -ls /	Lists files and directories in the HDFS root directory.
hdfs dfs -ls /	Also lists HDFS files/directories. This is the newer HDFS command form.
hdfs dfs -lsr /	Recursively lists files and directories under /.
sudo -u hdfs hadoop dfs -mkdir /Ayesha	Creates an HDFS directory named Ayesha.
hdfs dfs -touchz /Ayesha/myfile.txt	Creates an empty file in HDFS.
gedit kk.txt	Opens a local text file for entering/saving content.
sudo -u hdfs hadoop dfs -put kk.txt /Ayesha	Uploads kk.txt from the local system into HDFS /Ayesha.
sudo su	Switches to the root user.
hadoop fs -get /Ayesha/kk.txt /root/Desktop	Downloads a file from HDFS to the local Desktop directory.
exit	Exits the root user shell.
hadoop dfs -mkdir /taru	Creates an HDFS directory named taru.
hadoop dfs -cp /Ayesha /taru	Copies files/directories from /Ayesha to /taru.

<code>hadoop dfs -mv /Ayesha/PP.txt /taru</code>	Moves PP.txt into /taru.
<code>hadoop dfs -rm /Ayesha</code>	Removes a file; a directory generally needs recursive deletion.
<code>hadoop dfs -du /taru</code>	Shows disk usage of files/directories in /taru.
<code>hadoop dfs -dus /taru</code>	Shows summarized disk usage of /taru.
<code>hadoop dfs -setrep -R -w 4 /taru/PP.txt</code>	Sets the replication factor of the file to 4 and waits for replication to complete.
<code>hadoop dfs -stat /taru</code>	Displays status/metadata information about /taru.
<code>hadoop dfs -rm /taru/PP.txt</code>	Deletes PP.txt from HDFS.
<code>hadoop dfs -rmr /taru</code>	Recursively removes the /taru directory and its contents.
<code>service hadoop-hdfs-namenode stop</code>	Stops the HDFS NameNode service.