

DRAFT

This document is a draft and can only be used for review and feedback puposes

846 Inventory Inquiry/Advice

X12/V6010/846 : 846 Inventory Inquiry/Advice

Version: 1.0 Draft

Company:	Hewlett Packard
Publication:	5/16/2022
Trading Partner:	

Notes

Table of Contents

846	Inventory Inquiry/Advice	1
ISA	Interchange Control Header	2
GS	Functional Group Header	4
ST	Transaction Set Header	5
BIA	Beginning Segment for Inventory Inquiry/Advice	6
N1	Loop Party Identification	7
N1	Party Identification	8
LIN	Loop Item Identification	9
LIN	Item Identification	10
REF	Reference Information	11
QTY	Loop Quantity Information	12
QTY	Quantity Information	13
SCH	Loop Line Item Schedule	15
SCH	Line Item Schedule	16
CTT	Transaction Totals	17
SE	Transaction Set Trailer	18
GE	Functional Group Trailer	19
IEA	Interchange Control Trailer	20

846 Inventory Inquiry/Advice

Functional Group=IB

Purpose: This X12 Transaction Set contains the format and establishes the data contents of the Inventory Inquiry/Advice Transaction Set (846) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used in the following ways: (1) for a seller of goods and services to provide inventory information to a prospective purchaser, with no obligation to the purchaser to acquire these goods or services; (2) for a representative of a seller of goods and services to supply inventory information to that seller; (3) for one location to supply another location with inventory information; and (4) for an inquiry as to the availability of inventory with no obligation on the seller of goods and services to reserve that inventory.

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>
	ISA	Interchange Control Header	M	1		
	GS	Functional Group Header	M	1		

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>
0100	ST	Transaction Set Header	M	1		
0200	BIA	Beginning Segment for Inventory Inquiry/Advice	M	1		
LOOP ID - N1					5	
0800	N1	Party Identification	O	1		

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>
LOOP ID - LIN					>1	
0100	LIN	Item Identification	M	1		
1400	REF	Reference Information	O	>1		
LOOP ID - QTY					99	
3200	QTY	Quantity Information	O	1		
LOOP ID - SCH					25	
3600	SCH	Line Item Schedule	O	1		

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>
0100	CTT	Transaction Totals	O	1		N3/0100
0200	SE	Transaction Set Trailer	M	1		

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>
	GE	Functional Group Trailer	M	1		
	IEA	Interchange Control Trailer	M	1		

Notes:

3/0100 Number of line items (CTT01) is the accumulation of number of LIN segments. If used, hash total (CTT02) is the sum of the values of the quantities (QTY02) of each QTY segment.

ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

Purpose: To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier	M	ID	2/2	Must use
Description: Code identifying the type of information in the Authorization Information						
Code List Summary (Total Codes: 9, Included: 1)						
Code Name						
00 No Authorization Information Present (No Meaningful Information in I02)						
ISA02	I02	Authorization Information	M	AN	10/10	Must use
Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)						
ISA03	I03	Security Information Qualifier	M	ID	2/2	Must use
Description: Code identifying the type of information in the Security Information						
Code List Summary (Total Codes: 2, Included: 1)						
Code Name						
00 No Security Information Present (No Meaningful Information in I04)						
ISA04	I04	Security Information	M	AN	10/10	Must use
Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)						
ISA05	I05	Interchange ID Qualifier	M	ID	2/2	Must use
Description: Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified						
Code List Summary (Total Codes: 41, Included: 1)						
Code Name						
01 Duns (Dun & Bradstreet)						
ISA06	I06	Interchange Sender ID	M	AN	15/15	Must use
Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element						
ISA07	I05	Interchange ID Qualifier	M	ID	2/2	Must use
Description: Code indicating the system/method of code structure used to designate the sender or receiver ID element being qualified						
Code List Summary (Total Codes: 41, Included: 1)						
Code Name						
14 Duns Plus Suffix						
ISA08	I07	Interchange Receiver ID	M	AN	15/15	Must use
Description: Identification code published by the receiver of the data; When sending, it is						

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them				
ISA09	I08	Interchange Date	M	DT	6/6	Must use
		Description: Date of the interchange				
ISA10	I09	Interchange Time	M	TM	4/4	Must use
		Description: Time of the interchange				
ISA11	I65	Repetition Separator	M		1/1	Must use
		Description: Type is not applicable; the repetition separator is a delimiter and not a data element; this field provides the delimiter used to separate repeated occurrences of a simple data element or a composite data structure; this value must be different than the data element separator, component element separator, and the segment terminator				
ISA12	I11	Interchange Control Version Number	M	ID	5/5	Must use
		Description: Code specifying the version number of the interchange control segments				
		Code List Summary (Total Codes: 27, Included: 1)				
		Code Name				
		00400 ASC X12 Standards Issued by ANSI in 1997				
ISA13	I12	Interchange Control Number	M	N0	9/9	Must use
		Description: A control number assigned by the interchange sender				
ISA14	I13	Acknowledgment Requested	M	ID	1/1	Must use
		Description: Code indicating sender's request for an interchange acknowledgment				
		Code List Summary (Total Codes: 2, Included: 1)				
		Code Name				
		0 No Interchange Acknowledgment Requested				
ISA15	I14	Interchange Usage Indicator	M	ID	1/1	Must use
		Description: Code indicating whether data enclosed by this interchange envelope is test, production or information				
		Code List Summary (Total Codes: 3, Included: 1)				
		Code Name				
		P Production Data				
ISA16	I15	Component Element Separator	M		1/1	Must use
		Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator				

GS Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

Purpose: To indicate the beginning of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code	M	ID	2/2	Must use

Description: Code identifying a group of application related transaction sets

Code List Summary (Total Codes: 260, Included: 1)

Code Name

IB Inventory Inquiry/Advice (846)

GS02	142	Application Sender's Code	M	AN	2/15	Must use
------	-----	----------------------------------	---	----	------	----------

Description: Code identifying party sending transmission; codes agreed to by trading partners

GS03	124	Application Receiver's Code	M	AN	2/15	Must use
------	-----	------------------------------------	---	----	------	----------

Description: Code identifying party receiving transmission; codes agreed to by trading partners

GS04	373	Date	M	DT	8/8	Must use
------	-----	-------------	---	----	-----	----------

Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year

GS05	337	Time	M	TM	4/8	Must use
------	-----	-------------	---	----	-----	----------

Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)

GS06	28	Group Control Number	M	N0	1/9	Must use
------	----	-----------------------------	---	----	-----	----------

Description: Assigned number originated and maintained by the sender

GS07	455	Responsible Agency Code	M	ID	1/2	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480

Code List Summary (Total Codes: 2, Included: 1)

Code Name

X Accredited Standards Committee X12

GS08	480	Version / Release / Industry Identifier Code	M	AN	1/12	Must use
------	-----	---	---	----	------	----------

Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed

Code List Summary (Total Codes: 71, Included: 1)

Code Name

006010 Standards Approved for Publication by ASC X12 Procedures Review Board through October 2008

ST Transaction Set Header

Pos: 0100	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use

Description: Code uniquely identifying a Transaction Set

Code List Summary (Total Codes: 319, Included: 1)

Code Name

846 Inventory Inquiry/Advice

ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

BIA Beginning Segment for Inventory Inquiry/Advice

Pos: 0200	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

Purpose: To indicate the beginning of an Inventory Inquiry/Advice Transaction Set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>				
BIA01	353	Transaction Set Purpose Code	M	ID	2/2	Must use				
Description: Code identifying purpose of transaction set										
Code List Summary (Total Codes: 67, Included: 1)										
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>00</td><td>Original</td></tr></table>							<u>Code</u>	<u>Name</u>	00	Original
<u>Code</u>	<u>Name</u>									
00	Original									
BIA02	755	Report Type Code	M	ID	2/2	Must use				
Description: Code indicating the title or contents of a document, report or supporting item										
Code List Summary (Total Codes: 553, Included: 1)										
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>MB</td><td>Manufacturer/Distributor Inventory Report</td></tr></table>							<u>Code</u>	<u>Name</u>	MB	Manufacturer/Distributor Inventory Report
<u>Code</u>	<u>Name</u>									
MB	Manufacturer/Distributor Inventory Report									
BIA03	127	Reference Identification	M	AN	1/80	Must use				
Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier										
HPE USAGE:										
Warehouse ID or HPE Plant Number										
BIA04	373	Date	M	DT	8/8	Must use				
Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year										

Loop Party Identification

Pos: 0800	Repeat: 5
Optional	
Loop: N1	Elements: N/A

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>
0800	N1	Party Identification	O	1	

N1 Party Identification

Pos: 0800	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

Loop Path: N1

Purpose: To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use

Description: Code identifying an organizational entity, a physical location, property or an individual

Code List Summary (Total Codes: 1521, Included: 1)

<u>Code</u>	<u>Name</u>
-------------	-------------

HA	Owner
----	-------

HPE USAGE:

Owner of the Inventory

N102	93	Name	X	AN	1/60	Must use
------	----	------	---	----	------	----------

Description: Free-form name

N103	66	Identification Code Qualifier	X	ID	1/2	Must use
------	----	-------------------------------	---	----	-----	----------

Description: Code designating the system/method of code structure used for Identification Code (67)

Code List Summary (Total Codes: 251, Included: 1)

<u>Code</u>	<u>Name</u>
-------------	-------------

91	Assigned by Seller or Seller's Agent
----	--------------------------------------

N104	67	Identification Code	X	AN	2/80	Must use
------	----	---------------------	---	----	------	----------

Description: Code identifying a party or other code

Loop Item Identification

Pos: 0100	Repeat: >1
Mandatory	
Loop: LIN	Elements: N/A

Purpose: To specify basic item identification data

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>
0100	LIN	Item Identification	M	1	
1400	REF	Reference Information	O	>1	
3200		Loop QTY	O		99

LIN Item Identification

Pos: 0100	Max: 1
Detail - Mandatory	
Loop: LIN	Elements: 3

Loop Path: LIN

Purpose: To specify basic item identification data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
LIN01	350	Assigned Identification	O	AN	1/20	Must use
		Description: Alphanumeric characters assigned for differentiation within a transaction set				
LIN02	235	Product/Service ID Qualifier	M	ID	2/2	Must use
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		Code List Summary (Total Codes: 518, Included: 1)				
		Code	Name			
		VP	Vendor's (Seller's) Part Number			
LIN03	234	Product/Service ID	M	AN	1/80	Must use
		Description: Identifying number for a product or service				
		HPE USAGE:				
		<i>HPE Part Number</i>				

REF Reference Information

Pos: 1400	Max: >1
Detail - Optional	
Loop: LIN	Elements: 2

Loop Path: LIN

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

Code List Summary (Total Codes: 1795, Included: 1)

<u>Code</u>	<u>Name</u>
-------------	-------------

ZZ	Mutually Defined
----	------------------

HPE USAGE:

Stock Category - General or Special

REF02	127	Reference Identification	X	AN	1/80	Used
-------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

HPE USAGE:

Stock Category (General or Special)

Loop Quantity Information

Pos: 3200	Repeat: 99
Optional	
Loop: QTY	Elements: N/A

Loop Path: LIN

Purpose: To specify quantity information

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>
3200	QTY	Quantity Information	O	1	
3600		Loop SCH	O		25

QTY Quantity Information

Pos: 3200	Max: 1
Detail - Optional	
Loop: QTY	Elements: 4

Loop Path: LIN-QTY

Purpose: To specify quantity information

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
QTY01	673	Quantity Qualifier	M	ID	2/2	Must use

Description: Code specifying the type of quantity

Code List Summary (Total Codes: 1135, Included: 8)

Code	Name
15	Quantity in Hold Out
HPE USAGE:	
Blocked Stock	
17	Quantity on Hand
HPE USAGE:	
Unrestricted Stock	
19	Unverified Receipts
HPE USAGE:	
Quality Inspection	
26	Total Inventory
31	Additional Demand Quantity
HPE USAGE:	
Reserved Quantity	
74	Damaged Goods
76	Returns
QE	Quantity Deferred
HPE USAGE:	
Pending Investigation	

QTY02	380	Quantity	X	R	1/15	Must use
-------	-----	----------	---	---	------	----------

Description: Numeric value of quantity

QTY03	C001	Composite Unit of Measure	O	Comp		Used
-------	------	---------------------------	---	------	--	------

Description: To identify a composite unit of measure

(See Figures Appendix for examples of use)

QTY03-01	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
----------	-----	------------------------------------	---	----	-----	----------

Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken

Code List Summary (Total Codes: 895, Included: 1)

Code	Name
EA	Each

QTY04	61	Free-form Information	X	AN	1/30	Used
-------	----	-----------------------	---	----	------	------

Description: Free-form information

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
------------	-----------	---------------------	------------	-------------	----------------	--------------

Loop Line Item Schedule

Pos: 3600	Repeat: 25
Optional	
Loop: SCH	Elements: N/A

Loop Path: LIN-QTY

Purpose: To specify the data for scheduling a specific line-item

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>
3600	SCH	Line Item Schedule	O	1	

SCH Line Item Schedule

Pos: 3600	Max: 1
Detail - Optional	
Loop: SCH	Elements: 8

Loop Path: LIN-QTY-SCH

Purpose: To specify the data for scheduling a specific line-item

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SCH01	380	Quantity	M	R	1/15	Must use
Description: Numeric value of quantity						
SCH02	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						
SCH03	98	Entity Identifier Code	O	ID	2/3	Used
Description: Code identifying an organizational entity, a physical location, property or an individual						
Code List Summary (Total Codes: 1521, Included: 1)						
<u>Code</u> <u>Name</u>						
SU Supplier/Manufacturer						
SCH04	93	Name	X	AN	1/60	Used
Description: Free-form name						
SCH05	374	Date/Time Qualifier	M	ID	3/3	Must use
Description: Code specifying type of date or time, or both date and time						
Code List Summary (Total Codes: 1304, Included: 1)						
<u>Code</u> <u>Name</u>						
371 Estimated Arrival Date						
SCH06	373	Date	M	DT	8/8	Must use
Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year						
SCH11	326	Request Reference Number	O	AN	1/45	Used
Description: Reference number or RFQ number to use to identify a particular transaction set and query (additional reference number or description which can be used with contract number)						
SCH12	350	Assigned Identification	O	AN	1/20	Used
Description: Alphanumeric characters assigned for differentiation within a transaction set						

CTT Transaction Totals

Pos: 0100	Max: 1
Summary - Optional	
Loop: N/A	Elements: 1

Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use

Description: Total number of line items in the transaction set

SE Transaction Set Trailer

Pos: 0200	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
Description: Total number of segments included in a transaction set including ST and SE segments						
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

Purpose: To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included	M	N0	1/6	Must use
Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element						
GE02	28	Group Control Number	M	N0	1/9	Must use
Description: Assigned number originated and maintained by the sender						

IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

Purpose: To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups	M	N0	1/5	Must use
Description: A count of the number of functional groups included in an interchange						
IEA02	I12	Interchange Control Number	M	N0	9/9	Must use
Description: A control number assigned by the interchange sender						