

# GATE: CH - 45.2023

EE22BTECH11219 - Rada Sai Sujan

## QUESTION

Level ( $h$ ) in a steam boiler is controlled by manipulating the flow rate ( $F$ ) of the break-up(fresh) water using a proportional ( $P$ ) controller. The transfer function between the output and the manipulated input is

$$\frac{h(s)}{F(s)} = \frac{0.25(1-s)}{s(2s+1)}$$

The measurement and the valve transfer functions are both equal to 1. A process engineer wants to tune the controller so that the closed loop response gives the decaying oscillations under the servo mode. Which one of the following is the CORRECT value of the controller gain to be used by the engineer?

- (A) 0.25
- (B) 2
- (C) 4
- (D) 6

**Solution:**

PARAMETER	VALUE	DESCRIPTION
$G_c$	$K_c$	Proportional controller's transfer function
$G_f$	1	Valve transfer function
$G_p$	$\frac{0.25(1-s)}{s(2s+1)}$	Process transfer function
$G_M$	1	Measurement transfer function

TABLE I  
PARAMETER TABLE 1




Fig. 1. Block diagram

Characteristic equation of a second order system can be given by,

$$s^2 + 2\zeta\omega_n s + \omega_n^2 = 0 \quad (1)$$

PARAMETER	VALUE	DESCRIPTION
$X(s)$	$X(s)$	Laplace transform of input signal
$Y(s)$	$Y(s)$	Laplace transform of Output signal
$G(s)$	$G_c G_f G_p$	Open loop transfer function
$H(s)$	$G_M$	Feedback
$\omega_n$	$\omega_n$	Natural frequency
$\zeta$	$\zeta$	Damping coefficient

TABLE II  
PARAMETER TABLE 2

Characteristic equation of the above block diagram

can be given by,

$$1 + G(s)H(s) = 0 \quad (2)$$

$$\Rightarrow 1 + \frac{0.25K_c(1-s)}{s(2s+1)} = 0 \quad (3)$$

$$\Rightarrow s^2 + \left(\frac{4-K_c}{8}\right)s + \frac{K_c}{8} = 0 \quad (4)$$

From (1) and (??)

$$\zeta = \frac{4-K_c}{4\sqrt{2K_c}} \quad (5)$$

For the system to produce decaying oscillations  $\zeta < 1$ ,

By verifying options,

$$K_c = 2 \quad (6)$$