

A New Hybrid Machine Learning Method for Stellar Parameter Inference

SUJAY SHANKAR,¹ MICHAEL A. GULLY-SANTIAGO,¹ AND CAROLINE V. MORLEY¹

¹*Department of Astronomy, The University of Texas at Austin, Austin, TX 78712, USA*

ABSTRACT

The advent of machine learning (ML) is revolutionary to numerous scientific disciplines, with a growing number of examples in astronomical spectroscopic inference, as ML is expected to be more powerful than traditional techniques. Here we introduce a hybrid ML (HML) method combining automatic differentiation, interpolation, and Bayesian optimization to infer stellar parameters given stellar spectra. We study T_{eff} , $\log(g)$, and $[\text{Fe}/\text{H}]$, but this method **could be extended** to other **parameters** such as $[\alpha/\text{Fe}]$ (**alpha element abundance**), C/O (**carbon-oxygen ratio**), and f_{sed} (**sedimentation efficiency**). We first use **blase**'s nontraditional semi-empirical approach, **recasting** spectra **into** sets of tunable spectral lines. **blase** is **run** on 1,314 spectra from a **rectilinear subset** of the PHOENIX synthetic spectral model grid ($[\text{Fe}/\text{H}]$: **[-0.5, 0] dex**, T_{eff} : **[2300, 12000] K**, $\log(g)$: **[2, 6]**, λ : **[8038, 12849] Å**). For each of the **128,723** lines, we continuously map stellar parameters to spectral line parameters using regular grid linear interpolation. These manifolds are aggregated to create the PHOENIX generator, **enabling** parallelized reconstruction of spectra given stellar parameters. Gaussian Process minimization is then used to infer stellar parameters by minimizing the root-mean-square (RMS) loss between input and PHOENIX generator spectra. From testing, the inference error in T_{eff} was 185 K, $\log(g)$ was 0.19, and $[\text{Fe}/\text{H}]$ was 0.12 dex. Our products are an archive of the **blase models** of the PHOENIX subset, as well as the spectral reconstruction and inference algorithms themselves. This study is a proof of concept showing that semi-empirical HML is a viable alternative to traditional approaches.

1. INTRODUCTION

Stellar spectra are exceedingly rich sources of information about the stars that produce them. Spectra encode fundamental properties such as temperature, surface gravity, and chemical composition via their numerous absorption lines. Extrinsic properties such as the stellar radial velocity or the projected equatorial rotation shift the wavelengths of lines and broaden their widths, respectively. Observing the spectrum alters it again; the resolution, bandwidth, and other properties of the instrument change the fidelity at which we observe the spectrum, and can limit our ability to extract fundamental properties precisely. Observed stellar spectra thus represent extremely complex, data, influenced by multiple parameters, that have gone through multiple transformations before reaching our detectors.

Modern astronomical spectroscopy **takes advantage of intuitive, performant spectral models such as**

KORG (Wheeler et al. 2023), however it would **further** benefit from **the paradigm of interpretability**. The determination of fundamental properties, the creation of Extreme Precision Radial Velocity (EPRV) templates, and the application of composite spectral fitting could all leverage such an innovation. This ambitious aim may be broadly referred to as a “foundational spectroscopy model for astrophysics”, in reference to the same category of models used for large language models (LLMs) in artificial intelligence (AI). There are many challenges with creating such a foundational spectral model for astrophysics. Physical inputs into the spectral modeling process are imperfect, **and** simplifying assumptions in stellar (and substellar) atmospheres are necessarily inexact **due to factors such as asymmetries and unknown physics**. Computational costs **make** the training of such models **challenging; however, advances have been made with attention-based (Róžański et al. 2023) and transformer-based (Leung & Bovy 2024) models, among others**. Most prevailing solutions have had to choose either a model driven approach (**such as this work**), in which precomputed models are taken as gospel, or a data

driven/empirical approach (such as Lux (Horta et al. 2025)), in which our knowledge of stellar physics is ignored or treated phenomenologically, depending on the application. Hybrid solutions exist and have been implemented, such as those presented in Leung & Bovy 2019 and Rains et al. 2024. Although a lingering challenge is always how to ideally balance the fusion of model driven and data driven paradigms.

Spectroscopic surveys such as APOGEE (Majewski et al. 2017) use their own in-house pipelines to extract stellar parameters from spectra (ASPCAP (García Pérez et al. 2016) in the case of APOGEE), and these pipelines appear effective. The core assumption for the vast majority of pipelines is that the data to be analyzed is a list of pixels. Analysis pipelines may be closed-source or limited to the scope of the survey itself, causing a sort of siloing effect among surveys. This motivates the development of more universal, instrument-agnostic open-source frameworks that can apply broadly to a range of spectral observations with relatively little tuning.

Multiple efforts have been made in this direction, treating spectra in different ways. The standard practice is to treat the wavelength and flux as simply two arrays and use bespoke algorithms tailored to a small number of well-calibrated spectral lines to obtain fundamental stellar parameters and chemical compositions (e.g. the IGRINS YSO Survey (López-Valdivia et al. 2023) and the IRTF Spectral Library (Rayner et al. 2009)). Other whole-spectrum fitting abstractions decompose model spectra into an eigenbasis, implementing the data-model comparison stage as a tractable regression, such as starfish (Czekala et al. 2015).

Ideally, we want a system that can self-consistently learn, a genuine AI foundational spectral model. Such a system would enable the assignment of accurate stellar parameters, and could yield re-usable interpretable spectral models. **blase**, first presented in Gully-Santiago & Morley 2022, took an important, albeit limited, step in this direction, treating spectra not as a set of pixels or a set of eigenbasis coefficients but as a set of interpretable and traceable spectral lines, specifically Voigt profiles. Each of these approaches has tradeoffs, but one key scientific advantage of **blase** comes from its ability to adapt to new information, while preserving some adherence to physics-based models. This intelligent capability stems from its ability to fit a theoretically unlimited number of nonlinear spectral line parameters with automatic differentiation (autodiff). Autodiff is a technology that tracks transformations made to data using

the chain rule, even being able to differentiate control flow transformations involving if-else blocks, for example. With the gradient obtained from autodiff’s chain rule, we can optimize model parameters by just going against the direction of the gradient (because we usually want to minimize something such as a loss function, we go in the direction of greatest decrease, which is always the negative of the gradient). Autodiff has been used successfully in other astrophysical contexts such as exojax (Kawahara et al. 2022) and wobble (Bedell et al. 2019), but the recasting of spectra into sets of inherently nonlinear spectral lines positions **blase** as a unique and promising semi-empirical tool. The original **blase** paper demonstrated the ability to tune spectral lines with autodiff and ‘clone’ spectra, recasting them as ML models defined by interpretable sets of tuned spectral lines, however it was restricted to a pre-selected static synthetic model.

Here we introduce the next logical step in the sequence of expanding interpretable spectroscopic machine learning from operating on a single grid point and towards an entire 3D grid of precomputed spectra. We rebrand this augmentation as **blase3D**.

Ideally this process would be monolithic, with the end-to-end spectral inference code powered by a single autodiffable machine learning framework, like PyTorch (Paszke et al. 2019) or JAX (Bradbury et al. 2018). However, here we separate the problem into three pieces, only the first of which is currently differentiable. In section 2, we scale out the **blase** method to 1,314 precomputed synthetic spectral model clones, yielding a downloadable archive of pretrained machine learning models with 128,723 unique spectral lines. In section 3, we then fit manifolds mapping stellar parameters to uniformly-derived spectral line parameters using regular grid linear interpolation. Finally, in section 4, we show how reconstructions of the spectra using said manifolds can be used for inferring stellar fundamental properties from spectra. This final step resembles the aims of “atmospheric retrievals”, but in principle should be faster, adaptive, and reusable. An overview of this process is shown in Figure 1.

2. CLONING THE PHOENIX MODEL GRID

2.1. The PHOENIX Subset

For the purposes of this study, we chose the widely-adopted PHOENIX synthetic spectral model grid (Husser et al. 2013). Our approach can be straightforwardly applied to any other model grid in the future, including substellar atmosphere grids such as Sonora (Marley et al. 2021; Karalidi et al. 2021; Morley et al. 2024; Mukherjee et al. 2024), but for now we limit our




Figure 1. Overview of the process used in this study.

scope to a **rectilinear** subset of the PHOENIX grid, focusing on near solar metallicities and a broad range of effective temperature and surface gravity, with details given in Table 1. **This approach is taken due to the computational cost of interpolation algorithms. Future versions with more advanced models will be able to bypass the limitation of a rectilinear subset.**

2.2. Preprocessing with gollum

First, the PHOENIX subset was programmatically retrieved with gollum (Shankar et al. 2024), which downloaded spectra from the PHOENIX FTP server. The spectra were then put through a **short** preprocessing pipeline similar to that from Gully-Santiago & Morley 2022.

1. **Blackbody Division:** Since the T_{eff} of each spectrum is known, the **corresponding** blackbody spectrum was divided out.
2. **Continuum Normalization:** The spectra were further normalized by dividing them by a 5th order polynomial continuum fit using a peak-finding filter in order to eliminate curvature that would inhibit line modeling.

Mathematically, we can express the preprocessing as follows:

$$\bar{S} = \frac{S}{BQ_5} \quad (1)$$

where \bar{S} is the preprocessed spectrum, S is the original spectrum, B is the blackbody spectrum, and Q_n is the n^{th} order polynomial continuum fit. Arithmetic operations between arrays are assumed to be elementwise in all following notation.

2.3. Line Identification with blase

The next step was to convert the PHOENIX subset into a physically interpretable intermediate representation: a table of spectral line properties rather than an array of fluxes. We used blase, which models spectral lines as Voigt profiles and tunes the profiles to mimic the original PHOENIX spectrum with back propagation. Back propagation, put simply, is the process of moving in the autodiff gradient field to update ML model parameters (like mentioned earlier, usually against the gradient because we minimize loss functions). Four parameters were optimized: the line center μ , the log-amplitude $\ln(a)$, the Gaussian width σ , and the Lorentzian width γ . The optimization used the Adam optimizer (Kingma & Ba 2017) with a learning rate of 0.05 over 100 epochs. Gully-Santiago & Morley 2022 recommends this

Parameter	Symbol	Interval	Sampling
Alpha Element Abundance	α	[0] dex	N/A
Iron Abundance	[Fe/H]	[-0.5, 0] dex	0.5 dex
Effective Temperature	T_{eff}	[2300, 12000] K	100 K until 7000 K, then 200 K
Surface Gravity	$\log(g)$	[2, 6]	0.5
Wavelength	λ	[8038, 12849] Å	R = 500,000

Table 1. The subset of the PHOENIX grid used in this study. These limits were imposed to reduce the computational cost of the algorithms and to ensure a rectilinear parameter space in order to work with `scipy`’s `RegularGridInterpolator` (Virtanen et al. 2020). The wavelength limits in particular roughly line up with that of the Habitable Zone Planet Finder (HPF) spectrograph (Mahadevan et al. 2012). This subset is comprised of 1,314 individual spectra: 73 T_{eff} values, 9 $\log(g)$ values, and 2 [Fe/H] values.

setup as the minimum, and for a proof-of-concept implementation, we found it best to leave it as is.

In addition, we limited two custom parameters: wing cut to 6,000 and prominence to 0.005. Wing cut (**in pixels**) is a parameter that determines the extent of the Voigt profile to evaluate, saving computational resources by not evaluating negligible line wings. Prominence (**in normalized flux counts**) sets a lower limit for the amplitude of detected lines, which saves resources by disregarding shallow lines, so in our case we disregard lines **with amplitude** < 0.05 . In short, our choices for wing cut and prominence decrease the computational cost of `blase`’s cloning process at the expense of decreasing its accuracy slightly. `blase` uses the pseudo-Voigt approximation, which saves on computational cost while remaining accurate to about 1% (Ida et al. 2000). The pseudo-Voigt approximation uses a weighted average of a Gaussian and Lorentzian as opposed to a convolution. `blase`’s pseudo-Voigt profile implementation uses the following:

$$\tilde{V}_{\mu}(\lambda) = a [\eta \mathbf{L}(\lambda - \mu'; f) + (1 - \eta) \mathbf{G}(\lambda - \mu'; f)] \quad (2a)$$

$$\eta = \sum_{n=1}^3 \mathbf{u}_n \left(\frac{2\gamma}{f} \right)^n \quad (2b)$$

$$f = 32 \sum_{n=0}^5 \mathbf{v}_n \left(\sqrt{2 \ln(2)} \sigma \right)^{5-n} (\gamma)^n \quad (2c)$$

$$\mathbf{u} = \begin{bmatrix} 1.36603 \\ -0.47719 \\ 0.11116 \end{bmatrix} \quad \mathbf{v} = \begin{bmatrix} 1 \\ 2.69269 \\ 2.42843 \\ 4.47163 \\ 0.07842 \\ 1 \end{bmatrix}$$

where \mathbf{L} and \mathbf{G} are abbreviations for Lorentzian and Gaussian profiles, respectively. Notice that we use μ' instead of μ in the formula. This is because `blase` optionally allows the line center to shift slightly during optimization, and it is this shifted center which is used in computation. The individual Voigt profiles are

still indexed by μ for cross-model line identification, explained in the next section. Once optimization was complete, the list of identified lines was saved to a ‘state dictionary’: a common representation for pre-trained machine learning models that can be stored to disk for reuse later. These are stored in the `.pt` file format for each of the 1,314 PHOENIX subset grid points. The total disk space these files take up is 465 MB (382 MB when downloaded as a zip archive). For reference, the storage space the PHOENIX subset takes up on disk is approximately 8.1 GB. This represents a data compression factor of around 20 just by recasting the spectrum with `blase`. **The state dictionaries are available on Zenodo at <https://zenodo.org/records/11246174> (Shankar 2024).**

3. INTERPOLATING MANIFOLDS

3.1. Cross-Model Line Identification

As previously mentioned, `blase` tunes the line centers of detected lines. This means that from one PHOENIX spectrum to the next, the same line could have a slightly different line center. Since the goal of this study is to interpolate the properties of each line, we needed to identify the presence of a particular line across the PHOENIX subset, associating the same line with every occurrence. We decided to do this by using the line centers μ of the detected lines pre-optimization.

Pre-optimized line centers were required to be equal in order to group lines together. The values of μ pre-optimization are recorded by `blase` to 0.01 Å (picometer) precision; if they instead used the full available floating point precision, this method would likely detect singular (un-groupable) instances of spectral lines across the grid, completely negating the premise of this study. Of course, this method can be confused by species that produce spectral lines at very close wavelengths and other confounding factors, likely resulting in some false positives and negatives. However, we deem it sufficient to approx-

imate this way, as an in-depth treatment would be time-consuming and computationally expensive.

Now with each spectral line indexed by μ , we had four parameters to interpolate: μ' , $\ln(a)$, σ , and γ . Note that since we are dealing with the parameters of Voigt profiles, we can see in Equation 2 that even if the interpolation method is linear, a final spectral reconstruction will vary nonlinearly in flux.

Spectral lines were often only detected in some spectra from the PHOENIX subset. In Figure 2, we show that different grid points show differing counts of detected spectral lines.

The number of detected spectral lines changes as a function of stellar parameter for different reasons. Perhaps for astrophysical reasons: stellar atmospheres genuinely do not produce that line at detectable strength at the given temperature and surface gravity. Alternatively, **blase’s fitting or our line identification assumptions led to artifacts**. Whatever the cause, these missing lines have immediate practical consequences. Rectilinear interpolation schemes break in regions where a line does not appear; you can’t interpolate a quantity that simply doesn’t exist.

To solve this, we artificially populated missing grid points with log-amplitudes of -1000, which retained interpolator stability while nullifying the evaluated line. To prove the feasibility of this computational trick, we can do a simple thought experiment. Moving 1 K in T_{eff} away from a grid point on the boundary of detectability would reduce a line’s amplitude by a factor of over 20,000 (or more precisely, e^{10}). This is an extremely large reduction for an extremely small deviation from a grid point, meaning that to any realistic precision, the line immediately vanishes as soon as **blase no longer detects it**.

Examples of the appearance of missing sections in heatmaps where a line does not appear can be seen in Figure 3 and Figure 4, which show heatmaps of the 11617.66Å C I and the 10123.66Å He II lines (Kramida et al. 2023) varying over a solar metallicity slice of the PHOENIX subset stellar parameter space. Across the entire PHOENIX subset, **blase** detected 128,723 spectral lines with unique μ . On average, a PHOENIX spectrum has 9,167 detected spectral lines, with the minimum being 252 ($T_{\text{eff}} = 12,000$, $\log(g) = 6$, $[\text{Fe}/\text{H}] = -0.5$) and the maximum being 34,551 ($T_{\text{eff}} = 2,300$, $\log(g) = 3$, $[\text{Fe}/\text{H}] = 0$). Every one of these lines can be visualized as a manifold mapping a 3D stellar parameter vector to a 4D spectral line parameter vector, and every

one was interpolated to map stellar parameters to spectral line properties.

3.2. Continuously Evaluable Manifolds

For each line, the inputs to the interpolator were the three input parameters T_{eff} , $\log(g)$, and $[\text{Fe}/\text{H}]$, and the output was a list of four parameters, μ' , $\ln(a)$, σ , and γ . For each line, one of these interpolator objects was created using linear interpolation, and these interpolators were aggregated into a single list, which was then written to disk in the .pkl file storage format. These interpolators generate multiple manifolds representing the following mapping:

$$\begin{bmatrix} T_{\text{eff}} \\ \log(g) \\ [\text{Fe}/\text{H}] \end{bmatrix} \rightarrow \begin{bmatrix} \mu' \\ \ln(a) \\ \sigma \\ \gamma \end{bmatrix} \quad (3)$$

These interpolators could now be evaluated at any point lying within the domain of the PHOENIX subset, turning a discretely sampled PHOENIX subset into a continuously evaluable function, sometimes called a spectral emulator. With the given size of the PHOENIX subset, the interpolator list takes up 13.2 GB of disk space. **This is larger than the original PHOENIX subset by about 63% and than the state dictionary clone archive by a factor of over 34. This is due to the fact that we are now pickling entire function objects that must memorize the data.** Future work with more space-efficient models and clever storage strategies could reduce storage space requirements in exchange for I/O performance. This evaluation is able to reconstruct an existing PHOENIX spectrum or alternatively interpolate a new spectrum within the domain of the PHOENIX subset, so we call this the PHOENIX generator.

The spectral reconstruction process is done by iterating over the PHOENIX generator, evaluating each interpolator at the given coordinates, then reshaping the data into the same format that PyTorch uses for state dictionaries. During the iteration, if the interpolated log-amplitude of the line is less than -100, the line is excluded from the state dictionary. We do this to avoid artifacts in the manifolds due to the artificial population of log-amplitudes of -1000 where grid points were missing.

Finally, the state dictionary is fed into **blase’s SparseLinearEmulator**, which reconstructs the spectrum by constructing a forward model based on the input state dictionary. Any **nan** values are set to 1 (which we can do because the spectra are all normalized), and the spectral reconstruction is complete. We can observe




Figure 2. Number of detected spectral lines at each grid point of the PHOENIX subset. We can see that the number of detected lines decreases with increasing T_{eff} . **Remember** that from $T_{\text{eff}} = 7000$ K onward, PHOENIX’s sampling increment changes from 100 K to 200 K. **Due to some combination of computational artifacts from our line identification assumptions or innate behavior of PHOENIX grid spectra themselves, outliers such as the obvious one here at $T_{\text{eff}} = 7000$ K and $\log(g) = 6$ appear. Further exploration into why this happens is not in the scope of this study; for inference we are concerned with the lines themselves, not overall grid point behavior.**

in Figure 5 that a Fe I line from a reconstructed solar spectrum is not simply a pixel interpolation between the nearest PHOENIX grid point spectra. It is interpolating the spectral line properties using hundreds of thousands of manifolds, each representing a nonlinear parameter in the shape of the spectral line.

3.3. Spectral Reconstruction Time

A typical use case for the PHOENIX generator may be to batch reconstruct spectra from an array of input stellar parameters. Therefore, there is some motivation to reduce the computational cost of this procedure to tractable levels. We evaluate the computational time needed to use the PHOENIX generator in two distinct ways. First, for a single input, which would be relevant in serial applications. Second, for an array of multiple inputs, which would be relevant in parallel applications. `scipy`’s `RegularGridInterpolator` API allows for the passing in of an entire array of input coordinates to be evaluated at once. However using `blase` to reconstruct the spectrum from our interpolated state dictionary is always done serially, leading to what is actually more of a pseudo-parallel evaluation, but extremely performant

nonetheless. Performance results are shown in Figure 6, and we can see that the multi-reconstruction is much faster than a series of single reconstructions. While the generator takes around 15 seconds per spectrum serially, this drops to 1 second per spectrum as soon as 30 reconstructions. The speedup factor between the two methods increases as more spectra are generated, reaching a factor of 20 at 60 reconstructions. The computer used for this test has specifications shown in Table 2 (note that spectral reconstruction does not currently leverage the GPU):

CPU	AMD EPYC 7513 (32c/64t, 3.65 GHz boost)
RAM	256 GB
GPU	Nvidia A100 40GB ($\times 2$)

Table 2. Specifications of the machine used for computations, but not for generating visualizations.

4. BAYESIAN INFERENCE AND TESTING

4.1. Inference Algorithm




Figure 3. Heatmaps showing how $\ln(a)$, σ , γ , and $\mu' - \mu$ vary over the PHOENIX subset slice at solar metallicity of a C I spectral line. Notice the missing chunk in the top left; this could perhaps be due to the line center shifting to the point that blaze identified the chunk as a different line entirely (notice the line center offset increasing in magnitude approaching the chunk border). Since blaze did not detect a spectral line here, so we artificially populate those points with lines that have $\ln(a) = -1000$ during interpolation. This and all spectral lines shown in this paper were identified using the NIST spectral line database (Kramida et al. 2023).




Figure 4. Heatmap showing how $\ln(a)$ and σ vary over the PHOENIX subset slice at solar metallicity of a He II spectral line. This plot is much smaller than Figure 3 because *blaze* detects this line at a select chunk of grid points, leading to data only existing between T_{eff} 3600 K and 6600 K.

The goals of this study’s inference algorithm are to infer the stellar parameters T_{eff} , $\log(g)$, and $[\text{Fe}/\text{H}]$ by comparing a spectrum with our reconstructions and solving the optimization problem. We elected to use Bayesian optimization for this component, specifically the `gp_minimize` function from the `scikit-optimize` library (Head et al. 2018). This algorithm uses a Gaussian Process to model the objective function, which in this case was the RMS (Root-Mean-Square) loss between the interpolated spectrum M and

the true spectrum D , defined as:

$$\mathcal{L} = \langle (M - D)^2 \rangle^{1/2} \quad (4)$$

The optimizer was configured to first run 100 random evaluations to seed the surrogate model, then run 20 more evaluations now guided by the surrogate model. A random evaluation is simply a randomly generated tuple of stellar parameters within the parameter space of the PHOENIX generator, which is then evaluated with the generator to get a reconstruction and then compared with the inference target to retrieve its RMS error. The surrogate model is the approximation to the true objective function that the optimizer constructs based on the set of random evaluations (in this case defined by a set of 100 points rather than a fully continuous, infinitely resolved function). Guided evaluations are different, they are not randomly generated tuples of stellar parameters. They use the surrogate model in order to select new test points for the minimum of the objective function. This totals to 120 evaluations, 100 to create the surrogate model, then 20 guided evaluations, which was deemed sufficient for this study. Fine-tuning these numbers is possible, but simply not warranted for a proof-of concept method. Tweaking these numbers could lead to a more accurate inference, however it would incur additional computational cost as well. One inference run takes on average just under 7.5 minutes to complete.

4.2. Bayesian Optimizer Performance

To test the performance of the inference algorithm, we used the PHOENIX subset itself. This is possible for two reasons: first, the PHOENIX generator has not truly memorized the PHOENIX subset due to its Voigt profile basis and the ignoring of weaker features, and secondly, random samples within the parameter space are extremely unlikely to be PHOENIX grid points themselves, avoiding any overlap.

We know that in typical observational settings, a coarse estimate for T_{eff} tends to be fairly well-constrained from ancillary data such as photometric color index. So when testing the inference algorithm, we limited its search space to only include T_{eff} which lay within 500 K of the true value on either side. $\log(g)$ and $[\text{Fe}/\text{H}]$ were allowed to vary freely. The test sample consisted of 9 unique T_{eff} values, 3 unique $\log(g)$ values, and 2 unique $[\text{Fe}/\text{H}]$ values, totaling 54 unique spectra in the test set. T_{eff} ranged from 3000 K to 11000 K in increments of 1000 K, $\log(g)$ ranged from 2 to 6 in




Figure 5. Plot of an Fe I spectral line shown at the closest PHOENIX grid points to the Sun’s stellar parameters (**solid lines**), as well as a solar spectrum reconstructed with the PHOENIX generator (**dotted line**). We can see the spectral line shape be reconstructed mostly between the two native PHOENIX spectra, being closer to the 5800 K spectrum as the Sun’s T_{eff} used here is 5772 K.

477 increments of 2, and $[\text{Fe}/\text{H}]$ ranged from -0.5 to 0 in
478 increments of 0.5.

479 The results of the inference algorithm are as follows:
480 T_{eff} differed from the true result by an average of 185 K
481 or 2.6%. $\log(g)$ differed by an average of 0.19 or 6.8%.
482 $[\text{Fe}/\text{H}]$ differed by an average of 0.12 dex, which is 24%
483 of our search range. From this, we can see that T_{eff}
484 was the most accurately inferred parameter, followed by
485 $\log(g)$, and then $[\text{Fe}/\text{H}]$.

486 5. DISCUSSION

487 5.1. Scientific Applications

488 This study’s paradigm of spectral inference can enable
489 scientists to adopt self-consistent model grids and ana-
490 lyze their spectral line behavior in an interpretable fash-
491 ion, which has been fairly uncommon practice thus far.
492 Notably, this system tracks the shifting of spectral lines
493 as a function of stellar parameters, which traditionally
494 has been uncommon for algorithms to assess systemati-
495 cally. We balance rigidity in the Voigt profile basis
496 and flexibility in line parameter tunability, result-
497 ing in an interpretable system.

498 To summarize, we bring to scientists the ability to un-
499 derstand exactly what spectral properties we consider
500 mathematically and how we expect those properties to
501 behave on an incredibly detailed level (the 4 line param-
502 eters of all spectral lines and their corresponding interpo-
503 lating manifolds). **We treat the PHOENIX** precom-
504 puted model grid as the ground truth, **constructing**

505 **the PHOENIX** generator that then interfaces with
506 our inference algorithm.

507 5.2. Technical Considerations

508 To reiterate, the manifold fitting steps are not end-
509 to-end autodifferentiable. As seen in Figure 1, these
510 steps rely on `scipy`, which is not equipped with autodiff.
511 Without autodifferentiability, the ability to “machine
512 learn” is significantly reduced compared to a hypothet-
513 ical monolithic JAX or PyTorch system. We see three
514 reasons for developing a non-autodifferentiable sys-
515 tem. First, the familiar `scipy`-based system will serve
516 as an easy entry point for most practitioners who are
517 unfamiliar with autodiff, and may still benefit from and
518 modify the code without expert ML knowledge. Second,
519 this non-autodiff version serves as an **initial** benchmark
520 against which an inevitable autodifferentiable version of
521 **blase** may be compared. Finally, the inventory of fa-
522 miliar interpolation algorithms have not yet been ported
523 to PyTorch or JAX, since machine learning or Gaussian
524 Process fitting schemes are generally preferred within
525 the ML community.

526 The interpolation scheme presented here represents a
527 proof of concept, showing that leveraging the mapping
528 between synthetic spectral lines and their inputs can
529 yield a semi-empirical basis for data-model comparisons.
530 There are numerous design considerations that could be
531 improved upon with future work. These include but are
532 not limited to the following:




Figure 6. Plots showing the time taken to reconstruct varying numbers of spectra using the PHOENIX generator (lower is better). We can see that the time taken per spectrum for the serial implementation hovers around 15 seconds within run-to-run variance, while the pseudo-parallel implementation continually decreases in time taken per spectrum as the number of inputs increases. The speedup factor (higher is better) increases as more spectra are generated, which is also a desirable outcome.

- *Limited PHOENIX Subset:* The PHOENIX subset used in this study did not include the full PHOENIX grid, which expands the $[\text{Fe}/\text{H}]$ range

to $[-4.0, 1.0]$ dex and the $\log(g)$ range to $[0, 6]$, and also includes the alpha element abundance parameter, which we elected to fix at 0 for this study. In addition to the actual stellar parameters, we also took a subset of the PHOENIX wavelength range, with the full $[500, 55000]$ Å wavelength range also being left to future work. Users would be able to fit a greater variety of stellar spectra in many different wavelength regimes.

- *Strict Wavelength Range:* Currently, the generator only supports inference on spectra whose wavelength limits are either equal to it, or encompass that of the generator and have been truncated to match. However, when the spectrum in question has a smaller wavelength range than the generator, currently there is no functionality to truncate the generator. This would require externally indexing the generator's individual interpolators by line center position and selectively evaluating those to eliminate wasteful computation. This takes burden off the users to truncate their data to the PHOENIX generators, making use simpler.
- *Single Model Grid:* The PHOENIX grid is not the only model grid of synthetic spectra available, and it does not apply to all types of stars. Future work would extend the reach of this study's algorithm to encompass other model grids such as the Sonora series of substellar models (Marley et al. 2021; Karalidi et al. 2021; Morley et al. 2024; Mukherjee et al. 2024), ATLAS (Kurucz 2005), and coolTLUSTY (Lacy & Burrows 2023), reaching practitioners studying various types of stars and spectra. **Future blase versions will** be able to have an option for the user to input which model grid they would like to base the inference on, and to get even more advanced, perhaps even have the ability to intelligently determine which model grid to use automatically.

- *Memorization vs. Generalization:* The current design of the algorithm constructs manifolds using interpolation. This means that performance is good at points close to PHOENIX subset grid points, but is highly dependent on the type of interpolation used. As interpolators require memorization of the data, advanced interpolation becomes extremely expensive in terms of disk utilization. Future work would involve constructing manifolds using **more generalizable ML methods such as lasso or ridge regression**, which would allow for much better generalization, high

speed, and lower disk utilization at the expense of some accuracy.

- *Extrinsic Absence:* The current design of our algorithm does not account for extrinsic parameters that modify the appearance of spectra such as rotational broadening and Doppler shifting. Future work would need to develop ways to tune these extrinsic parameters alongside stellar parameters, enabling users to optimize these frequently-observed extrinsic parameters on top of the base stellar parameters.

- *Framework Overhead:* As this algorithm is currently more proof of concept than practical, it uses convenience functions from various libraries, which naturally introduces some level of overhead and leaves performance on the table. Future work would involve writing custom functions expressly designed for **blase**, most likely a complete rewrite of the library from the ground up. This has the potential to greatly increase the speed of this algorithm, depending on how much overhead is avoided with a bespoke implementation.

- *Pseudo-Interpretability:* Our algorithm boasts interpretability by considering spectral lines as the objects of interest as opposed to the rather uninterpretable flux values of other approaches. However, this is only a step in the direction of interpretability. True interpretability would decompose a spectrum not into a set of spectral lines, but into a set of species component spectra, which requires a much more advanced understanding of different species and their behavior, as well as direct access to a radiative transfer code as opposed to an off-the-shelf model grid. This approach would also extend the inference from just stellar parameters defined by a grid to any set of parameters accounted for in the radiative transfer model, down to specific species abundances. So while we were able to identify the spectral lines used in our figures, it is not necessarily valuable to try to identify all 128,723 lines that we identify as unique with our algorithm. **blase** is *agnostic* to the identity of the line that it is optimizing. We study these lines as **blase** sees them (i.e. their four shape parameters), because for the purposes of this study, that is the only information that is useful. Having more interpretability would let scientists actually study certain species and their spectral lines.

- *The Continuum Black Box:* Continuum normalization is a process that is not yet completely un-

derstood, and is currently done as a preprocessing step with a fairly simple algorithm. Future work would dive deeper into the science of continua and develop more advanced methods that can discern continua with greater accuracy and less modeling restrictions. This would increase accuracy for end users.

- *One Voigt Fits All:* The current assumption of **blase** is that every spectral line is a Voigt profile. This assumption is largely true, but there are situations where that is simply not enough. Future studies need to account for more advanced spectral line profiles and procedures to deal with phenomena such as ro-vibrational bands. This would increase accuracy for end users.

6. CONCLUSION

In this study, we have presented a proof-of-concept algorithm that **deals with** a subset of the PHOENIX spectral model grid ($[\text{Fe}/\text{H}]$: [-0.5, 0] dex, T_{eff} : [2300, 12000] K, $\log(g)$: [2, 6], λ : [8038, 12849] Å). We create state dictionaries for all spectra in the PHOENIX subset **using blase, recasting spectra into lists of Voigt profiles, and** lossily compress **the spectral data by** a factor of around 20. They are **available on Zenodo at** <https://zenodo.org/records/11246174> (Shankar 2024). We create the PHOENIX generator and implement a performant spectral reconstruction algorithm, enabling anyone to create reconstructions of PHOENIX spectra with continuously valued stellar parameters. We introduce and test our **GP minimization algorithm to infer stellar parameters**, with average absolute deviations from true values of 185 K in T_{eff} , 0.19 in $\log(g)$, and 0.12 dex in $[\text{Fe}/\text{H}]$. In its current state, our algorithm operates on spectra within the PHOENIX subset parameter ranges in [Table 1](#), requiring that the spectra not contain noticeable Doppler shifting, rotational broadening, or other confounding factors. The methods discussed here represent a step down a road not traveled in spectral inference, and have the potential to become more advanced in the future by fully utilizing the strengths of physics-informed machine learning.

This material is based on work supported by the National Aeronautics and Space Administration under grant No. 80NSSC21K0650 for the NNH20ZDA001N-ADAP:D.2 program. C.V.M. acknowledges support from the Alfred P. Sloan Foundation under grant number FG-2021-16592 and support from the National Science Foundation under grant number 1910969.

Software: `altair` (VanderPlas et al. 2018; Satya-
narayan et al. 2017), `astropy` (Astropy Collaboration
et al. 2013, 2018, 2022), `blasé/blase` (Gully-Santiago
& Morley 2022), `CUDA` (NVIDIA et al. 2020), `gollum`
(Shankar et al. 2024), `matplotlib` (Hunter 2007), `numpy`

(Harris et al. 2020), `pandas` (pandas development team
2020; Wes McKinney 2010), `Python` (Van Rossum &
Drake 2009), `PyTorch/torch` (Paszke et al. 2019), `scikit-
optimize/skopt` (Head et al. 2018), `scipy` (Virtanen
et al. 2020), `tqdm` (da Costa-Luis 2019), `vegafusion`
(Kruchten et al. 2022),

REFERENCES

- Astropy Collaboration, Robitaille, T. P., Tollerud, E. J.,
et al. 2013, *A&A*, 558, A33,
doi: [10.1051/0004-6361/201322068](https://doi.org/10.1051/0004-6361/201322068)
- Astropy Collaboration, Price-Whelan, A. M., Sipőcz, B. M.,
et al. 2018, *AJ*, 156, 123, doi: [10.3847/1538-3881/aabc4f](https://doi.org/10.3847/1538-3881/aabc4f)
- Astropy Collaboration, Price-Whelan, A. M., Lim, P. L.,
et al. 2022, *ApJ*, 935, 167, doi: [10.3847/1538-4357/ac7c74](https://doi.org/10.3847/1538-4357/ac7c74)
- Bedell, M., Hogg, D. W., Foreman-Mackey, D., Montet,
B. T., & Luger, R. 2019, *The Astronomical Journal*, 158,
164, doi: [10.3847/1538-3881/ab40a7](https://doi.org/10.3847/1538-3881/ab40a7)
- Bradbury, J., Frostig, R., Hawkins, P., et al. 2018, *JAX:*
composable transformations of Python+NumPy
programs, 0.3.13. <http://github.com/google/jax>
- Czekala, I., Andrews, S. M., Mandel, K. S., Hogg, D. W., &
Green, G. M. 2015, *ApJ*, 812, 128,
doi: [10.1088/0004-637X/812/2/128](https://doi.org/10.1088/0004-637X/812/2/128)
- da Costa-Luis, C. O. 2019, *Journal of Open Source
Software*, 4, 1277, doi: [10.21105/joss.01277](https://doi.org/10.21105/joss.01277)
- García Pérez, A. E., Allende Prieto, C., Holtzman, J. A.,
et al. 2016, *AJ*, 151, 144,
doi: [10.3847/0004-6256/151/6/144](https://doi.org/10.3847/0004-6256/151/6/144)
- Gully-Santiago, M., & Morley, C. V. 2022, *ApJ*, 941, 200,
doi: [10.3847/1538-4357/aca0a2](https://doi.org/10.3847/1538-4357/aca0a2)
- Harris, C. R., Millman, K. J., van der Walt, S. J., et al.
2020, *Nature*, 585, 357, doi: [10.1038/s41586-020-2649-2](https://doi.org/10.1038/s41586-020-2649-2)
- Head, T., MechCoder, Louppe, G., et al. 2018,
`scikit-optimize/scikit-optimize: v0.5.2, v0.5.2`, Zenodo,
doi: [10.5281/zenodo.1207017](https://doi.org/10.5281/zenodo.1207017)
- Horta, D., Price-Whelan, A. M., Hogg, D. W., Ness, M. K.,
& Casey, A. R. 2025, *arXiv e-prints*, arXiv:2502.01745.
<https://arxiv.org/abs/2502.01745>
- Hunter, J. D. 2007, *Computing in Science & Engineering*, 9,
90, doi: [10.1109/MCSE.2007.55](https://doi.org/10.1109/MCSE.2007.55)
- Husser, T. O., Wende-von Berg, S., Dreizler, S., et al. 2013,
A&A, 553, A6, doi: [10.1051/0004-6361/201219058](https://doi.org/10.1051/0004-6361/201219058)
- Ida, T., Ando, M., & Toraya, H. 2000, *Journal of Applied
Crystallography*, 33, 1311,
doi: <https://doi.org/10.1107/S0021889800010219>
- Karalidi, T., Marley, M., Fortney, J. J., et al. 2021, *ApJ*,
923, 269, doi: [10.3847/1538-4357/ac3140](https://doi.org/10.3847/1538-4357/ac3140)
- Kawahara, H., Kawashima, Y., Masuda, K., et al. 2022,
*ExoJAX: Spectrum modeling of exoplanets and brown
dwarfs*, *Astrophysics Source Code Library*, record
ascl:2206.003
- Kingma, D. P., & Ba, J. 2017, *Adam: A Method for
Stochastic Optimization*.
<https://arxiv.org/abs/1412.6980>
- Kramida, A., Yu. Ralchenko, Reader, J., & and NIST ASD
Team. 2023, *NIST Atomic Spectra Database (ver. 5.11)*,
[Online]. Available: <https://physics.nist.gov/asd>
[2024, June 12]. National Institute of Standards and
Technology, Gaithersburg, MD.
- Kruchten, N., Mease, J., & Moritz, D. 2022, in *2022 IEEE
Visualization and Visual Analytics (VIS)*, 11–15,
doi: [10.1109/VIS54862.2022.00011](https://doi.org/10.1109/VIS54862.2022.00011)
- Kurucz, R. L. 2005, *Memorie della Societa Astronomica
Italiana Supplementi*, 8, 14
- Lacy, B., & Burrows, A. 2023, *The Astrophysical Journal*,
950, 8, doi: [10.3847/1538-4357/acc8cb](https://doi.org/10.3847/1538-4357/acc8cb)
- Leung, H. W., & Bovy, J. 2019, *MNRAS*, 483, 3255,
doi: [10.1093/mnras/sty3217](https://doi.org/10.1093/mnras/sty3217)
- . 2024, *MNRAS*, 527, 1494, doi: [10.1093/mnras/stad3015](https://doi.org/10.1093/mnras/stad3015)
- López-Valdivia, R., Mace, G. N., Han, E., et al. 2023, *ApJ*,
943, 49, doi: [10.3847/1538-4357/acab04](https://doi.org/10.3847/1538-4357/acab04)
- Mahadevan, S., Ramsey, L., Bender, C., et al. 2012, in
*Society of Photo-Optical Instrumentation Engineers
(SPIE) Conference Series*, Vol. 8446, *Ground-based and
Airborne Instrumentation for Astronomy IV*, ed. I. S.
McLean, S. K. Ramsay, & H. Takami, 84461S,
doi: [10.1117/12.926102](https://doi.org/10.1117/12.926102)
- Majewski, S. R., Schiavon, R. P., Frinchaboy, P. M., et al.
2017, *AJ*, 154, 94, doi: [10.3847/1538-3881/aa784d](https://doi.org/10.3847/1538-3881/aa784d)
- Marley, M. S., Saumon, D., Visscher, C., et al. 2021, *ApJ*,
920, 85, doi: [10.3847/1538-4357/ac141d](https://doi.org/10.3847/1538-4357/ac141d)
- Morley, C. V., Mukherjee, S., Marley, M. S., et al. 2024,
arXiv e-prints, arXiv:2402.00758,
doi: [10.48550/arXiv.2402.00758](https://doi.org/10.48550/arXiv.2402.00758)
- Mukherjee, S., Fortney, J. J., Morley, C. V., et al. 2024,
arXiv e-prints, arXiv:2402.00756,
doi: [10.48550/arXiv.2402.00756](https://doi.org/10.48550/arXiv.2402.00756)

- 776 NVIDIA, Vingelmann, P., & Fitzek, F. H. 2020, CUDA,
 777 release: 10.2.89.
 778 <https://developer.nvidia.com/cuda-toolkit>
- 779 pandas development team, T. 2020, pandas-dev/pandas:
 780 Pandas, latest, Zenodo, doi: [10.5281/zenodo.3509134](https://doi.org/10.5281/zenodo.3509134)
- 781 Paszke, A., Gross, S., Massa, F., et al. 2019, PyTorch: An
 782 Imperative Style, High-Performance Deep Learning
 783 Library. <https://arxiv.org/abs/1912.01703>
- 784 Rains, A. D., Nordlander, T., Monty, S., et al. 2024,
 785 MNRAS, 529, 3171, doi: [10.1093/mnras/stae560](https://doi.org/10.1093/mnras/stae560)
- 786 Rayner, J. T., Cushing, M. C., & Vacca, W. D. 2009, ApJS,
 787 185, 289, doi: [10.1088/0067-0049/185/2/289](https://doi.org/10.1088/0067-0049/185/2/289)
- 788 Różański, T., Ting, Y.-S., & Jabłońska, M. 2023, arXiv
 789 e-prints, arXiv:2306.15703,
 790 doi: [10.48550/arXiv.2306.15703](https://doi.org/10.48550/arXiv.2306.15703)
- 791 Satyanarayan, A., Moritz, D., Wongsuphasawat, K., &
 792 Heer, J. 2017, IEEE transactions on visualization and
 793 computer graphics, 23, 341
- 794 Shankar, S. 2024, blase II: PHOENIX Subset Clone
 795 Archive, 0.0.1, Zenodo, doi: [10.5281/zenodo.11246174](https://doi.org/10.5281/zenodo.11246174)
- 796 Shankar, S., Gully-Santiago, M., Morley, C., et al. 2024,
 797 The Journal of Open Source Software, 9, 6601,
 798 doi: [10.21105/joss.06601](https://doi.org/10.21105/joss.06601)
- 799 Van Rossum, G., & Drake, F. L. 2009, Python 3 Reference
 800 Manual (Scotts Valley, CA: CreateSpace)
- 801 VanderPlas, J., Granger, B., Heer, J., et al. 2018, Journal of
 802 Open Source Software, 3, 1057, doi: [10.21105/joss.01057](https://doi.org/10.21105/joss.01057)
- 803 Virtanen, P., Gommers, R., Oliphant, T. E., et al. 2020,
 804 Nature Methods, 17, 261, doi: [10.1038/s41592-019-0686-2](https://doi.org/10.1038/s41592-019-0686-2)
- 805 Wes McKinney. 2010, in Proceedings of the 9th Python in
 806 Science Conference, ed. Stéfan van der Walt & Jarrod
 807 Millman, 56 – 61, doi: [10.25080/Majora-92bf1922-00a](https://doi.org/10.25080/Majora-92bf1922-00a)
- 808 Wheeler, A. J., Abruzzo, M. W., Casey, A. R., & Ness,
 809 M. K. 2023, AJ, 165, 68, doi: [10.3847/1538-3881/acaad](https://doi.org/10.3847/1538-3881/acaad)