

HORN: Directional Outlier Propagation in Hybrid Reasoners

Anonymous authors

Paper under double-blind review

Abstract

This is a living paper shell for a preregistered Mac-first experiment. HORN tests whether attention-to-SSM and SSM-to-attention boundaries differ in outlier magnitude and quantization-noise sensitivity. No positive result or native systems claim is made yet.

1 Current Gate

The branch must pass activation-magnitude, quantization-noise propagation, and cross-model/control gates before GPU validation. H1a first screens one live hybrid model for directional activation statistics, H1 requires the same selected direction on at least two hybrid models, H2 tests matched FP4-equivalent noise propagation, and H3 requires the direction to survive hybrid-model repeats while weakening on pure-attention and pure-Mamba controls. The current real trace packet builder/checker covers H1a/H1 boundary statistics. H2 and H3 now have executable follow-up contracts in `experimental/shared/followup_gate_contracts.py`: they require a fixed H1-selected direction, exact noise side and noise scale basis, paired clean/noisy rows, hook-off controls, and pure-attention plus pure-Mamba control rows. These contracts are not model evidence: no noise-propagation, precision-allocation, or cross-architecture claim is allowed until real H1a/H1 promotes and the H2/H3 contracts are filled from matched noisy replays and pure-architecture controls.

2 Mac Artifact Status

A deterministic synthetic H1a packet validates the directional-boundary real-schema contract. It emits 72 rows, selected max-abs ratio 4.044, non-boundary selected-direction control ratio 1.042, and permuted selected-direction control ratio 0.247, producing `SCHEMA_REHEARSAL_NOT_PROMOTABLE_SYNTHETIC_HORN_H1A`. This is synthetic-only: it is not model evidence, not a quantization-noise result, and not GPU evidence. The metadata-only model eligibility packet identifies live hybrid targets and records architecture-map hashes for admissible packets, but no target weights are cached repo-locally, so HORN has not yet produced real boundary rows on the current Mac.

3 Next Evidence

The next admissible row is a real H1a boundary activation dump from a hybrid model. HORN remains a control branch unless real H1/H2/H3 gates show consistent directional asymmetry that pure-attention and pure-Mamba controls do not share. Pure-architecture controls are an H3 requirement, not a blocker for the first H1a boundary-activation packet.

4 Admissible Real Packet

The real H1a/H1 packet must use the shared config-derived architecture maps rather than substring-only module classification. Each row must report `model_id`, `prompt_id`,

adjacent layer IDs, direction, matched_boundary_direction, boundary_index, normalization placement, max_abs, rms, kurtosis, and control_type. The required controls are boundary rows, non-boundary adjacent rows, and permuted-direction rows. A valid packet must cover both attention->ssm and ssm->attention in boundary rows and in matched control labels. The frozen trace plan schedules a matched non-boundary control for each observed boundary row, not merely one aggregate control per direction. Non-boundary controls may retain their true architecture direction, such as ssm->ssm, while matched_boundary_direction records the boundary direction they control for, and both matched directions must appear for every prompt; each permuted-direction row must match an observed boundary tuple with the same prompt ID, layer IDs, normalization positions, and measured metrics while flipping the actual direction label only. It cannot substitute a separately measured tensor for the null: the control is built by reusing the observed metrics and flipping its direction label. It cannot pass if the permuted controls preserve the selected high-magnitude direction; a faithful label flip may preserve unsigned asymmetry while moving the signal to the opposite label. Non-boundary controls must stay below the selected H1 threshold, not merely below the observed boundary ratio. It must also include at least 12 fixed prompt IDs unless the packet records an explicit resource limit. Any resource-limited packet must use a RESOURCE_LIMITED_NOT_PROMOTABLE decision. The packet must include prompt_ids_hash, architecture_map_hash, trace_plan_hash, per-row prompt_cluster_id, the exact trace_plan_path whose file SHA-256 matches that hash, and a summary with prompt count, boundary directions, selected H1a ratio, selected H1a prompt-cluster-bootstrap lower bound, support fraction, non-boundary control ratio, and permuted-direction ratio, then pass experimental.shared.check_gate_packet --mode real --project horn. The checker recomputes these H1a fields from raw rows and rejects stale or hand-filled summaries. Saved tensor packets must be converted with experimental.shared.hybrid_trace_packet.builder before validation. The current capture-manifest templates are generated by experimental.shared.hybrid_trace_capture_manifest; they must be filled from real boundary-activation captures before packet building. Served HF IDs are preserved as served_model_id while rows are validated against the canonical architecture-map model_id; permuted-direction entries use tensor_alias_of to reuse the observed boundary tensor. Saved tensor packets must carry tensors/tensor_manifest.json and the referenced tensor files. Each raw row copies tensor_name, tensor_source_name, tensor_storage_name, tensor_sha256, tensor_dtype, and tensor_shape from that manifest; permuted rows must reuse the observed boundary source and hash rather than introduce independently measured tensors.

Required control	Reviewer objection addressed
Explicit boundary map	Avoids substring artifacts.
Non-boundary adjacent pair	Separates boundary effects from depth effects.
Permuted direction label	Tests whether direction carries signal.
Matched normalization side	Controls RMSNorm/LayerNorm placement.
Pure-architecture control	Prevents generic outlier claims.

Table 1: Controls required before HORN can claim directional hybrid asymmetry.

5 Reviewer Packet

The reviewer-facing claim boundary is tracked in experimental/horn/paper/reviewer_pack.md. It records that HORN is not camera-ready as a method or measurement paper until real H1–H3 evidence exists.