

ThoughtFlow: A Preregistered Falsification Ladder for Sparse-Cache Retention

Anonymous authors

Paper under double-blind review

Abstract

We present a preregistered falsification protocol for training-free sparse KV-retention proposals on saved reasoning-style traces. The contribution is diagnostic, not a positive method: freeze a sparse-cache quality surface, preregister each successor signal before measurement, require matched-budget wins against R-KV-like and ThinKV-like proxies, separate stopped-family rows from proxy-baseline rows, and report paired uncertainty plus oracle/headroom diagnostics where those diagnostics are implemented. As a case study, the original anchor/recent/phase/math family is stopped, recurrence-distance utility (`rdu_topk`) clears one frozen 74-trace surface but fails stricter reproduction, prefix-surprisal utility (`psi_topk`) fails on a fresh 70-trace C2C GSM surface, and value-weighted attention contribution (`vwac_topk`) fails on a fresh 64-trace C2C SVAMP surface. The anchor/phase int8 quantization primitive passes Triton interpreter correctness tests against its CPU reference, but no real FP8, CUDA, latency, throughput, or live compression-method claim is made.

1 Contribution

The contribution is a reusable stop-rule protocol, not another sparse-cache policy. The protocol combines seven checks: no-retune frozen surfaces, pre-registered successor utilities, matched-budget proxy baselines, stopped-family/proxy-baseline separation, paired uncertainty, oracle/headroom diagnostics for the RDU demotion gates, and machine-checkable stop artifacts. ThoughtFlow-FP8 is the case study showing why each check matters: one plausible signal looks positive on a frozen surface, then fails to reproduce under stricter reproduction, while two later signals fail fresh-surface gates outright.

Protocol check	Purpose	Stop condition
Frozen surface	Prevent post-hoc tuning.	A successor is measured once after preregistration.
Matched budget	Avoid full-cache comparisons.	Must beat R-KV-like and ThinKV-like rows at the same keep rate.
Stopped/proxy split	Separate local family reuse from proxy-baseline robustness.	A stopped-family-only win is diagnostic, not a method claim.
Paired intervals	Avoid mean-only promotion.	Promotion requires the preregistered mean margin and paired CI high below zero.
Oracle/headroom	Show whether a useful policy exists at the budget.	Large oracle gaps block method claims.
Fresh surface	Test robustness.	Failure demotes or kills the signal.

Table 1: Falsification protocol used for each sparse-cache successor.

The next table is included only to show why the branch looked promising before the fresh gates. It is not a current leaderboard: every compressed method row in the table is superseded by the demotion ladder that follows.

Signal	Final surface	Final state
anchor family	74-trace frozen sparse-cache gate with matched ThinKV-like and R-KV-like proxies.	Stopped: no robust matched-budget win.
rdu_topk	Alternate surface plus independent 89-trace saved-trace reproduction.	Killed: first-surface pass fails reproduction.
psi_topk	Fresh 70-trace C2C GSM saved-trace surface.	Killed: large NLL regression versus both proxies.
vwac_topk	Fresh 64-trace C2C SVAMP saved-trace surface.	Killed: worse than both proxies with paired intervals.

Table 2: Final status matrix. The contribution is the auditable stop protocol and its failure modes, not a live sparse-cache method.

2 Signals Under Test

The original policy protects anchors and phase labels. The first successor adds a small recent-token reserve. The second successor protects anchors, reserves half the retained budget for recent tokens, and lets phase markers compete with math-state and high-importance reasoning tokens under a saliency bonus. Those policies are now stopped on the current saved traces. The pre-registered `rdu_topk` successor is demoted after stricter reproduction; later `psi_topk` and `vwac_topk` successors are killed by fresh-surface gates.

The proxy rows in Table 3 are deliberately simple matched-budget controls, not faithful reimplementations of the cited systems: R-KV-like keeps the first four anchor tokens plus the most recent tail, ThinKV-like keeps a recent reserve plus a math-state importance bonus, and LongFlow-like is an importance top- k retention rule. The local definitions live in `experimental/thoughtflow_fp8/phase2/simulate_phase_retention.py`; the paper uses them only as falsification controls for the stopped signal family.

Policy	Keep rate	NLL	Δ NLL vs full	PPL
full context	1.000	2.101	0.000	9.7
R-KV-like	0.210	3.419	1.319	38.7
ThinKV-like	0.210	3.583	1.482	44.6
LongFlow-like	0.210	3.961	1.861	74.2
ThoughtFlow	0.210	3.961	1.861	74.2
ThoughtFlow-recent	0.210	3.562	1.461	44.2
ThoughtFlow-saliency-recent	0.210	3.434	1.333	38.1
Held-out R-KV-like	0.211	3.482	–	43.7
Held-out sweep best	0.211	3.480	–	43.7

Table 3: Case-study retained-context continuation proxy on distilgpt2 traces. Lower NLL is better. Full context is not a matched-budget baseline. The held-out sweep row is selected on 12 train traces and reported on 12 held-out traces, so its NLL is not directly averaged with the all-trace rows.

3 Hidden/KV Telemetry

We then ran a Mac-local telemetry gate using real distilgpt2 tensors rather than only text markers. The probe ranks retained tokens by attention received, final-hidden norm, key norm, value norm, or combined KV norm. This is still not sparse-KV decoding, but it checks whether the interpretable phase policy is merely preserving labels that hidden/KV saliency would not select.

Paired against `value_norm_topk`, ThoughtFlow’s phase-recall delta is +0.508 with 95% CI [+0.436, +0.579]. The math-state delta is only +0.073 with 95% CI [-0.078, +0.223]. This rules out a method claim based on phase recall alone: it may be marker preservation rather than useful cache retention.

Policy	Keep rate	Anchor	Phase	Math-state
ThoughtFlow	0.207	1.000	1.000	0.918
LongFlow-like	0.207	1.000	1.000	0.918
ThinKV-like	0.207	1.000	0.948	0.848
value_norm_topk	0.207	0.000	0.492	0.845
train-selected sweep	0.207	1.000	0.430	0.956

Table 4: Hidden/KV saliency telemetry on 24 distilgpt2 traces. The strongest real-saliency proxy by phase+math recall is value_norm_topk. ThoughtFlow beats it on phase recall, but LongFlow-like ties ThoughtFlow under the local importance heuristic.

4 Sparse-Cache Case Study Gate

We next ran a CPU-only sparse-cache probe. The model processes the full prefix once, each policy prunes the returned KV cache to the same 0.20 budget, and the continuation is scored from the pruned cache. This is not a Triton, CUDA, FP8, latency, or throughput result, but it is stronger than retained-text NLL because the model actually receives a sparse cache.

Policy	Keep rate	NLL	Paired Δ vs R-KV-like
full cache	1.000	2.142	-1.296 [-1.533,-1.066]
ThoughtFlow-saliency-recent	0.210	3.372	-0.067 [-0.151,+0.011]
ThinKV-like	0.210	3.389	-0.049 [-0.192,+0.077]
ThoughtFlow-recent	0.210	3.399	-0.040 [-0.169,+0.074]
ThoughtFlow sweep best	0.210	3.436	-0.002 [-0.007,+0.000]
R-KV-like	0.210	3.438	0.000
LongFlow-like	0.210	3.588	+0.150 [-0.016,+0.300]
ThoughtFlow	0.210	3.588	+0.150 [-0.006,+0.297]

Table 5: CPU sparse-KV continuation quality on 24 distilgpt2 traces. Negative paired delta is better than R-KV-like. ThoughtFlow-saliency-recent is best in mean NLL, but it clears the strongest non-ThoughtFlow row by only 0.017 NLL and remains below the pre-registered 0.03 promotion margin.

A bounded sparse-cache sweep over 24 nearby anchor/recent/phase/math configurations selects tf_sparse_r0.55_p0.05_m0.12_a2 on the 12 train traces. On the 12 held-out traces it gets NLL 3.340 versus ThinKV-like 3.385 and R-KV-like 3.420. This clears the mean 0.03 margin, and the paired delta versus R-KV-like is -0.080 with 95% CI [-0.152,-0.014]. However, the paired delta versus ThinKV-like is -0.045 with 95% CI [-0.226,+0.182]. The fixed ThoughtFlow-saliency-recent incumbent has lower held-out mean NLL, 3.304, but its paired CIs also cross zero. This is a promising falsification candidate, not a method result.

We then froze ThoughtFlow-saliency-recent and tf_sparse_r0.55_p0.05_m0.12_a2 and ran a larger 74-trace sparse cache slice with no retuning. ThinKV-like is the best compressed row among the stopped family comparison at NLL 3.900. The frozen sparse ThoughtFlow row gets 3.908, with paired delta -0.031 versus R-KV-like and 95% CI [-0.078,+0.020], but +0.008 versus ThinKV-like with 95% CI [-0.060,+0.085]. ThoughtFlow-saliency-recent gets 3.920. The larger no-retuning gate therefore stops this policy family.

After that stop decision, we pre-registered rdu_topk. It computes recurrence-distance utility from full-prefix prefill attentions using lag buckets [8,15], [16,31], [32,63], and [64, ∞], then keeps the top budget by utility with ties broken by lower position. It does not use continuation tokens, trace labels, recent reserves, anchors, phase markers, or math-state bonuses. After rdu_topk failed reproduction, we pre-registered psi_topk (high self-surprisal prefix tokens) and vvac_topk (future attention weighted by cached value-vector norm).

5 Evidence Ladder

Gate	Readout	Decision
Synthetic retention	Anchor/phase labels can be protected at matched keep rate.	Intuition only.
Retained-text NLL	Original ThoughtFlow rows do not beat the strongest proxy.	Weakened.
Hidden/KV telemetry	Phase recall improves, but math-state impact is not stable and LongFlow-like ties the heuristic.	Diagnostic.
CPU sparse-cache probe	A tuned sparse ThoughtFlow row is promising in mean but not robust against ThinKV-like uncertainty.	Not promoted.
Frozen 74-trace gate	rdu_topk beats ThinKV-like and R-KV-like on the first frozen surface.	Candidate only.
Same-slice rerun	Cached result reproduces exactly on the deterministic Mac stack.	Repro bookkeeping.
Alternate surface	Cross-family rows still lose, but a stopped same-family row beats rdu_topk by 0.006 NLL.	Weakened.
Independent saved traces	R-KV-like is best compressed at NLL 3.981; rdu_topk reaches 4.014.	Killed.
Prefix-surprisal fresh surface	psi_topk reaches NLL 7.899 versus ThinKV-like 3.906 and R-KV-like 3.960.	Killed.
Value-weighted attention fresh surface	vwac_topk reaches NLL 4.336 versus R-KV-like 4.096 and ThinKV-like 4.162.	Killed.

Table 6: ThoughtFlow-FP8 evidence ladder. The first-surface pass is shown as one step that failed to reproduce, not as the headline result.

Registration	SHA-256 prefix	Measurement artifact
rdu_topk	676d5239	Same-surface pass, alternate-surface failure, and independent-trace failure are bundled in the diagnostic packet.
psi_topk	04da2bd0	One-shot fresh C2C GSM sparse-cache check, artifact SHA prefix d0a08035.
vwac_topk	1574c853	One-shot fresh C2C SVAMP sparse-cache check, artifact SHA prefix 80a35954.

Table 7: Registration-to-measurement ledger. Full hashes and artifact paths are recorded in the tracked diagnostic packet; this table exposes the audit chain inside the paper.

Policy	Traces	Keep rate	NLL	Paired Δ vs ThinKV-like
full cache	74	1.000	2.848	-1.052 [-1.199,-0.919]
rdu_topk	74	0.213	3.779	-0.121 [-0.211,-0.037]
ThinKV-like	74	0.213	3.900	0.000
frozen sparse ThoughtFlow	74	0.213	3.908	+0.008 [-0.060,+0.085]
ThoughtFlow-saliency-recent	74	0.213	3.920	+0.020 [-0.030,+0.074]
R-KV-like	74	0.214	3.939	+0.039 [-0.015,+0.099]
LongFlow-like	74	0.213	4.158	+0.258 [+0.178,+0.337]

Table 8: Historical one-shot frozen sparse-cache successor evaluation. rdu_topk also beats R-KV-like by -0.160 NLL with 95% CI [-0.264,-0.050] on this first surface, but later alternate-surface and independent-trace gates fail to reproduce the promotion.

The independent saved-trace check rules out claiming rdu_topk as a robust method on the available surfaces. A coarse trace-level decomposition explains where the reproduction fails: rdu_topk is +0.213 NLL worse than R-KV-like on long-prefix/high-RDU-density

rdu_topk check	Readout	Decision
First frozen surface	74 traces, NLL 3.779 versus ThinKV-like 3.900.	First-surface pass.
Same-slice rerun	Exact deterministic reproduction; 0.145 NLL above compressed oracle.	Bookkeeping only.
Alternate surface	Same rule, NLL 3.594; a stopped same-family row reaches 3.588.	Weakened.
Independent traces	89 SVAMP traces; R-KV-like 3.981, rdu_topk 4.014.	Killed.
Failure bucket	+0.213 NLL on long-prefix/high-RDU-density rows.	Mechanism target.

Table 9: rdu_topk demotion ladder. The first-surface pass is preserved as evidence that the protocol catches tempting positives, not as a live method claim.

rows but -0.049 better on short-prefix/low-density rows. The large-regression buckets are exactly the buckets a robust policy would need to handle before any long-context claim.

Lesson	Observed failure	Protocol implication
First-surface positives are weak evidence.	rdu_topk passed one frozen slice, then failed same-family and independent surfaces.	Require fresh-surface reproduction before promotion.
Density regimes matter.	Long-prefix/high-RDU-density rows regress by +0.213 NLL.	Bucket diagnostics should be mandatory, not post-hoc color.
Oracle gaps prevent over-claiming.	Same-slice reproduction remained 0.145 NLL above the compressed oracle.	Report headroom before adding implementation work.
Consumed signals should stay consumed.	psi_topk and vwac_topk failed one-shot gates.	Do not retune failed utility families on the same traces.

Table 10: Methodological lessons from the stopped sparse-cache ladder.

Prefix-surprisal successor. A later consumed successor tested whether retaining high self-surprisal prefix tokens could preserve information that is hard to reconstruct. The signal uses only prefill logits, not continuation loss, trace labels, recent reserves, or RDU lag buckets. On a fresh 70-trace C2C GSM saved-trace surface, psi_topk fails decisively: ThinKV-like is best compressed at NLL 3.906, R-KV-like reaches 3.960, and psi_topk reaches 7.899. Paired deltas are +3.939 [+3.720,+4.144] versus R-KV-like and +3.994 [+3.773,+4.205] versus ThinKV-like, where positive is worse for psi_topk. This rules out this exact signal in the current Mac sparse-cache harness.

Value-weighted attention successor. The next consumed successor tested a cache-state utility: future prefix attention to a token multiplied by the token’s cached value-vector norm. On a fresh 64-trace C2C SVAMP surface, vwac_topk also fails. R-KV-like is best compressed at NLL 4.096, ThinKV-like reaches 4.162, and vwac_topk reaches 4.336. Paired deltas are +0.241 [+0.030,+0.530] versus R-KV-like and +0.174 [+0.002,+0.392] versus ThinKV-like.

6 Claim Boundary

Limitations. The ladder is demonstrated on Mac-local saved traces and CPU sparse-cache scoring, not native serving. The trace families are useful falsification surfaces, but they do not establish broad task coverage. The stopped signals also do not rule out future sparse-cache utilities; they only rule out the pre-registered policies under the reported surfaces and budgets. The scored surfaces use distilgpt2 saved continuations and saved prefix/KV telemetry as falsification fixtures; they are not reasoning-model benchmarks

Claimed	Not claimed
Preregistered sparse-cache falsification ladder.	State-of-the-art KV compression.
Matched-budget Mac sparse-cache scoring.	Native FP8 serving quality.
Stopped-family/proxy-baseline and fresh-surface stop rules.	CUDA kernel speed, latency, throughput, or HBM savings.
Triton-interpreter parity for an int8 anchor/phase primitive.	A live deployable compression method.

Table 11: Boundary between the workshop claim and the stopped systems-method target.

and not faithful external implementations of ThinkKV, R-KV, LongFlow, LazyEviction, ForesightKV, PM-KVQ, or KVQuant.

7 Stop Rule and Reopen Gate

The branch now contributes a diagnostic falsification ladder. The stopped anchor/recent/phase/math policy family remains ruled out as a tunable branch on this trace set, `rdu_topk` fails reproduction, and `psi_topk/vwac_topk` fail their fresh-surface gates. A paper-ready method claim now requires a genuinely new pre-registered utility signal evaluated once on a fresh/larger frozen surface with strict stopped-family, proxy-baseline, and oracle/headroom reporting. The Triton interpreter gate is no longer the blocker for the quantization scaffold; method evidence is. This means no real FP8, CUDA, latency, or throughput result is claimed.

8 Related Work and Scope

This draft intentionally does not claim a new state-of-the-art KV-compression method. ThinkKV, LongFlow, R-KV/R-KVHash-style retention, LazyEviction/ForesightKV-style future-use ideas, PM-KVQ, and KVQuant already occupy much of the sparse-cache and quantized-cache design space ThinkKV (2026); LongFlow (2026); R-KV (2025); LazyEviction (2025); ForesightKV (2026); PM-KVQ (2025); KVQuant (2024). Our contribution is narrower: a Mac-local falsification ladder that shows how plausible interpretable retention signals can clear one frozen surface, fail stricter reproduction, or collapse on fresh surfaces. The project name retains “FP8” because that was the original systems target, but the current artifacts only validate CPU sparse-cache scoring and an int8/Triton-interpreter reference primitive; they do not measure FP8 numerical drift or native FP8 serving.

9 Reproducibility

All reported gates use tracked scripts under `experimental/thoughtflow.fp8/phase2/` and the repo-local `./venv_arm64`. The frozen sparse-cache probe, same-slice rerun, alternate-surface rerun, independent saved-trace rerun, and fresh-surface successor checks each write Markdown and JSON artifacts with promotion criteria, paired intervals, and no-retuning decisions; oracle/headroom fields are present on the RDU demotion gates and are not claimed for the PSI/VWAC fresh successor packets. The tracked diagnostic packet hashes the saved JSON artifacts and records available model/source metadata plus input hashes for each saved artifact where those inputs are explicit. Legacy default trace paths are labeled as inferred from `run_real_trace_retention.DEFAULT_TRACES`. Its builder refuses regeneration when `experimental/thoughtflow.fp8/` is dirty, and the current manifest records a clean path status at generation. The hashed C2C fresh-surface inputs are tracked in the repository despite the root results ignore rule. The current package should still be read as a machine-checked falsification note rather than a full artifact-evaluation release. The stable local correctness command is:

```
TRITON_CPU_BACKEND=1 TRITON_INTERPRET=1 \
```

```
TRITON_HOME="$PWD/.debug/triton_home" \
./venv_arm64/bin/python -m pytest \
  experimental/thoughtflow_fp8/phase2/tests \
  experimental/thoughtflow_fp8/phase4/tests -q -rs
```

Gate artifact	Rebuild command	Input surface	Hash prefix
frozen probe	phase2/frozen.sparse.cache.probe.py	frozen mixed traces, 74 scored	f79c286c
same-surface RDU	phase2/rdu.no_retune.reproduction.check.py	same frozen traces, 74 scored	9a6420cf
alternate RDU	phase2/rdu.alt.surface.reproduction.check.py	alternate measured surface, 73 scored	1302ce31
independent RDU	phase2/rdu.independent.trace.reproduction.check.py	separately chat traces, 89 scored	5a568e1c
psi_topk	phase2/psi.fresh.sparse.cache.check.py	C2C GSM, 70 scored	d0a08035
vwac_topk	phase2/vwac.fresh.sparse.cache.check.py	C2C SVAMP, 64 scored	80a35954

Table 12: Diagnostic-packet command map. Full commands, source metadata, and input SHA-256 values are in the tracked manifest.

10 Artifacts

Key artifacts are the current decision manifest, tracked diagnostic provenance packet, reviewer pack, workshop shell, README/progress handoff, RDU independent reproduction check, PSI/VWAC fresh-surface checks, and repo-local Triton interpreter note: `experimental/thoughtflow_fp8/phase2/current_decision_manifest.20260506.md`, `experimental/thoughtflow_fp8/phase2/diagnostic_packets/thoughtflow_diagnostic_packet.20260506/manifest.json`, `experimental/thoughtflow_fp8/paper/reviewer_pack.md`, `experimental/thoughtflow_fp8/paper/colm_workshop_shell.md`, `experimental/thoughtflow_fp8/README.md`, `experimental/thoughtflow_fp8/progress.md`, `experimental/thoughtflow_fp8/phase2/rdu_independent_trace_reproduction_check.md`, `experimental/thoughtflow_fp8/phase2/psi_fresh_sparse_cache_check.md`, `experimental/thoughtflow_fp8/phase2/vwac_fresh_sparse_cache_check.md`, and `experimental/thoughtflow_fp8/phase4/triton_interpreter_note.20260506.md`.

References

- ThinKV: Thought-Adaptive KV Cache Compression for Efficient Reasoning Models. ICLR, 2026. <https://openreview.net/forum?id=M3CeHnZKNC>.
- LongFlow: Efficient KV Cache Compression for Reasoning Models. arXiv:2603.11504, 2026. <https://arxiv.org/abs/2603.11504>.
- R-KV: Redundancy-aware KV Cache Compression for Training-Free Reasoning Models Acceleration. arXiv:2505.24133, 2025. <https://arxiv.org/abs/2505.24133>.
- LazyEviction: Lagged KV Eviction with Attention Pattern Observation. arXiv:2506.15969, 2025. <https://arxiv.org/abs/2506.15969>.
- ForesightKV: Optimizing KV Cache Eviction for Reasoning Models by Learning Long-Term Contribution. arXiv:2602.03203, 2026. <https://arxiv.org/abs/2602.03203>.
- PM-KVQ: Progressive Mixed-precision KV Cache Quantization for Long-CoT LLMs. arXiv:2505.18610, 2025. <https://arxiv.org/abs/2505.18610>.
- KVQuant: Towards 10 Million Context Length LLM Inference with KV Cache Quantization. arXiv:2401.18079, 2024. <https://arxiv.org/abs/2401.18079>.