

# BEA API for Data Retrieval

---

## User Guide

### Introduction

The Bureau of Economic Analysis (BEA) publishes economic statistics in a variety of formats. This document describes the BEA Data Retrieval Application Programming Interface (API) – including detailed instructions for retrieving data and meta-data published by BEA. The API is intended to provide programmatic access to published economic statistics using industry-standard methods and procedures. The intended audience of this document is programmers who are familiar with the concepts and techniques of retrieving data from Web Services.

The BEA API includes methods for retrieving a subset of BEA statistical data, and meta-data that describes it. As additional datasets are added, the meta-data retrieval methods can be used to discover the current data accessible through the API.

### Access to the BEA API

The API is available to registered users on the BEA public web site. Before using the API, users must obtain a unique 36-character UserID by registering at <https://apps.bea.gov/api/signup/>. To register, API users must provide their name (or organization name), a valid email address, and agree to the published terms of service. After completing the registration form an email is sent containing the assigned UserID, and a link that completes the registration process. Assigned UserIDs are activated when the link has been clicked.

#### NOTE:

In mid-2018, BEA restructured its website and created a new subdomain, **[apps.bea.gov](https://apps.bea.gov)**, to host all dynamic, database-driven web applications referenced from the primary domain, **[www.bea.gov](https://www.bea.gov)**. While API registration and documentation links remain on the primary domain, the URI for the API is accessed on the **[apps.bea.gov](https://apps.bea.gov)** subdomain, as shown below.

The URI<sup>1</sup> of the API is: <https://apps.bea.gov/api/data>. All API access is through this URI; no other paths are used. Data is retrieved by sending an HTTP GET to the URI with appropriate (querystring) parameters supplied. The minimum parameters for every request include the UserID and the name of the method being invoked. For example:

<https://apps.bea.gov/api/data?&UserID=Your-36Character-Key&method=GETDATASETLIST&>

would retrieve a list of the datasets currently offered by the BEA API (if the UserID was valid – it's not).

Statistical data offered by the API is organized into defined “Datasets”. An API data retrieval request always specifies one dataset by name. Each dataset has a number of defined parameters, and each parameter has a defined set of valid values. There are four API methods that return meta-data about the API – corresponding to datasets, parameters, and valid parameter values. There is one method that returns data.

---

<sup>1</sup> Uniform Resource Identifier

## JavaScript Usage

While the API may be used from any language capable of issuing HTTP requests (Java, PHP, Perl, Python, C, etc. ), two features are supported that allow JavaScript to issue requests without violating same-origin security checks - CORS and JSONP.

If you're writing a browser-based web application for modern web browsers with support for CORS then you may simply use an XMLHttpRequest as usual, without any changes. All HTTP responses generated by the API will include the necessary CORS headers.

If you're writing a browser-based web application for legacy browsers without support for CORS then your request URL query string may include a *jsonp* argument. If present, this prefix will be wrapped around the response, allowing you to capture the result of the query.

For example:

[http://apps.bea.gov/api/data/?UserID=Your-36Character-Key&method=GetData&datasetname=Regional&TableName=CAINC4&LineCode=30&GeoFIPS=COUNTY&Year=2013&ResultFormat=json&jsonp=MY\\_FUNCTION\\_NAME](http://apps.bea.gov/api/data/?UserID=Your-36Character-Key&method=GetData&datasetname=Regional&TableName=CAINC4&LineCode=30&GeoFIPS=COUNTY&Year=2013&ResultFormat=json&jsonp=MY_FUNCTION_NAME)

## Data Return Format

The API returns data in one of two formats: JSON<sup>2</sup> or XML<sup>3</sup>. The optional *ResultFormat* parameter can be included on any request to specify the format of the results. If *ResultFormat* is not supplied on the request, or an invalid *ResultFormat* is specified, the default format returned is JSON.

The valid values for *ResultFormat* are “JSON” and “XML”. For example, the following request would return a list of the available datasets in XML format:

<http://apps.bea.gov/api/data?UserID=Your-36Character-Key&method=GETDATASETLIST&ResultFormat=XML>

This request would return a list of the available datasets in JSON format:

<http://apps.bea.gov/api/data?&UserID=Your-36Character-Key&method=GETDATASETLIST&ResultFormat=JSON>

The data returned from the API always has the following basic structure, with some additional structure depending on the data requested:

```
<BEAAPI>
  <Request>
    <RequestParam ParameterValue="GETDATASETLIST" ParameterName="METHOD" />
    <RequestParam ParameterValue=" Your-36Character-Key" ParameterName="USERID" />
    <RequestParam ParameterValue="XML" ParameterName="RESULTFORMAT" />
  </Request>
  <Dataset DatasetDescription="Standard NIPA tables" DatasetName="NIPA" />
  <Dataset DatasetDescription="Standard NI underlying detail tables" DatasetName="NI UnderlyingDetail" />
  <Dataset DatasetDescription="Multinational Enterprises" DatasetName="MNE" />
  <Dataset DatasetDescription="Standard Fixed Assets tables" DatasetName="FixedAssets" />
  <Dataset DatasetDescription="International Transactions Accounts" DatasetName="ITA" />
  <Dataset DatasetDescription="International Investment Position" DatasetName="IIP" />
  <Dataset DatasetDescription="GDP by Industry" DatasetName="GDPbyIndustry" />
  <Dataset DatasetDescription="Regional Income data sets" DatasetName="RegionalIncome" />
  <Dataset DatasetDescription="Regional Product data sets" DatasetName="RegionalProduct" />
  <Dataset DatasetDescription="Regional data sets" DatasetName="Regional" />
</Results>
</BEAAPI>
```

---

<sup>2</sup> Java Script Object Notation

<sup>3</sup> Extensible Markup Language

In XML form, the root node is always **<BEAAPI>**, followed by the child node **<Request>**. The **<Request>** node contains **<RequestParam>** children that echo the parameters passed in the request. The root node, **<BEAAPI>**, then has another child node, **<Results>**, containing the results of the request. The Results content is different depending on the method and parameters passed. In this example, the result of the GetDatasetList method is shown to be a simple list of Dataset names and descriptions.

In JSON form, the example above returns data as follows (white-space and indentation added for clarity):

```
{
  "BEAAPI": {
    "Request": {
      "RequestParam": [
        {
          "ParameterName": "USERID",
          "ParameterValue": " Your-36Character-
            Key "
        },
        {
          "ParameterName": "RESULTFORMAT",
          "ParameterValue": "JSON"
        },
        {
          "ParameterName": "METHOD",
          "ParameterValue": "GETDATASETLIST"
        }
      ]
    },
    "Results": {
      "Dataset": [
        {
          "DatasetName": "NIPA",
          "DatasetDescription": "Standard NIPA
            tables"
        },
        {
          "DatasetName": "NIUnderlyingDetail",
          "DatasetDescription": "Standard NI underlying
            detail tables"
        },
        {
          "DatasetName": "MNE",
          "DatasetDescription": "Multinational
            Enterprises"
        },
        {
          "DatasetName": "FixedAssets",
          "DatasetDescription": "Standard Fixed
            Assets tables"
        },
        {
          "DatasetName": "ITA",
          "DatasetDescription": "International Transactions Accounts"
        },
        {
          "DatasetName": "IIP",
          "DatasetDescription": "International Investment Position"
        },
        {
          "DatasetName": "GDPbyIndustry",
          "DatasetDescription": "GDP by
            Industry"
        },
        {
          "DatasetName": "RegionalIncome",
          "DatasetDescription": "Regional Income data
            sets"
        },
        {
          "DatasetName": "RegionalProduct",
          "DatasetDescription": "Regional Product data
            sets"
        },
        {
          "DatasetName": "Regional",
          "DatasetDescription": "Regional data sets"
        }
      ]
    }
  }
}
```

```

    }
  }
}

```

## Error Return Format

When invalid values are supplied for parameters in a request, or required parameters are missing, the results contain an error message – for example:

```

<BEAAPI>
  <Request>
    <RequestParam ParameterName="USERID" ParameterValue="Your-36Character-Key" />
    <RequestParam ParameterName="METHOD" ParameterValue="GETDATASETLIST" />
    <RequestParam ParameterName="ResultFormat" ParameterValue="XML" />
  </Request>
  <Results>
    <Error APIErrorCode="3" APIErrorDescription="The BEA API UserID provided in the request does not exist." />
  </Results>
</BEAAPI>

```

## API Calling Limits

The API has default calling limits as shown below. These limits are meant to protect BEA's API and webserver infrastructure from activity that may be detrimental to that infrastructure and/or unfairly impede other API users.

- 1000 API calls per minute, and/or
- 30 errors per minute, and/or
- 100 MB (raw data) per minute.

Any user that exceeds the above calling limits will receive an explanatory error message for each API call until the per-minute cause has expired. The best way to avoid such errors is to design your application to call the API within these limits, e.g., programmatically regulate the frequency/size of API calls.

## Meta-Data API Methods

The API contains three methods for retrieving meta-data as follows:

*GetDataSetList* – retrieves a list of the datasets currently offered.

Required Parameters: UserID, Method

Optional Parameters: ResultFormat

Result: *Dataset* node with *DatasetName* and *DatasetDescription* attributes.

Example Request:

<http://apps.bea.gov/api/data?&UserID=Your-36Character-Key&method=GETDATASETLIST&ResultFormat=XML&ResultFormat=XML&>

Example Return:

```

<BEAAPI>
  <Request>
    <RequestParam ParameterValue="GETDATASETLIST" ParameterName="METHOD" />
    <RequestParam ParameterValue="Your-36Character-Key" ParameterName="USERID" />
    <RequestParam ParameterValue="XML" ParameterName="RESULTFORMAT" />
  </Request>
  <Results>
    <Dataset DatasetDescription="Standard NIPA tables" DatasetName="NIPA" />
    <Dataset DatasetDescription="Standard NI underlying detail tables" DatasetName="NIUnderlyingDetail" />
    <Dataset DatasetDescription="Multinational Enterprises" DatasetName="MNE" />
    <Dataset DatasetDescription="Regional data sets" DatasetName="Regional" />
    <Dataset DatasetDescription="Standard Fixed Assets tables" DatasetName="FixedAssets" />
    <Dataset DatasetDescription="International Transactions Accounts" DatasetName="ITA" />
  </Results>
</BEAAPI>

```

```

<Dataset DatasetDescription="International Investment Position" DatasetName="IIP" />
<Dataset DatasetDescription="GDP by Industry" DatasetName="GDPbyIndustry" />
<Dataset DatasetDescription="Regional Income data sets" DatasetName="Regional Income" />
<Dataset DatasetDescription="Regional Product data sets" DatasetName="Regional Product" />
</Results>
</BEAAPI>

```

The *RegionalData* data set is obsolete and API calls using this data set will no longer function. Users should instead access the dataset *Regional*, which provides comprehensive detail in statistics, industries, geography, and years. See Appendix N for instructions on how to use the *Regional* data set. In addition, BEA continues to add new datasets as appropriate, and while any new datasets will be announced on the BEA's website *Developers* page (<https://apps.bea.gov/developers>), we also encourage users to periodically call the above *GETDATASETLIST* discover new datasets.

*GetParameterList* – retrieves a list of the parameters (required and optional) for a particular dataset.

Required Parameters: UserID, Method, DatasetName

Optional Parameters: ResultFormat

Result: *Parameter* node with attributes:

- ParameterName – the name of the parameter as used in a data request
- ParameterDataType – String or Integer
- ParameterDescription – a description of the parameter
- ParameterIsRequired – 0 if the parameter can be omitted from a request, 1 if required
- ParameterDefaultValue – the default value used for the request if the parameter is not supplied
- MultipleAcceptedFlag – 0 if the parameter may only have a single value, 1 if multiple values are permitted. Note that multiple values for a parameter are submitted as a comma-separated string.
- AllValue – the special value for a parameter that means all valid values are used without supplying them individually.

Example Request 1:

<https://apps.bea.gov/api/data?&UserID=Your-36Character-Key&method=getparameterlist&datasetname=Regional&ResultFormat=XML>

Example Return 1:

```

<BEAAPI>
<Request>
<RequestParam ParameterName="USERID" ParameterValue="Your-36Character-Key" />
<RequestParam ParameterName="METHOD" ParameterValue="GetParameterList" />
<RequestParam ParameterName="DatasetName" ParameterValue="Regional" />
<RequestParam ParameterName="ResultFormat" ParameterValue="XML" />
</Request>
<Results>
<Parameter ParameterName="GeoFips" MultipleAcceptedFlag="1" ParameterIsRequiredFlag="1"
  ParameterDataType="string" ParameterDescription="Comma-delimited list of 5-character geographic codes;
  COUNTY for all counties, STATE for all states, MSA for all MSAs, MIC for all Micropolitan Areas, PORT for
  all state metro/nonmetro portions, DIV for all Metropolitan Divisions, CSA for all Combined Statistical
  Areas, state post office abbreviation for all counties in one state (e.g. NY)" />
<Parameter ParameterName="TableName" MultipleAcceptedFlag="0" ParameterIsRequiredFlag="1" ParameterDataType="string"
  ParameterDescription="Income or employment table to retrieve" />
<Parameter ParameterName="LineCode" MultipleAcceptedFlag="0" ParameterIsRequiredFlag="1" ParameterDataType="integer"
  ParameterDescription="Line code for a statistic or industry" />
<Parameter ParameterName="Year" MultipleAcceptedFlag="1" ParameterIsRequiredFlag="0" ParameterDescription="Comma-delimited
  list of years; LAST5 for latest 5 years; LAST10 for latest 10 years; ALL for all years" ParameterDefaultValue="LAST5"
  ParameterDataType="string" />
</Results>
</BEAAPI>

```

In this example, the parameters for the “Regional” dataset are being requested. The results indicate that the

dataset has four parameters: GeoFips, LineCode, TableName, and Year.

GeoFips is a string typed parameter indicating the geographic codes requested. GeoFIPS is required. Multiple values are accepted, in a comma-delimited list, and there are special values such as COUNTY for all counties.

TableName is a string typed parameter that specifies what table has the statistic requested. We can't tell from this what the valid TableNames are, but we can see that it is required (and therefore has no default value), and that multiple values are not allowed (and therefore there is no special "all" value).

LineCode specifies the requested statistic in the table. This integer is the line code in the table specified in the TableName parameter. We don't know what these line codes are, but we can send another request to find out.

Year is a string typed parameter containing the years requested. It is not required in a request, and if is not included, the default value used is "LAST5". A comma-delimited list of years is accepted, as well as other special values like "LAST10" and "ALL".

Example Request 2:

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=getparameterlist&datasetname=IntlServTrade&ResultFormat=XML>

Example Return 2:

```
<BEAAPI>
  <Request>
    <RequestParam ParameterValue="XML" ParameterName="RESULTFORMAT" />
    <RequestParam ParameterValue="Your- 36Character- Key" ParameterName="USERID" />
    <RequestParam ParameterValue="INTLSERVTRADE" ParameterName="DATASETNAME" />
    <RequestParam ParameterValue="GETPARAMETERLIST" ParameterName="METHOD" />
  </Request>
  <Results>
    <Parameter ParameterName="TypeOfService" AllValue="ALL" MultipleAcceptedFlag="1" ParameterDefaultValue="ALL"
      ParameterIsRequiredFlag="0" ParameterDescription="The type of service requested" ParameterDataType="string" />
    <Parameter ParameterName="TradeDirection" AllValue="ALL" MultipleAcceptedFlag="1" ParameterDefaultValue="ALL"
      ParameterIsRequiredFlag="0" ParameterDescription="The type of trade direction requested"
      ParameterDataType="string" />
    <Parameter ParameterName="Affiliation" AllValue="ALL" MultipleAcceptedFlag="1" ParameterDefaultValue="ALL"
      ParameterIsRequiredFlag="0" ParameterDescription="The affiliation requested" ParameterDataType="string" />
    <Parameter ParameterName="AreaOrCountry" AllValue="ALL" MultipleAcceptedFlag="1" ParameterDefaultValue="All Countries"
      ParameterIsRequiredFlag="0" ParameterDescription="The area or country requested" ParameterDataType="string" />
    <Parameter ParameterName="Year" AllValue="ALL" MultipleAcceptedFlag="1" ParameterDefaultValue="ALL"
      ParameterIsRequiredFlag="0" ParameterDescription="The year requested" ParameterDataType="string" />
  </Results>
</BEAAPI>
```

In this example, the parameters for the "IntlServTrade" dataset are being requested. The results indicate that the dataset has five parameters: TypeOfService, TradeDirection, Affiliation, AreaOrCountry, and Year.

TypeOfService is a string typed parameter described as the type of service. It is not required. Multiple values are accepted, and there is a value to select all types of service, "All".

The other parameters have characteristics like the first. To get more information about the parameters, "GetParameterValues" should be used.

*GetParameterValues* – retrieves a list of the valid values for a particular parameter.

Required Parameters: UserID, Method, DatasetName, ParameterName

Optional Parameters: ResultFormat

Result: *ParamValue* node with attributes that contain the actual permissible values (and usually a description of the value).

Example Request 1:

<https://apps.bea.gov/api/data?&UserID=Your-36Character-Key&method=GetParameterValues&datasetname=INTLSERVTRADE&ParameterName=TradeDirection&ResultFormat=XML>

Example Return 1:

```
<BEAAPI>
<Request>
  <RequestParam ParameterName="USERID" ParameterValue="Your-36Character-Key" />
  <RequestParam ParameterName="METHOD" ParameterValue="GetParameterValues" />
  <RequestParam ParameterName="DatasetName" ParameterValue="INTLSERVTRADE" />
  <RequestParam ParameterName="ParameterName" ParameterValue="TRADEDIRECTION" />
  <RequestParam ParameterName="ResultFormat" ParameterValue="XML" />
</Request>
<Results>
  <ParamValue Desc="Balance" Key="Balance" />
  <ParamValue Desc="Exports" Key="Exports" />
  <ParamValue Desc="Imports" Key="Imports" />
  <ParamValue Desc="Supplemental detail on insurance transactions" Key="SupplementalIns" />
</Results>
</BEAAPI>
```

Example Request 2:

<https://apps.bea.gov/api/data?&UserID=Your-36Character-Key&method=GetParameterValues&datasetname=Regional&ParameterName=TableName&ResultFormat=XML>

Example Return 2:

```
<BEAAPI>
<Request>
  <RequestParam ParameterValue="Your-36Character-Key" ParameterName="USERID" />
  <RequestParam ParameterValue="XML" ParameterName="RESULTFORMAT" />
  <RequestParam ParameterValue="REGIONAL" ParameterName="DATASETNAME" />
  <RequestParam ParameterValue="GETPARAMETERVALUES" ParameterName="METHOD" />
  <RequestParam ParameterValue="TABLENAME" ParameterName="PARAMETERNAME" />
</Request>
<Results>
  <ParamValue Desc="ACPSA Compensation (NAICS)" Key="ACArtsComp" />
  <ParamValue Desc="ACPSA Employment (NAICS)" Key="ACArtsEmp" />
  <ParamValue Desc="ACPSA Value Added (NAICS)" Key="ACArtsVA" />
  <ParamValue Desc="Total Compensation (NAICS)" Key="ACComp" />
  <ParamValue Desc="Arts Compensation Location Quotient (NAICS)" Key="ACCompLQ" />
  <ParamValue Desc="Arts Compensation Ratio (NAICS)" Key="ACCompRatio" />
  <ParamValue Desc="Total Employment (NAICS)" Key="ACEmp" />
  <ParamValue Desc="Arts Employment Location Quotient (NAICS)" Key="ACEmpLQ" />
  <ParamValue Desc="Arts Employment Ratio (NAICS)" Key="ACEmpRatio" />
  <ParamValue Desc="Total Value Added (NAICS)" Key="ACVA" />
  <ParamValue Desc="Arts Value Added Location Quotient (NAICS)" Key="ACVALQ" />
  <ParamValue Desc="Arts Value Added Ratio (NAICS)" Key="ACVARatio" />
  <ParamValue Desc="Total Full-Time and Part-Time Employment by NAICS Industry (NAICS)" Key="CAEMP25N" />
  <ParamValue Desc="Total Full-Time and Part-Time Employment by SIC Industry (SIC)" Key="CAEMP25S" />
  <ParamValue Desc="Personal Income Summary: Personal Income, Population, Per Capita Personal Income (Non-Industry)" Key="CAINC1" />
  <ParamValue Desc="Economic Profile (Non-Industry)" Key="CAINC30" />
  <ParamValue Desc="Personal Current Transfer Receipts (Non-Industry)" Key="CAINC35" />
  <ParamValue Desc="Personal Income and Employment by Major Component (Non-Industry)" Key="CAINC4" />
  <ParamValue Desc="Farm Income and Expenses (Non-Industry)" Key="CAINC45" />
  <ParamValue Desc="Personal Income by Major Component and Earnings by NAICS Industry (NAICS)" Key="CAINC5N" />
  <ParamValue Desc="Personal Income by Major Component and Earnings by SIC Industry (SIC)" Key="CAINC5S" />
  <ParamValue Desc="Compensation of Employees by NAICS Industry (NAICS)" Key="CAINC6N" />
  <ParamValue Desc="Compensation of Employees by SIC Industry (SIC)" Key="CAINC6S" />
  <ParamValue Desc="Gross Flow of Earnings (Non-Industry)" Key="CAINC91" />
  <ParamValue Desc="Per capita real GDP by metropolitan area (NAICS)" Key="MAGDP10" />
  <ParamValue Desc="Gross domestic product (GDP) by metropolitan area (NAICS)" Key="MAGDP2" />
  <ParamValue Desc="Quantity indexes for real GDP by metropolitan area (2009=100.0) (NAICS)" Key="MAGDP8" />
  <ParamValue Desc="Real GDP by metropolitan area (NAICS)" Key="MAGDP9" />
  <ParamValue Desc="Personal Income Summary: Personal Income, Population, Per Capita Personal Income (Non-Industry)" Key="MAINC1" />
</Results>
</BEAAPI>
```



```

<ParamValue Desc="Economic Profile (Non-Industry)" Key="MAINC30"/>
<ParamValue Desc="Personal Income and Employment by Major Component (Non-Industry)" Key="MAINC4"/>
<ParamValue Desc="Implicit Price Deflators by MSA (Non-Industry)" Key="MAIRPD"/>
<ParamValue Desc="Real Personal Income by MSA (Non-Industry)" Key="MARPI"/>
<ParamValue Desc="Regional Price Parities by MSA (Non-Industry)" Key="MARPP"/>
<ParamValue Desc="Implicit Price Deflators by Portion (Non-Industry)" Key="PAIRPD"/>
<ParamValue Desc="Real Personal Income by Portion (Non-Industry)" Key="PARPI"/>
<ParamValue Desc="Regional Price Parities by Portion (Non-Industry)" Key="PARPP"/>
<ParamValue Desc="Total Full-Time and Part-Time Employment by NAICS Industry (NAICS)" Key="SAEMP25N"/>
<ParamValue Desc="Full-Time and Part-Time Wage and Salary Employment by NAICS Industry (NAICS)" Key="SAEMP27N"/>
<ParamValue Desc="Total personal consumption expenditures (PCE) by state (NAICS)" Key="SAEXP1"/>
<ParamValue Desc="Per capita personal consumption expenditures (PCE) by state (NAICS)" Key="SAEXP2"/>
<ParamValue Desc="Per capita real GDP by state (NAICS)" Key="SAGDP10N"/>
<ParamValue Desc="Per capita real GDP by state (SIC)" Key="SAGDP10S"/>
<ParamValue Desc="Contributions to percent change in real GDP (NAICS)" Key="SAGDP11N"/>
<ParamValue Desc="Gross domestic product (GDP) by state (NAICS)" Key="SAGDP2N"/>
<ParamValue Desc="Gross domestic product (GDP) by state (SIC)" Key="SAGDP2S"/>
<ParamValue Desc="Taxes on production and imports less subsidies (NAICS)" Key="SAGDP3N"/>
<ParamValue Desc="Taxes on production and imports less subsidies (SIC)" Key="SAGDP3S"/>
<ParamValue Desc="Compensation of employees (NAICS)" Key="SAGDP4N"/>
<ParamValue Desc="Compensation of employees (SIC)" Key="SAGDP4S"/>
<ParamValue Desc="Subsidies (NAICS)" Key="SAGDP5N"/>
<ParamValue Desc="Subsidies (SIC)" Key="SAGDP5S"/>
<ParamValue Desc="Taxes on production and imports (NAICS)" Key="SAGDP6N"/>
<ParamValue Desc="Taxes on production and imports (SIC)" Key="SAGDP6S"/>
<ParamValue Desc="Gross operating surplus (NAICS)" Key="SAGDP7N"/>
<ParamValue Desc="Gross operating surplus (SIC)" Key="SAGDP7S"/>
<ParamValue Desc="Quantity indexes for real GDP by state (2009=100.0) (NAICS)" Key="SAGDP8N"/>
<ParamValue Desc="Quantity indexes for real GDP by state (1997=100.0) (SIC)" Key="SAGDP8S"/>
<ParamValue Desc="Real GDP by state (NAICS)" Key="SAGDP9N"/>
<ParamValue Desc="Real GDP by state (SIC)" Key="SAGDP9S"/>
<ParamValue Desc="Personal Income Summary: Personal Income, Population, Per Capita Personal Income (Non-Industry)"
Key="SAINCI"/>
<ParamValue Desc="Economic Profile (Non-Industry)" Key="SAINC30"/>
<ParamValue Desc="Personal Current Transfer Receipts (Non-Industry)" Key="SAINC35"/>
<ParamValue Desc="Personal Income and Employment by Major Component (Non-Industry)" Key="SAINC4"/>
<ParamValue Desc="Property Income (Non-Industry)" Key="SAINC40"/>
<ParamValue Desc="Farm Income and Expenses (Non-Industry)" Key="SAINC45"/>
<ParamValue Desc="Personal Current Taxes (Non-Industry)" Key="SAINC50"/>
<ParamValue Desc="Disposable Personal Income Summary: Disposable Personal Income, Population, and Per Capita Disposable
Personal Income (Non-Industry)" Key="SAINC51"/>
<ParamValue Desc="Personal Income by Major Component and Earnings by NAICS Industry (NAICS)" Key="SAINC5N"/>
<ParamValue Desc="Compensation of Employees by NAICS Industry (NAICS)" Key="SAINC6N"/>
<ParamValue Desc="Wages and Salaries by NAICS Industry (NAICS)" Key="SAINC7N"/>
<ParamValue Desc="Implicit Price Deflators by state (Non-Industry)" Key="SAIRPD"/>
<ParamValue Desc="Real Personal Income by state (Non-Industry)" Key="SARPI"/>
<ParamValue Desc="Regional Price Parities by state (Non-Industry)" Key="SARPP"/>
<ParamValue Desc="Contributions to percent change in real GDP (NAICS)" Key="SQGDP11"/>
<ParamValue Desc="Gross domestic product (GDP) by state (NAICS)" Key="SQGDP2"/>
<ParamValue Desc="Quantity indexes for real GDP by state (2009=100.0) (NAICS)" Key="SQGDP8"/>
<ParamValue Desc="Real GDP by state (NAICS)" Key="SQGDP9"/>
<ParamValue Desc="Personal Income Summary: Personal Income, Population, Per Capita Personal Income (Non-Industry)"
Key="SQINCI"/>
<ParamValue Desc="Personal Current Transfer Receipts (Non-Industry)" Key="SQINC35"/>
<ParamValue Desc="Personal Income by Major Component (Non-Industry)" Key="SQINC4"/>
<ParamValue Desc="Personal Income by Major Component and Earnings by NAICS Industry (NAICS)" Key="SQINC5N"/>
<ParamValue Desc="Compensation of Employees by NAICS Industry (NAICS)" Key="SQINC6N"/>
<ParamValue Desc="Wages and Salaries by NAICS Industry (NAICS)" Key="SQINC7N"/>
</Results>
</BEAPI>

```



To summarize, the API includes three methods that retrieve meta-data about the statistics that are available: GetDatasetList, GetParameterList, and GetParameterValues. **There is also a *new* method called GetParameterValuesFiltered.**

*GetParameterValuesFiltered* – retrieves a list of the valid values for a particular parameter based on other provided parameters.

In our example above with the Regional data set, it is necessary to supply a TableName and LineCode. You will want to discover the LineCode values available for a given TableName. The GetParameterValuesFiltered method is designed to do this.

GetParameterValuesFiltered will return values for one target parameter based on the values of other named parameters.

Example request to retrieve the valid LineCode values for a given TableName:

<http://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetParameterValuesFiltered&datasetname=Regional&TargetParameter=LineCode&TableName=SAINC1&ResultFormat=XML>

Example return:

```
<BEAAPI>
<Request>
  <RequestParam ParameterValue="Your- 36Character- Key" ParameterName="USERID" />
  <RequestParam ParameterValue="XML" ParameterName="RESULTFORMAT" />
  <RequestParam ParameterValue="LINECODE" ParameterName="TARGETPARAMETER" />
  <RequestParam ParameterValue="SAINC1" ParameterName="TABLENAME" />
  <RequestParam ParameterValue="REGIONAL" ParameterName="DATASETNAME" />
  <RequestParam ParameterValue="GETPARAMETERVALUESFILTERED" ParameterName="METHOD" />
</Request>
<Results>
  <ParamValue Desc="[SAINC1] Personal income (millions of dollars)" Key="1"/>
  <ParamValue Desc="[SAINC1] Population (persons)" Key="2"/>
  <ParamValue Desc="[SAINC1] Per capita personal income (dollars)" Key="3"/>
</Results>
</BEAAPI>
```

All results from GetParameterValuesFiltered contain “Desc” and “Key”. Key is the value you will want to pass in as a parameter to the data request for the target parameter you specified. In our example, a desired Key will be passed into LineCode.

Although there is only one TargetParameter, multiple other parameters may be passed in. For example you may want to know what years are available for a given TableName and GeoFips--

Example request:

<http://apps.bea.gov/api/data/?UserID=Your-36Character-Key&method=GetParameterValuesFiltered&datasetname=Regional&TargetParameter=Year&TableName=CAINC5N&GeoFips=01001&ResultFormat=XML>

Example return:

```
<BEAAPI>
<Request>
  <RequestParam ParameterValue="YEAR" ParameterName="TARGETPARAMETER" />
  <RequestParam ParameterValue="CAINC5N" ParameterName="TABLENAME" />
  <RequestParam ParameterValue="XML" ParameterName="RESULTFORMAT" />
  <RequestParam ParameterValue="REGIONAL" ParameterName="DATASETNAME" />
  <RequestParam ParameterValue="01001" ParameterName="GEOFIPS" />
  <RequestParam ParameterValue="GETPARAMETERVALUESFILTERED" ParameterName="METHOD" />
  <RequestParam ParameterValue="Your- 36CharacterKey" ParameterName="USERID" />
</Request>
```

```

</Request>
<Results>
  <ParamValue Desc="2001" Key="2001"/>
  <ParamValue Desc="2002" Key="2002"/>
  <ParamValue Desc="2003" Key="2003"/>
  <ParamValue Desc="2004" Key="2004"/>
  <ParamValue Desc="2005" Key="2005"/>
  <ParamValue Desc="2006" Key="2006"/>
  <ParamValue Desc="2007" Key="2007"/>
  <ParamValue Desc="2008" Key="2008"/>
  <ParamValue Desc="2009" Key="2009"/>
  <ParamValue Desc="2010" Key="2010"/>
  <ParamValue Desc="2011" Key="2011"/>
  <ParamValue Desc="2012" Key="2012"/>
  <ParamValue Desc="2013" Key="2013"/>
  <ParamValue Desc="2014" Key="2014"/>
  <ParamValue Desc="2015" Key="2015"/>
  <ParamValue Desc="2016" Key="2016"/>
</Results>
</BEAAPI>

```

There are many more examples of using `GetParameterValuesFiltered` in the Regional appendix N.

**Please note that the `GetParameterValuesFiltered` method does not yet work with all BEA data sets. If you try `GetParameterValuesFiltered` on a data set that does not yet support it, an error will be returned--**

```

<BEAAPI>
<Request>
  <RequestParam ParameterValue="GETPARAMETERVALUESFILTERED" ParameterName="METHOD"/>
  <RequestParam ParameterValue="Your-36CharacterKey" ParameterName="USERID"/>
  <RequestParam ParameterValue="1" ParameterName="TABLEID"/>
  <RequestParam ParameterValue="NIPA" ParameterName="DATASETNAME"/>
  <RequestParam ParameterValue="XML" ParameterName="RESULTFORMAT"/>
  <RequestParam ParameterValue="Q" ParameterName="FREQUENCY"/>
  <RequestParam ParameterValue="YEAR" ParameterName="TARGETPARAMETER"/>
</Request>
<Results>
  <Error APIErrorDescription="The GetParameterValuesFiltered method has not been implemented on this dataset (coming soon). "
APIErrorCode="34"/>
</Results>
</BEAAPI>

```

## Data Retrieval API Method

The API has one method for retrieving data – *GetData*.

Every data retrieval request requires the `UserID`, `Method`, and `DatasetName` parameters. Each dataset has a defined set of parameters – some required and others optional. Each dataset returns different results that are documented in appendices to this document.

### *GetData*

Required Parameters: `UserID`, `Method`, `DatasetName`, *additional required parameters* (depending on the dataset)

Optional Parameters: `ResultFormat`, *additional optional parameters* (depending on the dataset)

Result: *Dimensions* nodes with attributes:

- `Ordinal` – ordinal number indicating a standardized order of returned dimensions – note that attributes in returned data are not guaranteed to be in any particular order. Programmatic usage of attributes should refer to them by name.
- `Name` – The Name of each data dimension returned
- `DataType` – *string* or *numeric* – whether the data dimension is purely numeric or should be treated as string data

- IsValue – most datasets have one dimension that represents the statistic of interest, and the other dimensions are descriptive of the statistic. IsValue = 1 for the data dimension that is the statistic of interest, otherwise 0. The statistic of interest is usually numeric so that it can be summarized or aggregated based on the descriptive dimension values.

Each Dataset contains different dimensions. There are a few pre-defined dimensions that are common to most Datasets, including:

- CL\_UNIT – a descriptor of the units reported for the data value (e. g. USD for U. S. dollars, and PC for percent)
- UNIT\_MULT – a descriptor of the multiplier that applies to the data value. This value is the base-10 exponent that should be applied to the data value (e. g. amounts reported in millions would have a UNIT\_MULT of 6; amounts reported in billions would have a UNIT\_MULT of 9).

The specific meaning of each dimension is described in the Appendix for each dataset.

The result then includes *Data* nodes containing the actual results specified in the parameters. Each *Data* node contains one attribute for each data dimension (specified in the Dimensions nodes).

Finally, the result may include *Note* nodes. Notes (as in footnotes) further describe or qualify any of the other nodes in the result (or the result node itself). A result node qualified by a *Note* has an attribute named *NoteRef*. If a result node includes the *NoteRef* attribute, the value for it will always be present among the Notes nodes.

Example Request 1:

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&datasetname=Regional&TableName=CAINC1&LineCode=3&GeoFIPS=DE&Year=2014&ResultFormat=XML>

In this example, the GetData method is used to return a result from the dataset named Regional. The TableId and LineCode parameters are used to request statistic for “Per Capita personal income (county annual income)”. The GeoFIPS parameter value is “DE” – meaning the data for all counties in Delaware are requested. A single year’s data is requested – 2014.

Note that the GeoFIPS parameter could have been “COUNTY” for all counties, or a list of individual state or county GeoFIPS codes. Also, multiple years could have been requested by providing them in a comma-separated list, or the special year parameters “LAST5” or “LAST10” could be used.

Example Return 1:

```
<BEAAPI>
<Request>
  <RequestParam ParameterValue="Your-36Character-Key" ParameterName="USERID"/>
  <RequestParam ParameterValue="REGIONAL" ParameterName="DATASETNAME"/>
  <RequestParam ParameterValue="GETDATA" ParameterName="METHOD"/>
  <RequestParam ParameterValue="DE" ParameterName="GEOFIPS"/>
  <RequestParam ParameterValue="CAINC1" ParameterName="TABLENAME"/>
  <RequestParam ParameterValue="3" ParameterName="LINECODE"/>
  <RequestParam ParameterValue="2014" ParameterName="YEAR"/>
  <RequestParam ParameterValue="XML" ParameterName="RESULTFORMAT"/>
</Request>
<Results NoteRef="2" UTCProductionTime="2017-03-03T14:37:59.443" PublicTable="CAINC1 Personal Income Summary: Personal Income, Population, Per Capita Personal Income" UnitOfMeasure="dollars" Statistic="Per capita personal income">
  <Dimensions IsValue="0" DataType="string" Name="Code"/>
  <Dimensions IsValue="0" DataType="string" Name="GeoFips"/>
```

```

<Dimensions IsValue="0" DataType="string" Name="GeoName" />
<Dimensions IsValue="0" DataType="string" Name="TimePeriod" />
<Dimensions IsValue="1" DataType="numeric" Name="DataValue" />
<Dimensions IsValue="0" DataType="string" Name="CL_UNIT" />
<Dimensions IsValue="0" DataType="numeric" Name="UNIT_MULT" />
<Data DataValue="45284" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2014" GeoName="Delaware" GeoFips="10000" Code="CA1-3" />
<Data DataValue="36845" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2014" GeoName="Kent, DE" GeoFips="10001" Code="CA1-3" />
<Data DataValue="48503" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2014" GeoName="New Castle, DE" GeoFips="10003" Code="CA1-3" />
<Data DataValue="43710" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2014" GeoName="Sussex, DE" GeoFips="10005" Code="CA1-3" />
<Notes NoteRef="2" NoteText="Per capita personal income was computed using Census Bureau midyear population estimates. Estimates for 2010-2015 reflect county population estimates available as of March 2016." />
<Notes NoteRef="Note-" NoteText="All dollar estimates are in current dollars (not adjusted for inflation)." />
<Notes NoteRef=" " NoteText="Last updated: November 17, 2016-- new estimates for 2015; revised estimates for 1998-2014." />
</Results>
</BEAAPI>

```

In this example the *Result* node contains a *NoteRef* attribute having the value “2”, and there is a *Notes* node having the NoteRef value of “2”. This should be interpreted as meaning that the NoteText attribute for that *Notes* node applies to the whole result.

## Example Request 2:

<http://apps.bea.gov/api/data?&UserID=Your-36Character-Key&method=GetData&datasetname=Regional&TableName=SAINC1&GeoFIPS=STATE&LineCode=3&Year=2013&ResultFormat=XML>

In this example, the *GetData* method is used to return the dataset named *Regional*. The *TableName* and *LineCode* parameters are used to request statistic for “Per capita personal income (dollars)” – as shown in the result of the first *GetParameterValuesFiltered* example above. The *GeoFIPS* parameter value is “STATE” – meaning the data for all states is requested. Finally, a single year’s data is requested – 2013.

Note that the *GeoFIPS* parameter could have been a list of 5-digit geographic codes. Also, multiple years could have been requested by providing them in a comma-separated list.

## Example Return 2:

```

<BEAAPI>
<Request>
  <RequestParam ParameterValue="2013" ParameterName="YEAR" />
  <RequestParam ParameterValue="3" ParameterName="LINECODE" />
  <RequestParam ParameterValue="REGIONAL" ParameterName="DATASETNAME" />
  <RequestParam ParameterValue="STATE" ParameterName="GEOFIPS" />
  <RequestParam ParameterValue="Your-36Character-Key" ParameterName="USERID" />
  <RequestParam ParameterValue="GETDATA" ParameterName="METHOD" />
  <RequestParam ParameterValue="SAINC1" ParameterName="TABLENAME" />
  <RequestParam ParameterValue="XML" ParameterName="RESULTFORMAT" />
</Request>
<Results NoteRef="2" UTCProductionTime="2015-04-24T14:22:56.983" PublicTable="SA1 Personal Income Summary: Personal Income, Population, Per Capita Personal Income" UnitOfMeasure="dollars" Statistic="Per capita personal income">
  <Dimensions IsValue="0" DataType="string" Name="Code" Ordinal="1" />
  <Dimensions IsValue="0" DataType="string" Name="GeoFips" Ordinal="2" />
  <Dimensions IsValue="0" DataType="string" Name="GeoName" Ordinal="3" />
  <Dimensions IsValue="0" DataType="string" Name="TimePeriod" Ordinal="4" />
  <Dimensions IsValue="1" DataType="numeric" Name="DataValue" Ordinal="5" />
  <Data DataValue="44,765" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="United States" GeoFips="00000" Code="SA1-3" />
  <Data DataValue="36,481" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Alabama" GeoFips="01000" Code="SA1-3" />
  <Data NoteRef="*" DataValue="50,150" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Alaska" GeoFips="02000" Code="SA1-3" />
  <Data DataValue="36,983" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Arizona" GeoFips="04000" Code="SA1-3" />
  <Data DataValue="36,698" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Arkansas" GeoFips="05000" Code="SA1-3" />
  <Data DataValue="48,434" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="California" GeoFips="06000" Code="SA1-3" />
  <Data DataValue="46,897" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Colorado" GeoFips="08000" Code="SA1-3" />
  <Data DataValue="60,658" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Connecticut" GeoFips="09000" Code="SA1-3" />
  <Data DataValue="44,815" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Delaware" GeoFips="10000" Code="SA1-3" />

```

```

    <Data DataValue="75,329" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="District of Columbia" GeoFips="11000"
Code="SA1-3"/>
    <Data DataValue="41,497" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Florida" GeoFips="12000" Code="SA1-
3"/>
    <Data DataValue="37,845" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Georgia" GeoFips="13000" Code="SA1-3"/>
    <Data NoteRef="*" DataValue="45,204" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Hawaii" GeoFips="15000"
Code="SA1-3"/>
    <Data DataValue="36,146" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Idaho" GeoFips="16000" Code="SA1-3"/>
    <Data DataValue="46,980" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Illinois" GeoFips="17000" Code="SA1-
3"/>
    <Data DataValue="38,622" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Indiana" GeoFips="18000" Code="SA1-
3"/>
    <Data DataValue="44,763" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Iowa" GeoFips="19000" Code="SA1-3"/>
    <Data DataValue="44,417" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Kansas" GeoFips="20000" Code="SA1-
3"/>
    <Data DataValue="36,214" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Kentucky" GeoFips="21000" Code="SA1-
3"/>
    <Data DataValue="41,204" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Louisiana" GeoFips="22000" Code="SA1-
3"/>
    <Data DataValue="40,924" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Maine" GeoFips="23000" Code="SA1-3"/>
    <Data DataValue="53,826" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Maryland" GeoFips="24000" Code="SA1-
3"/>
    <Data DataValue="57,248" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Massachusetts" GeoFips="25000"
Code="SA1-3"/>
    <Data DataValue="39,055" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Michigan" GeoFips="26000" Code="SA1-
3"/>
    <Data DataValue="47,500" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Minnesota" GeoFips="27000" Code="SA1-
3"/>
    <Data DataValue="33,913" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Mississippi" GeoFips="28000" Code="SA1-
3"/>
    <Data DataValue="40,663" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Missouri" GeoFips="29000" Code="SA1-
3"/>
    <Data DataValue="39,366" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Montana" GeoFips="30000" Code="SA1-
3"/>
    <Data DataValue="47,157" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Nebraska" GeoFips="31000" Code="SA1-
3"/>
    <Data DataValue="39,235" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Nevada" GeoFips="32000" Code="SA1-
3"/>
    <Data DataValue="51,013" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="New Hampshire" GeoFips="33000"
Code="SA1-3"/>
    <Data DataValue="55,386" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="New Jersey" GeoFips="34000" Code="SA1-
3"/>
    <Data DataValue="35,965" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="New Mexico" GeoFips="35000" Code="SA1-
3"/>
    <Data DataValue="54,462" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="New York" GeoFips="36000" Code="SA1-
3"/>
    <Data DataValue="38,683" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="North Carolina" GeoFips="37000"
Code="SA1-3"/>
    <Data DataValue="53,182" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="North Dakota" GeoFips="38000"
Code="SA1-3"/>
    <Data DataValue="41,049" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Ohio" GeoFips="39000" Code="SA1-3"/>
    <Data DataValue="41,861" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Oklahoma" GeoFips="40000" Code="SA1-
3"/>
    <Data DataValue="39,848" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Oregon" GeoFips="41000" Code="SA1-
3"/>
    <Data DataValue="46,202" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Pennsylvania" GeoFips="42000"
Code="SA1-3"/>
    <Data DataValue="46,989" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Rhode Island" GeoFips="44000"
Code="SA1-3"/>
    <Data DataValue="35,831" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="South Carolina" GeoFips="45000"
Code="SA1-3"/>
    <Data DataValue="46,039" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="South Dakota" GeoFips="46000"
Code="SA1-3"/>
    <Data DataValue="39,558" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Tennessee" GeoFips="47000" Code="SA1-
3"/>
    <Data DataValue="43,862" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Texas" GeoFips="48000" Code="SA1-3"/>
    <Data DataValue="36,640" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Utah" GeoFips="49000" Code="SA1-3"/>
    <Data DataValue="45,483" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Vermont" GeoFips="50000" Code="SA1-
3"/>
    <Data DataValue="48,838" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Virginia" GeoFips="51000" Code="SA1-
3"/>
    <Data DataValue="47,717" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Washington" GeoFips="53000" Code="SA1-
3"/>
    <Data DataValue="35,533" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="West Virginia" GeoFips="54000"
Code="SA1-3"/>
    <Data DataValue="43,244" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Wisconsin" GeoFips="55000" Code="SA1-
3"/>
    <Data DataValue="52,826" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Wyoming" GeoFips="56000" Code="SA1-
3"/>
    <Data DataValue="54,797" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="New England" GeoFips="91000" Code="SA1-
3"/>
    <Data DataValue="52,485" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Midwest" GeoFips="92000" Code="SA1-
3"/>
    <Data DataValue="42,192" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Great Lakes" GeoFips="93000" Code="SA1-
3"/>
    <Data DataValue="44,796" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Plains" GeoFips="94000" Code="SA1-
3"/>
    <Data DataValue="39,760" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Southeast" GeoFips="95000" Code="SA1-
3"/>
    <Data DataValue="42,074" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Southwest" GeoFips="96000" Code="SA1-
3"/>
    <Data DataValue="42,391" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Rocky Mountain" GeoFips="97000"
Code="SA1-3"/>
    <Data DataValue="47,185" UNIT_MULT="0" CL_UNIT="dollars" TimePeriod="2013" GeoName="Far West" GeoFips="98000" Code="SA1-
3"/>
    <Notes NoteRef="2" NoteText="Per capita personal income is total personal income divided by total midyear population."/>
    <Notes NoteRef="*" NoteText="Estimates prior to 1950 are not available for Alaska and Hawaii."/>
    <Notes NoteRef="Note--" NoteText="All dollar estimates are in current dollars (not adjusted for inflation)."/>

```

```
<Notes NoteRef=" " NoteText="Last updated: March 25, 2015-- new estimates for 2014." />
</Results>
</BEAAPI>
```

In this example the *Result* node contains a *NoteRef* attribute having the value “2”, and there is a *Notes* node having the *NoteRef* value of “2”. This should be interpreted as meaning that the *NoteText* attribute for that *Notes* node applies to the whole result.

There are two *Data* nodes having a *NoteRef* attribute with the value “\*”, and there is one *Notes* nodes having the matching *NoteRef* attribute (“\*”). This should be interpreted to mean that the *Notes* node having *NoteRef* = “\*” apply as a group to the corresponding *Data* nodes.

## DataSet Documentation

BEA expects to publish several API Datasets containing a variety of economic statistics. The Datasets that are currently available are each documented separately as appendices here.

## Appendix A – RegionalData (DEPRECATED)

*The RegionalData data set is obsolete and API calls using this data set will no longer function. Users should instead access the datasets RegionalIncome and RegionalProduct, which provide comprehensive detail in statistics, industries, geography, and years. See Appendices I and J for instructions on how to use these two data sets.*



## Appendix B – NIPA (National Income and Product Accounts)

The DataSetName is NIPA. This dataset contains data from the National Income and Product Accounts which include measures of the value and composition of U.S. production and the incomes generated in producing it. NIPA data is provided on a table basis; individual tables contain between fewer than 10 to more than 200 distinct data series. Three parameters are used to retrieve data from the NIPA dataset, as follows:

Name	Type	Description	Is Required	Multiple Values Accepted	“All” value
TableName	String	The standard NIPA table identifier	No	No	N/A
Frequency	String	List of frequencies to retrieve	Yes	Yes	N/A
Year	String	List of year(s) of data to retrieve	Yes	Yes	X ALL

### Example calls

Percent change in Real Gross Domestic Product, Annually and Quarterly for all years

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&DataSetName=NIPA&TableName=T10101&Frequency=A,Q&Year=ALL&ResultFormat=xml>

Personal Income, Monthly, for 2015 and 2016

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&DataSetName=NIPA&TableName=T20600&Frequency=M&Year=2015,2016&ResultFormat=xml>

### API Call [GETPARAMETERVALUES] to Obtain a List of Available Values & Descriptions for Each Parameter

*[Details of each are described in the section below. ]*

Parameter Name	Parameter Value List
TableName	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=NIPA&amp;ParameterName=TableName&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=NIPA&amp;ParameterName=TableName&amp;ResultFormat=xml</a>
Frequency	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=NIPA&amp;ParameterName=Frequency&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=NIPA&amp;ParameterName=Frequency&amp;ResultFormat=xml</a>
Year	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=NIPA&amp;ParameterName=Year&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=NIPA&amp;ParameterName=Year&amp;ResultFormat=xml</a>

### **TableName Parameter** – (required)

The TableName parameter is a string that identifies a specific NIPA table. Only one NIPA table can be requested in each data request. Requests with an invalid combination of TableName, Frequency or Year values will result in an error. The TableName parameter must be passed or an error will result.

### **TableID Parameter** – (discontinued; February 2018)

The TableID parameter is discontinued. The TableName parameter replaces the TableId parameter. A crosswalk between TableId and TableName values can be found in the appendix to this document.

### **Frequency Parameter** – (required, multiple values allowed)

The Frequency parameter is a string that refers to the time series for the requested NIPA table. Multiple frequencies are requested by specifying them as a comma-delimited string, e. g. “A,Q,M”.

When data is requested for frequencies that are not available for the requested NIPA table, only data that is available is returned; if no data is available for the requested frequencies, an error will be returned.

When calling the GetParameterValues method and passing a TableName value the response will identify the valid frequencies for that table.

Accepted parameter values are:

1. A – Annual
2. Q – Quarterly
3. M – Monthly

### **Year Parameter** – (required, multiple values allowed)

The Year parameter specifies the year(s) of the data requested. When quarterly or monthly data are requested all available quarters for the specified year(s) will be returned. Multiple years are requested by specifying them as a comma-delimited string, e. g. “2000,2001,2002”.

If the request supplies the special value X or ALL for the Year parameter, all available years of data for that NIPA table returned. Note that using the X or ALL value for all years can return large amounts of data, and should be avoided when the actual required years are known.

When data is requested for years that are not available for the requested NIPA table, only data that is available is returned; if no data is available for the requested year(s), an error will be returned.

When calling the GetParameterValues method and passing a TableName value the response will identify the valid years for that table.

## **NIPA Dataset Result Data**

### **NIPA (National Income and Product Accounts) Dimensions Elements in Return Data**

Parameter Name	Ordinal	Datatype	IsValue	Description
----------------	---------	----------	---------	-------------

<b>TableName</b>	1	String	No	Unique identifier for the NIPA table requested.
<b>SeriesCode</b>	2	String	No	A unique identifier for the time series of the data item.
<b>LineNumber</b>	3	String	No	Sequence of the data item within the table.
<b>LineDescription</b>	4	String	No	A description of the transactions measured in the data item.
<b>TimePeriod</b>	5	String	No	Time period for the data item in the form YYYY for annual data; YYYYQn for quarterly data (where n is the quarter digit); or YYYYMx for monthly data (where x is the month digit).
<b>Metric_Name</b>	6	String	No	String indicating the measurement of the data item. Example values are Current Dollars, Fisher Price Index, etc.
<b>CL_UNIT</b>	7	String	No	The calculation type of the data item.
<b>UNIT_MULT</b>	8	String	No	An integer representing the base-10 exponent of the multiplier used to interpret the data value. For example “6” refers to millions ( $\text{DataValue} \times 10^6$ ).
<b>DataValue</b>	9	Numeric	Yes	Value of the data item, formatted with commas.

A NoteRef attribute is also included in all data elements and acts as a reference to one of the Notes elements in the returned data. The NoteRef attribute may have multiple values represented by a comma-delimited string. Any NoteRef attribute included in the data is guaranteed to have a corresponding Notes element. For the NIPA dataset, every data element includes at least one Noteref that corresponds to a Note element containing the title of the table.

### *Additional Information*

Explanation of the estimates can be found in the National section of our website: <https://www.bea.gov/national/>. Please consult the [schedule of releases](#) which impacts data and table availability. Updates and changes to the accounts are detailed at: <https://www.bea.gov/national/an1.htm>. National Income and Product Account Methodologies can be found in our [handbook](#).

### *TableName – TableID Mapping*

TableName	TableId	TableName	TableId	TableName	TableId	TableName	TableId
T10101	1	T10803	45	T30200	87	T40203	131
T10102	2	T10806	46	T30300	88	T40204	132
T10103	3	T10903	47	T30400	89	T40205	133
T10104	4	T10904	48	T30500	90	T40206	134
T10105	5	T10905	49	T30600	91	T4030A	135
T10106	6	T10906	50	T30700	92	T4030B	136
T10106A	7	T11000	51	T30800	93	T50100	137
T10106B	8	T11100	52	T30901	94	T50203	138
T10106C	9	T11200	53	T30902	95	T50205	139
T10106D	10	T11300	54	T30903	96	T50206	140
T10107	11	T11400	55	T30904	97	T50301	141
T10108	12	T11500	56	T30905	98	T50302	142
T10109	13	T11600	57	T30906	99	T50303	143
T10110	14	T11701	316	T31001	100	T50304	144
T10111	310	T11705	317	T31003	101	T50305	145
T10201	15	T11706	318	T31004	102	T50306	146
T10202	16	T20100	58	T31005	103	T50401	147
T10203	17	T20200A	59	T31006	104	T50402	148
T10204	18	T20200B	60	T31101	105	T50403	149
T10205	19	T20301	61	T31102	326	T50404	150
T10206	20	T20302	62	T31103	106	T50405	151
T10301	21	T20303	63	T31104	107	T50406	152
T10303	22	T20304	64	T31105	108	T50501	153
T10304	23	T20305	65	T31106	109	T50502	154
T10305	24	T20306	66	T31200	110	T50503	155
T10306	25	T20307	67	T31300	111	T50504	156
T10401	26	T20403	68	T31400	112	T50505	157
T10403	27	T20404	69	T31501	113	T50506	158
T10404	28	T20405	70	T31502	114	T50601	327
T10405	29	T20406	71	T31503	115	T50602	328
T10406	30	T20503	72	T31504	116	T50603	329
T10501	31	T20504	73	T31505	117	T50604	330
T10502	32	T20505	74	T31506	118	T50605	331
T10503	33	T20506	75	T31600	119	T50606	332
T10504	34	T20600	76	T31700	120	T50705A	163
T10505	35	T20700A	77	T31800A	121	T50705B	164
T10506	36	T20700B	78	T31800B	122	T50706A	165
T10604	37	T20801	79	T31900	123	T50706B	166
T10607	38	T20803	80	T32000	124	T50805A	173
T10608	39	T20804	81	T32100	125	T50805B	174
T10701	40	T20805	82	T32200	126	T50806A	175
T10703	41	T20806	83	T32300	127	T50806B	176
T10704	42	T20807	84	T40100	128	T50809A	333
T10705	43	T20900	85	T40201	129	T50809B	334
T10706	44	T30100	86	T40202	130	T50903A	335

TableName	TableId	TableName	TableId	TableName	TableId
T50903B	336	T61100A	216	T62200B	261
T50904A	337	T61100B	217	T62200C	262
T50904B	338	T61100C	218	T62200D	263
T50905A	339	T61100D	219	T70100	264
T50905B	340	T61200A	220	T70201A	265
T50906B	342	T61200B	221	T70201B	266
T51000	178	T61200C	222	T70203A	267
T51100	343	T61200D	223	T70203B	268
T60100B	179	T61300A	224	T70204A	269
T60100C	180	T61300B	225	T70204B	270
T60100D	181	T61300C	226	T70205A	271
T60200A	182	T61300D	227	T70205B	272
T60200B	183	T61400A	228	T70206B	273
T60200C	184	T61400B	229	T70303	274
T60200D	185	T61400C	230	T70304	275
T60300A	186	T61400D	231	T70305	276
T60300B	187	T61500A	232	T70306	277
T60300C	188	T61500B	233	T70403	278
T60300D	189	T61500C	234	T70404	279
T60400A	190	T61500D	235	T70405	280
T60400B	191	T61600A	236	T70406	281
T60400C	192	T61600B	237	T70500	282
T60400D	193	T61600C	238	T70600	283
T60500A	194	T61600D	239	T70700	284
T60500B	195	T61700A	240	T70800	285
T60500C	196	T61700B	241	T70900	286
T60500D	197	T61700C	242	T71000	287
T60600A	198	T61700D	243	T71100	288
T60600B	199	T61800A	244	T71200	289
T60600C	200	T61800B	245	T71300	290
T60600D	201	T61800C	246	T71400	291
T60700A	202	T61800D	247	T71500	292
T60700B	203	T61900A	248	T71600	293
T60700C	204	T61900B	249	T71700	294
T60700D	205	T61900C	250	T71800	295
T60800A	206	T61900D	251	T71900	297
T60800B	207	T62000A	252	T72000	296
T60800C	208	T62000B	253	T72100	392
T60800D	209	T62000C	254	T72200	393
T60900B	210	T62000D	255	T72300	394
T60900C	211	T62100A	256	T72400	395
T60900D	212	T62100B	257	T72500	397
T61000B	213	T62100C	258		
T61000C	214	T62100D	259		
T61000D	215	T62200A	260		



## Appendix C – NIPA Underlying Detail (National Income and Product Accounts)

The DataSetName is NIUnderlyingDetail. This dataset contains underlying detail data from the National Income and Product Accounts which include measures of the value and composition of U.S. production and the incomes generated in producing it. NIPA Underlying Detail data is provided on a table basis; individual tables contain between fewer than 10 to more than 200 distinct data series. Four parameters are used to retrieve data from the NIPA Underlying Detail dataset, as follows:

Name	Type	Description	Is Required	Multiple Values Accepted	“All” value
TableName	String	The standard NIPA table identifier	No	No	N/A
Frequency	String	List of frequencies to retrieve	Yes	Yes	N/A
Year	String	List of year(s) of data to retrieve	Yes	Yes	X ALL

### Example calls

Personal Consumption Expenditures, Current Dollars, Annually, Quarterly and Monthly for all years

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&DataSetName=NIUnderlyingDetail&TableName=U20305&Frequency=A,Q,M&Year=ALL&ResultFormat=xml>

Auto and Truck Unit Sales, Production, Inventories, Expenditures and Price, Monthly, for 2015 and 2016

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&DataSetName=NIUnderlyingDetail&TableName=U70205S&Frequency=M&Year=2015,2016&ResultFormat=xml>

### API Call [GETPARAMETERVALUES] to Obtain a List of Available Values & Descriptions for Each Parameter

*[Details of each are described in the section below. ]*

Parameter Name	Parameter Value List
TableName	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=NIUnderlyingDetail&amp;ParameterName=TableName&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=NIUnderlyingDetail&amp;ParameterName=TableName&amp;ResultFormat=xml</a>
Frequency	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=NIUnderlyingDetail&amp;ParameterName=Frequency&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=NIUnderlyingDetail&amp;ParameterName=Frequency&amp;ResultFormat=xml</a>
Year	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=NIUnderlyingDetail&amp;ParameterName=Year&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=NIUnderlyingDetail&amp;ParameterName=Year&amp;ResultFormat=xml</a>



### ***TableName Parameter*** – (required)

The TableName parameter is a string that identifies a specific NIPA Underlying Detail table. Only one NIPA Underlying Detail table can be requested in each data request. Requests with an invalid combination of TableName, Frequency or Year values will result in an error. The TableName must be passed or an error will result.

### ***TableID Parameter*** – (discontinued; February 2018)

The TableID parameter is discontinued. The TableName parameter replaces the TableId parameter. A crosswalk between TableId and TableName values can be found in the appendix to this document.

### ***Frequency Parameter*** – (required, multiple values allowed)

The Frequency parameter is a string that refers to the time series for the requested NIPA Underlying Detail table. Multiple frequencies are requested by specifying them as a comma-delimited string, e. g. “A,Q,M”.

When data is requested for frequencies that are not available for the requested NIPA Underlying Detail table, only data that is available is returned; if no data is available for the requested frequencies, an error will be returned.

When calling the GetParameterValues method and passing a TableName value the response will identify the valid frequencies for that table.

Accepted parameter values are:

1. A – Annual
2. Q – Quarterly
3. M – Monthly

### ***Year Parameter*** – (required, multiple values allowed)

The Year parameter specifies the year(s) of the data requested. When quarterly or monthly data are requested all available quarters for the specified year(s) will be returned. Multiple years are requested by specifying them as a comma-delimited string, e. g. “2000,2001,2002”.

If the request supplies the special value X or ALL for the Year parameter, all available years of data for that NIPA Underlying Detail table returned. Note that using the X or ALL value for all years can return large amounts of data, and should be avoided when the actual required years are known.

When data is requested for years that are not available for the requested NIPA Underlying Detail table, only data that is available is returned; if no data is available for the requested year(s), an error will be returned.

When calling the GetParameterValues method and passing a TableName value the response will identify the valid years for that table.

## **NIPA Underlying Detail Dataset Result Data**

### **NIPA (National Income and Product Accounts) Dimensions Elements in Return Data**

Parameter Name	Ordinal	Datatype	IsValue	Description
<b>TableName</b>	1	String	No	Unique identifier for the NIPA table requested.
<b>SeriesCode</b>	2	String	No	A unique identifier for the time series of the data item.
<b>LineNumber</b>	3	String	No	Sequence of the data item within the table.
<b>LineDescription</b>	4	String	No	A description of the transactions measured in the data item.
<b>TimePeriod</b>	5	String	No	Time period for the data item in the form YYYY for annual data; YYYYQn for quarterly data (where n is the quarter digit); or YYYYMx for monthly data (where x is the month digit).
<b>Metric_Name</b>	6	String	No	String indicating the measurement of the data item. Example values are Current Dollars, Fisher Price Index, etc.
<b>CL_UNIT</b>	7	String	No	The calculation type of the data item.
<b>UNIT_MULT</b>	8	String	No	An integer representing the base-10 exponent of the multiplier used to interpret the data value. For example “6” refers to millions ( $\text{DataValue} \times 10^6$ ).
<b>DataValue</b>	9	Numeric	Yes	Value of the data item, formatted with commas.

A NoteRef attribute is also included in all data elements and acts as a reference to one of the Notes elements in the returned data. The NoteRef attribute may have multiple values represented by a comma-delimited string. Any NoteRef attribute included in the data is guaranteed to have a corresponding Notes element. For the NIPA dataset, every data element includes at least one Noteref that corresponds to a Note element containing the title of the table.

### *Additional Information*

Explanation of the estimates can be found in the National section of our website:

<https://www.bea.gov/national/>. Please consult the [schedule of releases](#) which impacts data and table availability. Updates and changes to the accounts are detailed at: <https://www.bea.gov/national/an1.htm>. National Income and Product Account Methodologies can be found in our [handbook](#).

### TableName – TableID Mapping

TableName	TableId	TableName	TableId	TableName	TableId	TableName	TableId
U001A	2001	U20305	2014	U50203	2070	U50705BU3	2092
U001A2	2012	U20306	2015	U50205	2071	U50706AM	2093
U001B	2023	U20403	2074	U50206	2072	U50706AU	2094
U001BC	2034	U20404	2016	U50404	2029	U50706BM	2095
U002AU	2045	U20405	2017	U50405	2030	U50706BU	2096
U002AUI	2056	U20406	2018	U50406	2031	U51100	2053
U002BU	2059	U30400	2019	U50504	2032	U70204	2054
U002BUI	2060	U30500	2020	U50505	2033	U70205	2057
U003AU	2061	U30600	2021	U50506	2035	U70205S	2055
U003BU	2002	U30700	2022	U50705AM1	2081	U70206	2058
U004A1	2003	U30800	2024	U50705AM2	2082	U90100	2075
U004A2	2004	U31200	2025	U50705AM3	2083	U90200	2076
U004A3	2005	U31300	2026	U50705AU1	2084	U90300	2077
U004B1	2006	U32400	2027	U50705AU2	2085	U90400	2078
U004B2	2007	U32500	2028	U50705AU3	2086	U90500	2079
U004B3	2008	U40203	2114	U50705BM1	2087		
U00500	2009	U40204	2111	U50705BM2	2088		
U00600	2010	U40205	2113	U50705BM3	2089		
U00700	2011	U40206	2112	U50705BU1	2090		
U20304	2013	U4030B	2073	U50705BU2	2091		

## Appendix D – Fixed Assets

The DataSetName is FixedAssets. This dataset contains data from the standard set of Fixed Assets tables as published online. Two parameters are used to retrieve data from the Fixed Assets dataset, as follows:

Name	Type	Description	Is Required	Multiple Values Accepted	“All” value
TableName	String	The standard NIPA table identifier	Yes	No	N/A
Year	String	List of year(s) of data to retrieve	Yes	Yes	X ALL

### Example calls

Current-Cost Net Stock of Private Fixed Assets, Equipment, Structures, and Intellectual Property Products by Type, for all years

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&DataSetName=FixedAssets&TableName=FAAt201&Year=ALL&ResultFormat=xml>

Chain-Type Quantity Indexes for Depreciation of Private Nonresidential Fixed Assets by Industry Group and Legal Form of Organization, for 2015 and 2016

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&DataSetName=FixedAssets&TableName=FAAt405&Year=2015,2016&ResultFormat=xml>

### API Call [GETPARAMETERVALUES] to Obtain a List of Available Values & Descriptions for Each Parameter

*[Details of each are described in the section below. ]*

Parameter Name	Parameter Value List
TableName	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=FixedAssets&amp;ParameterName=TableName&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=FixedAssets&amp;ParameterName=TableName&amp;ResultFormat=xml</a>
Year	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=FixedAssets&amp;ParameterName=Year&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=FixedAssets&amp;ParameterName=Year&amp;ResultFormat=xml</a>

### TableName Parameter – (required)

The TableName parameter is a string that identifies a specific NIPA table. Only one NIPA table can be requested in each data request. Requests with an invalid combination of TableName and Year values will result in an error. The TableName parameter must be passed or an error will result.

### **TableID Parameter** – (discontinued; October 2018)

The TableID parameter is discontinued. The TableName parameter replaces the TableId parameter. A crosswalk between TableId and TableName values can be found in the appendix to this document.

### **Year Parameter** – (required, multiple values allowed)

The Year parameter specifies the year(s) of the data requested. Multiple years are requested by specifying them as a comma-delimited string, e. g. “2000,2001,2002”.

If the request supplies the special value X or ALL for the Year parameter, all available years of data for that NIPA table returned. Note that using the X or ALL value for all years can return large amounts of data, and should be avoided when the actual required years are known.

When data is requested for years that are not available for the requested NIPA table, only data that is available is returned; if no data is available for the requested year(s), an error will be returned.

When calling the GetParameterValues method and passing a TableName value the response will identify the valid years for that table.

## **NIPA Dataset Result Data**

### **NIPA (National Income and Product Accounts) Dimensions Elements in Return Data**

Parameter Name	Ordinal	Datatype	IsValue	Description
<b>TableName</b>	1	String	No	Unique identifier for the NIPA table requested.
<b>SeriesCode</b>	2	String	No	A unique identifier for the time series of the data item.
<b>LineNumber</b>	3	String	No	Sequence of the data item within the table.
<b>LineDescription</b>	4	String	No	A description of the transactions measured in the data item.
<b>TimePeriod</b>	5	String	No	Time period for the data item in the form YYYY for annual data; YYYYQn for quarterly data (where n is the quarter digit); or YYYYMx for monthly data (where x is the month digit).
<b>Metric_Name</b>	6	String	No	String indicating the measurement of the data item. Example values are Current Dollars, Fisher Price Index, etc.

<b>CL_UNIT</b>	7	String	No	The calculation type of the data item.
<b>UNIT_MULT</b>	8	String	No	An integer representing the base-10 exponent of the multiplier used to interpret the data value. For example “6” refers to millions ( $\text{DataValue} \times 10^6$ ).
<b>DataValue</b>	9	Numeric	Yes	Value of the data item, formatted with commas.

A NoteRef attribute is also included in all data elements and acts as a reference to one of the Notes elements in the returned data. The NoteRef attribute may have multiple values represented by a comma-delimited string. Any NoteRef attribute included in the data is guaranteed to have a corresponding Notes element. For the NIPA dataset, every data element includes at least one Noteref that corresponds to a Note element containing the title of the table.

#### *Additional Information*

Explanation of the estimates can be found in the Fixed Assets section of our website:

<https://www.bea.gov/resources/learning-center/what-to-know-fixed-assets>. Fixed Assets data is updated once per year, typically between late-August through early October.

*TableName – TableID Mapping*

TableName	TableId	TableName	TableId	TableName	TableId
FAAt101	16	FAAt307ESI	138	FAAt610	119
FAAt102	17	FAAt307I	139	FAAt701	149
FAAt103	86	FAAt307S	55	FAAt702	150
FAAt104	87	FAAt308E	57	FAAt703	151
FAAt105	96	FAAt308ESI	140	FAAt704	152
FAAt106	97	FAAt308I	141	FAAt705	153
FAAt107	105	FAAt308S	147	FAAt706	154
FAAt108	124	FAAt309E	108	FAAt707	155
FAAt109	125	FAAt309ESI	142	FAAt801	32
FAAt201	18	FAAt309I	143	FAAt802	33
FAAt202	19	FAAt309S	110	FAAt803	50
FAAt203	42	FAAt310E	111	FAAt804	83
FAAt204	65	FAAt310ESI	144	FAAt805	148
FAAt205	66	FAAt310I	145	FAAt806	85
FAAt206	67	FAAt310S	113	FAAt807	63
FAAt207	51	FAAt401	26	FAAt808	64
FAAt208	52	FAAt402	27	FAAt809	122
FAAt209	106	FAAt403	46	FAAt810	123
faaT210	146	FAAt404	77	FAAt901	34
FAAt301E	21	FAAt405	78	FAAt902	95
FAAt301ESI	126	FAAt406	79	FAAt903	104
FAAt301I	127	FAAt407	59		
FAAt301S	22	FAAt408	60		
FAAt302E	24	FAAt409	114		
FAAt302ESI	128	FAAt410	115		



FAAt302I	129	FAAt501	28		
FAAt302S	25	FAAt502	29		
FAAt303E	44	FAAt503	47		
FAAt303ESI	130	FAAt504	88		
FAAt303I	131	FAAt505	89		
FAAt303S	45	FAAt506	90		
FAAt304E	69	FAAt507	98		
FAAt304ESI	132	FAAt508	99		
FAAt304I	133	FAAt509	116		
FAAt304S	70	FAAt510	117		
FAAt305E	72	FAAt601	41		
FAAt305ESI	134	FAAt602	48		
FAAt305I	135	FAAt603	49		
FAAt305S	73	FAAt604	80		
FAAt306E	75	FAAt605	81		
FAAt306ESI	136	FAAt606	82		
FAAt306I	137	FAAt607	61		
FAAt306S	76	FAAt608	62		
FAAt307E	54	FAAt609	118		

## Appendix E – Data on Direct Investment and Multinational Enterprises (MNEs)

The DataSetName is MNE. This dataset contains two types of statistics:

1. Direct Investment (DI)—income and financial transactions in direct investment that underlie the U. S. balance of payments statistics, and direct investment positions that underlie the U. S. international investment positions; and
2. Activities of Multinational Enterprises (AMNE)—operations and finances of U. S. parent enterprises and their foreign affiliates and U. S. affiliates of foreign MNEs.

API requests for the two types of statistics share most of the same parameters, though the allowable values for each parameter may be different, depending on the type of statistic desired (e. g. , DI or AMNE).

### Type 1: Direct Investment (DI) Data Request

Parameter Name	Type	Description	Required	Multiple Values Accepted	“All” value	Default
<a href="#">DirectionOfInvestment</a>	String	Outward = US direct investment abroad Inward = Foreign investment in the US	Yes	No	Not accepted	
<a href="#">SeriesID</a>	Integer	Data Series Identifier	No	Yes	All	All
<a href="#">Classification</a>	String	Results by country and/or industry	Yes	No	Not accepted	
<a href="#">Year</a>	String	Time Period	Yes	Yes	All	
<a href="#">Country</a>	String	Geographic Area Code	No	Yes	All	All
<a href="#">Industry</a>	String	Industry Code	No	Yes	All	All
<a href="#">GetFootnotes</a>	String	Yes = Include footnotes No = Exclude footnotes	No	No	Not accepted	No

### Examples of Direct Investment (DI) Data Requests

U. S. direct investment position in China and Asia for 2011 and 2012

<https://apps.bea.gov/api/data/?&SeriesId=30&UserID=Your-36Character-Key&method=GetData&DataSetName=MNE&Year=2012,2011&Country=650,699&DirectionOfInvestment=Outward&Classification=Country&ResultFormat=xml>

Foreign direct investment position in the U. S. from Germany in the manufacturing industry for 2011 and 2012

<https://apps.bea.gov/api/data/?&SeriesId=22,23,24,25,26,27&UserID=Your-36Character-Key&method=GetData&DataSetName=MNE&Year=2013,2012,2011,2010&Country=308&Industry=3000&DirectionOfInvestment=Inward&Classification=CountryByIndustry&ResultFormat=xml>

## Type 2: Activities of Multinational Enterprises (AMNE) Data Request

Parameter Name	Type	Description	Required	Multiple Values Accepted	"All" value	Default
<a href="#">DirectionOfInvestment</a>	String	Outward, Inward, State, Parent	Yes	No	Not accepted	
<a href="#">OwnershipLevel</a>	Binary	0 = Majority-Owned Affiliates 1 = All Affiliates	Yes	No	Not accepted	
<a href="#">NonBankAffiliatesOnly</a>	Binary	0 = Both Bank and NonBank Affiliates 1 = Nonbank Affiliates	Yes	No	Not accepted	
<a href="#">SeriesID</a>	Integer	Data Series Identifier	No	Yes	All	All
<a href="#">Classification</a>	String	Results by country and/or industry	Yes	No	Not accepted	
<a href="#">Year</a>	String	Time Period	Yes	Yes	All	
<a href="#">Country</a>	String	Geographic Area Code	No	Yes	All	All
<a href="#">Industry</a>	String	Industry Code	No	Yes	All	All
<a href="#">State</a>	String	Two-digit State FIPS Code	No	No	All	All
<a href="#">GetFootnotes</a>	String	Yes = Include footnotes No = Exclude footnotes	No	No	Not accepted	No

## Examples of Activities of Multinational Enterprises (AMNE) Data Requests

Net income and sales for Brazilian affiliates of U. S. parent enterprises, all industries, 2011 and 2012

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&DataSetName=MNE&Year=2012,2011&Country=202&Industry=all&DirectionOfInvestment=Outward&Classification=CountryByIndustry&SeriesId=5,4&NonBankAffiliatesOnly=0&OwnershipLevel=0&ResultFormat=xml>

Total employment in U. S. affiliates of foreign-owned enterprises, all countries, 2011, include footnotes

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&DataSetName=MNE&Year=2011&Country=all&Industry=0000&DirectionOfInvestment=Inward&Classification=Country&SeriesId=8&OwnershipLevel=0&NonbankAffiliatesOnly=0&GetFootnotes=Yes&ResultFormat=xml>

## API Call [GETPARAMETERVALUES] to Obtain a List of Available Values & Descriptions for Each Parameter

*[Details of each are described in the section below. ]*

Parameter Name	Parameter Value List
<a href="#"><u>DirectionOfInvestment</u></a>	<a href="https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key Y&amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=DirectionOfInvestment&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key Y&amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=DirectionOfInvestment&amp;ResultFormat=xml</a>
<a href="#"><u>OwnershipLevel</u></a>	<a href="https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=OwnershipLevel&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=OwnershipLevel&amp;ResultFormat=xml</a>
<a href="#"><u>NonBankAffiliatesOnly</u></a>	<a href="https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=NonbankAffiliatesOnly&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=NonbankAffiliatesOnly&amp;ResultFormat=xml</a>
<a href="#"><u>SeriesID</u></a>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=SeriesID&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=SeriesID&amp;ResultFormat=xml</a>
<a href="#"><u>Classification</u></a>	<a href="https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=Classification&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=Classification&amp;ResultFormat=xml</a>
<a href="#"><u>Year</u></a>	<a href="https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=Year&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=Year&amp;ResultFormat=xml</a>
<a href="#"><u>Country</u></a>	<a href="https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=country&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=country&amp;ResultFormat=xml</a>
<a href="#"><u>Industry</u></a>	<a href="https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=Industry&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=Industry&amp;ResultFormat=xml</a>
<a href="#"><u>State</u></a>	<a href="https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=state&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=state&amp;ResultFormat=xml</a>
<a href="#"><u>GetFootnotes</u></a>	<a href="https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=GetFootnotes&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID= Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=MNE&amp;ParameterName=GetFootnotes&amp;ResultFormat=xml</a>

## Parameter Details

### *DirectionOfInvestment Parameter* – (Required, single value)

DirectionOfInvestment can take on two values for DI statistics and four for AMNE statistics. The two values shared by DI and AMNE statistics are:

1. ‘Outward’ – for AMNE statistics, provides data for foreign affiliates; for DI statistics, provides data on transactions and positions between foreign affiliates and their U. S. parent enterprises.
2. ‘Inward’ – for AMNE statistics, provides data for U. S. affiliates; for DI statistics, provides data on transactions and positions between U. S. affiliates and their foreign parent groups.

*For AMNE statistics only* there are two additional options:

3. ‘State’ – provides data on U. S. affiliates of foreign multinational enterprises at the state level. Note that only data on employment (and for 2007 and earlier years, property, plant, and equipment) are available at the state level.
4. ‘Parent’ – provides data on U. S. parent enterprises.

### *OwnershipLevel Parameter* – (used with AMNE statistics only, required, single value)

1. 1 – Returns data for all affiliates
2. 0 – Returns data for majority-owned affiliates only

If DirectionOfInvestment = “Parent” then OwnershipLevel must be set to 1.

### *NonBankAffiliatesOnly Parameter* – (used with AMNE statistics only, required, single value)

1. 1 – Returns data for nonbank affiliates only
2. 0 – Returns data for both bank and nonbank affiliates only

Select NonBankAffiliatesOnly = 0 for data from 2009 – present for ‘outward’ AMNE and from 2007 – present for ‘inward’ AMNE

Select NonBankAffiliatesOnly = 1 for data up to 2008 for ‘outward’ AMNE and up to 2006 for ‘inward’ AMNE

### *SeriesID Parameter* – (optional, default = 0, multiple values allowed)

Refer to the GETPARAMETERVALUES API call above for the list of SeriesID values and their descriptions. Note that not all series are available for all classes of ownership and years.

A value of 0 will return data for all available series given the other parameters. Separate

multiple values with a comma.

*Classification Parameter* – (required, single value)

Refer to the GETPARAMETERVALUES API call above for the list of CLASSIFICATION parameter values and their descriptions. Note that not all series are available for all classifications. The CLASSIFICATION parameter is required and must be single-valued.

*Year Parameter* (required, multiple values allowed)

Use the four-digit year to request data for a specific year. Use ‘all’ to return data for all available years. Separate multiple values with a comma.

*Country Parameter* – (optional, default = all, multiple values allowed)

Refer to the GETPARAMETERVALUES API call above for the list of three-digit country and region identification values. Use ‘000’ for the total of all countries and ‘all’ for all available countries and regions. Separate multiple values with a comma.

*Industry Parameter* – (optional, default = all, multiple values allowed)

Refer to the GETPARAMETERVALUES API call above for the list of four-digit industry identification values. These generally follow the North American Industry Classification System (NAICS). Use ‘0000’ for the all- industries total and ‘all’ for all available industries. Separate multiple values with a comma.

*State Parameter* – (optional, default = all, multiple values allowed)

At the state level, data are only available on employment and (for limited years), gross property, plant, and equipment.

Refer to the GETPARAMETERVALUES API call above for the list of the two-digit Federal Information Processing Standards (FIPS) codes, available at:

<https://www.bls.gov/cew/cewedr10.htm>.

Use ‘70’ for “Other U. S. Areas”, ‘75’ for “Foreign”, ‘00’ for total U. S., and ‘all’ for all states and areas. Separate multiple values with a comma.

*GetFootnotes Parameter* – (optional, default=no, single value)

1. ‘yes’ – Include footnotes with data returned
2. ‘no’ – Do not include footnotes with data returned

## Appendix F – Gross Domestic Product by Industry (GDPbyIndustry)

The gross domestic product by industry data are contained within a dataset called GDPbyIndustry. BEA's industry accounts are used extensively by policymakers and businesses to understand industry interactions, productivity trends, and the changing structure of the U. S. economy. The GDP-by-industry dataset includes data in both current and chained (real) dollars. The dataset contains estimates for value added, gross output, intermediate inputs, KLEMS and employment statistics.

### Gross Domestic Product by Industry (GDPbyIndustry) Data Request

Parameter Name	Type	Description	Required	Multiple Values Accepted	"All" value	Default
TableID	Integer	The unique GDP by Industry table identifier (ALL for All)	Yes	Yes	ALL	N/A
<u>Frequency</u>	String	A - Annual, Q-Quarterly	Yes	Yes	A,Q	N/A
<u>Year</u>	Integer	List of year(s) of data to retrieve (ALL for All)	Yes	Yes	ALL	N/A
Industry	String	List of industries to retrieve (ALL for All)	Yes	Yes	ALL	N/A

### Examples of GDP by Industry (GDPbyIndustry) Data Requests

Annual Value Added by Industry data for all industries for years 2011 and 2012:

<https://apps.bea.gov/api/data/?&UserID=%20Your-36Character-Key&method=GetData&DataSetName=GDPbyIndustry&Year=2012,2011&Industry=ALL&tableID=1&Frequency=A&ResultFormat=xml>

All annual and quarterly data in all tables for the Agriculture industry in 2010.

<https://apps.bea.gov/api/data/?&UserID=%20Your-36Character-Key&method=GetData&DataSetName=GDPbyIndustry&Year=2010&Industry=11&tableID=ALL&Frequency=A,Q&ResultFormat=xml>

### API Call [GETPARAMETERVALUES] to Obtain a List of Available Values & Descriptions for Each Parameter

*[Details of each are described in the section below. ]*

Parameter Name	Parameter Value List
----------------	----------------------



<u>TableID</u>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=GDPbyIndustry&amp;ParameterName=TableID&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=GDPbyIndustry&amp;ParameterName=TableID&amp;ResultFormat=xml</a>
Frequency	<a href="https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=GDPbyIndustry&amp;ParameterName=Frequency&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=GDPbyIndustry&amp;ParameterName=Frequency&amp;ResultFormat=xml</a>
Year	<a href="https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=GDPbyIndustry&amp;ParameterName=Year&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=GDPbyIndustry&amp;ParameterName=Year&amp;ResultFormat=xml</a>
Industry	<a href="https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=GDPbyIndustry&amp;ParameterName=Industry&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=GDPbyIndustry&amp;ParameterName=Industry&amp;ResultFormat=xml</a>

## Parameter Details

**TableID Parameter** – (Required, multiple values accepted, no default value, ‘ALL’ for all tables)

- The TableID parameter is a unique table identifier. This parameter is required to query data and does accept multiple comma separated values. If all tables are required, use the ‘ALL’ keyword.
- All tables are published annually, but only a subset are published quarterly. The Descr in the GetParameterValues result will contain (A) if the table is published annually and (Q) indicating that the table is also published quarterly.

**Frequency Parameter** – (Required, multiple values accepted, no default value, ‘A,Q’ for all frequencies)

- The Frequency parameter indicates whether annual or quarterly data are to be returned. This parameter is required to query data and does accept multiple comma separated values.
- All tables are published annually (Frequency = A) but only a subset are published quarterly (Frequency = Q)
- If a data request is submitted for both annual and quarterly data from a table that is only published annually then only the annual data will be returned.
- If a data request is submitted for quarterly data from a table that is only published annually then the user will receive the following error:

```
<Error APIErrorCode="204" APIErrorDescription="Error retrieving GDP by Industry data. ">
  <ErrorDetail Description="This TableID is not published quarterly: 25" />
</Error>
```

**Year Parameter** – (Required, multiple values accepted, no default value, ‘ALL’ for all years)

- The Year parameter indicates what periods of data are requested. This parameter is required to query data and does accept multiple comma separated values. Use the keyword ‘ALL’ to return all periods of data.
- If requesting quarterly frequency data, all available quarters for a year will be returned.
- Annual data publications begin in 1997 for most tables and 1998 for percent change and contributions tables. Quarterly data began publication in 2005.

- If a data request is submitted for quarterly or annual data before the earliest estimate period the user will receive one of the following errors:

```
<Error APIErrorCode="204" APIErrorDescription="Error retrieving GDP by Industry data. ">
  <ErrorDetail Description="Quarterly data begin in 2005. Invalid year: 1997" />
</Error>
```

```
<Error APIErrorCode="204" APIErrorDescription="Error retrieving GDP by Industry data. ">
  <ErrorDetail Description="Annual data begin in 1997 and quarterly data begins in
2005. Invalid year: 1996" />
</Error>
```

**Industry Parameter** – (Required, multiple values accepted, no default value, ‘ALL’ for all industries)

- The Industry parameter indicates what periods of data are requested. This parameter is required to query data and does accept multiple comma separated values. Use the keyword ‘ALL’ to return all industries.
- All industries are published annually, but only a subset are published quarterly. The Descr in the GetParameterValues result will contain (A) if the industry is published annually and (Q) indicating that the industry is also published quarterly.
- If a data request is submitted for an industry that is not published in the requested tables the user will receive the following error:

```
<Error APIErrorCode="204" APIErrorDescription="Error retrieving GDP by Industry data. ">
  <ErrorDetail Description="Invalid industry: 111CA" />
</Error>
```

### **General Use**

- Data will be returned for all data cells that fit the requested criteria. If the request contains parameter values requesting data for which only part of a set is available, only the data matching the criteria will be returned. For example, requesting ALL TableIDs for 1997 will return only annual data because the quarterly publications begin in estimate year 2005. Blanks will not be returned for missing data.
- If no data fit the selected criteria the user will receive the following error:

```
<Error APIErrorCode="204" APIErrorDescription="Error retrieving GDP by Industry data. ">
  <ErrorDetail Description="No data exist for selected criteria" />
</Error>
```

## Appendix G – ITA (International Transactions)

The DataSetName is ITA. This dataset contains data on U. S. international transactions. BEA's international transactions (balance of payments) accounts include all transactions between U. S. and foreign residents. Four parameters are used to retrieve data from the ITA dataset, as follows:

### ITA (International Transactions) Data Request Parameters

Parameter Name	Type	Description	Required	Multiple Values Accepted	“All” value	Default
<b>Indicator</b>	String	The indicator code for the type of transaction requested	No	Yes	All	All
<b>AreaOrCountry</b>	String	The area or country requested	No	Yes	All	AllCountries
<b>Frequency</b>	String	A - Annual, QSA - Quarterly seasonally adjusted, QNSA - Quarterly not seasonally adjusted	No	Yes	All	All
<b>Year</b>	String	Year requested	No	Yes	All	All

### Examples of ITA (International Transactions) Data Requests

Balance on goods with China for 2011 and 2012

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&DataSetName=ITA&Indicator=BalGds&AreaOrCountry=China&Frequency=A&Year=2011,2012&ResultFormat=xml>

Net U. S. acquisition of portfolio investment assets (quarterly not seasonally adjusted) for 2013

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&DataSetName=ITA&Indicator=PfInvAssets&AreaOrCountry=AllCountries&Frequency=QNSA&Year=2013&ResultFormat=xml>

## API Call [GETPARAMETERVALUES] to Obtain a List of Available Values & Descriptions for Each Parameter

*[Details of each are described in the section below. ]*

Parameter Name	Parameter Value List
<b>Indicator</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=ITA&amp;ParameterName=Indicator&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=ITA&amp;ParameterName=Indicator&amp;ResultFormat=xml</a>
<b>AreaOrCountry</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=ITA&amp;ParameterName=AreaOrCountry&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=ITA&amp;ParameterName=AreaOrCountry&amp;ResultFormat=xml</a>
<b>Frequency</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=ITA&amp;ParameterName=Frequency&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=ITA&amp;ParameterName=Frequency&amp;ResultFormat=xml</a>
<b>Year</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=ITA&amp;ParameterName=Year&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=ITA&amp;ParameterName=Year&amp;ResultFormat=xml</a>

### Parameter Details

*Indicator Parameter* – (optional, multiple values allowed)

The Indicator parameter specifies the type of transaction. The Indicator parameter values usually correspond to lines in ITA tables at <https://www.bea.gov/iTable/iTableHtml.cfm?reqid=62&step=2&isuri=1&6210=1>.

Exactly one Indicator parameter value must be provided in all data requests unless exactly one AreaOrCountry parameter value other than “ALL” and “AllCountries” is requested. That is, multiple Indicators can only be specified if a single AreaOrCountry is specified.

*AreaOrCountry Parameter* – (optional, multiple values allowed)

The AreaOrCountry parameter specifies the counterparty area or country of the transactions.

The default parameter value (“AllCountries”) returns the total for all countries, while “All” returns all data available by area and country.

Exactly one AreaOrCountry parameter value must be provided in all data requests unless exactly one Indicator parameter value is requested. This single parameter value may not be either “ALL” or “AllCountries.” That is, a list of countries or the grand total for all countries can only be specified if a single Indicator is specified.

For information on geographic area definitions, see

[https://www.bea.gov/international/bp\\_web/geographic\\_area\\_definitions.cfm](https://www.bea.gov/international/bp_web/geographic_area_definitions.cfm)

*Frequency Parameter* – (optional, multiple values allowed)

3. A – Annual
4. QSA – Quarterly seasonally adjusted
5. QNSA – Quarterly not seasonally adjusted

**Year Parameter** – (optional, multiple values allowed)

The Year parameter specifies the year of the data requested. When quarterly data are requested, all available quarters for the specified year will be returned.

## ITA (International Transactions) Dimensions Elements in Return Data

Parameter Name	Ordinal	Datatype	IsValue	Description
<b>Indicator</b>	1	String	No	The Indicator parameter value of the data item.
<b>AreaOrCountry</b>	2	String	No	The AreaOrCountry parameter value of the data item.
<b>Frequency</b>	3	String	No	The Frequency parameter value of the data item.
<b>Year</b>	4	String	No	The Year parameter value of the data item.
<b>TimeSeriesId</b>	5	String	No	A unique identifier for the time series of the data item.
<b>TimeSeriesDescription</b>	6	String	No	A description of the transactions measured in the data item.
<b>TimePeriod</b>	7	String	No	A string containing the time period for the data item in the form YYYY for annual data and YYYYQn for quarterly data (where n is the quarter digit)
<b>CL_UNIT</b>	8	String	No	A string indicating the base unit of measurement of the data item. For example, “USD” is used when the reported statistic is in U. S. dollars.
<b>UNIT_MULT</b>	9	String	No	An integer representing the base-10 exponent of the multiplier used to interpret the data value. For example “6” refers to millions ( $\text{DataValue} \times 10^6$ ).
<b>DataValue</b>	10	Numeric	No	An integer or decimal value of the statistic. May be blank.

A NoteRef attribute is also included in all data elements and acts as a reference to one of the Notes elements in the returned data. The NoteRef attribute may have multiple values represented by a comma-delimited string. Any NoteRef attribute included in the data is guaranteed to have a corresponding Notes element. The NoteRef attribute may be blank.

## Appendix H – IIP (International Investment Position)

The DataSetName is IIP. This dataset contains data on the U. S. international investment position. BEA's international investment position accounts include the end of period value of accumulated stocks of U. S. financial assets and liabilities. Four parameters are used to retrieve data from the IIP dataset, as follows:

### IIP (International Investment Position) Data Request Parameters

Parameter Name	Type	Description	Required	Multiple Values Accepted	“All” value	Default
<b>TypeOfInvestment</b>	String	Type of investment	No	Yes	All	All
<b>Component</b>	String	Component of changes in position	No	Yes	All	All
<b>Frequency</b>	String	A - Annual, QNSA - Quarterly not seasonally adjusted	No	Yes	All	All
<b>Year</b>	String	Year requested	No	Yes	All	All

### Examples of IIP (International Investment Position) Data Requests

U. S. assets excluding financial derivatives; change in position attributable to price changes for all available years

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&DataSetName=IIP&TypeOfInvestment=FinAssetsExclFinDeriv&Component=ChgPosPrice&Frequency=A&Year=ALL&ResultFormat=xml>

U. S. liabilities to foreign official agencies (quarterly not seasonally adjusted) for 2013

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&DataSetName=IIP&TypeOfInvestment=FinLiabsFoa&Component=Pos&Frequency=QNSA&Year=2013&ResultFormat=xml>

## API Call [GETPARAMETERVALUES] to Obtain a List of Available Values & Descriptions for Each Parameter

*[Details of each are described in the section below. ]*

Parameter Name	Parameter Value List
<b>TypeOfInvestment</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IIP&amp;ParameterName=TypeOfInvestment&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IIP&amp;ParameterName=TypeOfInvestment&amp;ResultFormat=xml</a>
<b>Component</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IIP&amp;ParameterName=Component&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IIP&amp;ParameterName=Component&amp;ResultFormat=xml</a>
<b>Frequency</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IIP&amp;ParameterName=Frequency&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IIP&amp;ParameterName=Frequency&amp;ResultFormat=xml</a>
<b>Year</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IIP&amp;ParameterName=Year&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IIP&amp;ParameterName=Year&amp;ResultFormat=xml</a>

### Parameter Details

**TypeOfInvestment Parameter** – (optional, multiple values allowed)

The TypeOfInvestment parameter specifies the type of investment. The TypeOfInvestment parameter values usually correspond to lines in IIP tables at <https://www.bea.gov/iTable/iTableHtml.cfm?reqid=62&step=5&isuri=1&6210=2>.

Exactly one TypeOfInvestment parameter value must be provided in all data requests unless exactly one Year parameter value other than “ALL” is requested. That is, more than one TypeOfInvestment can only be specified if a single Year is specified.

**Component Parameter** – (optional, multiple values allowed)

The Component parameter specifies either the position (“Pos”) or a component in the change of position from the previous period. For instance, the parameter value “ChgPosTrans” specifies changes due to financial-account transactions.

**Frequency Parameter** – (optional, multiple values allowed)

1. A – Annual
2. QNSA – Quarterly not seasonally adjusted

**Year Parameter** – (optional, multiple values allowed)

The Year parameter specifies the year of the data requested. When quarterly data are requested, all available quarters for the specified year will be returned.

Exactly one Year parameter value must be provided in all data requests unless exactly one TypeOfInvestment parameter value other than “ALL” is requested. That is, more than one Year can only be specified if a single TypeOfInvestment is specified.

## IIP (International Investment Position) Dimensions Elements in Return Data

Parameter Name	Ordinal	Datatype	IsValue	Description
<b>TypeOfInvestment</b>	1	String	No	The TypeOfInvestment parameter value of the data item.
<b>Component</b>	2	String	No	The Component parameter value of the data item.
<b>Frequency</b>	3	String	No	The Frequency parameter value of the data item.
<b>Year</b>	4	String	No	The Year parameter value of the data item.
<b>TimeSeriesId</b>	5	String	No	A unique identifier for the time series of the data item.
<b>TimeSeriesDescription</b>	6	String	No	A description of the transactions measured in the data item.
<b>TimePeriod</b>	7	String	No	A string containing the time period for the data item in the form YYYY for annual data and YYYYQn for quarterly data (where n is the quarter digit)
<b>CL_UNIT</b>	8	String	No	A string indicating the base unit of measurement of the data item. For example, “USD” is used when the reported statistic is in U. S. dollars.
<b>UNIT_MULT</b>	9	String	No	An integer representing the base-10 exponent of the multiplier used to interpret the data value. For example “6” refers to millions ( $\text{DataValue} \times 10^6$ ).
<b>DataValue</b>	10	Numeric	No	An integer or decimal value of the statistic. May be blank.

A NoteRef attribute is also included in all data elements and acts as a reference to one of the Notes elements in the returned data. The NoteRef attribute may have multiple values represented by a comma-delimited string. Any NoteRef attribute included in the data is guaranteed to have a corresponding Notes element. The NoteRef attribute may be blank.



## Appendix I – RegionalIncome (detailed regional income and employment data sets)

### ⚠ NOTE:

In November 2018 the Regional dataset was introduced to replace the RegionalIncome and RegionalProduct datasets. More information may be found at <http://apps.bea.gov/regional/docs/RegionalApi.cfm>

This dataset has been replaced by the Regional dataset. Please see Appendix N.

The RegionalIncome dataset contains income and employment estimates from the Regional Economic Accounts by state, county, and metropolitan area.

### RegionalIncome Request Parameters

#### Method=GetData

Parameter Name	Type	Description	Required	Multiple Values Accepted	“All” value*	Default
<b>TableName</b>	String	Published table name	Yes	No		
<b>LineCode</b>	Integer	Line code in table	Yes	No		
<b>GeoFips</b>	String	The state, county or MSA code	Yes	Yes	STATE COUNTY MSA MIC PORT DIV CSA PO code	
<b>Year</b>	String	Year requested	No	Yes	ALL LAST5 LAST10	LAST5

### Parameter Details for GetData method

*TableName* parameter – (required, single value)

TableName specifies a published table from the regional income accounts. Exactly one TableName must be provided.

TableName	Description	Years	Areas
CA1	Personal Income Summary: Personal Income, Population, Per Capita Personal Income	1969-->	All
CA25	Total Full-Time and Part-Time Employment by SIC Industry	1969-2000	All
CA25N	Total Full-Time and Part-Time Employment by NAICS Industry	2001-2014	All
CA30	Economic Profile	1969→	All
CA35	Personal Current Transfer Receipts	1969→	All
CA4	Personal Income and Employment by Major Component	1969→	All
CA45	Farm Income and Expenses	1969→	All
CA5	Personal Income by Major Component and Earnings by SIC Industry	1969-2000	All
CA5N	Personal Income by Major Component and Earnings by NAICS Industry	2001→	All
CA6	Compensation of Employees by SIC Industry	1998-2000	All
CA6N	Compensation of Employees by NAICS Industry	2001→	All
CA91	Gross Flow of Earnings	1990→	Counties
IRPD1	Implicit Regional Price Deflator by state	2008→	States
IRPD2	Implicit Regional Price Deflator by MSA and state portion	2008→	MSAs, Portions
RPI1	Real Personal Income by state	2008→	States, US
RPI2	Real Personal Income by MSA and state portion	2008→	MSA, Portions
RPP1	Regional Price Parities by state	2008→	States, US
RPP2	Regional Price Parities by MSA and state portion	2008→	MSAs, Portions

SA1	Personal Income Summary: Personal Income, Population, Per Capita Personal Income	1929→	States, Regions, US
SA25	Total Full-Time and Part-Time Employment by SIC Industry	1969-2001	States, Regions, US
SA25N	Total Full-Time and Part-Time Employment by NAICS Industry	1998→	States, Regions, US
SA27	Full-Time and Part-Time Wage and Salary Employment by SIC Industry	1969-2001	States, Regions, US
SA27N	Full-Time and Part-Time Wage and Salary Employment by NAICS Industry	1998→	States, Regions, US
SA30	Economic Profile	1958→	States, Regions, US
SA35	Personal Current Transfer Receipts	1929→	States, Regions, US
SA4	Personal Income and Employment by Major Component	1929→	States, Regions, US
SA40	Property Income	1958→	States, Regions, US
SA45	Farm Income and Expenses	1969→	States, Regions, US
SA5	Personal Income by Major Component and Earnings by SIC Industry	1958-2001	States, Regions, US
SA50	Personal Current Taxes	1948→	States, Regions, US
SA51	Disposable Personal Income Summary: Disposable Personal Income, Population, and Per Capita Disposable Personal Income	1948→	States, Regions, US
SA5H	Personal Income by Major Component and Earnings by Industry (Historical)	1929-1957	States, Regions, US
SA5N	Personal Income by Major Component and Earnings by NAICS Industry	1998→	States, Regions, US

SA6	Compensation of Employees by SIC Industry	1958-2001	States, Regions, US
SA6N	Compensation of Employees by NAICS Industry	1998→	States, Regions, US
SA7	Wages and Salaries by SIC Industry	1958-2001	States, Regions, US
SA7H	Wages and Salaries by Industry (Historical)	1929-1957	States, Regions, US
SA7N	Wages and Salaries by NAICS Industry	1998→	States, Regions, US
SQ1	Personal Income Summary: Personal Income, Population, Per Capita Personal Income	1948→	States, Regions, US
SQ35	Personal Current Transfer Receipts	1948→	States, Regions, US
SQ4	Personal Income by Major Component	1948→	States, Regions, US
SQ5	Personal Income by Major Component and Earnings by SIC Industry	1958-2001	States, Regions, US
SQ5H	Personal Income by Major Component and Earnings by Industry (Historical)	1948-1957	States, Regions, US
SQ5N	Personal Income by Major Component and Earnings by NAICS Industry	1998→	States, Regions, US
SQ6	Compensation of Employees by SIC Industry	1958-2001	States, Regions, US
SQ6N	Compensation of Employees by NAICS Industry	1998→	States, Regions, US
SQ7	Wages and Salaries by SIC Industry	1958-2001	States, Regions, US
SQ7H	Wages and Salaries by Industry (Historical)	1948-1957	States, Regions, US

SQ7N	Wages and Salaries by NAICS Industry	1998→	States, Regions, US
ACEmp	Total Employment (Arts and Culture Satellite Account)	2001→	States
ACComp	Total Compensation (Arts and Culture Satellite Account)	2001→	States
ACEmpRatio	Arts Employment Ratio	2001→	States
ACCompRatio	Arts Compensation Ratio	2001→	States
ACArtsEmp	ACPSA Employment	2001→	States
ACArtsComp	ACPSA Compensation	2001→	States
ACEmpLQ	Arts Employment Location Quotient	2001→	States
ACCompLQ	Arts Compensation Location Quotient	2001→	States

**LineCode parameter** – (required, single value)

LineCode corresponds to the statistic in a table. Exactly one LineCode must be provided.

**GeoFips parameter** – (required, multiple value)

GeoFips specifies geography. It can be all states (STATE), all counties (COUNTY), all Metropolitan Statistical Areas (MSA), all Micropolitan Statistical Areas (MIC), all Metropolitan Divisions (DIV), all Combined Statistical Areas (CSA), all metropolitan/nonmetropolitan portions (PORT), or state post office abbreviation for all counties in one state (e.g. NY). It can also be a list of ANSI state-county codes or metropolitan area codes. For example, the counties in Connecticut and Delaware—

09001,09003,09005,09007,09009,09011,09013,09015,10001,10003,10005

State, county, and metropolitan statistical area FIPS codes can be obtained from Census at

<https://www.census.gov/geo/www/ansi/ansi.html>. A comprehensive list of MSAs and their component counties can be accessed at <https://apps.bea.gov/regional/docs/msalist.cfm>.

**Year parameter** – (optional, multiple value)

Year is either a list of comma delimited years, LAST5, LAST10, or ALL. Year will default to LAST5 years if the parameter is not specified.

## Errors

An invalid parameter value will result in an error code of 40, “The dataset requested requires parameters that were missing from the request” plus a detailed message that explains the invalid value(s) entered.

Examples:

- For Invalid TableName a detailed message with “TableName entered is invalid” will display.
- When two or more parameter values are incompatible a detailed message will display “TableName entered is incompatible with the entered GeoFips, LineCode and Year”.

## Examples of RegionalIncome Getdata method Requests

Personal income for 2012 and 2013 for all counties, in JSON format

<https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&method=GetData&datasetname=RegionalIncome&TableName=CA1&LineCode=1&Year=2012,2013&GeoFips=COUNTY&ResultFormat=json>

Real per capita personal income for all states, all years, in XML format

<https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&method=GetData&datasetname=RegionalIncome&TableName=RPI1&LineCode=2&Year=ALL&GeoFips=STATE&ResultFormat=xml>

## Method=GetParameterValuesFiltered

API Call [GETPARAMETERVALUESFILTERED] to Obtain a List of Available Values & Descriptions for Each Parameter, Filtered by Another Parameter *[Examples below]*

Target Parameter Name	Filtered Parameter Names	Parameter Value List	Explanation
<b>Year</b>	<b>TableName</b>	<a href="https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalIncome&amp;TargetParameter=Year&amp;TableName=CA5N,CA25N&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalIncome&amp;TargetParameter=Year&amp;TableName=CA5N,CA25N&amp;ResultFormat=xml</a>	List Years for given TableNames
<b>GeoFips</b>	<b>TableName LineCode</b>	<a href="https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalIncome&amp;TargetParameter=GeoFips&amp;TableName=CA4&amp;LineCode=10&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalIncome&amp;TargetParameter=GeoFips&amp;TableName=CA4&amp;LineCode=10&amp;ResultFormat=xml</a>	List of GeoFips for a given TableName and LineCode
<b>Table Name</b>	<b>Year Geofips</b>	<a href="https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalIncome&amp;TargetParameter=TableName&amp;GeoFips=00000&amp;Year=2014&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalIncome&amp;TargetParameter=TableName&amp;GeoFips=00000&amp;Year=2014&amp;ResultFormat=xml</a>	List of TableNames for a given Year and GeoFips

<b>LineCode</b>	<b>TableName</b>	<a href="https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalIncome&amp;TargetParameter=LineCode&amp;TableName=SA25N&amp;ResultFormat=json">https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalIncome&amp;TargetParameter=LineCode&amp;TableName=SA25N&amp;ResultFormat=json</a>	List of LineCodes for a TableName
-----------------	------------------	---	--------------------------------------

## Parameter Details for GetParameterValuesFiltered method when used as filtered parameters

**TableName parameter** – (optional, single or Multiple values)

TableName specifies a published table from the regional income accounts. Multiple comma-delimited TableName values can be provided.

**LineCode parameter** – (optional, single or multiple values)

LineCode corresponds to the statistic in a table. Multiple comma-delimited LineCode values can be provided. The available LineCodes are queried using the GetParameterValuesFiltered method. For example:

<https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&method=GetParameterValuesFiltered&datasetname=RegionalIncome&TargetParameter=LineCode&TableName=SA25N&ResultFormat=json>

**GeoFips parameter** – (optional, single or multiple values)

GeoFips specifies geography. It can be all states (STATE), all counties (COUNTY), all Metropolitan Statistical Areas (MSA), or state post office abbreviation for all counties in one state (e.g. NY). It can also be a list of ANSI state-county codes or metropolitan area codes. For example, the counties in Connecticut and Delaware–

09001,09003,09005,09007,09009,09011,09013,09015,10001,10003,10005

State, county, and metropolitan statistical area FIPS codes can be obtained from Census at

<https://www.census.gov/geo/www/ansi/ansi.html>. A comprehensive list of MSAs and their component counties can be accessed at <https://apps.bea.gov/regional/docs/msalist.cfm>.

**Year parameter** – (optional, multiple value)

Year is either a single value, a list of comma-delimited years, or ALL

### Errors

An invalid TableName LineCode, GeoFips or Year will result in an error code of 203, “No parameter values match the filtered list requested” plus a detailed message that explains the invalid value(s) entered.

Examples:

- For Invalid LineCode a detailed message with “LineCode entered is invalid” will display.
- When there are no available GeoFips data for the entered LineCode a detailed message with “Values of GeoFips and LineCode are incompatible” will display.

### Additional information

Explanation of the estimates, including a schedule of the release of new regional data and Income and Product methodologies can be found on our website: <https://www.bea.gov>. Definitions of the estimates can be accessed

at our glossary of regional definitions, at <https://apps.bea.gov/regional/definitions/>.



## Appendix J – RegionalProduct (detailed state and MSA product data sets)

### NOTE:

In November 2018 the Regional dataset was introduced to replace the RegionalIncome and RegionalProduct datasets. More information may be found at <http://apps.bea.gov/regional/docs/RegionalApi.cfm>

This dataset has been replaced by the Regional dataset. Please see Appendix N.

The RegionalProduct dataset contains Gross Domestic Product (GDP) estimates from the Regional Economic Accounts by state and metropolitan area.

### RegionalProduct Request Parameters

#### Method=GetData

Parameter Name	Type	Description	Required	Multiple Values Accepted	“All” value	Default
Component	String	Component name	Yes	No		
IndustryId	Integer	Industry code of the Component	Yes	No		
GeoFips	String	The state or MSA code	Yes	Yes	STATE MSA	
Year	String	Year requested	No	Yes	ALL LAST5 LAST10	LAST5

### Parameter Details for GetData method

#### *Component parameter* – (required, single value)

Component specifies a published table from the regional product accounts. Exactly one Component must be provided.

#### *IndustryId parameter* – (required, single value)

IndustryId is an integer used to specify which industry is being requested for a given Component. Exactly one IndustryId must be provided.

#### *GeoFips parameter* – (required, multiple value)

GeoFips specifies geography. It can be all states (STATE) or all Metropolitan Statistical Areas (MSA) or state post office abbreviation for all counties in one state (e.g. NY).. It can also be a list of ANSI state-county codes or metropolitan area codes.

State and metropolitan statistical area FIPS codes can be obtained from Census at

<https://www.census.gov/geo/www/ansi/ansi.html>. A comprehensive list of MSAs and their component counties can be accessed here <https://www.bea.gov/regional/docs/msalist.cfm>.

*Year parameter* – (optional, multiple value)

Year is either a single value, list of comma delimited years, LAST5, LAST10, or ALL. Year will default to all available years if the parameter is not specified.

## Examples of RegionalProduct Requests

Real GDP for all years for all MSAs, in JSON format

[https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&method=GetData&datasetname=RegionalProduct&Component=RGDP\\_MAN&IndustryId=1&Year=ALL&GeoFips=MSA&ResultFormat=json](https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&method=GetData&datasetname=RegionalProduct&Component=RGDP_MAN&IndustryId=1&Year=ALL&GeoFips=MSA&ResultFormat=json)

GDP for 2012 and 2013 for selected Southeast states, for the Retail Trade industry, in XML format

[https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&method=GetData&datasetname=RegionalProduct&Component=GDP\\_SAN&IndustryId=35&Year=2012,2013&GeoFips=01000,05000,12000,13000,21000,22000,28000,37000,45000,47000,51000,54000&ResultFormat=XML](https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&method=GetData&datasetname=RegionalProduct&Component=GDP_SAN&IndustryId=35&Year=2012,2013&GeoFips=01000,05000,12000,13000,21000,22000,28000,37000,45000,47000,51000,54000&ResultFormat=XML)

## Method=GetParameterValuesFiltered

API Call [GETPARAMETERVALUESFILTERED] to Obtain a List of Available Values & Descriptions for Each Parameter, Filtered by Another Parameter *[Examples below]*

Target Parameter Name	Filtered Parameter Names	Parameter Value List Explanation	
Year	Component	<a href="https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalProduct&amp;TargetParameter=Year&amp;Component=PCRGDP_SAN&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalProduct&amp;TargetParameter=Year&amp;Component=PCRGDP_SAN&amp;ResultFormat=xml</a>	List Years for given Component
GeoFips	Component IndustryId	<a href="https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalProduct&amp;TargetParameter=GeoFips&amp;Component=GDP_SAN&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalProduct&amp;TargetParameter=GeoFips&amp;Component=GDP_SAN&amp;ResultFormat=xml</a>	List of GeoFips for a given Component

<b>Component</b>	<b>Year</b>	<b>GeoFips</b>	<a href="https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalProduct&amp;TargetParameter=Component&amp;GeoFips=00000&amp;Year=201000">https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalProduct&amp;TargetParameter=Component&amp;GeoFips=00000&amp;Year=201000</a>	List of Components for a given Year and GeoFips
<b>IndustryId</b>	<b>Component</b>		<a href="https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalProduct&amp;TargetParameter=IndustryId&amp;Component=GDP_SAS&amp;resultFormat=xml">https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=RegionalProduct&amp;TargetParameter=IndustryId&amp;Component=GDP_SAS&amp;resultFormat=xml</a>	List of IndustryIds for a Component

## Parameter Details for GetParameterValuesFiltered method when used as filtered parameters

*Component parameter* – (optional, single or Multiple values)

Component specifies a published table from the regional product accounts. Multiple comma-delimited Component values can be provided.

Component	Series	Description	Years
GDP_SQN	State Quarterly NAICS	GDP in current dollars	2005→
QI_SQN	State Quarterly NAICS	Quantity indexes for real GDP	2005→
RGDP_SQN	State Quarterly NAICS	Real GDP in chained dollars	2005→
GDP_MAN	Metro Annual NAICS	GDP in current dollars	2001→
PCRGDP_MAN	Metro Annual NAICS	Per capita real GDP	2001→
QI_MAN	Metro Annual NAICS	Quantity indexes for real GDP	2001→
RGDP_MAN	Metro Annual NAICS	Real GDP in chained dollars	2001→
COMP_SAN	State Annual NAICS	Compensation of employees	1997→
GDP_SAN	State Annual NAICS	GDP in current dollars	1997→
GOS_SAN	State Annual NAICS	Gross operating surplus	1997→
PCRGDP_SAN	State Annual NAICS	Per capita real GDP	1997→

QI_SAN	State Annual NAICS	Quantity indexes for real GDP	1997→
RGDP_SAN	State Annual NAICS	Real GDP in chained dollars	1997→
SUBS_SAN	State Annual NAICS	Subsidies	1997→
TOPI_SAN	State Annual NAICS	TOPI	1997→
TOPILS_SAN	State Annual NAICS	TOPI less subsidies	1997→
GDP_SAS	State Annual SIC	Gross domestic product (GDP) by state	1963-1997
TOPILS_SAS	State Annual SIC	Taxes on production and imports less subsidies	1963-1997
COMP_SAS	State Annual SIC	Compensation of employees	1963-1997
SUBS_SAS	State Annual SIC	Subsidies	1963-1997
TOPI_SAS	State Annual SIC	Taxes on production and imports	1963-1997
GOS_SAS	State Annual SIC	Gross operating surplus	1963-1997
QI_SAS	State Annual SIC	Quantity indexes for real GDP by state	1963-1997
RGDP_SAS	State Annual SIC	Real GDP by state	1963-1997
PCRGDP_SAS	State Annual SIC	Per capita real GDP by state	1963-1997
PCE_SAN	State Annual	Personal Consumption Expenditures (PCE) by state	1997→
PCPCE_SAN	State Annual	Per capita Personal Consumption Expenditures (PCE) by state	1997→

**IndustryId parameter** – (optional, single or Multiple values)

IndustryId is an integer used to specify which industry is being requested for a given Component. Multiple comma-delimited IndustryId values can be provided.

**GeoFips parameter**– (optional, single or multiple values)

GeoFips specifies geography. It can be all states (STATE) or all Metropolitan Statistical Areas (MSA) or state post office abbreviation for one state (e.g. NY). It can also be a list of ANSI state-county codes or metropolitan area codes.

State and metropolitan statistical area FIPS codes can be obtained from Census at <https://www.census.gov/geo/www/ansi/ansi.html>. A comprehensive list of MSAs and their component counties can be accessed here <https://apps.bea.gov/regional/docs/msalist.cfm>.

**Year parameter** – (optional, single or multiple value)

Year is a single value, list of years, or ALL.

### *Errors*

An invalid Component or IndustryId , GeoFips or Year will result in an error code of 203, “No parameter values match the filtered list requested” plus a detailed message that explains the invalid value(s) entered.

Examples:

- For Invalid Component a detailed message with “Component entered is invalid” will display.
- When there are no available GeoFips data for the entered Component, a detailed message with “Values of GeoFips and Component are incompatible” will display.

### *Additional information*

Explanation of the estimates, including a schedule of the release of new regional data and Income and Product methodologies can be found on our website: <https://www.bea.gov>. Definitions of the estimates can be accessed at our glossary of regional definitions, at <https://apps.bea.gov/regional/definitions/>.

## Appendix K – Input-Output Statistics (InputOutput)

The Input-Output Statistics are contained within a dataset called InputOutput. BEA's industry accounts are used extensively by policymakers and businesses to understand industry interactions, productivity trends, and the changing structure of the U.S. economy. The input-output accounts provide a detailed view of the interrelationships between U.S. producers and users. The Input-Output dataset contains Make Tables, Use Tables, and Direct and Total Requirements tables.

### InputOutput Data Request

Parameter Name	Type	Description	Required	Multiple Values Accepted	“All” value	Default
TableID	Integer	The unique Input Output table identifier	Yes	Yes	N/A	N/A
<u>Year</u>	Integer	List of year(s) of data to retrieve	Yes	Yes	ALL	N/A

### Examples of InputOutput Data Requests

Data from The Use of Commodities by Industries, Before Redefinitions (Producer’s Prices) sector level table for years 2010, 2011, and 2012:

<https://apps.bea.gov/api/data/?&UserID=%Your-36Character-Key&method=GetData&DataSetName=InputOutput&Year=2010,2011,2012,2013&tableID=2&&ResultFormat=xm>  
[ml](#)

Data for 2007 from The Make of Commodities by Industries, Before Redefinitions sector and summary level tables:

<https://apps.bea.gov/api/data/?&UserID=%Your-36Character-Key&method=GetData&DataSetName=InputOutput&Year=2007&tableID=46,47&&ResultFormat=xml>

### API Call [GETPARAMETERVALUES] to Obtain a List of Available Values & Descriptions for Each Parameter

*[Details of each are described in the section below.]*

Parameter Name	Parameter Value List
<u>TableID</u>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=%Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=InputOutput&amp;ParameterName=TableID&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=%Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=InputOutput&amp;ParameterName=TableID&amp;ResultFormat=xml</a>

Year	<a href="https://apps.bea.gov/api/data/?&amp;UserID=%Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=InputOutput&amp;ParameterName=Year&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=%Your-36Character-Key &amp;method=GetParameterValues&amp;DataSetName=InputOutput&amp;ParameterName=Year&amp;ResultFormat=xml</a>
------	--

## Parameter Details

**TableID Parameter** (Required, multiple values accepted, no default value)

- The TableID parameter is a unique table identifier. This parameter is required to query data and does accept multiple comma separated values.

**Year Parameter** (Required, multiple values accepted, no default value, 'ALL' for all years)

- The Year parameter indicates what periods of data are requested. This parameter is required to query data and does accept multiple comma separated values. Use the keyword 'ALL' to return all periods of data.

## General Use

- Data will be returned for all data cells that fit the requested criteria. If the request contains parameter values requesting data for which only part of a set is available, only the data matching the criteria will be returned. For example, requesting ALL Years Use Tables evaluated in Purchasers Value will return data for only 2007 because these tables are only published in benchmark years. Blanks will not be returned for missing data.
- If no data fit the selected criteria the user will receive the following error:

```
<Error APIErrorCode="205" APIErrorDescription="Error retrieving Input-Output data.">  
  <ErrorDetail Description="No data exist for selected criteria" />  
</Error>
```

## Appendix L – Underlying Gross Domestic Product by Industry (UnderlyingGDPbyIndustry)

The underlying gross domestic product by industry data are contained within a dataset called UnderlyingGDPbyIndustry. BEA's industry accounts are used extensively by policymakers and businesses to understand industry interactions, productivity trends, and the changing structure of the U.S. economy. The underlying GDP-by-industry dataset includes data in both current and chained (real) dollars. The dataset contains estimates for value added, gross output, and intermediate input statistics. This dataset is structurally similar to the GDPbyIndustry dataset (Appendix F), but contains additional industry detail.

**Please Note:** Cautionary Note on use of underlying detail tables -- The Bureau of Economic Analysis does not include these detailed estimates in the published tables because their quality is significantly less than that of the higher level aggregates in which they are included.

### Underlying Gross Domestic Product by Industry (UnderlyingGDPbyIndustry) Data Request

Parameter Name	Type	Description	Required	Multiple Values Accepted	"All" value	Default
TableID	Integer	The unique GDP by Industry table identifier (ALL for All)	Yes	Yes	ALL	N/A
<u>Frequency</u>	String	Q-Quarterly	Yes	Yes	Q	N/A
<u>Year</u>	Integer	List of year(s) of data to retrieve (ALL for All)	Yes	Yes	ALL	N/A
Industry	String	List of industries to retrieve (ALL for All)	Yes	Yes	ALL	N/A

### Examples of Underlying GDP by Industry (UnderlyingGDPbyIndustry) Data Requests

Quarterly Value Added by Industry data for all industries for years 2012 and 2013:

<https://apps.bea.gov/api/data/?&UserID=%20Your-36Character-Key&method=GetData&DataSetName=underlyingGDPbyIndustry&Year=2013,2012&Industry=ALL&tableID=1&Frequency=Q&ResultFormat=xml>

All quarterly data in all tables for the Agriculture industry in 2012.

<https://apps.bea.gov/api/data/?&UserID=%20Your-36Character-Key&method=GetData&DataSetName=underlyingGDPbyIndustry&Year=2012&Industry=11&tableID=ALL&Frequency=Q&ResultFormat=xml>



## API Call [GETPARAMETERVALUES] to Obtain a List of Available Values & Descriptions for Each Parameter

*[Details of each are described in the section below.]*

Parameter Name	Parameter Value List
<b>TableID</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=underlyingGDPbyIndustry&amp;ParameterName=TableID&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=underlyingGDPbyIndustry&amp;ParameterName=TableID&amp;ResultFormat=xml</a>
<b>Frequency</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=underlyingGDPbyIndustry&amp;ParameterName=Frequency&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=underlyingGDPbyIndustry&amp;ParameterName=Frequency&amp;ResultFormat=xml</a>
<b>Year</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=underlyingGDPbyIndustry&amp;ParameterName=Year&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=underlyingGDPbyIndustry&amp;ParameterName=Year&amp;ResultFormat=xml</a>
<b>Industry</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=underlyingGDPbyIndustry&amp;ParameterName=Industry&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=%20Your-36Character-Key%20Y&amp;method=GetParameterValues&amp;DataSetName=underlyingGDPbyIndustry&amp;ParameterName=Industry&amp;ResultFormat=xml</a>

### Parameter Details

**TableID Parameter** (Required, multiple values accepted, no default value, 'ALL' for all tables)

- The TableID parameter is a unique table identifier. This parameter is required to query data and does accept multiple comma separated values. If all tables are required, use the 'ALL' keyword.
- The Descr in the GetParameterValues result will contain a (Q) indicating that the table is published quarterly. No Annual data is available in the underlying GDP by industry dataset

**Frequency Parameter** (Required, multiple values accepted, no default value)

- The Frequency parameter indicates whether annual or quarterly data are to be returned. This parameter is required to query data and does accept multiple comma separated values.
- All tables are published quarterly (Frequency = Q). No Annual data is currently available in the underlying GDP by industry dataset
- If a data request is submitted for annual data then the user will receive the following error:

```
<Error APIErrorCode="206" APIErrorDescription="Error retrieving GDP by Industry data.">
  <ErrorDetail Description="No annual data available in Underlying GDP by Industry:A" />
</Error>
```

**Year Parameter** (Required, multiple values accepted, no default value, 'ALL' for all years)

- The Year parameter indicates what periods of data are requested. This parameter is required to query data and does accept multiple comma separated values. Use the keyword 'ALL' to return all periods of data.
- All available quarters for a year will be returned.

- Underlying GDP by industry data publications begin in 2012 to present
- If a data request is submitted for quarterly data before the earliest estimate period the user will receive one of the following errors:

```
<Error APIErrorDescription="Error retrieving GDP by Industry data." APIErrorCode="206">
  <ErrorDetail Description="Invalid year: 2010"/>
</Error>
```

**Industry Parameter** (Required, multiple values accepted, no default value, 'ALL' for all industries)

- The Industry parameter indicates what periods of data are requested. This parameter is required to query data and does accept multiple comma separated values. Use the keyword 'ALL' to return all industries.
- The Descr in the GetParameterValues result will contain (Q) if the industry is published quarterly and (A) indicating that the industry is also published annually.
- If a data request is submitted for an industry that is not published in the requested tables the user will receive the following error:

```
<Error APIErrorCode="206" APIErrorDescription="Error retrieving GDP by Industry data.">
  <ErrorDetail Description="Invalid industry: 11" />
</Error>
```

### General Use

- Data will be returned for all data cells that fit the requested criteria. If the request contains parameter values requesting data for which only part of a set is available, only the data matching the criteria will be returned. For example, requesting 1,101 TableIDs for 2012 will return only table 1 data because the tableID 101 does not exist. Blanks will not be returned for missing data.
- If no data fit the selected criteria the user will receive the following error:

```
<Error APIErrorCode="206" APIErrorDescription="Error retrieving GDP by Industry data.">
  <ErrorDetail Description="No data exist for selected criteria" />
</Error>
```

## Appendix M – IntlServTrade (International Services Trade)

The DataSetName is IntlServTrade. This dataset contains annual data on U.S. international trade in services. These data are updated each October to reflect the International Transactions Accounts annual update released in June. BEA's statistics on services supplied through affiliates by multinational enterprises are not included in this dataset. Five parameters are used to retrieve data from the IntlServTrade dataset, as follows:

### IntlServTrade (International Services Trade) Data Request Parameters

Parameter Name	Type	Description	Required	Multiple Values Accepted	"All" value	Default
<b>TypeOfService</b>	String	The type of service requested	No	Yes	All	All
<b>TradeDirection</b>	String	The trade direction requested	No	Yes	All	All
<b>Affiliation</b>	String	The affiliation requested	No	Yes	All	All
<b>AreaOrCountry</b>	String	The area or country requested	No	Yes	All	AllCountries
<b>Year</b>	String	The year requested	No	Yes	All	All

### Examples of IntlServTrade (International Services Trade) Data Requests

Imports of services from Germany for 2014 and 2015

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&DataSetName=IntlServTrade&TypeOfService=AllServiceTypes&TradeDirection=Imports&Affiliation=AllAffiliations&AreaOrCountry=Germany&Year=2014,2015&ResultFormat=xml>

Exports of telecommunications services by U.S. parents to their foreign affiliates for all years

<https://apps.bea.gov/api/data/?&UserID=Your-36Character-Key&method=GetData&DataSetName=IntlServTrade&TypeOfService=Telecom&TradeDirection=Exports&Affiliation=UsParents&AreaOrCountry=AllCountries&Year=All&ResultFormat=xml>

## API Call [GETPARAMETERVALUES] to Obtain a List of Available Values & Descriptions for Each Parameter

*[Details of each are described in the section below.]*

Parameter Name	Parameter Value List
<b>TypeOfService</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IntlServTrade&amp;ParameterName=TypeOfService&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IntlServTrade&amp;ParameterName=TypeOfService&amp;ResultFormat=xml</a>
<b>TradeDirection</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IntlServTrade&amp;ParameterName=TradeDirection&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IntlServTrade&amp;ParameterName=TradeDirection&amp;ResultFormat=xml</a>
<b>Affiliation</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IntlServTrade&amp;ParameterName=Affiliation&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IntlServTrade&amp;ParameterName=Affiliation&amp;ResultFormat=xml</a>
<b>AreaOrCountry</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IntlServTrade&amp;ParameterName=AreaOrCountry&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IntlServTrade&amp;ParameterName=AreaOrCountry&amp;ResultFormat=xml</a>
<b>Year</b>	<a href="https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IntlServTrade&amp;ParameterName=Year&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?&amp;UserID=Your-36Character-Key&amp;method=GetParameterValues&amp;DataSetName=IntlServTrade&amp;ParameterName=Year&amp;ResultFormat=xml</a>

### Parameter Details

#### *TypeOfService Parameter* (optional, multiple values allowed)

The TypeOfService parameter specifies the type of service being traded (e.g. travel, transport, or insurance services).

Exactly one TypeOfService parameter value other than “All” must be provided in all data requests unless exactly one AreaOrCountry parameter value other than “All” is requested. That is, multiple Indicators can only be specified if a single AreaOrCountry parameter is specified.

#### *TradeDirection Parameter* (optional, multiple values allowed)

The TradeDirection parameter specifies the trade direction of the services transactions. There are four valid parameter values other than “All”:

1. Exports – Exports
2. Imports – Imports
3. Balance – Balance (exports less imports)
4. SupplementalIns – Supplemental detail on insurance transactions

#### *Affiliation Parameter* (optional, multiple values allowed)

The Affiliation parameter specifies the trade direction for the services transactions. There are five valid parameter values other than “All”:

1. AllAffiliations – The total for all trade, whether affiliated or unaffiliated

2. Unaffiliated – Unaffiliated trade
3. Affiliated – Affiliated trade
4. UsParents – U.S. parents’ trade with their foreign affiliates
5. UsAffiliates – U.S. affiliates’ trade with their foreign parent groups

**AreaOrCountry Parameter** (optional, multiple values allowed)

The AreaOrCountry parameter specifies the counterparty area or country of the services transactions. The default parameter value (“AllCountries”) returns the total for all countries, while “All” returns all data available by area and country.

Exactly one AreaOrCountry parameter value must be provided in all data requests unless exactly one TypeOfService parameter value other than “All” is requested. That is, a list of countries can only be specified if a single TypeOfService is specified.

For information on geographic area definitions, see

[https://www.bea.gov/international/bp\\_web/geographic\\_area\\_definitions.pdf](https://www.bea.gov/international/bp_web/geographic_area_definitions.pdf)

**Year Parameter** (optional, multiple values allowed)

The Year parameter specifies the year of the data requested.

## IntlServTrade (International Services Trade) Dimensions Elements in Return Data

Parameter Name	Ordinal	Datatype	IsValue	Description
<b>TypeOfService</b>	1	String	No	The TypeOfService parameter value of the data item.
<b>TradeDirection</b>	2	String	No	The TradeDirection parameter value of the data item.
<b>Affiliation</b>	3	String	No	The Affiliation parameter value of the data item.
<b>AreaOrCountry</b>	4	String	No	The AreaOrCountry parameter value of the data item.
<b>Year</b>	5	String	No	The Year parameter value of the data item.
<b>TimeSeriesId</b>	6	String	No	A unique identifier for the time series of the data item.
<b>TimeSeriesDescription</b>	7	String	No	A description of the transactions measured in the data item.
<b>TimePeriod</b>	8	String	No	A string containing the time period for the data item in the form YYYY for annual data
<b>CL_UNIT</b>	9	String	No	A string indicating the base unit of measurement of the data item. For example, “USD” is used when the reported statistic is in U.S. dollars.
<b>UNIT_MULT</b>	10	String	No	An integer representing the base-10 exponent of the multiplier used to interpret the data value. For example “6” refers to millions (DataValue × 10 <sup>6</sup> ).
<b>DataValue</b>	11	Numeric	No	An integer or decimal value of the statistic. May be blank.

A NoteRef attribute is also included in all data elements and acts as a reference to one of the Notes elements in the returned data. The NoteRef attribute may have multiple values represented by a comma-delimited string. Any NoteRef attribute included in the data is guaranteed to have a corresponding Notes element. The NoteRef attribute may be blank.

## Appendix N – Regional (income, product, and employment by state and local area)

The Regional dataset contains income and employment estimates from the Regional Economic Accounts by state, county, and metropolitan area. All data accessible through the Regional Interactive Tables on [bea.gov](http://apps.bea.gov/regional/docs/RegionalApi.cfm) are available through this dataset. The Regional dataset replaces the RegionalIncome and RegionalProduct datasets. Additional information may be found at <http://apps.bea.gov/regional/docs/RegionalApi.cfm>

### Regional Request Parameters

#### Method=GetData

Parameter Name	Type	Description	Required	Multiple Values Accepted	“All” value*	Default
TableName	String	Published table name	Yes	No		
LineCode	Integer	Line code in table	Yes	No		
GeoFips	String	The state, county or MSA code	Yes	Yes	STATE COUNTY MSA MIC PORT DIV CSA PO code	
Year	String	Year requested	No	Yes	ALL LAST5 LAST10	LAST5

### Parameter Details for GetData method

#### *TableName* parameter – (required, single value)

TableName specifies a published table from the regional accounts. Exactly one TableName must be provided.

TableName	Description	Years	Main Areas
CAEMP25N	Total Full-Time and Part-Time Employment by NAICS Industry	2001→	Counties, Metros
CAEMP25S	Total Full-Time and Part-Time Employment by SIC Industry	1969-2000	Counties,

				Metros
CAINC1	Personal Income Summary: Personal Income, Population, Per Capita Personal Income	1969→		Counties
CAINC30	Economic Profile	1969→		Counties
CAINC35	Personal Current Transfer Receipts	1969→		Counties, Metros
CAINC4	Personal Income and Employment by Major Component	1969→		Counties
CAINC45	Farm Income and Expenses	1969→		Counties, Metros
CAINC5N	Personal Income by Major Component and Earnings by NAICS Industry	2001→		Counties, Metros
CAINC5S	Personal Income by Major Component and Earnings by SIC Industry	1969-2000		Counties, Metros
CAINC6N	Compensation of Employees by NAICS Industry	2001→		Counties, Metros
CAINC6S	Compensation of Employees by SIC Industry	1998-2000		Counties, Metros
CAINC91	Gross Flow of Earnings	1990→		Counties
MAGDP10	Per capita real GDP by metropolitan area	2001→		MSAs
MAGDP2	Gross domestic product (GDP) by metropolitan area	2001→		MSAs
MAGDP8	Quantity indexes for real GDP by metropolitan area (2009=100.0)	2001→		MSAs
MAGDP9	Real GDP by metropolitan area	2001→		MSAs
MAINC1	Personal Income Summary: Personal Income, Population, Per Capita Personal Income	1969→		MSAs
MAINC30	Economic Profile	1969→		MSAs
MAINC4	Personal Income and Employment by Major Component	1969→		MSAs
MAIRPD	Implicit Price Deflators by MSA	2008→		MSAs
MARPI	Real Personal Income by MSA	2008→		MSAs



MARPP	Regional Price Parities by MSA	2008→	MSAs
PAIRPD	Implicit Price Deflators by Portion	2008→	State portions
PARPI	Real Personal Income by Portion	2008→	State portions
PARPP	Regional Price Parities by Portion	2008→	State portions
SAEMP25N	Total Full-Time and Part-Time Employment by NAICS Industry	1998→	States
SAEMP25S	Total Full-Time and Part-Time Employment by SIC Industry	1969-2001	States
SAEMP27N	Full-Time and Part-Time Wage and Salary Employment by NAICS Industry	1998→	States
SAEMP27S	Full-Time and Part-Time Wage and Salary Employment by SIC Industry	1969-2001	States
SAEXP1	Total personal consumption expenditures (PCE) by state	1998→	States
SAEXP2	Per capita personal consumption expenditures (PCE) by state	1998→	States
SAGDP10N	Per capita real GDP by state	1997→	States
SAGDP10S	Per capita real GDP by state	1963-1997	States
SAGDP11N	Contributions to percent change in real GDP	1998→	States
SAGDP2N	Gross domestic product (GDP) by state	1997→	States
SAGDP2S	Gross domestic product (GDP) by state	1963-1997	States
SAGDP3N	Taxes on production and imports less subsidies	1997→	States
SAGDP3S	Taxes on production and imports less subsidies	1963-1997	States
SAGDP4N	Compensation of employees	1997→	States
SAGDP4S	Compensation of employees	1963-1997	States
SAGDP5N	Subsidies	1997→	States
SAGDP5S	Subsidies	1963-1997	States

SAGDP6N	Taxes on production and imports	1997→	States
SAGDP6S	Taxes on production and imports	1963-1997	States
SAGDP7N	Gross operating surplus	1997→	States
SAGDP7S	Gross operating surplus	1963-1997	States
SAGDP8N	Quantity indexes for real GDP by state (2009=100.0)	1997→	States
SAGDP8S	Quantity indexes for real GDP by state (1997=100.0)	1963-1997	States
SAGDP9N	Real GDP by state	1997→	States
SAGDP9S	Real GDP by state	1963-1997	States
SAINC1	Personal Income Summary: Personal Income, Population, Per Capita Personal Income	1929→	States
SAINC30	Economic Profile	1958→	States
SAINC35	Personal Current Transfer Receipts	1929→	States
SAINC4	Personal Income and Employment by Major Component	1929→	States
SAINC40	Property Income	1958→	States
SAINC45	Farm Income and Expenses	1969→	States
SAINC50	Personal Current Taxes	1948→	States
SAINC51	Disposable Personal Income Summary: Disposable Personal Income, Population, and Per Capita Disposable Personal Income	1948→	States
SAINC5H	Personal Income by Major Component and Earnings by Industry (Historical)	1929-57	States
SAINC5N	Personal Income by Major Component and Earnings by NAICS Industry	1998→	States
SAINC5S	Personal Income by Major Component and Earnings by SIC Industry	1958-2001	States
SAINC6N	Compensation of Employees by NAICS Industry	1998→	States
SAINC6S	Compensation of Employees by SIC Industry	1958→	States

SAINC7H	Wages and Salaries by Industry (Historical)	1929-57	States
SAINC7N	Wages and Salaries by NAICS Industry	1998→	States
SAINC7S	Wages and Salaries by SIC Industry	1958-2001	States
SAIRPD	Implicit Price Deflators by state	2008→	States
SARPI	Real Personal Income by state	2008→	States
SARPP	Regional Price Parities by state	2008→	States
SQGDP11	Contributions to percent change in real GDP	2005→	States
SQGDP2	Gross domestic product (GDP) by state	2005→	States
SQGDP8	Quantity indexes for real GDP by state (2009=100.0)	2005→	States
SQGDP9	Real GDP by state	2005→	States
SQINC1	Personal Income Summary: Personal Income, Population, Per Capita Personal Income	1948→	States
SQINC35	Personal Current Transfer Receipts	1948→	States
SQINC4	Personal Income by Major Component	1948→	States
SQINC5H	Personal Income by Major Component and Earnings by Industry (Historical)	1948-57	States
SQINC5N	Personal Income by Major Component and Earnings by NAICS Industry	1998→	States
SQINC5S	Personal Income by Major Component and Earnings by SIC Industry	1958-2001	States
SQINC6N	Compensation of Employees by NAICS Industry	1998→	States
SQINC6S	Compensation of Employees by SIC Industry	1958-2001	States
SQINC7H	Wages and Salaries by Industry (Historical)	1948-57	States
SQINC7N	Wages and Salaries by NAICS Industry	1998→	States
SQINC7S	Wages and Salaries by SIC Industry	1958-2001	States

ACEmp	Total Employment	2001→	States
ACComp	Total Compensation	2001→	States
ACEmpRatio	Arts Employment Ratio	2001→	States
ACCompRatio	Arts Compensation Ratio	2001→	States
ACArtsEmp	ACPSA Employment	2001→	States
ACArtsComp	ACPSA Compensation	2001→	States
ACEmpLQ	Arts Employment Location Quotient	2001→	States
ACCompLQ	Arts Compensation Location Quotient	2001→	States
ACVA	Total Value Added	2001→	States
ACVARatio	Arts Value Added Ratio	2001→	States
ACArtsVA	ACPSA Value Added	2001→	States
ACVALQ	Arts Value Added Location Quotient	2001→	States

**LineCode parameter** – (required, single value)

LineCode corresponds to the statistic in a table. Exactly one LineCode must be provided.

**GeoFips parameter** – (required, multiple value)

GeoFips specifies geography. It can be all states (STATE), all counties (COUNTY), all Metropolitan Statistical Areas (MSA), all Micropolitan Statistical Areas (MIC), all Metropolitan Divisions (DIV), all Combined Statistical Areas (CSA), all metropolitan/nonmetropolitan portions (PORT), or state post office abbreviation for all counties in one state (e.g. NY). It can also be a list of ANSI state-county codes or metropolitan area codes. For example, the counties in Connecticut and Delaware–

09001,09003,09005,09007,09009,09011,09013,09015,10001,10003,10005

State, county, and metropolitan statistical area FIPS codes can be obtained from Census at

<https://www.census.gov/geo/www/ansi/ansi.html>. A comprehensive list of MSAs and their component counties can be accessed at <https://apps.bea.gov/regional/docs/msalist.cfm>.

**Year parameter** – (optional, multiple value)

Year is either a list of comma delimited years, LAST5, LAST10, or ALL. Year will default to LAST5 years if the parameter is not specified.

### Errors

An invalid parameter value will result in an error code of 40, “The dataset requested requires parameters that were missing from the request” plus a detailed message that explains the invalid value(s) entered.

Examples:

- For Invalid TableName a detailed message with “TableName entered is invalid” will display.
- When two or more parameter values are incompatible a detailed message will display “TableName entered is incompatible with the entered GeoFips, LineCode and Year”.
- In the case of incompatible entries, the error message will tell the user which parameters are incompatible and suggestions of the compatible values will be listed.

## Examples of Regional Getdata method Requests

Personal income for 2012 and 2013 for all counties, in JSON format

<https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&method=GetData&datasetname=Regional&TableName=CAINC1&LineCode=1&Year=2012,2013&GeoFips=COUNTY&ResultFormat=json>

Real GDP for all states, all years, in XML format

<https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&method=GetData&datasetname=Regional&TableName=SAGDP9N&LineCode=2&Year=ALL&GeoFips=STATE&ResultFormat=xml>

## Method=GetParameterValuesFiltered

API Call [GETPARAMETERVALUESFILTERED] to Obtain a List of Available Values & Descriptions for Each Parameter, Filtered by Another Parameter *[Examples below]*

Target Parameter Name	Filtered Parameter Names	Parameter Value List	Explanation
<b>Year</b>	<b>TableName</b>	<a href="https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=Regional&amp;TargetParameter=Year&amp;TableName=CAINC5N,CAINC25N&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=Regional&amp;TargetParameter=Year&amp;TableName=CAINC5N,CAINC25N&amp;ResultFormat=xml</a>	List Years for given TableNames
<b>GeoFips</b>	<b>TableName LineCode</b>	<a href="https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=Regional&amp;TargetParameter=GeoFips&amp;TableName=CAINC4&amp;LineCode=10&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=Regional&amp;TargetParameter=GeoFips&amp;TableName=CAINC4&amp;LineCode=10&amp;ResultFormat=xml</a>	List of GeoFips for a given TableName and LineCode
<b>TableName</b>	<b>Year GeoFips</b>	<a href="https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=Regional&amp;TargetParameter=TableName&amp;GeoFips=00000&amp;Year=2014&amp;ResultFormat=xml">https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=Regional&amp;TargetParameter=TableName&amp;GeoFips=00000&amp;Year=2014&amp;ResultFormat=xml</a>	List of TableNames for a given Year and GeoFips

<b>LineCode</b>	<b>TableName</b>	<a href="https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=Regional&amp;TargetParameter=LineCode&amp;TableName=SAEMP25N&amp;ResultFormat=json">https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&amp;method=GetParameterValuesFiltered&amp;datasetname=Regional&amp;TargetParameter=LineCode&amp;TableName=SAEMP25N&amp;ResultFormat=json</a>	List of LineCodes for a TableName
-----------------	------------------	---	--------------------------------------

## Parameter Details for GetParameterValuesFiltered method when used as filtered parameters

**TableName parameter** – (optional, single or Multiple values)

TableName specifies a published table from the regional accounts. Multiple comma-delimited TableName values can be provided.

**LineCode parameter** – (optional, single or multiple values)

LineCode corresponds to the statistic in a table. Multiple comma-delimited LineCode values can be provided. The available LineCodes are queried using the GetParameterValuesFiltered method. For example:

<https://apps.bea.gov/api/data/?UserID=Your-36Character-Key&method=GetParameterValuesFiltered&datasetname=Regional&TargetParameter=LineCode&TableName=SAEMP25N&ResultFormat=json>

**GeoFips parameter** – (optional, single or multiple values)

GeoFips specifies geography. It can be all states (STATE), all counties (COUNTY), all Metropolitan Statistical Areas (MSA), or state post office abbreviation for all counties in one state (e.g. NY). It can also be a list of ANSI state-county codes or metropolitan area codes. For example, the counties in Connecticut and Delaware–

09001,09003,09005,09007,09009,09011,09013,09015,10001,10003,10005

State, county, and metropolitan statistical area FIPS codes can be obtained from Census at

<https://www.census.gov/geo/www/ansi/ansi.html>. A comprehensive list of MSAs and their component counties can be accessed at <https://apps.bea.gov/regional/docs/msalist.cfm>.

**Year parameter** – (optional, multiple value)

Year is either a single value, a list of comma-delimited years, or ALL

### Errors

An invalid TableName LineCode, GeoFips or Year will result in an error code of 203, “No parameter values match the filtered list requested” plus a detailed message that explains the invalid value(s) entered.

Examples:

- For Invalid LineCode a detailed message with “LineCode entered is invalid” will display.
- When there are no available GeoFips data for the entered LineCode a detailed message with “Values of GeoFips and LineCode are incompatible” will display, followed by a suggestion of compatible values.

### Additional information

Explanation of the estimates, including a schedule of the release of new regional data and Income and Product methodologies can be found on our website: <https://www.bea.gov>. Definitions of the estimates can be accessed

at our glossary of regional definitions, at <https://apps.bea.gov/regional/definitions/>.