

Answer the following.

1. How do you create a class-based view in Django?

To create a **class-based view (CBV)** in Django:

Step 1: Import View

```
from django.views import View  
from django.http import HttpResponse
```

Step 2: Define the class and HTTP method(s)

```
class MyView(View):
```

```
    def get(self, request):  
        return HttpResponse("This is a GET request response.")
```

Step 3: Connect the view in urls.py

```
from django.urls import path  
from .views import MyView
```

```
urlpatterns = [  
    path('my-view/', MyView.as_view(), name='my_view'),  
]
```

2. What is the role of urls.py in connecting a view to a URL?

The **urls.py** file maps URL patterns to corresponding view functions or classes.

Role:

- It acts as a router that decides which view should handle a given URL request.
- It enables Django to direct HTTP requests to the correct logic.

Example:

```
# urls.py  
from django.urls import path  
from .views import home_view
```

```
urlpatterns = [  
    path('home/', home_view, name='home'),
```

]

3. What is the purpose of the context dictionary in Django views?

The context dictionary is used to pass data from a view to a template.

Purpose:

- Allows dynamic content rendering in templates.
- Makes it possible to populate HTML pages with data (e.g., from the database).

Example:

```
# views.py
from django.shortcuts import render

def greeting_view(request):
    context = {'name': 'Alice'}
    return render(request, 'greeting.html', context)

<!-- greeting.html -->
<p>Hello, {{ name }}!</p>
```