Big Data Analytics (BDA)

In-class SQL Queries — Lecture Attendance Submission

Student Name	PRN	Date	Course
Sukhada Dhingra	_____	09 September 2026	Big Data Analytics

PRN was not available in the workspace. Please write your Permanent Registration Number on the blank line above before submitting.

Assumptions

Queries are written for a single denormalized retail table named **orders**, using the column names from the worksheet: `order_status`, `category`, `revenue`, `customer_segment`, `sales_channel`, `payment_method`, `profit`, `customer_rating`, `city`, `product`. If the Hive / Spark table in your notebook has a different name, replace `orders` with that table name. Syntax is Spark SQL / HiveQL compatible (`LIMIT`).

Task 1

Show all delivered orders.

```
SELECT *
FROM orders
WHERE order_status = 'Delivered';
```

Task 2

Show Electronics orders with revenue above 50,000.

```
SELECT *
FROM orders
WHERE category = 'Electronics'
  AND revenue > 50000;
```

Task 3

Count orders by customer_segment.

```
SELECT
    customer_segment,
    COUNT(*) AS order_count
FROM orders
GROUP BY customer_segment;
```

Task 4

Calculate total revenue by sales_channel.

```
SELECT
    sales_channel,
    SUM(revenue) AS total_revenue
FROM orders
GROUP BY sales_channel;
```

Task 5

Calculate total profit by payment_method.

```
SELECT
    payment_method,
    SUM(profit) AS total_profit
FROM orders
GROUP BY payment_method;
```

Task 6

Find average customer rating by city.

```
SELECT
    city,
    AVG(customer_rating) AS avg_customer_rating
FROM orders
GROUP BY city;
```

Task 7

Find the top 10 products by total profit.

```
SELECT
    product,
    SUM(profit) AS total_profit
FROM orders
GROUP BY product
ORDER BY total_profit DESC
LIMIT 10;
```

Task 8

Find the top 10 city/category combinations by revenue.

```
SELECT
    city,
    category,
    SUM(revenue) AS total_revenue
FROM orders
GROUP BY city, category
ORDER BY total_revenue DESC
LIMIT 10;
```

Notes

Write your PRN on page 1 before uploading or printing this worksheet. If a column in your notebook differs (for example `product_name` instead of `product`, or `status` instead of `order_status`), change only that identifier.