Is Now Part of

ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at
www.onsemi.com

FAIRCHILD SEMICONDUCTOR™

April 2007

FDC6331L

Integrated Load Switch

General Description

This device is particularly suited for compact power management in portable electronic equipment where 2.5V to 8V input and 2.8A output current capability are needed. This load switch integrates a small N-Channel power MOSFET (Q1) that drives a large P-Channel power MOSFET (Q2) in one tiny SuperSOT™-6 package.

Applications

- Load switch
- Power management

Features

- –2.8 A, –8 V. $R_{DS(ON)}$ = 55 mΩ @ V_{GS} = –4.5 V
  $R_{DS(ON)}$ = 70 mΩ @ V_{GS} = –2.5 V
  $R_{DS(ON)}$ = 100 mΩ @ V_{GS} = –1.8 V
- Control MOSFET (Q1) includes Zener protection for ESD ruggedness (>6KV Human body model)
- High performance trench technology for extremely low $R_{DS(ON)}$



SuperSOT™-6



See Application Circuit

Equivalent Circuit



Absolute Maximum Ratings

T_A=25°C unless otherwise noted

Symbol	Parameter		Ratings	Units
V_{IN}	Maximum Input Voltage		± 8	V
$V_{ON/OFF}$	High level ON/OFF voltage range		–0.5 to 8	V
I_{Load}	Load Current – Continuous	(Note 1)	2.8	A
	– Pulsed		9	
P_D	Maximum Power Dissipation	(Note 1)	0.7	W
T_J, T_{STG}	Operating and Storage Junction Temperature Range		–55 to +150	°C

Thermal Characteristics

$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	(Note 1)	180	°C/W
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	(Note 1)	60	°C/W

Package Marking and Ordering Information

Device Marking	Device	Reel Size	Tape width	Quantity
.331	FDC6331L	7”	8mm	3000 units

Electrical Characteristics

T_A = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
Off Characteristics						
BV_{IN}	Vin Breakdown Voltage	$V_{ON/OFF}$ = 0 V, I_D = –250 μA	8			V
I_{Load}	Zero Gate Voltage Drain Current	V_{IN} = 6.4 V, $V_{ON/OFF}$ = 0 V			–1	μA
I_{FL}	Leakage Current, Forward	$V_{ON/OFF}$ = 0 V, V_{IN} = 8 V			–100	nA
I_{RL}	Leakage Current, Reverse	$V_{ON/OFF}$ = 0 V, V_{IN} = –8 V			100	nA
On Characteristics (Note 2)						
$V_{ON/OFF\ (th)}$	Gate Threshold Voltage	V_{IN} = $V_{ON/OFF}$, I_D = –250 μA	0.4	0.9	1.5	V
$R_{DS(on)}$	Static Drain–Source On–Resistance (Q2)	V_{GS} = –4.5 V, I_D = –2.8A V_{GS} = –2.5 V, I_D = –2.5 A V_{GS} = –1.8 V, I_D = –2.0 A		34 45 64	55 70 100	mΩ
$R_{DS(on)}$	Static Drain–Source On–Resistance (Q1)	V_{GS} = 4.5 V, I_D = 0.4A V_{GS} = 2.7 V, I_D = 0.2 A		3.1 3.8	4 5	Ω
Drain–Source Diode Characteristics and Maximum Ratings						
I_S	Maximum Continuous Drain–Source Diode Forward Current				–0.6	A
V_{SD}	Drain–Source Diode Forward Voltage	$V_{ON/OFF}$ = 0 V, I_S = –0.6 A (Note 2)			–1.2	V

Notes:
1. $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. $R_{\theta JC}$ is guaranteed by design while $R_{\theta JA}$ is determined by the user's board design.

2. Pulse Test: Pulse Width < 300μs, Duty Cycle < 2.0%.

FDC6331L Load Switch Application Circuit



External Component Recommendation:
For additional in-rush current control, R2 and C1 can be added. For more information, see application note AN1030.



Figure 1. Conduction Voltage Drop Variation with Load Current.



Figure 2. Conduction Voltage Drop Variation with Load Current.



Figure 3. Conduction Voltage Drop Variation with Load Current.



Figure 4. On-Resistance Variation With Input Voltage



Figure 5. Transient Thermal Response Curve.

Thermal characterization performed on the conditions described in Note 2. Transient thermal response will change depends on the circuit board design.

FAIRCHILD
SEMICONDUCTOR®

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx®	HiSeC™	Programmable Active Droop™	TinyLogic®
Across the board. Around the world™	*i-Lo*™	QFET®	TINYOPTO™
ActiveArray™	ImpliedDisconnect™	QS™	TinyPower™
Bottomless™	IntelliMAX™	QT Optoelectronics™	TinyWire™
Build it Now™	ISOPLANAR™	Quiet Series™	TruTranslation™
CoolFET™	MICROCOUPLER™	RapidConfigure™	μSerDes™
CROSSVOLT™	MicroPak™	RapidConnect™	UHC®
CTL™	MICROWIRE™	ScalarPump™	UniFET™
Current Transfer Logic™	MSX™	SMART START™	VCX™
DOME™	MSXPro™	SPM®	Wire™
E^2CMOS™	OCX™	STEALTH™	
EcoSPARK®	OCXPro™	SuperFET™	
EnSigna™	OPTOLOGIC®	SuperSOT™-3	
FACT Quiet Series™	OPTOPLANAR®	SuperSOT™-6	
FACT®	PACMAN™	SuperSOT™-8	
FAST®	POP™	SyncFET™	
FASTr™	Power220®	TCM™	
FPS™	Power247®	The Power Franchise®	
FRFET®	PowerEdge™	™	
GlobalOptoisolator™	PowerSaver™	TinyBoost™	
GTO™	PowerTrench®	TinyBuck™	

PRODUCT STATUS DEFINITIONS
Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild Semiconductor.The datasheet is printed for reference information only.

Rev. I24

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Fairchild Semiconductor:

FDC6331L