
:As per OA/PO agreement





USTOMER

SSTOMER SPECIFICATION

ANJANI STAINLESS STEELS PRIVATE LIMITED

NO.NO.

:Mumbai

:1384560\_BHAVYADEEP IMPEX/PPPFEB20

PO DATE:26.02.2024

DATE

CERTIFICATE NO. :JSL-CRD/QA/2024-25/DOM/01850034

:24.05.2024

VEHICLE NO.

:HR39E4193

SALES ORDER NO.

:0558105771

:3.097

:6100086499 / 2101238711 | NET WT(MT) T/DELIVERY NO. STAINLESS STEET 304/1,4301

BATCH NO. HRC/PLATE PKT/PALLET WEIGHT HEAT NO. тик WIDTH LENGTH FINISH EDGE QUALITY NO. NO (MT) (mm) (mm) (mm) 2002542222 J1028688 3.097 40229D02 1.500 1,250.00 2,500.00 N4P Mill Edge PRIME

HEAT NO **%М**п %P %SI % N 402291)02 0.025 1,24 0.002 0.030 0.39 8.02 18.03 0.068

A COMPLANTION PROPERTY SAMPLED DESCRIPTIONS THAN SYCREGAL AND SAMPLED SAMPLED SAMPLED DESCRIPTIONS THAN SYCREGAL AND SAMPLED										
Sr to	Rµ 0,2/ YS Мря	Rp 1,0 Мра	Rm/ TS Mpa	%EL GL=50 mm	%EL G1,= 80 mm	GL- KAP SO MM	Hardness HRBW	Bend Tost		
I	311	344	654	58			.83 / 84	· ·	<del></del>	· · · · · · · · · · · · · · · · · · ·

IMATERIAL SOLUTION ANNIALED AT TEMPERATURE 1040°C MINIMUM AND QUENCHED IN AIR WATER MIST AT A SUFFICIENT RATE TO PREVENT RE-PRECIPITATION OF CARBIDES VE MATERIAL FULLY CONFORMS TO IS 6911:2017 AMD NO.3 CHEMICAL & MECHANICAL PROPERTIES OF PRODUCT AS TESTED IN ACCORDANCE WITH THE SCHEME

JF Ta 5 & INSPECTION CONTAINED IN BIS CERTIFICATION.

11 ABC AATERIAL ATSO FULFIL THE REQUIREMENTS OF ASTM A480/A480M/ASME SA 480/SA480M

1) MATERIAL GRADE AS PER IS 6911 :2017 AMD NO.3: 304

ATFINEITIES HOT ROLLED NI, ID("NI" STANDS FOR NO.1). COLD ROLLED 2D, 2B, HA, N4, BX, HC, LN, MMT, MR, SCB, SL, SR ("N4" STANDS FOR NO.4, BY: STANDS FOR BOX FINISH, "HC" STANDS FOR HONEY COMB, "LIN" STANDS FOR LINEN, "MMT" STANDS FOR MACROMAT, "MR" STANDS FOR MOON ROCK, "SCB" STANDS FOR SCOTCH BRITE, "SL" STANDS FOR SLIP FREE, "SR" STANDS FOR STRIPE) "P" STANDS FOR WITH TOP PVC. "H" STANDS FOR WITH BOTH SIDE FVC. H) PLATE, MATERIAL 5 MM AND OVER IN THICKNESS AND OVER 250 MM IN WIDTH (AS PER ASTMIASME STANDARD) & THICKNESS 3 MM OR OVER 465 PER DIN SEANDARD) C) SUBSTEMATERIAL UNDER 5 MM IN TRUCKNESS AND 600 MM AND OVER IN WIDTH (AS PER ASTM/ASME STANDARD) & THICKNESS LESS THAN 3 MM (ASPER DIN STANDARD) D) COLLIN "PHYSICAL DESCRIPTION" LENGTH MENTIONED AS "COLL". E) NO WELD REPAIR HAS BEEN DONE ON ANY PRODUCT. F) DIMENSION TOPERANCE AS FER SO/OA

Inulat Stumbers Lemited, Calif Rolling Division, O.F. Findel Marg. HISAR-125005.INDIA, 11:.. 91-1662 - 222971-83, FAN - 91-1662 - 222971-83, mad enating tologomidal transfers.com onnat ref = QAD-CRA99F REV.15 EED ate 02/03/2023

ISO 9001- 2015 ISO 14001-2015 ISO 45001:2018 ISO 50001:2018 CERTIFIED CO



Any anasyltarised usage of this Test Certificate will warrant Legal Action,

Ε/L