



React Tutorial

Lesson 4

Today's lesson will cover

- ─ Impossible States
- ─ JavaScript Fetch API
- ─ Data Fetching and Re-Fetching
- ─ Memorized Handler
- ─ Explicit Data Fetching
- ─ Third-party libraries
- ─ Async/Await
- ─ Forms
- ─ React Legacy: Class Components and State



Intro to React

Impossible States

- A Impossible states are not easy to spot, which makes them infamous for causing bugs in the UI
- There is nothing wrong with multiple useState hooks in one React component. Be wary once you see multiple state updater functions in a row, however. These conditional states can lead to impossible states, and undesired behavior in the UI
- The impossible state happens when an error occurs for the asynchronous data. The state for the error is set, but the state for the loading indicator isn't revoked

JavaScript Fetch API

- One of the most challenging parts with understanding how JavaScript (JS) works is understanding how to deal with asynchronous requests, which requires understanding in how promises and callbacks work.
- AJAX stands for Asynchronous JavaScript and XML, and it allows web pages to be updated asynchronously by exchanging data with a web server while the app is running. In short, it essentially means that you can update parts of a web page without reloading the whole page (the URL stays the same)
- **Why Fetch API?** This allows us to perform declarative HTTP requests to a server. The benefit of Fetch API is that it is fully supported by the JS ecosystem, and is also a part of the [MDN Mozilla docs](#).
- The `fetch()` method returns a `Promise` that resolves the `Response` from the `Request` to show the status (successful or not). If you ever get this message `promise {}` in your console log screen, don't panic – it basically means that the `Promise` works, but is waiting to be resolved. So in order to resolve it we need the `.then()` handler (callback) to access the content.
- Clone the [template repository](#)

Data Fetching and Re-Fetching with React

- Impossible states are not easy to spot, which makes them infamous for causing bugs in the UI
- There is nothing wrong with multiple `useState` hooks in one React component. Be wary once you see multiple state updater functions in a row, however. These conditional states can lead to impossible states, and undesired behavior in the UI
- The impossible state happens when an error occurs for the asynchronous data. The state for the error is set, but the state for the loading indicator isn't revoked
- Re-fetching data each time someone types into the input field isn't optimal because this implementation stresses the API, you might experience errors if you use requests too often.
- For our project, we will use the reliable and informative [Hacker News API](#) to request popular tech stories.
 - API endpoint: `http://hn.algolia.com/api/v1/search?query=`

Memoized Handler

- A bit advanced concept based on memorization, Memoized handler can be applied on top of handlers and callback handlers
- React useCallback hook allows you to do so

Third party libraries

- Third party libraries usually allow you to handle verbose complicated tasks in much convenient fashion
- For instance alternative to native fetch API is stable library like axios which performs asynchronous requests to remote APIs
- Usually you would have to install the package of another library from npm registry using following command: `npm install libraryname` and afterwards you import it in your component



Self Study Assignments

To Dos

- Start working on React or Fullstack JavaScript project, OR complete FCC Frontend Library Certification : Bootstrap, React, Redux, React & Redux, projects; APIs and Microservices Certification :
<https://www.freecodecamp.org/learn>
- Refer to Reactjs official documentation as the best place to learn underlying main concepts of React with examples: <https://reactjs.org/docs/hello-world.html>