

# INTRO TO JAVASCRIPT

# TODAY'S OBJECTIVES

- **What is Client-Side Scripting and Why Use it?**
- **What is Javascript?**
  - Compiled languages vs. interpreted languages
  - Statically typed vs. dynamically typed
- **Variables in JavaScript**
  - Declaring variables
  - Naming
- **Data Types**
  - Strict vs. loose equality
  - Number, String, Boolean, Object (includes arrays), undefined
  - Type coercion
  - Null vs undefined
- **Branching**
  - if/else if/else
  - switch
- **Loops**
  - for/while/do

# TODAY'S OBJECTIVES

- **Arrays**
  - push/pop
  - unshift/shift
  - indexOf/lastIndexOf
- **JavaScript Objects**
- **Functions in JavaScript**
  - Signature
  - Variable scope
- **Built-In Functions**
  - String methods
  - Numbers, Math, and Dates

# WHAT IS CLIENT-SIDE SCRIPTING?

- Executes code on the user's browser, allowing us to interact with the HTML rendered and the CSS sent by the server.
- Interacts with HTML on the page (the DOM - Document Object Model).
- JavaScript is the scripting language all browsers understand.

# WHY DO WE USE CLIENT-SIDE SCRIPTING?

- Creates less stress on the server and more interactive engaging experiences for users.
  - Allows client (browser) to perform validation immediately.
  - Fewer calls to server.
- Allows page interaction/manipulation.
  - Can respond to user events.
  - Can make calls to web services/APIs to dynamically update page.
  - Can update page without page refresh via DOM manipulation.
- Separation of Concerns.
  - HTML: Presentation content
  - CSS: Presentation styling
  - JavaScript: Behavior and logic

# WHAT IS JAVASCRIPT?

- Programming language with similarities to Java.
- How is JavaScript different than Java
  - Java requires a runtime while JavaScript requires a browser.
  - Java is compiled while JavaScript is interpreted.
  - Java is statically typed while JavaScript is dynamically typed.

# ADDING JAVASCRIPT TO AN HTML DOCUMENT

- `<script>` tag:
  - `<script> // some JavaScript </script>`
  - `<script src="exercises.js"></script>`

# DECLARING JAVASCRIPT VARIABLES

- JavaScript doesn't require data type in declaration.
- Declare variables that will change using **let**.

```
let myText = 'Hello world!';  
  
// can be changed  
  
myText = 'Howdy world!';  
  
// can also be declared without value,  
  
let myOtherText;  
  
// then assigned later  
  
myOtherText = 'Hello other world!';
```



# DECLARING JAVASCRIPT VARIABLES

- Declare variables that will not change using **const**.

```
const MY_CONST_TEXT = 'Hello world!';  
  
// CANNOT change: below will throw an error  
  
MY_CONST_TEXT = 'Howdy world!';  
  
// CANNOT be declared without value:  
// below will throw an error  
  
let myOtherText;
```

# DECLARING JAVASCRIPT VARIABLES

- Avoid using **var** - considered **harmful!**
  - Used in older versions of JavaScript
  - Allows multiple declarations without warning
  - Function scope (vs. block scope)
  - Use **let** or **const** instead

# JAVASCRIPT VARIABLE NAMING

- Variable names are comprised of letters **A-Z**, **a-z**, characters **\_**, **\$**, and **digits 0-9**.
- Variable names must start with a **letter**, **\_**, or **\$**.
- Variable names are case-sensitive.
- Variable names may be not be a reserved keyword.
- Follow best practice conventions:
  - Use camelCase for multi-word variable names.
  - Use uppercase for constants and separate words with an underscore, **\_**.
  - Boolean variable should begin with **is**

# JAVASCRIPT DATA TYPES

- Number
  - integer
  - floating-point
  - **NaN**
- String
  - Zero or more characters enclosed in double(") or single (') quotation marks ("foo" or 'foo').
  - Build larger strings from smaller ones in code with string concatenation using the concatenation operator, +, just as you do in Java.
- Boolean

# JAVASCRIPT DATA TYPES

## **null vs. undefined:**

- **null** is a value of type **Object**
- **undefined** is a value of type **undefined**
- **null** must be assigned. It means **nothing**.
- **undefined** occurs from the "**let var\_name;**" statement
  - It also may be assigned

# JAVASCRIPT DATA TYPES

## JavaScript is loosely typed

- Variables aren't associated with any particular data type when declared and are free to hold any type of value.
- Variables can be assigned and re-assigned values of any datatype.
- JavaScript does type coercion as necessary.

# JAVASCRIPT DATA TYPES

## Strict and loose equality

- === vs. ==
- === means types and values are equal (strict equality)
- == means values are equal (loose equality)
- Types are coerced
- !== and != are the "not equal" equivalents
- **Falsy** values:
  - When coerced to Boolean, value is false
  - false, 0, "", null, undefined, NaN
- All other values are **Truthy**
- More craziness: <https://codeburst.io/javascript-double-equals-vs-tripleequals-61d4ce5a121a>

# LOGICAL BRANCHING

- if
- else if
- else
- switch



# LOOPING

- for
- while
- do

```
for (let i = 0; i < 5; i++) {  
    console.log("Hello world!");  
}  
  
let i = 0;  
while (i < 5) {  
    console.log("Hello world!");  
    i++;  
}  
  
let i=0;  
do {  
    console.log("Hello world!");  
    i++;  
} while (i < 5);
```

# STRING INTERPOLATION IN JAVASCRIPT

- String interpolation in JavaScript use the ` mark (know as a tick) to enclose the literal template.
- Values enclosed in `\${}` are populated with the variable name with the {}.

```
let birthDate = '03/15/1970';  
  
console.log(`Birthdate is ${birthDate }`);
```

# JAVASCRIPT SCOPE

- Can declare a variable at any point in a block, but you must declare it before you use it.
- Once declared, the variable is in scope.
- Variables are in scope until the end of the block when they are discarded and go out of scope.
- Nested blocks:
  - Each nested block can declare and use its own set of local variables.
  - Statements within the inner block can use both variables from the inner and outer scope
  - JavaScript allows a variable in an inner block to have the same name as a variable in an outer block (this is called variable shadowing) but this should be avoided.

# JAVASCRIPT ARRAYS

- Defining arrays:
  - `let scores = [];`
  - `let scores = [10, 20, 30];`
- Accessing arrays
  - `scores[2];`
  - **index is 0 based.**
- Array size can be modified in JavaScript!
- Can check size of array with **length** property.

# JAVASCRIPT ARRAY FUNCTIONS

- **push** adds element to end of array
- **pop** removes element from end of array
  - returns element removed
- **unshift** adds element before first element of array
- **shift** removes element at first element of array
  - returns element removed
- **includes** indicates whether an array contains a given value
- **indexOf** returns the index of first occurrence of value in array, or -1 if not found
- **lastIndexOf** returns the index of last occurrence of value in array, or -1 if not found

# JAVASCRIPT OBJECT LITERALS

- { } denotes an object
- Key : value pairs, separated by commas

```
const person = {  
  firstName: 'Lisa',  
  lastName: 'Simpson',  
  age: 42,  
  relatives: [  
    'Marge Simpson',  
    'Homer Simpson',  
    'Bart Simpson'  
  ]  
};
```

- Access element: person.firstName

# JAVASCRIPT FUNCTIONS (JAVASCRIPT VERSION OF METHODS)

- no access modifier
- function keyword
- function name
  - usually camel-case
- no return type
- parameter names
  - no type defined
- return statement

```
function sumVals(val1, val2)
{
    return val1 + val2;
}
```

# BUILT-IN FUNCTIONS

## String methods

- [https://www.w3schools.com/js/js\\_string\\_methods.asp](https://www.w3schools.com/js/js_string_methods.asp)
- [https://developer.mozilla.org/enUS/docs/Web/JavaScript/Guide/Text\\_formatting](https://developer.mozilla.org/enUS/docs/Web/JavaScript/Guide/Text_formatting)

## Numbers, Math and Dates

- [https://developer.mozilla.org/enUS/docs/Web/JavaScript/Guide/Numbers\\_and\\_dates](https://developer.mozilla.org/enUS/docs/Web/JavaScript/Guide/Numbers_and_dates)
- [https://www.w3schools.com/js/js\\_number\\_methods.asp](https://www.w3schools.com/js/js_number_methods.asp)
- [https://www.w3schools.com/js/js\\_math.asp](https://www.w3schools.com/js/js_math.asp)
- [https://www.w3schools.com/js/js\\_dates.asp](https://www.w3schools.com/js/js_dates.asp)



# USING THE DEV TOOLS JAVASCRIPT DEBUGGER

# EXERCISE NOTES

- **exercises.js**
  - **createObject()** is intended to be a function that returns an object with the given fields and using your info for the values in those fields
- **challenge-exercises.js**
  - **titleCase:**
    - Words not in minor words list should be Pascal case
    - Words that ARE in minor words list should be all lowercase