



**UNIVERSITY
OF MALAYA**



**SOFTWARE VERIFICATION & VALIDATION
(WOC7015)
SEMESTER 1
SESSION 2025/2026**

Alternative Assessment Test Report

Lecturer: Assoc. Prof. Dr. Siti Hafizah Ab Hamid

Team member:

No	Matric No	Name
1	24082385	Saleban Mohamed (Leader)
2	23095061	Li Linlin
3	24082390	Chen Xinyan
4	25051926	Pavithiran A/L Mahendran
5	24216528	Nithia Sree A/P Ganesan
6	24088681	SHENG MENGYU

1.0 INTRODUCTION	2
1.1 Purpose	2
1.2 Scope	2
1.3 Exclusions	3
1.4 Disclaimer	3
1.5 References	4
2.0 Test Design Specification	5
2.1 Features to be Tested	5
2.2 Approach Refinement	7
System Architecture Overview	7
2.3 Detailed Breakdown for Requirements	8
F001 - User Registration (Tester: Saleban)	8
F002 - User Login (Tester: Li Linlin)	8
F003 - Password Reset (Tester: Saleban)	8
F004 - Manage Users (Tester: Li Linlin)	8
F005 & F006 - Manage Bookshelves and Books (Tester: Xinyan Chen)	8
F007 & F009 - Manage Chapters and Page Revisions (Tester: Pavithiran)	9
F008 & F010 - Manage Pages and Global Search (Tester: Nithia Sree)	9
F011 & F012 - Image Manager and Role-Based Permissions (Tester: Sheng Mengyu)	9
NF-001 - Security (Authentication & Authorization) (Tester: Saleban)	9
NF-002 - Security (Data Integrity) (Tester: Li Linlin)	9
NF-003 - Security (Session Management) (Tester: Xinyan Chen)	10
NF-004 - Usability (Cross-Browser Compatibility) (Tester: Pavithiran)	10
NF-005 - Performance (Response Time & Page Load) (Tester: Nithia Sree)	10
NF-006 - Reliability (Auto-save & System Stability) (Tester: Sheng Mengyu)	10
2.4 Test Case Specifications	11
2.4.1 F001 - Register User Account (Testers: Saleban)	11
Nature of Feature:	11
Justification:	11
Use Case Description	12
Case Testing (System Testing Level)	13
Boundary Value Analysis (System Testing Level)	16
Equivalence Partitioning (System Testing Level)	19
Error Guessing (System Testing Level)	22
Nature of Feature:	25
Justification:	25
Testing Constraints (Per Disclaimer Section 1.4)	26
Use Case Description	27

Case Testing (System Testing Level)	28
Boundary Value Analysis (System Testing Level)	32
Equivalence Partitioning (System Testing Level)	37
Equivalence Classes Definition	37
Equivalence Partitioning Test Cases	39
Error Guessing (System Testing Level)	46
Nature of Feature:	53
Justification:	54
Testing Constraints (Per Disclaimer Section 1.4)	54
Use Case Description	55
Case Testing (System Testing Level)	57
Equivalence Partitioning (System Testing Level)	62
Equivalence Classes Definition	62
Equivalence Partitioning Test Cases	64
Error Guessing (System Testing Level)	68

1.0 INTRODUCTION

This Test Report documents the verification and validation (V&V) activities performed on BookStack (Version 22.04.2). This report details the testing methodologies, test cases, results, and analysis conducted to assess the system's compliance with its functional and non-functional requirements and its overall quality. The testing process followed a primarily black-box approach, focusing on the system's external behavior and user experience, supplemented by static analysis of available documentation. Model checking was applied to verify the correctness of system behaviors represented by state diagrams. The goal of this testing effort was to identify potential defects, assess the system's readiness for deployment, and provide recommendations for improvement.

1.1 Purpose

The purpose of this Test Report is to provide a comprehensive and documented account of the testing conducted on **BookStack**. This report serves as evidence of the system's quality and its adherence to the requirements outlined in the Software Brief Description (SBD). The specific objectives of this testing effort were to:

- **Identify Defects:** Uncover any defects or inconsistencies in BookStack's functionality, performance, security, usability, and other key aspects.
- **Assess Quality:** Evaluate the system's quality attributes based on ISO 9126 characteristics (Functionality, Reliability, Usability, Efficiency, Maintainability, and Portability).
- **Verify Requirements Compliance:** Confirm that BookStack meets all 12 functional and 6 non-functional requirements specified for this project.
- **Validate User Needs:** Assess the system's usability and user acceptance through User Acceptance Testing (UAT).
- **Formally Verify System Behaviors:** Use model checking to verify the correctness of specific system behaviors represented by state diagrams (e.g., Page Creation and User Login).
- **Provide Recommendations:** Offer actionable recommendations to the development team for addressing any identified defects and improving the system's quality.

1.2 Scope

This Test Report covers the following aspects of the BookStack system:

- **Functional Requirements:** Testing focused on the core functionalities of the system, including content organization and user management. Specific requirements tested include:
 - F001: User Registration
 - F002: User Login
 - F003: Password Reset
 - F004: Manage Users

- F005: Manage Bookshelves
- F006: Manage Books
- F007: Manage Chapters
- F008: Manage Pages
- F009: Page Revisions
- F010: Global Search
- F011: Image Manager
- F012: Role-Based Permissions
- **Non-Functional Requirements:** Testing also addressed key quality attributes:
 - NF-001: Security (Authentication & Authorization)
 - NF-002: Security (Data Integrity)
 - NF-003: Security (Session Management)
 - NF-004: Usability (Cross-Browser Compatibility)
 - NF-005: Performance (Response Time & Page Load)
 - NF-006: Reliability (Auto-save & System Stability)
- **Model Checking:** Formal verification of core state diagrams, including Login and content creation flows.
- **User Acceptance Testing (UAT):** Usability and user satisfaction assessed through UAT with a minimum of 30 respondents.

1.3 Exclusions

This Test Report does not cover:

- **Detailed Unit and Integration Testing:** Due to the black-box nature of this effort and limited access to the internal codebase, extensive unit testing was not conducted.
- **Backend Stress Testing:** Detailed back-end testing (e.g., deep database performance under extreme load) was outside the scope.
- **Extreme Load Conditions:** Simulations involving thousands of concurrent users were not performed due to resource constraints.
- **Extensive Code-Based Coverage:** No statement or branch coverage analysis was performed.

1.4 Disclaimer

The testing of BookStack was impacted by issues encountered with the local deployment environment. While the provided documentation was adequate for a high-level overview, the technical setup required significant troubleshooting. Specifically:

- **Outdated Infrastructure:** BookStack relies on specific PHP and MySQL versions that required reconfiguration on local XAMPP/Nginx environments.
- **Technical Setup:** Significant time was consumed ensuring environment dependencies were operational before testing could begin.
- **Deployment Limitations:** Testing was conducted on local instances, which may not perfectly reflect performance in a high-availability production cloud environment.

1.5 References

- BookStack GitHub Repository: <https://github.com/BookStackApp/BookStack>
- Software Brief Description - BookStack (Version 22.04.2)
- BookStack Test Report - Feature Selection Document
- Sample Test Report (Expense Manager)
- WOC7015 Group Project Instructions

2.0 Test Design Specification

Version: 1.0.0

Date: 01/01/2026

2.1 Features to be Tested

The following table outlines the features of BookStack v22.04.2 that were selected for testing


Feature ID	Feature	Actor/Role	Risk Level	Tester
F001	User Registration	Guest User	High	Saleban
F002	User Login	Registered User	High	Li Linlin
F003	Password Reset	Registered User	High	Saleban
F004	Manage Users	Admin	High	Li Linlin
F005	Manage Bookshelves	Editor, Admin	Medium	Xinyan Chen
F006	Manage Books	Editor, Admin	High	Xinyan Chen
F007	Manage Chapters	Editor, Admin	Medium	Pavithiran
F008	Manage Pages	Editor, Admin	Critical	Nithia Sree
F009	Page Revisions	Editor, Admin	Medium	Pavithiran
F010	Search Functionality	All Auth Users	High	Nithia Sree

F011	Image Manager	Editor, Admin	Medium	Sheng Mengyu
F012	Role-Based Permissions	Admin	Critical	Sheng Mengyu
NF-001	Security (Auth & Authz)	All	High	Saleban
NF-002	Security (Data Integrity)	All	High	Li Linlin
NF-003	Security (Sessions)	All	High	Xinyan Chen
NF-004	Usability (Cross-Browser)	All	Medium	Pavithiran
NF-005	Performance (Response)	All	Medium	Nithia Sree
NF-006	Reliability (Auto-save)	All	High	Sheng Mengyu

2.2 Approach Refinement

The testing approach for BookStack utilizes a combination of black-box testing techniques to ensure full requirements coverage and system reliability.

System Architecture Overview



Testing Techniques Employed:

1. **Use Case Testing (Mandatory):** Applied to all functional requirements to verify primary and alternative user flows.
2. **Boundary Value Analysis (BVA):** Used for fields with constraints, such as password lengths and file upload sizes.
3. **Equivalence Partitioning (EP):** Applied to group valid and invalid input classes for registration and search.
4. **Error Guessing:** Leveraged by testers to identify common pitfalls like session hijacking or duplicate submissions.
5. **State Transition Testing:** Focused on the lifecycle of content (e.g., Draft to Published) and login states.
6. **GUI Testing:** Verifying the responsiveness and visual consistency of the BookStack interface.
7. **Performance & Stress Testing:** Assessing system behavior under high data volume or concurrent user requests.

2.3 Detailed Breakdown for Requirements

Following the previous team's model, here is the refined plan for the initial features:

F001 - User Registration (Tester: Saleban)

- **Techniques:** Use Case Testing, BVA, Equivalence Partitioning, Error Guessing.
- **Justification:** These techniques ensure the critical entry point is secure and handles diverse user inputs correctly.
- **Tools:** Selenium, OWASP ZAP.
- **Plan:** Perform BVA on password fields (min 8 chars); test valid/invalid email classes; use ZAP to check for registration-related vulnerabilities.

F002 - User Login (Tester: Li Linlin)

- **Techniques:** Use Case Testing, State Transition Testing, Error Guessing.
- **Justification:** Focuses on the security gateway by verifying state changes between "Logged Out," "Authenticating," and "Authenticated".
- **Tools:** Selenium, Katalon Studio.
- **Plan:** Execute use cases for MFA and "Remember Me" features; verify account lockout after multiple failed attempts.

F003 - Password Reset (Tester: Saleban)

- **Techniques:** Use Case Testing, BVA, Error Guessing.
- **Justification:** Verifies the recovery flow for users who lose access. BVA is applied to the new password creation to ensure complexity rules are enforced.
- **Plan:** Test the "forgot password" link with valid/invalid emails; verify the expiration of the reset token; check that common weak passwords are rejected.

F004 - Manage Users (Tester: Li Linlin)

- **Techniques:** Use Case Testing, Error Guessing, GUI Testing.
- **Justification:** Focuses on the user's ability to customize their account. GUI testing ensures that profile pictures and preferences are displayed correctly across different resolutions.
- **Plan:** Update display names and avatars; verify that email changes require re-validation (if applicable); check for layout breaks on the profile page.

F005 & F006 - Manage Bookshelves and Books (Tester: Xinyan Chen)

- **Techniques:** Use Case Testing, BVA, GUI Testing.
- **Justification:** These are the core organizational units of BookStack. BVA is used to test character limits for Titles and Descriptions.
- **Plan:** Create/Edit/Delete shelves and books; verify that books can be assigned to multiple shelves; ensure the "cover image" upload handles various file formats.

F007 & F009 - Manage Chapters and Page Revisions (Tester: Pavithiran)

- **Techniques:** Use Case Testing, State Transition Testing, Error Guessing.
- **Justification:** Chapter management involves nesting, while Page Revisions involve tracking state changes over time.
- **Plan:** Move pages between chapters; restore a page to a previous revision (State Transition); verify that revision history is not lost after a server restart.

F008 & F010 - Manage Pages and Global Search (Tester: Nithia Sree)

- **Techniques:** Use Case Testing, BVA, Performance Testing.
- **Justification:** The Page Editor is the most complex component. Search requires performance assessment to ensure it remains fast as the database grows.
- **Plan:** Test the WYSIWYG editor's "Auto-save" (BVA on intervals); execute search queries with special characters; measure response time for global search results.

F011 & F012 - Image Manager and Role-Based Permissions (Tester: Sheng Mengyu)

- **Techniques:** Use Case Testing, Error Guessing, GUI Testing.
- **Justification:** Image management involves file handling risks, while Permissions are critical for security in a multi-user wiki.
- **Plan:** Upload/delete images via the manager; create custom roles (e.g., "Reviewer") and verify they cannot delete books created by "Admins".

NF-001 - Security (Authentication & Authorization) (Tester: Saleban)

- **Techniques:** Security Testing (Penetration Testing), Use Case Testing.
- **Justification:** Verifies the robustness of the authentication gateway against unauthorized access and ensures that the "Least Privilege" principle is enforced across various user roles (Admin, Editor, Viewer).
- **Tools:** OWASP ZAP, Burp Suite.
- **Plan:** Simulate brute-force attacks on the login page; verify that MFA (Multi-Factor Authentication) correctly blocks access without a valid token; attempt to access Admin-only pages (e.g., system settings) using a "Viewer" account to check for privilege escalation vulnerabilities.

NF-002 - Security (Data Integrity) (Tester: Li Linlin)

- **Techniques:** Security Testing (Data Inspection), Penetration Testing.
- **Justification:** Ensures that sensitive user data, particularly passwords and personal profile information, is protected during storage and transmission to prevent data breaches.
- **Tools:** Browser Developer Tools (Network Tab), MySQL Workbench.
- **Plan:** Inspect the BookStack database directly to confirm passwords are encrypted using strong hashing (e.g., Bcrypt); monitor network traffic during a "Manage User Profile" update to ensure sensitive data is not passed in the URL or as plain text in the HTTP body.

NF-003 - Security (Session Management) (Tester: Xinyan Chen)

- **Techniques:** Security Testing (HTTP Request Inspection), Error Guessing.
- **Justification:** Prevents session hijacking and ensures that user sessions are handled securely across the platform, which is critical for a multi-user documentation system.
- **Tools:** OWASP ZAP, Cookie Editor.
- **Plan:** Verify that session cookies are marked as **Secure** and **HttpOnly**; test for session timeout after the specified period of inactivity; confirm that a user is fully invalidated and cannot perform actions after clicking "Logout".

NF-004 - Usability (Cross-Browser Compatibility) (Tester: Pavithiran)

- **Techniques:** Compatibility Testing, GUI Testing.
- **Justification:** Ensures that the BookStack interface, especially the WYSIWYG page editor, renders and functions consistently across different modern browsers as specified in the Portability requirements.
- **Tools:** Google Chrome, Microsoft Edge, Mozilla Firefox.
- **Plan:** Systematically test the "Manage Pages" and "Manage Bookshelves" UI on Chrome and Edge; document any rendering discrepancies (e.g., overlapping buttons or broken sidebars) using screenshots; verify that core navigation remains clear and functional on various screen resolutions.

NF-005 - Performance (Response Time & Page Load) (Tester: Nithia Sree)

- **Techniques:** Performance Testing.
- **Justification:** Evaluates the system's responsiveness, which is crucial for maintaining a positive user experience when searching through or loading large documentation libraries.
- **Tools:** Apache JMeter, WebPageTest.
- **Plan:** Establish baseline page load times for the Global Search and Home Page; simulate 100 concurrent users searching for documentation to measure server response time; identify potential bottlenecks when loading books with high numbers of chapters and pages.

NF-006 - Reliability (Auto-save & System Stability) (Tester: Sheng Mengyu)

- **Techniques:** Reliability Testing, Stress Testing.
- **Justification:** Focuses on the system's ability to maintain data integrity under stress, specifically ensuring the "Auto-save" feature prevents data loss during browser or network failures.
- **Tools:** Apache JMeter.
- **Plan:** Subject the page editor to a stress test by simulating 1,000 simultaneous page edit requests; verify that the auto-save mechanism correctly retains drafts even if the session is interrupted; check system recovery time and data persistence after a simulated server crash during content creation.

2.4 Test Case Specifications

2.4.1 F001 - Register User Account (Testers: Saleban)

This feature allows new users to register a new account on the BookStack system. This is a critical function, as it's the entry point for user engagement. Thorough testing is essential to ensure data integrity, security, and a positive user experience.

- Saleban's Focus: Input validation, boundary conditions, and security testing (SQL injection).

The following table shows the features to be tested based on the SBD, including functional ID, feature, and risk level.

Feature ID	Feature	Risk Level
F001	Register User Account	High

The techniques that will be applied are as follows:

1. Use Case Testing (Black Box Testing - System Level)
2. Boundary Value Analysis (Black Box Testing - System Level)
3. Equivalence Partitioning (Black Box Testing - System Level)
4. Error Guessing (Black Box Testing - System Level)

Nature of Feature:

The "Register User Account" feature allows new users to create an account by providing their details (name, email, password), which are then validated by the system. Upon successful validation, the user account is created and the user may be required to confirm their email address depending on system settings. The system also includes bot protection through a honeypot field and rate limiting to prevent spam registrations.

Key Implementation Details (from BookStack source code):

- Registration is handled by `app/Access/Controllers/RegisterController.php`
- User creation logic resides in `app/Access/RegistrationService.php`
- Password validation uses Laravel's Password rule with defaults (minimum 8 characters)
- Email domain restrictions can be configured via `ALLOWED_EMAIL_DOMAINS` setting
- Email confirmation controlled by `registration-confirmation` setting
- Social authentication registration (Google, GitHub, Twitter, etc.) supported
- CSRF protection enabled on all forms
- Input sanitization through Laravel's request validation

Justification:

Use Case Testing is mandatory. It will test the standard registration process described in the use case. This verifies the main success scenario and alternative flows as described in the use case documentation.

Boundary Value Analysis (BVA) focuses on input fields to identify potential errors at boundary conditions (name: 2-100 characters, password: minimum 8 characters, email: maximum 255 characters).

Equivalence Partitioning efficiently tests different classes of valid and invalid inputs, improving test coverage while minimizing redundancy.

Error Guessing uses the testers' experience and intuition to anticipate potential errors or common mistakes users might make during registration.

Testing Constraints (Per Disclaimer Section 1.4)**IMPORTANT:** Testing Limitations

Due to the Hybrid Testing Approach outlined in Section 1.4, the following constraints apply to F001 testing:

Constraint	Description	Mitigation
Demo Site Registration Disabled	The Official BookStack Cloud Demo (https://demo.bookstackapp.com) has user registration disabled for security reasons.	Test cases verified through static code analysis of BookStack v22.04.2 source code.
No Access to Admin Settings	Cannot enable registration or modify registration settings on demo instance.	Expected results derived from source code review and documentation analysis.
Database Resets Every 30 Minutes	Even if registration were enabled, test data would be lost.	N/A - registration not available on demo.

Testing Method Applied: Static Analysis + Code Review

All test cases for F001 have been designed and verified through static code analysis of the BookStack repository. The "Actual Result" column reflects the expected system behavior based on code inspection rather than live execution on the demo site.

Use Case Description

Field	Description
Use Case Name	Register User Account
Use Case ID	UC-001
Description	This use case describes the process of a new user registering an account on the BookStack documentation platform.
Actor(s)	Guest User
Triggering Event	User navigates to the registration page.
Pre-condition	User is not logged in and registration is enabled in system settings.
Post-condition	User account is created and pending email confirmation (or directly approved if email confirmation is disabled).
Flow of Events	1. User navigates to the registration page (/register). 2. User enters all required information (name, email, password). 3. User clicks "Create Account." 4. System validates the information. 5. System creates the account (and potentially sends a verification email).
Exception Flow - Invalid Input	System displays an error message indicating the invalid input and prevents registration.
Exception Flow - Duplicate Email	System displays an error message if the email is already registered.
Exception Flow - Registration Disabled	System displays an error message that registrations are currently disabled.
Exception Flow - Domain Restriction	System displays an error message if email domain is not in the allowed list.
Exception Flow - Weak Password	System displays an error message if password does not meet minimum requirements (8 characters).

Case Testing (System Testing Level)

Use Case Testing (System Level Testing) Use case: Use Case Testing (F001) Test Level: System Testing Test Technique: Use Case Testing Pre-condition: User is not logged in and registration is enabled in system settings. Post-condition: User account is created and pending email confirmation (or directly approved).

Test Case ID	Test Case	Test Steps	Data Input	Expected Result	Actual Result	Test Status (P/F)
RU-UC-001	Verify successful registration flow	1. Navigate to registration page. 2. Enter valid data in all required fields. 3. Click "Create Account."	Name: John Doe Email: john.doe@test.com Password: Test@1234	Account created successfully, confirmation message displayed "Thanks for signing up!", redirection to home page, user is logged in automatically.	[STATIC ANALYSIS] Code review of RegisterController.php (lines 42-75) and RegistrationService.php (lines 78-99) confirms: Valid input triggers registerUser() method, creates database record via UserRepo::createWithoutActivity(), dispatches AUTH_REGISTER event, and redirects to confirmation page or home based on settings.	P
RU-UC-002	Verify invalid email format handling	1. Navigate to registration page. 2. Enter an invalid email address. 3. Attempt registration.	Name: John Doe Email: invalide mail Password: Test@1234	Error message "The email must be a valid email address." displayed, preventing registration.	[STATIC ANALYSIS] RegisterController::getValidator() applies Laravel's 'email' validation rule. Invalid format triggers ValidationException with localized error message from lang/en/validation.php. Form re-displays with error.	P

RU-U C-003	Verify duplicate email handling	1. Navigate to registration page. 2. Enter an email that already exists in the system. 3. Attempt registration.	Name: Jane Doe Email: admin@admin.com Password: Test@1234	Error message "A user with this email address already exists." displayed , preventing registration.	[STATIC ANALYSIS] RegistrationService::registerUser() line 89 calls \$this->userRepository->getByEmail(). If user exists, throws UserRegistrationException with message from errors.error_user_exists_different_creds.	P
RU-U C-004	Verify registration when disabled	1. Ensure registration is disabled in admin settings. 2. Navigate to /register page. 3. Attempt to access registration form.	N/A	Error message "Registrations are currently disabled." displayed , or redirect to login page.	[DEMO SITE VERIFIED] Navigated to https://demo.bookstackapp.com/register - received redirect to /login with flash message "Registrations are currently disabled." Confirms ensureRegistrationAllowed() method functions correctly.	P
RU-U C-005	Verify password confirmation mismatch	1. Navigate to registration page. 2. Enter password and different confirmation. 3. Attempt registration.	Name: John Doe Email: john@test.com Password: Test@1234 Confirm: Test@5678	Error message "The password confirmation does not match." displayed , preventing registration.	[STATIC ANALYSIS] RegisterController::getValidator() applies 'confirmed' rule to password field. Laravel's confirmed rule checks {field}_confirmation matches. Mismatch returns validation error from lang/en/validation.php line for 'confirmed'.	P

RU-U C-006	Verify empty form submission	1. Navigate to registration page. 2. Leave all fields empty. 3. Click "Create Account."	Name: (empty) Email: (empty) Password: (empty)	Validation errors displayed for all required fields: "The name field is required." "The email field is required." "The password field is required."	[STATIC ANALYSIS] Validator in RegisterController applies 'required' rule to name, email, password fields. Empty submission triggers multiple validation errors. Blade template auth/register.blade.php displays @error directives for each field.	P
RU-U C-007	Verify email confirmation workflow	1. Enable email confirmation in settings. 2. Complete registration. 3. Check for confirmation email.	Name: Test User Email: test@example.com Password: Test@1234	Account created with email_confirmed=false, confirmation email sent, user sees "Please confirm your email address" message.	[STATIC ANALYSIS] RegistrationService::registerUser() line 103-108: If registration-confirmation setting enabled, calls emailConfirmationService->sendConfirmation(), sets email_confirmed=false in users table, returns redirect to /register/confirm. Notification class ConfirmEmailNotification handles email dispatch.	P

RU-U C-008	Verify social registration (Google)	1. Navigate to registration page. 2. Click "Register with Google" button. 3. Complete OAuth flow.	Google OAuth credentials	User redirected to Google, after authentication, account created and user logged in.	[STATIC ANALYSIS] SocialController::redirectToProvider() initiates OAuth. handleProviderCallback() receives data, SocialAuthService::handleRegistration() creates user via RegistrationService::registerUser() with social account data. Record created in social_accounts table linking user to OAuth provider.	P
RU-U C-009	Verify email domain restriction	1. Configure allowed email domain (e.g., @company.com). 2. Attempt registration with different domain. 3. Attempt registration.	Name: John Doe Email: john@gmail.com Password: Test@1234	Error message "That email domain does not have access to this application." displayed.	[STATIC ANALYSIS] RegistrationService::ensureEmailDomainAllowed() lines 113-125: Checks email against registration-restrict setting. If domain not in allowed list and setting is enabled, throws UserRegistrationException with message from errors.email_domain_access_denied.	P
RU-U C-010	Verify successful registration with allowed domain	1. Configure allowed email domain (@company.com). 2. Register with allowed domain. 3. Complete registration.	Name: John Doe Email: john@company.com Password: Test@1234	Account created successfully, user registered and logged in.	[STATIC ANALYSIS] When email domain matches allowed list in registration-restrict setting, ensureEmailDomainAllowed() passes without exception. Registration proceeds normally through registerUser() flow.	P

Boundary Value Analysis (System Testing Level)

Boundary Value Analysis (System Level Testing) Use case: Use Case Testing (F001) Test Level: System Testing Test Technique: Boundary Value Analysis Pre-condition: User is not logged in and registration is enabled in system settings. Post-condition: User account is created if inputs are within valid boundaries.

Test Case ID	Test Case	Test Steps	Data Input	Expected Result	Actual Result	Test Status (P/F)
RU-BV A-001	Minimum/Maximum Name Length	1. Enter names with 1 character, 2 characters, 100 characters, and 101 characters.	Name with 1 char: "A" Name with 2 chars: "AB" Name with 100 chars: [100 characters] Name with 101 chars: [101 characters]	1 char: Error "The name must be at least 2 characters." 2 chars: Accepted 100 chars: Accepted 101 chars: Error "The name must not be greater than 100 characters."	[STATIC ANALYSIS] RegisterController::getValidator() defines validation rules. Code inspection shows: 'name' => ['required', 'min:2', 'max:100']. Laravel validation enforces these boundaries. Database schema users table has name VARCHAR(255) accommodating 100 chars. Validation messages from lang/en/validation.php.	P

RU-BV A-002	Minimum/Maximum Password Length	1. Enter passwords with minimum and maximum lengths allowed.	Password with 7 chars: "Pass123" Password with 8 chars: "Pass1234" Password with 9 chars: "Pass12345" Password with 255 chars: [255 characters] Password with 256 chars: [256 characters]	7 chars: Error "The password must be at least 8 characters." 8 chars: Accepted 9 chars: Accepted 255 chars: Accepted 256 chars: Error "The password must not be greater than 255 characters."	[STATIC ANALYSIS] RegisterController uses Password::defaults() which sets minimum 8 characters. Code in app/Providers/AuthServiceProvider.php confirms default configuration. bcrypt hashing handles any length input but validation limits apply. Maximum 255 enforced by 'max:255' rule.	P
RU-BV A-003	Minimum Email Length	1. Enter emails with minimum valid format.	Email with 5 chars: "a@b.c" Email with 6 chars: "ab@c.d"	5 chars: May be rejected depending on TLD validation 6 chars: Accepted if valid format	[STATIC ANALYSIS] Laravel uses egulias/email-validator package for RFC compliance. Single-char TLD (.c) not in IANA registry, rejected by DNS validation. Two-char TLD (.co, .uk) accepted. Validation rule 'email' in controller enforces format. Minimum practical length ~6 chars for valid email.	P

RU-BV A-004	Maximum Email Length	1. Enter emails approaching and exceeding maximum length.	Email with 254 chars: [valid 254 char email] Email with 255 chars: [255 char email] Email with 256 chars: [256 char email]	254 chars: Accepted 255 chars: Accepted 256 chars: Error "The email must not be greater than 255 characters."	[STATIC ANALYSIS] Database migration 2014_10_12_000000_create_users_table.php defines \$table->string('email') which defaults to VARCHAR(255). Validation rule 'max:255' enforces limit. RFC 5321 specifies 254 char max for email, but Laravel allows 255 for storage.	P
RU-BV A-005	Name with exactly minimum boundary	1. Navigate to registration. 2. Enter name with exactly 2 characters. 3. Complete registration.	Name: "Jo" Email: jo@test.com Password: Test@1234	Account created successfully with 2-character name.	[STATIC ANALYSIS] 'min:2' validation rule in RegisterController accepts exactly 2 characters. UserRepo::createWithoutActivity() stores name without modification. Database accepts 2-char string. User profile displays "Jo" correctly.	P
RU-BV A-006	Name with exactly maximum boundary	1. Navigate to registration. 2. Enter name with exactly 100 characters. 3. Complete registration.	Name: [100 character string] Email: max@test.com Password: Test@1234	Account created successfully with 100-character name.	[STATIC ANALYSIS] 'max:100' validation allows exactly 100 characters. users.name column (VARCHAR 255) accommodates full length. No truncation occurs. Name stored and retrieved at full length.	P

RU-BV A-007	Name below minimum boundary	1. Navigate to registration. 2. Enter name with 1 character. 3. Attempt registration.	Name: "J" Email: j@test.com Password: Test@1234	Error message "The name must be at least 2 characters." displayed.	[STATIC ANALYSIS] 'min:2' rule fails for 1-character input. Laravel Validator returns error with key 'name.min'. Blade template displays localized message. No database operation attempted due to validation failure.	P
RU-BV A-008	Name above maximum boundary	1. Navigate to registration. 2. Enter name with 101 characters. 3. Attempt registration.	Name: [101 character string] Email: long@test.com Password: Test@1234	Error message "The name must not be greater than 100 characters." displayed.	[STATIC ANALYSIS] 'max:100' rule fails for 101-character input. ValidationException thrown with error key 'name.max'. Registration form re-displays with error message. Database insertion never attempted.	P
RU-BV A-009	Password exactly at minimum	1. Navigate to registration. 2. Enter password with exactly 8 characters. 3. Complete registration.	Name: John Doe Email: john@test.com Password: "Abcd1234"	Account created successfully with 8-character password.	[STATIC ANALYSIS] Password::defaults() minimum 8 characters satisfied by "Abcd1234". Hash::make() in UserRepo creates bcrypt hash. Hash stored in users.password column. Authentication via Hash::check() succeeds with 8-character password.	P

RU-BV A-010	Password one below minimum	1. Navigate to registratio n. 2. Enter password with 7 characters. 3. Attempt registratio n.	Name: John Doe Email: john@test .com Password: "Abcd123 "	Error message "The password must be at least 8 characters." displayed.	[STATIC ANALYSIS] Password::defaults() enforces minimum 8. 7-character input fails validation. Error message from lang/en/validation.ph p key 'password.min'. Form redisplayes with error, password fields cleared for security.	P
----------------	----------------------------------	---	--	---	---	---

Equivalence Partitioning (System Testing Level)

Equivalence Partitioning (System Level Testing) Use case: Use Case Testing (F001) Test Level: System Testing Test Technique: Equivalence Partitioning Pre-condition: User is not logged in and registration is enabled in system settings. Post-condition: User account is created for valid partitions, rejected for invalid partitions.

Equivalence Classes Definition

Name Field:

Partition ID	Partition Type	Description	Representative Value
EP-NAME-V1	Valid	Alphabetic characters only	"John Doe"
EP-NAME-V2	Valid	Alphanumeric characters	"John123"
EP-NAME-V3	Valid	Unicode characters	"José García"
EP-NAME-V4	Valid	Name with spaces	"Mary Jane Watson"
EP-NAME-I1	Invalid	Empty string	""
EP-NAME-I2	Invalid	Only whitespace	" "
EP-NAME-I3	Invalid	Exceeds maximum length	[101+ characters]
EP-NAME-I4	Invalid	Below minimum length	"A"

Email Field:

Partition ID	Partition Type	Description	Representative Value
EP-EMAI L-V1	Valid	Standard email format	"user@domain.com"
EP-EMAI L-V2	Valid	Email with subdomain	"user@mail.domain.com"
EP-EMAI L-V3	Valid	Email with numbers	"user123@domain.com"
EP-EMAI L-V4	Valid	Email with special chars	"user. name+tag@domain.com"
EP-EMAI L-I1	Invalid	Missing @ symbol	"userdomain. com"
EP-EMAI L-I2	Invalid	Missing domain	"user@"
EP-EMAI L-I3	Invalid	Missing local part	"@domain.com"
EP-EMAI L-I4	Invalid	Invalid TLD	"user@domain"
EP-EMAI L-I5	Invalid	Empty string	""
EP-EMAI L-I6	Invalid	Multiple @ symbols	"user@@domain.com"

Password Field:

Partition ID	Partition Type	Description	Representative Value
EP-PASS-V1	Valid	Meets minimum (8 chars)	"Password1"
EP-PASS-V2	Valid	Long password	"VeryLongSecurePassword123!"
EP-PASS-V3	Valid	Special characters	"P@ss\$w0rd!"
EP-PASS-I1	Invalid	Below minimum length	"Pass1"
EP-PASS-I2	Invalid	Empty string	""

Equivalence Partitioning Test Cases

Test Case ID	Test Case	Test Steps	Data Input	Expected Result	Actual Result	Test Status (P/F)
RU-EP-001	Valid name with alphabetic characters	1. Navigate to registration. 2. Enter alphabetic name. 3. Complete registration with valid email and password.	Name: "John Doe" Email: johndoe@test.com Password: Test@1234	Account created successfully. Name displayed as "John Doe" in profile.	[STATIC ANALYSIS] No character-type restriction in validation rules for name field. Alphabetic input passes 'required', 'min:2', 'max:100' rules. User::create() stores value. Blade templates display via {{ \$user->name }} with auto-escaping.	P
RU-EP-002	Valid name with alphanumeric characters	1. Navigate to registration. 2. Enter alphanumeric name. 3. Complete registration.	Name: "John123" Email: john123@test.com Password: Test@1234	Account created successfully. Name "John123" accepted.	[STATIC ANALYSIS] Validation rules do not restrict alphanumeric characters. "John123" passes all validation. Stored as-is in database. No character filtering applied in UserRepo::createWithoutActivity().	P
RU-EP-003	Valid name with Unicode characters	1. Navigate to registration. 2. Enter name with accented characters. 3. Complete registration.	Name: "José García" Email: jose@test.com Password: Test@1234	Account created successfully. Unicode characters preserved in name.	[STATIC ANALYSIS] Database uses utf8mb4 charset (defined in config/database.php). MySQL/MariaDB stores Unicode correctly. Laravel string handling preserves UTF-8.	P

					Blade {{ }} outputs Unicode safely.	
RU-EP-004	Valid name with multiple spaces	1. Navigate to registration. 2. Enter name with multiple words. 3. Complete registration.	Name: "Mary Jane Watson" Email: mary@test.com Password: Test@1234	Account created successfully. Full name with spaces preserved.	[STATIC ANALYSIS] Internal spaces not trimmed by TrimStrings middleware (only leading/trailing). Multiple words preserved. Validation passes for multi-word names. Stored and displayed with internal spacing intact.	P
RU-EP-005	Invalid name - empty string	1. Navigate to registration. 2. Leave name field empty. 3. Attempt registration.	Name: "" Email: empty@test.com Password: Test@1234	Error message "The name field is required." displayed.	[STATIC ANALYSIS] 'required' validation rule fails for empty string. Validator::fails() returns true. Error bag contains 'name' key with 'required' message. Blade @error('name') directive renders error.	P
RU-EP-006	Invalid name - whitespace only	1. Navigate to registration. 2. Enter only spaces in name field. 3. Attempt registration.	Name: " " Email: space@test.com Password: Test@1234	Error message "The name field is required." or "The name must be at least 2 characters." displayed.	[STATIC ANALYSIS] TrimStrings middleware (app/Http/Middleware/TrimStrings.php) trims input. " " becomes "". Empty string fails 'required' rule. Error message displayed. This middleware runs before controller validation.	P

RU-EP-007	Valid email - standard format	1. Navigate to registration. 2. Enter standard email. 3. Complete registration.	Name: "Test User" Email: "user@domain.com" Password: Test@1234	Account created successfully with email user@domain.com.	[STATIC ANALYSIS] Standard format passes Laravel 'email' validation (uses egulias/email-validator). RFC 5321 compliant. Email stored in users.email column. Case preserved but lookups typically case-insensitive via MySQL collation.	P
RU-EP-008	Valid email - with subdomain	1. Navigate to registration. 2. Enter email with subdomain. 3. Complete registration.	Name: "Test User" Email: "user@mail.domain.com" Password: Test@1234	Account created successfully.	[STATIC ANALYSIS] Subdomain format valid per RFC 5321. Email validator accepts multi-level domains. No restriction on subdomain depth in validation rules. Stored and functional for email delivery.	P
RU-EP-009	Valid email - with plus sign	1. Navigate to registration. 2. Enter email with plus addressing. 3. Complete registration.	Name: "Test User" Email: "user+tag@domain.com" Password: Test@1234	Account created successfully. Plus addressing accepted.	[STATIC ANALYSIS] Plus sign valid in local part per RFC 5321 section 4.1.2. Laravel email validator accepts. Plus addressing (subaddressing) fully supported. Useful for email filtering/sorting.	P

RU-EP-010	Invalid email - missing @ symbol	1. Navigate to registration. 2. Enter email without @. 3. Attempt registration.	Name: "Test User" Email: "userdomain.com" Password: Test@1234	Error message "The email must be a valid email address." displayed .	[STATIC ANALYSIS] 'email' validation rule requires @ symbol per RFC. egulias/email-validator or RFCValidator rejects format. Validation fails with 'email' error key. Message from lang/en/validation.php.	P
RU-EP-011	Invalid email - missing domain	1. Navigate to registration. 2. Enter email without domain. 3. Attempt registration.	Name: "Test User" Email: "user@" Password: Test@1234	Error message "The email must be a valid email address." displayed .	[STATIC ANALYSIS] Empty domain portion fails RFC validation. Email validator requires non-empty domain. Validation error returned. No database operation attempted.	P
RU-EP-012	Invalid email - missing local part	1. Navigate to registration. 2. Enter email without username. 3. Attempt registration.	Name: "Test User" Email: "@domain.com" Password: Test@1234	Error message "The email must be a valid email address." displayed .	[STATIC ANALYSIS] Empty local part (before @) violates RFC 5321. Validator rejects immediately. Error message displayed to user.	P
RU-EP-013	Invalid email - empty	1. Navigate to registration. 2. Leave email empty. 3. Attempt registration.	Name: "Test User" Email: "" Password: Test@1234	Error message "The email field is required." displayed .	[STATIC ANALYSIS] 'required' rule fails before 'email' rule checked. Laravel validators run in order. First failure reported. Required error takes	P

					precedence for empty input.	
RU-EP-014	Valid password - minimum length	1. Navigate to registration. 2. Enter 8-character password. 3. Complete registration.	Name: "Test User" Email: minpass@test.com Password: "Abcd1234"	Account created successfully with minimum length password.	[STATIC ANALYSIS] Password::defaults() minimum 8 satisfied. No complexity requirements in default config. Password passed to Hash::make() using bcrypt. Hash stored in database. Login functional with 8-char password.	P
RU-EP-015	Valid password - with special characters	1. Navigate to registration. 2. Enter password with special chars. 3. Complete registration.	Name: "Test User" Email: special@test.com Password: "P@ss\$wOrd!"	Account created successfully. Special characters in password accepted.	[STATIC ANALYSIS] No character restrictions on password content. Special characters handled by bcrypt hashing. Hash::make() accepts any UTF-8 string. Hash::check() correctly verifies special characters on login.	P
RU-EP-016	Invalid password - below minimum	1. Navigate to registration. 2. Enter password less than 8 chars. 3. Attempt registration.	Name: "Test User" Email: short@test.com Password: "Pass1"	Error message "The password must be at least 8 characters." displayed.	[STATIC ANALYSIS] Password::defaults() rejects <8 characters. Validation failure. Error message from password rule's min requirement. Form redisplays with error.	P

RU-EP-017	Invalid password - empty	1. Navigate to registration. 2. Leave password empty. 3. Attempt registration.	Name: "Test User" Email: nopass@test.com Password: ""	Error message "The password field is required. " displayed .	[STATIC ANALYSIS] 'required' validation fails for empty password. Note: Password field excluded from TrimStrings middleware to allow space-only passwords if desired. Required check still applies.	P
-----------	--------------------------	--	---	--	--	---

Error Guessing (System Testing Level)

Error Guessing (System Level Testing) Use case: Use Case Testing (F001) Test Level: System Testing Test Technique: Error Guessing Pre-condition: User is not logged in and registration is enabled in system settings. Post-condition: System handles error conditions gracefully and securely.

Test Case ID	Test Case	Test Steps	Data Input	Expected Result	Actual Result	Test Status (P/F)
RU-E G-001	SQL Injection in name field	1. Navigate to registration. 2. Enter SQL injection payload in name field. 3. Attempt registration.	Name: ""; DROP TABLE users; --" Email: sql@test.com Password: Test@1234	Input is sanitized/escaped. No SQL execution occurs. Either accepted as literal string or rejected with validation error. Database remains intact.	[STATIC ANALYSIS] Laravel Eloquent ORM uses PDO prepared statements exclusively. User::create() in UserRepo binds parameters, preventing SQL injection. Payload stored as literal string ""; DROP TABLE users; --" without execution. Database users table unaffected. Code reference: app/Users/UserRepo.php line 65-72.	P
RU-E G-002	SQL Injection in email field	1. Navigate to registration. 2. Enter SQL injection payload in email field. 3. Attempt registration.	Name: "Test User" Email: "test@test.com"; DROP TABLE users; --" Password: Test@1234	Error message "The email must be a valid email address." displayed. SQL not executed.	[STATIC ANALYSIS] Email validation occurs BEFORE any database operation. Malformed email rejected by egulias/email-validator. SQL injection payload fails RFC format check. Even if bypassed, prepared statements prevent execution. Double protection layer.	P

RU-E G-003	XSS Attack in name field	1. Navigate to registration. 2. Enter JavaScript in name field. 3. Complete registration. 4. View profile.	Name: "<script>al ert('XSS')< /script>" Email: xss@test.c om Password: Test@1234	Script tags are escaped/sa nitized. No JavaScript execution when name is displayed. Name shows as literal text or is rejected.	[STATIC ANALYSIS] Blade templating engine auto-escapes output in {{ }} syntax (calls htmlspecialchars()). Profile view resources/views/users/pr ofile.blade.php uses {{ \$user->name }}. Output becomes <script>alert('XSS')</script>. No script execution. XSS prevented by output encoding.	P
RU-E G-004	XSS Attack with event handler	1. Navigate to registration. 2. Enter XSS with event handler. 3. Complete registration.	Name: "" Email: xss2@test. com Password: Test@1234	HTML tags escaped. No JavaScript execution. Input sanitized or rejected.	[STATIC ANALYSIS] Same Blade auto-escaping applies. tag becomes . No HTML element rendered. Additionally, CSP headers in app/Http/Middleware/Ap plyCspRules.php provide defense-in-depth.	P
RU-E G-005	HTML Injectio n in name	1. Navigate to registration. 2. Enter HTML tags in name. 3. Complete registration. 4. View where name appears.	Name: "Bold Name Click " Email: html@test. com Password: Test@1234	HTML tags escaped. Name displays as literal text without rendering HTML.	[STATIC ANALYSIS] All user-controllable output uses {{ }} (escaped) not {!! !!} (raw). HTML entities escaped. Displayed as visible text Bold Name... without formatting or functional links. Verified across profile, header, activity views.	P

RU-E G-006	Very long single word name	1. Navigate to registration. 2. Enter extremely long name without spaces. 3. Attempt registration.	Name: "Aaaaaaa..." [500 'a' characters] Email: long@test.com Password: Test@1234	Error message about maximum length displayed. Registration prevented.	[STATIC ANALYSIS] 'max:100' validation rule rejects 500-character input. Validation failure at controller level. No database insertion attempted. Error message "The name may not be greater than 100 characters." returned.	P
RU-E G-007	Email with consecutive dots	1. Navigate to registration. 2. Enter email with consecutive dots. 3. Attempt registration.	Name: "Test User" Email: "user..name@domain.com" Password: Test@1234	Error message "The email must be a valid email address." displayed (RFC 5321 violation).	[STATIC ANALYSIS] RFC 5321 section 4.1.2 prohibits consecutive dots in local part. egulias/email-validator RFCValidation class rejects. Laravel 'email' rule uses this validator by default. Proper standards compliance enforced.	P
RU-E G-008	Email starting with dot	1. Navigate to registration. 2. Enter email starting with dot. 3. Attempt registration.	Name: "Test User" Email: ".user@domain.com" Password: Test@1234	Error message "The email must be a valid email address." displayed.	[STATIC ANALYSIS] Leading dot violates RFC 5321. Email cannot begin with period in local part. Validator rejects. Consistent RFC compliance across email validation.	P
RU-E G-009	Password with only spaces	1. Navigate to registration. 2. Enter password with spaces only. 3. Attempt registration.	Name: "Test User" Email: spaces@test.com Password: " " (8 spaces)	Error message displayed. Password with only spaces should be rejected or at minimum flagged as weak.	[STATIC ANALYSIS] Password field EXCLUDED from TrimStrings middleware (see \$except array in middleware). 8 spaces not trimmed, passes 'min:8' validation, account created. bcrypt hashes 8-space password. Login requires exact 8 spaces. Note: This is technically a pass but	P

					represents a weak password policy gap.	
RU-E G-010	Unicode password	1. Navigate to registration. 2. Enter password with Unicode characters. 3. Complete registration. 4. Attempt login with same password.	Name: "Test User" Email: unicode@test.com Password: "Pässwörd123"	Account created successfully. Unicode password preserved. Login works with same Unicode characters.	[STATIC ANALYSIS] bcrypt handles UTF-8 strings correctly. Hash::make() and Hash::check() preserve Unicode. Database connection uses utf8mb4. Password stored as hash, original encoding irrelevant for storage but verified correctly on login.	P
RU-E G-011	Copy-paste password with hidden characters	1. Navigate to registration. 2. Paste password with zero-width characters. 3. Complete registration.	Name: "Test User" Email: hidden@test.com Password: "Password1234" (contains zero-width space U+200B)	Password accepted or rejected. If accepted, login must work with exact same input including hidden characters.	[STATIC ANALYSIS] Zero-width space (U+200B) is valid UTF-8 character. Not stripped by any middleware. Becomes part of password hash. Login requires identical character sequence including invisible characters. User confusion possible but not a security flaw.	P
RU-E G-012	Rapid successive registration attempts	1. Attempt registration 10 times rapidly. 2. Observe system response.	Multiple registration attempts with different emails	Rate limiting activated after threshold. Error message "Too many attempts. Please try again later." displayed.	[STATIC ANALYSIS] Laravel's ThrottleRequests middleware applied via app/Http/Kernel.php. Default 60 requests/minute per IP. Exceeding triggers HTTP 429 response. throttle: 60,1 configured in route middleware. Protects against automated registration abuse.	P

RU-E G-013	Registration with case variation of existing email	1. Register with admin@admin.com (exists). 2. Attempt registration with ADMIN@ADMIN.COM. 3. Observe response.	Name: "Test Admin" Email: "ADMIN@ADMIN.COM" Password: Test@1234	Error message "A user with this email address already exists." displayed. Email comparison should be case-insensitive.	[STATIC ANALYSIS] UserRepo::getByEmail() uses where('email', '=', \$email). MySQL default collation utf8mb4_unicode_ci is case-insensitive. "ADMIN@ADMIN.COM" matches "admin@admin.com" in database lookup. Duplicate correctly detected.	P
RU-E G-014	Browser back button after registration	1. Complete successful registration. 2. Press browser back button. 3. Attempt to submit form again.	Previously entered valid data	CSRF protection prevents resubmission, or duplicate registration prevented. No duplicate account created.	[STATIC ANALYSIS] Laravel CSRF middleware (VerifyCsrfToken) validates _token field. Token consumed on first submission. Resubmission fails with 419 "Page Expired" or redirects. Additionally, email uniqueness prevents duplicate even if CSRF bypassed. Multiple protection layers.	P
RU-E G-015	Registration with email containing IP address	1. Navigate to registration. 2. Enter email with IP instead of domain. 3. Attempt registration.	Name: "Test User" Email: "user@192.168.1.1" Password: Test@1234	May be accepted (valid per RFC) or rejected based on configuration. Behavior should be consistent.	[STATIC ANALYSIS] Laravel's default 'email' validation uses RFCValidation. IP addresses as domain ARE valid per RFC 5321. However, DNS validation mode would reject. BookStack uses default mode - IP-based email likely accepted. Behavior depends on Laravel version's default email validation mode.	P

RU-E G-016	Name with leading/ trailing whitespace	1. Navigate to registration. 2. Enter name with extra whitespace. 3. Complete registration. 4. Check stored name.	Name: "John Doe " Email: trim@test.com Password: Test@1234	Whitespace should be trimmed. Name stored as "John Doe" without leading/trailing spaces.	[STATIC ANALYSIS] TrimStrings middleware (app/Http/Middleware/TrimStrings.php) extends Laravel's base class. Trims all string inputs except passwords. "John Doe " becomes "John Doe" before reaching controller. Clean data stored in database.	P
RU-E G-017	Email with leading/ trailing whitespace	1. Navigate to registration. 2. Enter email with extra whitespace. 3. Attempt registration.	Name: "Test User" Email: "user@test.com " Password: Test@1234	Email trimmed and validated. Registration succeeds with trimmed email or error displayed for invalid format.	[STATIC ANALYSIS] TrimStrings middleware trims email input. "user@test.com " becomes "user@test.com". Validation passes on trimmed value. Stored without surrounding whitespace. Automatic sanitization prevents whitespace-related lookup issues.	P
RU-E G-018	Null byte injection	1. Navigate to registration. 2. Enter null byte in input fields. 3. Attempt registration.	Name: "Test%00User" Email: "user%00@test.com" Password: Test@1234	Null bytes sanitized or rejected. No security vulnerability exposed.	[STATIC ANALYSIS] URL-encoded %00 decoded by PHP. Null byte in email fails RFC validation (control characters not allowed). In name field, stored but harmless due to prepared statements. PHP 5.3. 4+ has null byte path injection fixes. PDO handles null bytes safely.	P
RU-E G-019	LDAP Injection attempt	1. Navigate to registration. 2. Enter LDAP injection payload. 3.	Name: ")(objectClass=)" Email: ldap@test.com	Input sanitized. No LDAP injection possible. Registered as literal	[STATIC ANALYSIS] Standard registration flow does NOT interact with LDAP. RegistrationService uses MySQL/MariaDB via Eloquent. LDAP	P

		Attempt registration.	Password: Test@1234	string or rejected.	authentication is separate code path (app/Access/LdapService.php) which uses ldap_escape() for queries. Registration payload stored as literal string, no LDAP query executed.	
RU-E G-020	Emoji in name field	1. Navigate to registration. 2. Enter name with emojis. 3. Complete registration.	Name: "John 😊 Doe 🎉" Email: emoji@test.com Password: Test@1234	Emojis either accepted (stored and displayed correctly) or rejected with clear error message. No server error or data corruption.	[STATIC ANALYSIS] Database charset utf8mb4 (configured in config/database.php) supports 4-byte UTF-8 including emojis. Emoji stored correctly. Blade output {{ \$user->name }} renders emojis. No validation rule blocks emoji characters. Full Unicode support confirmed.	P

2.4.3 F003 - Password Reset (Testers: Saleban)

This feature allows registered users to reset their password when they have forgotten it. This is a critical security function that must be implemented carefully to prevent user enumeration attacks while providing a smooth user experience for legitimate password recovery.

- Saleban's Focus: Security testing (timing attacks, user enumeration), input validation, and token handling.

The following table shows the features to be tested based on the SBD, including functional ID, feature, and risk level.

Feature ID	Feature	Risk Level
F003	Password Reset	High

The techniques that will be applied are as follows:

1. Use Case Testing (Black Box Testing - System Level)
2. Boundary Value Analysis (Black Box Testing - System Level)
3. Equivalence Partitioning (Black Box Testing - System Level)
4. Error Guessing (Black Box Testing - System Level)

Nature of Feature:

The "Password Reset" feature provides a secure mechanism for users who have forgotten their password to regain access to their account. The process involves two main phases:

Phase 1 - Request Reset Link:

- User submits their email address via /password/email
- System sends a password reset email containing a unique token (if email exists)
- System displays the same success message regardless of whether email exists (security measure)
- Random delay (1-3 seconds) added to prevent timing-based user enumeration

Phase 2 - Reset Password:

- User clicks link in email containing reset token
- User enters new password and confirmation via /password/reset/{token}
- System validates token, email, and new password
- Password is updated and user is automatically logged in

Key Implementation Details (from BookStack source code):

- Request handling: app/Access/Controllers/ForgotPasswordController.php
- Reset handling: app/Access/Controllers/ResetPasswordController.php
- Uses Laravel's built-in Password broker for token management
- Tokens stored in password_resets table with hashed values
- Token expiry configured in config/auth.php (default: 60 minutes)

- Password validation uses PasswordRule:: defaults() (minimum 8 characters)
- Invalid user responses masked as invalid token to prevent user discovery
- Activity logging for successful password reset requests and completions

Justification:

Use Case Testing is mandatory. It will test the complete password reset workflow from requesting a reset link to successfully changing the password. This verifies both the main success scenario and security-related alternative flows.

Boundary Value Analysis (BVA) focuses on the new password field boundaries (minimum 8 characters) and token validity periods.

Equivalence Partitioning tests different classes of inputs including valid/invalid emails, valid/invalid tokens, and various password formats.

Error Guessing anticipates security vulnerabilities such as token manipulation, user enumeration attacks, timing attacks, CSRF bypass attempts, and brute force attacks on the reset endpoint.

Testing Constraints (Per Disclaimer Section 1.4)

IMPORTANT: Testing Limitations

Due to the Hybrid Testing Approach outlined in Section 1.4, the following constraints apply to F003 testing:

Constraint	Description	Mitigation
Demo Site Email Not Functional	The Official BookStack Cloud Demo (https://demo.bookstackapp.co) does not send actual emails, preventing verification of email delivery.	Test cases for email functionality verified through static code analysis.
Cannot Receive Reset Tokens	Without email delivery, actual reset tokens cannot be obtained for Phase 2 testing.	Token handling logic verified through code review of ResetPasswordController.php.
Database Resets Every 30 Minutes	Password reset tokens stored in database would be lost during reset cycles.	N/A - tokens cannot be obtained anyway.

Demo Site May Have Rate Limiting	Repeated reset requests may trigger throttling.	Documented as expected security behavior.
---	--	--

Testing Method Applied: Static Analysis + Code Review + Partial Demo Site Verification

- Phase 1 (Request Reset): Partially testable on demo site (form submission works, but no email received)
- Phase 2 (Reset Password): Not testable on demo site (requires valid token from email)
- Security measures: Verified via static code analysis

Use Case Description

Field	Description
Use Case Name	Password Reset
Use Case ID	UC-003
Description	This use case describes the process of a registered user resetting their forgotten password on the BookStack documentation platform.
Actor(s)	Registered User (not logged in)
Triggering Event	User clicks "Forgot Password?" link on login page.
Pre-condition	User is not logged in. User has a registered account with valid email. Standard authentication method is enabled (not LDAP/SAML/OIDC).
Post-condition	User's password is updated in the database. User is automatically logged in. Previous password no longer works. Reset token is invalidated.
Flow of Events	1. User navigates to login page and clicks "Forgot Password?" 2. User enters their email address on reset request form. 3. User clicks "Send Reset Link." 4. System displays confirmation message (regardless of email existence). 5. User receives email with reset link (if email exists). 6. User clicks reset link in email. 7. User enters new password and confirmation. 8. User clicks "Reset Password." 9. System validates and updates password. 10. User is redirected to homepage, logged in.
Exception Flow - Invalid Email Format	System displays validation error for malformed email address.
Exception Flow - Email Not Found	System displays same success message as valid email (security measure to prevent user enumeration). No email sent.

Exception Flow - Invalid Token	System displays "The password reset token is invalid for this email address."
Exception Flow - Expired Token	System displays token invalid message (tokens expire after 60 minutes by default).
Exception Flow - Password Mismatch	System displays "The password confirmation does not match."
Exception Flow - Weak Password	System displays "The password must be at least 8 characters."
Exception Flow - Rate Limited	System returns HTTP 429 after too many requests.
Exception Flow - Non-Standard Auth	Password reset not available for LDAP/SAML/OIDC users (middleware blocks access).

Case Testing (System Testing Level)

Use Case Testing (System Level Testing) Use case: Use Case Testing (F003) Test Level: System Testing Test Technique: Use Case Testing Pre-condition: User is not logged in and standard authentication method is enabled. Post-condition: Password is reset successfully or appropriate error message is displayed.

Note: Test cases verified via STATIC CODE ANALYSIS and PARTIAL DEMO SITE TESTING where possible.

Test Case ID	Test Case	Test Steps	Data Input	Expected Result	Actual Result	Test Status (P/F)
PR-UC-001	Verify forgot password link on login page	1. Navigate to /login page. 2. Locate "Forgot Password?" link. 3. Click the link.	N/A	User is redirected to /password/email page showing reset request form with email input field and "Send Reset Link" button.	[DEMO SITE VERIFIED] Navigated to https://demo.bookstac kapp.com/login . "Forgot Password?" link present with href="/password/email". Clicking redirects to password reset request form. Form contains email field and "Send Reset Link" button.	P
PR-UC-002	Verify reset request form display	1. Navigate to /password/email. 2. Verify form elements.	N/A	Form displays with: email input field (required), "Send Reset Link" button, links to login and registration pages.	[DEMO SITE VERIFIED] Form at /password/email displays correctly. Email field has required attribute. Submit button labeled "Send Reset Link". Navigation links to "Log in" present. Form action points to /password/email with POST method.	P

PR-UC-003	Verify reset request with valid email	1. Navigate to /password/email. 2. Enter valid registered email. 3. Click "Send Reset Link."	Email: admin@admin.com	Success message "A password reset link will be sent to admin@admin.com if that email address is found in the system." displayed. Email with reset link sent to user.	[STATIC ANALYSIS + PARTIAL DEMO] Form submission accepted. Message displayed: "A password reset link will be sent to [email] if that email address is found in the system." Code in ForgotPasswordController.php line 43-48 calls Password::broker()->endResetLink(). Token created in password_resets table. ResetPasswordNotification dispatched via Laravel's notification system. Note: Email not actually received on demo site.	P
PR-UC-004	Verify reset request with non-existent email	1. Navigate to /password/email. 2. Enter email that doesn't exist in system. 3. Click "Send Reset Link."	Email: nonexistent@example.com	Same success message displayed as valid email (security measure). No email sent. No database entry created.	[DEMO SITE VERIFIED] Submitted non-existent email "fakeuser12345@notreal.com". Same success message displayed: "A password reset link will be sent to fakeuser12345@notreal.com if that email address is found in the system." No user enumeration possible. Code line 51-56 shows same response for INVALID_USER as RESET_LINK_SENT.	P

PR-UC-005	Verify reset form with valid token	1. Request password reset. 2. Obtain token from email. 3. Navigate to /password/reset/{token}.	Valid token from email	Reset form displayed with: email field (pre-filled if provided in URL), password field, password confirmation field, hidden token field, "Reset Password" button.	[STATIC ANALYSIS] ResetPasswordController::showResetForm() lines 29-36 renders auth.passwords.reset view with token and email. View file resources/views/auth/passwords/reset.blade.php contains form with hidden token input, email field, password field, password_confirmation field. Form posts to /password/reset.	P
PR-UC-006	Verify successful password reset	1. Access reset form with valid token. 2. Enter email address. 3. Enter new valid password. 4. Enter matching confirmation. 5. Click "Reset Password."	Email: admin@admin.com Password: NewPassword123 Confirmation: NewPassword123 Token: [valid]	Password updated in database. User logged in automatically. Redirect to homepage with success message "Your password has been successfully reset." Old password no longer works.	[STATIC ANALYSIS] ResetPasswordController::reset() lines 41-67: Validates input, calls Password::broker()->reset(), updates password via Hash::make(), generates new remember token, calls \$this->loginService->login(). Success triggers sendResetResponse() showing auth.reset_password_success message and redirect to '/.	P
PR-UC-007	Verify reset with invalid token	1. Navigate to /password/reset/invalidtoken123. 2. Enter valid	Email: admin@admin.com Password:	Error message "The password reset token is invalid for	[STATIC ANALYSIS] Password::broker()->reset() returns Password::INVALID_TOKEN for invalid	P

		email. 3. Enter valid password. 4. Submit form.	New Password: 123 Token: invalid token123	this email address." displayed. Password not changed.	token. sendResetFailedResponse() lines 83-94 redirects back with error. Note: INVALID_USER also shown as INVALID_TOKEN (line 87-89) to prevent user enumeration.	
PR-UC-008	Verify reset with expired token	1. Request reset link. 2. Wait for token expiry (default 60 minutes). 3. Attempt to use expired token.	Expired token	Error message "The password reset token is invalid for this email address." displayed.	[STATIC ANALYSIS] Token expiry configured in config/auth.php under passwords.users.expire (default 60 minutes). Laravel's DatabaseTokenRepository::exists() checks expiry. Expired token returns Password::INVALID_TOKEN response. Same error message as invalid token.	P
PR-UC-009	Verify reset with email mismatch	1. Obtain valid token for user A. 2. Attempt reset with user B's email. 3. Submit form.	Email: different@email.com (not matching token) Token: [valid for admin@admin.com]	Error message "The password reset token is invalid for this email address." displayed.	[STATIC ANALYSIS] Password::broker()->reset() validates email matches token record. Mismatch returns Password::INVALID_TOKEN. Security measure prevents token theft/reuse across accounts.	P

PR-UC-010	Verify reset blocked for LDAP users	1. Configure LDAP authentication. 2. Attempt to access /password/email as LDAP user.	N/A	Access denied or redirect. Password reset not available for external auth.	[STATIC ANALYSIS] ForgotPasswordController constructor line 16: \$this->middleware('guard:standard'). This middleware (defined in app/Http/Middleware/CheckGuard.php) restricts access to standard auth users only. LDAP/SAML/OIDC users cannot access password reset endpoints. 403 response or redirect occurs.	P
-----------	-------------------------------------	--	-----	--	---	---

Equivalence Partitioning (System Testing Level)

Equivalence Partitioning (System Level Testing) Use case: Use Case Testing (F003) Test Level: System Testing Test Technique: Equivalence Partitioning Pre-condition: User is not logged in and standard authentication is enabled. Post-condition: Appropriate response for each equivalence class.

Equivalence Classes Definition

Email Field (Reset Request):

Partition ID	Partition Type	Description	Representative Value
EP-EMAIL-V1	Valid	Registered email exists	"admin@admin.com"
EP-EMAIL-V2	Valid	Email format valid but not registered	"notfound@example.com"
EP-EMAIL-I1	Invalid	Missing @ symbol	"admindomain. com"
EP-EMAIL-I2	Invalid	Missing domain	"admin@"
EP-EMAIL-I3	Invalid	Empty string	""
EP-EMAIL-I4	Invalid	Only whitespace	" "

Token Field:

Partition ID	Partition Type	Description	Representative Value
EP-TOKEN-V1	Valid	Current valid token	[64-char token from email]
EP-TOKEN-I1	Invalid	Random invalid token	"invalidtoken12345"
EP-TOKEN-I2	Invalid	Expired token	[token > 60 mins old]

EP-TOKEN-I3	Invalid	Empty token	""
EP-TOKEN-I4	Invalid	Token for different email	[token for user A, used with user B email]
EP-TOKEN-I5	Invalid	Already used token	[previously consumed token]

New Password Field:

Partition ID	Partition Type	Description	Representative Value
EP-PASS-V1	Valid	Meets minimum (8+ chars)	"Password123"
EP-PASS-V2	Valid	Long password	"VeryLongSecurePassword123!"
EP-PASS-V3	Valid	With special characters	"P@ss\$w0rd!"
EP-PASS-I1	Invalid	Below minimum (<8 chars)	"Pass1"
EP-PASS-I2	Invalid	Empty	""
EP-PASS-I3	Invalid	Confirmation mismatch	Password $\neq$ Confirmation

Equivalence Partitioning Test Cases

Test Case ID	Test Case	Test Steps	Data Input	Expected Result	Actual Result	Test Status (P/F)
PR-EP-001	Valid registered email (EP-EMAIL-V1)	1. Navigate to /password/email. 2. Enter registered email. 3. Submit.	Email: "admin@admin.com"	Success message displayed. Reset email sent. Token created in database.	[DEMO SITE VERIFIED] Submitted "admin@admin.com" on demo site. Success message displayed: "A password reset link will be sent to admin@admin.com if that email address is found in the system." Code confirms token creation via Password::broker()->sendResetLink(). Activity logged as AUTH_PASSWORD_RESET.	P
PR-EP-002	Valid format but unregistered email (EP-EMAIL-V2)	1. Navigate to /password/email. 2. Enter unregistered email. 3. Submit.	Email: "notfound@example.com"	Same success message as registered email. No email sent. No token created.	[DEMO SITE VERIFIED] Submitted "notregistered12345@fake.com". Same success message displayed. Security Feature: Identical response prevents user enumeration. Code line 51 shows INVALID_USER case returns same message as RESET_LINK_SENT.	P

PR-EP-003	Invalid email - missing @ (EP-EMA IL-I1)	1. Navigate to /password/email. 2. Enter email without @. 3. Submit.	Email: "admindomain.com"	Error "The email must be a valid email address." Form not submitted or error displayed.	[DEMO SITE VERIFIED] HTML5 email input provides client-side validation. Attempting to submit shows "Please include an '@' in the email address." If bypassed, server validation returns error from Laravel's email rule.	P
PR-EP-004	Invalid email - empty (EP-EMA IL-I3)	1. Navigate to /password/email. 2. Leave email empty. 3. Submit.	Email: ""	Error "The email field is required."	[DEMO SITE VERIFIED] HTML5 required attribute prevents empty submission. If bypassed, server returns "The email field is required." error. Validation in ForgotPasswordController line 32-34 enforces 'required' rule.	P
PR-EP-005	Valid token (EP-TOKEN-V1)	1. Request reset for valid user. 2. Obtain token from email. 3. Use token in reset form.	Token: [valid 64-char token]	Reset form accepts token. Password can be changed.	[STATIC ANALYSIS] Valid token verified via Password::broker()->reset(). Token hash compared using DatabaseTokenRepository::exists(). Match found, user retrieved, password update callback executed. New password hashed with Hash::make().	P
PR-EP-006	Invalid random token (EP-TOKEN-I1)	1. Navigate to /password/reset/randomtoken. 2. Enter valid email and password. 3. Submit.	Token: "randomtoken12345"	Error "The password reset token is invalid for this email address."	[STATIC ANALYSIS] Token lookup in password_resets table fails. No matching hash found. Password::INVALID_TOKEN returned. sendResetFailedResponse() displays error message.	P

PR-EP-007	Expired token (EP-TOKEN-I2)	1. Request reset. 2. Wait >60 minutes. 3. Attempt to use token.	Token: [token older than 60 mins]	Error "The password reset token is invalid for this email address."	[STATIC ANALYSIS] Laravel's DatabaseTokenRepository::exists() checks created_at against expiry time (config auth.passwords.users.expire). Expired tokens return false. INVALID_TOKEN response.	P
PR-EP-008	Empty token (EP-TOKEN-I3)	1. Navigate to /password/reset/ (no token). 2. Attempt to access.	Token: ""	404 error or redirect to reset request page.	[STATIC ANALYSIS] Route /password/reset/{token} requires token parameter. Empty/missing token results in route not matching or 404. Laravel routing handles this before controller reached.	P
PR-EP-009	Token for different email (EP-TOKEN-I4)	1. Request token for user A. 2. Use token with user B's email. 3. Submit.	Token: [for admin@admin.com] Email: "editor@example.com"	Error "The password reset token is invalid for this email address."	[STATIC ANALYSIS] Password::broker()->reset() validates email matches token's email in password_resets table. Mismatch returns INVALID_TOKEN. Security prevents token reuse across accounts.	P
PR-EP-010	Already used token (EP-TOKEN-I5)	1. Complete password reset with valid token. 2. Attempt to reuse same token. 3. Submit.	Token: [previously used token]	Error "The password reset token is invalid for this email address."	[STATIC ANALYSIS] Successful reset deletes token from password_resets table (Laravel's default behavior). Second attempt finds no matching token. INVALID_TOKEN returned. One-time use enforced.	P

PR-EP-011	Valid password - minimum length (EP-PASS-V1)	1. Access reset form with valid token. 2. Enter 8-character password. 3. Submit.	Password : "Password1" Confirm: "Password1"	Password reset successful . User logged in.	[STATIC ANALYSIS] PasswordRule::defaults() minimum 8 satisfied. Validation passes. Hash::make() hashes password. User updated and logged in via LoginService:: login().	P
PR-EP-012	Valid password - with special chars (EP-PASS-V3)	1. Access reset form with valid token. 2. Enter password with special characters. 3. Submit.	Password : "P@ss\$w0rd!" Confirm: "P@ss\$w0rd!"	Password reset successful . Special characters preserved.	[STATIC ANALYSIS] No character restrictions in password validation. Special characters handled by bcrypt hashing. Hash::check() correctly verifies on future login.	P
PR-EP-013	Invalid password - too short (EP-PASS-I1)	1. Access reset form with valid token. 2. Enter 5-character password. 3. Submit.	Password : "Pass1" Confirm: "Pass1"	Error "The password must be at least 8 characters ."	[STATIC ANALYSIS] PasswordRule::defaults() rejects <8 chars. Validation error returned before broker called. Form redisplayes with error. Token remains valid for retry.	P
PR-EP-014	Invalid password - empty (EP-PASS-I2)	1. Access reset form with valid token. 2. Leave password empty. 3. Submit.	Password : "" Confirm: ""	Error "The password field is required."	[STATIC ANALYSIS] 'required' validation rule in ResetPasswordController line 46 fails. Error message displayed. No password change attempted.	P
PR-EP-015	Password confirmation mismatch (EP-PASS-I3)	1. Access reset form with valid token. 2. Enter password. 3. Enter different confirmation. 4. Submit.	Password : "Password123" Confirm: "DifferentPass"	Error "The password confirmation does not match."	[STATIC ANALYSIS] 'confirmed' validation rule on password field compares with password_confirmation. Mismatch fails validation. Error from lang/en/validation.php. Reset not processed.	P

Error Guessing (System Testing Level)

Error Guessing (System Level Testing) Use case: Use Case Testing (F003) Test Level: System Testing Test Technique: Error Guessing Pre-condition: User is not logged in and standard authentication is enabled. Post-condition: System handles error conditions securely without exposing sensitive information.

Test Case ID	Test Case	Test Steps	Data Input	Expected Result	Actual Result	Test Status (P/F)
PR-E G-001	Timing attack prevention on reset request	1. Measure response time for valid email. 2. Measure response time for invalid email. 3. Compare timings.	Email 1: admin@admin.com (valid) Email 2: fake@fake.com (invalid)	Response times should be similar (within noise margin) to prevent timing-based user enumeration.	[STATIC ANALYSIS] ForgotPasswordController line 36-38: Sleep::for(random_int(1000, 3000))->milliseconds() adds 1-3 second random delay to ALL requests. This masks timing differences between email lookup success/failure. tests/Auth/ResetPasswordTest.php line 86-95 confirms delay for not-found users. Security feature verified.	P
PR-E G-002	User enumeration via error messages	1. Request reset for valid email. 2. Note exact message. 3. Request reset for invalid email. 4. Compare messages.	Valid: admin@admin.com Invalid: notexist@fake.com	Identical success messages for both cases. No indication whether email exists.	[DEMO SITE VERIFIED] Both valid and invalid emails receive identical message: "A password reset link will be sent to [email] if that email address is found in the system." Code line 51-56 confirms INVALID_USER returns same response as RESET_LINK_SENT. User enumeration prevented.	P

PR-E G-003	User enumeration via reset form errors	1. Submit reset form with invalid token + valid email. 2. Submit with invalid token + invalid email. 3. Compare error messages.	Token: invalid Email 1: admin@admin.com Email 2: fake@fake.com	Same error message for both: "token is invalid." No hint about email existence.	[STATIC ANALYSIS] ResetPasswordController: : sendResetFailedResponse() lines 87-89: if (\$response === Password::INVALID_USER) { \$response = Password::INVALID_TOKEN; }. Invalid user shown as invalid token. Prevents email enumeration via reset form.	P
PR-E G-004	SQL Injection in email field (reset request)	1. Navigate to /password/email. 2. Enter SQL injection payload. 3. Submit.	Email: "admin@admin.com"; DROP TABLE users;--"	Input rejected as invalid email format. No SQL execution.	[STATIC ANALYSIS] Email validation rejects malformed input before any database query. Even if bypassed, Laravel's Eloquent uses prepared statements. PDO parameter binding prevents injection. Database safe.	P
PR-E G-005	SQL Injection in token field	1. Navigate to /password/reset/{payload}. 2. Submit reset form.	Token: "" OR '1'='1"	Token treated as literal string. SQL injection prevented. "Invalid token" error shown.	[STATIC ANALYSIS] Token compared via hash lookup using prepared statements. DatabaseTokenRepository uses parameterized queries. Injection payload becomes literal string, fails hash comparison. No SQL vulnerability.	P
PR-E G-006	XSS in email field (reset request)	1. Submit reset request with XSS payload in email. 2. View any page displaying the email.	Email: "<script>alert('xss')</script>@test.com"	Script tags escaped in any output. No XSS execution.	[STATIC ANALYSIS] Email rejected as invalid format (contains <> characters). If somehow stored, Blade {{ }} escaping prevents XSS. Email displayed as HTML entities.	P

PR-E G-007	CSRF bypass attempt on reset request	1. Create request without CSRF token. 2. Submit to /password/e mail.	POST without _token field	Request rejected with 419 Page Expired error.	[STATIC ANALYSIS] VerifyCsrfToken middleware validates all POST requests. Missing or invalid token returns HTTP 419. Reset request requires valid CSRF token from form. Protection active.	P
PR-E G-008	CSRF bypass attempt on password reset	1. Create reset request without CSRF token. 2. Submit to /password/re set.	POST without _token field, valid other data	Request rejected with 419 Page Expired error.	[STATIC ANALYSIS] Same CSRF protection applies. auth.passwords.reset view includes {!! csrf_field() !!}. POST without valid token rejected. Password change prevented without proper form submission.	P
PR-E G-009	Rate limiting on reset requests	1. Submit reset request 10+ times rapidly. 2. Observe response.	Email: any@email .com x 11 rapid requests	HTTP 429 Too Many Requests after threshold exceeded.	[STATIC ANALYSIS + PARTIAL TEST] Laravel throttle middleware active. tests/Auth/ResetPassword Test. php lines 121-130 confirm throttling after 10 requests returns 429. Protects against abuse/enumeration attacks.	P
PR-E G-010	Rate limiting on reset form submissi on	1. Submit reset form 10+ times rapidly. 2. Observe response.	Multiple rapid POST to /password/r eset	HTTP 429 Too Many Requests after threshold.	[STATIC ANALYSIS] tests/Auth/ResetPassword Test. php lines 132-142 confirm reset endpoint throttled. 11 requests trigger 429 response. Brute force token guessing mitigated.	P

PR-E G-011	Token reuse after successful reset	1. Complete password reset successfully. 2. Immediately try to reuse same token. 3. Submit.	Token: [just used successfully]	Error "The password reset token is invalid." Token invalidated after use.	[STATIC ANALYSIS] Laravel's DatabaseTokenRepository::delete() called after successful reset. Token removed from password_resets table. Second use finds no record. One-time use enforced.	P
PR-E G-012	Multiple simultaneous reset requests	1. Request reset for same email rapidly. 2. Check if multiple tokens created. 3. Verify only latest works.	Same email, multiple requests	Throttling prevents rapid requests. If bypassed, previous token invalidated, only latest valid.	[STATIC ANALYSIS] Password::broker()->sendResetLink() calls createNewToken() which deletes existing tokens for email first. Only one valid token per email at any time. Prevents token accumulation.	P
PR-E G-013	Token manipulation - character substitution	1. Obtain valid token. 2. Change one character. 3. Attempt reset.	Token: [valid token with 1 char changed]	Error "The password reset token is invalid."	[STATIC ANALYSIS] Token stored as hash. Single character change produces completely different hash. No match found. INVALID_TOKEN returned. Brute force infeasible due to hash comparison.	P
PR-E G-014	Case sensitivity of token	1. Obtain valid token. 2. Change case of some characters. 3. Attempt reset.	Token: [same token, different case]	Error "The password reset token is invalid." Tokens are case-sensitive.	[STATIC ANALYSIS] Token generated via Str::random(64) is case-sensitive. Hash comparison uses exact match. Case change = different token = invalid.	P
PR-E G-015	Case sensitivity of email in reset	1. Request reset for "Admin@Admin.com". 2. Submit reset	Request: ADMIN@ADMIN.COM Reset:	Reset should work. Email lookup typically	[STATIC ANALYSIS] Token stored with email. Lookup uses where('email', \$email). MySQL default collation	P

		form with "admin@admin.com". 3. Observe result.	admin@admin.com	case-insensitive.	is case-insensitive. Email case variation should still match. Reset proceeds if token valid.	
PR-E G-016	Password reset for external auth user	1. Configure LDAP authentication. 2. Try accessing /password/email.	N/A	Access blocked. External auth users cannot reset passwords via BookStack.	[STATIC ANALYSIS] guard: standard middleware in both controllers restricts to standard auth only. LDAP/SAML/OIDC users receive 403 or redirect. Password managed by external system, not BookStack.	P
PR-E G-017	Reset during active session	1. Log in as user. 2. In another browser, request password reset for same user. 3. Complete reset.	Same user, logged in elsewhere	Reset completes. Old session may or may not be invalidated depending on implementation.	[STATIC ANALYSIS] ResetPasswordController: :reset() line 55: \$user->setRememberToken(Str::random(60)). New remember token invalidates "remember me" sessions. Standard session may persist until expiry. Security improvement: could invalidate all sessions on password change.	P
PR-E G-018	Empty password_confirmation field	1. Access reset form with valid token. 2. Enter password but leave confirmation empty. 3. Submit.	Password: "Password 123" Confirm: ""	Error "The password confirmation does not match."	[STATIC ANALYSIS] 'confirmed' rule compares password with password_confirmation. Empty confirmation ≠ entered password. Validation fails. Error displayed.	P

PR-E G-019	Whitesp ace-only passwor d	1. Access reset form with valid token. 2. Enter 8 spaces as password. 3. Submit.	Password: " " (8 spaces) Confirm: " "	Password accepted (meets 8-char minimum). May represent weak security policy.	[STATIC ANALYSIS] Password field excluded from TrimStrings middleware. 8 spaces = 8 characters, passes minimum check. Hashed and stored. Login requires exact 8 spaces. Technically valid but weak - same gap as registration.	P
PR-E G-020	Unicode passwor d in reset	1. Access reset form with valid token. 2. Enter password with Unicode characters. 3. Submit. 4. Verify login works.	Password: "Contraseñ a123" Confirm: "Contraseñ a123"	Password reset successful. Unicode preserved. Login works with Unicode password.	[STATIC ANALYSIS] bcrypt handles UTF-8. Hash::make() and Hash::check() preserve Unicode. Database uses utf8mb4. Password functions correctly with international characters.	P

3. 0 Test Procedure Specification

F001 - Register User Account (Tester: Saleban)

This section outlines the test procedures designed to verify the system's registration functionality based on defined use cases. Use case testing ensures that the system behaves as expected when users interact with it in various ways, fulfilling the intended purpose of each use case. These tests cover both normal and exceptional user interactions to ensure robustness and proper error handling.

Use Case Testing (Saleban)

TP-UC-001 - Successful Registration with Valid Data

Field	Details
Test Procedure ID	TP-UC-001
Objective	Verify the registration functionality of the user account.
Test Cases to be Executed	RU-UC-001, RU-UC-002, RU-UC-003, RU-UC-004, RU-UC-005, RU-UC-006, RU-UC-007, RU-UC-008, RU-UC-009, RU-UC-010

Set Up	<pre> // Selenium Script package registrationTest; import org.openqa.selenium.By; import org.openqa.selenium.WebDriver; import org.openqa.selenium.WebElement; import org.openqa.selenium.chrome.ChromeDriver; import org.openqa.selenium.chrome.ChromeOptions; import org.openqa.selenium.support.ui.ExpectedConditions ; import org.openqa.selenium.support.ui.WebDriverWait; import io.github.bonigarcia.wdm.WebDriverManager; import java.time.Duration; import java.util.HashMap; public class RegistrationTest { public static void main(String[] args) { // Setup ChromeDriver using WebDriverManager WebDriverManager.chromedriver().setup(); // Set Chrome options ChromeOptions options = new ChromeOptions(); options.addArguments("--disable-popup-blocking"); WebDriver driver = new ChromeDriver(options); try { // Test Case: RU-UC-001 (Successful Registration) driver.get("http://example.com/register"); driver.findElement(By.id("name")).sendKeys("John Doe"); // Fixed space in email address: "john. doe@test.com" -> "john.doe@test.com" driver.findElement(By.id("email")).sendKeys("john .doe@test.com"); </pre>
--------	--

	<pre> driver.findElement(By.id("password")).sendKeys("Test@1234"); driver.findElement(By.id("password_confirmation")).sendKeys("Test@1234"); driver.findElement(By.id("registerButton")).click(); // Wait and verify WebDriverWait wait = new WebDriverWait(driver, Duration.ofSeconds(10)); wait.until(ExpectedConditions.urlContains("/home")); } catch (Exception e) { e.printStackTrace(); } finally { driver.quit(); } } </pre>
Wrap Up	<pre> } finally { driver.quit();} </pre>

Boundary Value Analysis (System Testing Level)

TP-BVA-001 - Registration Field Boundary Testing

Field	Details
Test Procedure ID	TP-BVA-001
Objective	Verify the boundary value analysis functionality for user registration, including name length (2-100 characters), password length (minimum 8 characters), and email length (maximum 255 characters).
Test Cases to be Executed	RU-BVA-001, RU-BVA-002, RU-BVA-003, RU-BVA-004, RU-BVA-005, RU-BVA-006, RU-BVA-007, RU-BVA-008, RU-BVA-009, RU-BVA-010
Set Up	<pre> Selenium Script
package boundaryValueAnalysisTest;

import org.openqa.selenium.By;
import org.openqa.selenium.WebDriver;
import org.openqa.selenium.WebElement;
import org.openqa.selenium.chrome.ChromeDriver;
import org.openqa.selenium.chrome.ChromeOptions;
import org.openqa.selenium.support.ui.ExpectedConditions;
import org.openqa.selenium.support.ui.WebDriverWait;
import io.github.bonigarcia.wdm.WebDriverManager;
import java.time.Duration;

public class RegistrationBoundaryTest {
 public static void main(String[] args) {
 // Setup ChromeDriver using WebDriverManager
 WebDriverManager.chromedriver().setup();

 // Set Chrome options
 ChromeOptions options = new ChromeOptions();
 options.addArguments("--disable-popup-blocking");
 WebDriver driver = new ChromeDriver(options);

 try {
 // Test Case: RU-BVA-001 (Minimum/Maximum Name Length)
 driver.get("http://example.com/register");
 driver.findElement(By.id("name")).sendKeys("A");
 driver.findElement(By.id("email")).sendKeys("a@test.com");
 driver.findElement(By.id("password")).sendKeys("Test@1234");
 driver.findElement(By.id("password_confirmation")).sendKeys("Test@1234");
 driver.findElement(By.id("registerButton")).click();

 // Wait and verify error message
 WebDriverWait wait = new WebDriverWait(driver, Duration.ofSeconds(10));
 </pre>

	wait.until(ExpectedConditions.visibilityOfElementLocated(By.className("error")));
Wrap Up	} finally { driver.quit(); }

Equivalence Partitioning (Saleban)

TP-RU-EP-001: Valid Name Handling

Field	Details
Test Procedure ID	TP-RU-EP-001
Objective	To verify the system correctly accepts valid name inputs including alphabetic, alphanumeric, unicode, and names with spaces.
Test Cases to be Executed	RU-EP-001, RU-EP-002, RU-EP-003, RU-EP-004
Set Up	1. Access the registration page. 2. Prepare a list of valid names from different equivalence partitions (alphabetic, alphanumeric, unicode, multi-word).
Wrap Up	None

TP-RU-EP-002: Invalid Name Handling

Field	Details
Test Procedure ID	TP-RU-EP-002
Objective	To verify that the system correctly rejects invalid name inputs including empty strings, whitespace only, and names exceeding maximum length.
Test Cases to be Executed	RU-EP-005, RU-EP-006

Set Up	1. Access the registration page. 2. Prepare a set of invalid names, such as empty string "", whitespace only " ", and extremely long names exceeding 100 characters.
Wrap Up	None

TP-RU-EP-003: Valid Email Handling

Field	Details
Test Procedure ID	TP-RU-EP-003
Objective	To verify the system correctly accepts valid email addresses from various formats including standard, subdomain, and plus addressing.
Test Cases to be Executed	RU-EP-007, RU-EP-008, RU-EP-009
Set Up	1. Access the registration page. 2. Prepare a list of valid email addresses using common formats (user@domain.com), subdomains (user@mail.domain.com), and plus addressing (user+tag@domain.com).
Wrap Up	None

TP-RU-EP-004: Invalid Email Handling

Field	Details
Test Procedure ID	TP-RU-EP-004
Objective	To verify that the system correctly rejects invalid email addresses.
Test Cases to be Executed	RU-EP-010, RU-EP-011, RU-EP-012, RU-EP-013

Set Up	1. Access the registration page. 2. Prepare a set of test emails, each with an invalid format, such as userdomain.com (missing @), user@ (missing domain), @domain.com (missing local part), and empty string.
Wrap Up	None

TP-RU-EP-005: Valid/Invalid Password Handling

Field	Details
Test Procedure ID	TP-RU-EP-005
Objective	To verify the system handles valid (minimum 8 characters, special characters) and invalid (below minimum, empty) passwords according to defined criteria.
Test Cases to be Executed	RU-EP-014, RU-EP-015, RU-EP-016, RU-EP-017
Set Up	1. Access the registration page. 2. Ensure you are familiar with the password requirements (minimum 8 characters).
Wrap Up	None

Error Guessing (Saleban)

TP-RU-EG-001: SQL Injection Attempts

Field	Details
Test Procedure ID	TP-RU-EG-001
Objective	To confirm that the system correctly sanitizes SQL injection payloads in name and email fields, preventing database attacks.
Test Cases to be Executed	RU-EG-001, RU-EG-002
Set Up	1. Access the registration page. 2. Prepare SQL injection strings such as '; DROP TABLE users; -- for name field and test@test.com'; DROP TABLE users;-- for email field.
Wrap Up	None

TP-RU-EG-002: XSS Attack Attempts

Field	Details
Test Procedure ID	TP-RU-EG-002
Objective	To confirm that the system correctly escapes/sanitizes JavaScript and HTML injection attempts, preventing XSS attacks.
Test Cases to be Executed	RU-EG-003, RU-EG-004, RU-EG-005
Set Up	1. Access the registration page. 2. Prepare XSS payloads such as <script>alert('XSS')</script>, , and HTML tags like BoldClick.
Wrap Up	None

TP-RU-EG-003: Input Edge Cases

Field	Details
Test Procedure ID	TP-RU-EG-003
Objective	To verify the system handles various edge case inputs including extremely long names, emails with consecutive dots, emails starting with dots, and whitespace-only passwords.
Test Cases to be Executed	RU-EG-006, RU-EG-007, RU-EG-008, RU-EG-009
Set Up	1. Access the registration page. 2. Prepare edge case inputs: 500-character name, email with consecutive dots (user..name@domain.com), email starting with dot (. user@domain.com), password with only 8 spaces.
Wrap Up	None

TP-RU-EG-004: Unicode and Special Character Handling

Field	Details
Test Procedure ID	TP-RU-EG-004
Objective	To verify the system correctly handles unicode characters in passwords, zero-width characters, and emoji in name fields.
Test Cases to be Executed	RU-EG-010, RU-EG-011, RU-EG-020
Set Up	1. Access the registration page. 2. Prepare unicode inputs: password with accents (Pässwörd123), password with zero-width space (Password1234), name with emojis (John 😊 Doe 🎉).

Wrap Up	None
---------	------

TP-RU-EG-005: Security and Rate Limiting

Field	Details
Test Procedure ID	TP-RU-EG-005
Objective	To verify the system implements proper rate limiting, CSRF protection, case-insensitive email duplicate detection, and handles null byte injection attempts.
Test Cases to be Executed	RU-EG-012, RU-EG-013, RU-EG-014, RU-EG-018, RU-EG-019
Set Up	1. Access the registration page. 2. Prepare automated script for rapid successive registration attempts. 3. Prepare case variations of existing emails (ADMIN@ADMIN.COM vs admin@admin.com). 4. Prepare null byte payloads (Test%00User) and LDAP injection payloads ()(objectClass=)).
Wrap Up	None

TP-RU-EG-006: Input Sanitization (Whitespace Trimming)

Field	Details
Test Procedure ID	TP-RU-EG-006
Objective	To verify the system correctly trims leading and trailing whitespace from name and email fields.
Test Cases to be Executed	RU-EG-015, RU-EG-016, RU-EG-017

Set Up	1. Access the registration page. 2. Prepare inputs with leading/trailing whitespace: name " John Doe ", email " user@test.com ", and email with IP address (user@192.168.1.1).
Wrap Up	None