

Practice: Exploring Significant Predictors

Open the file VSSTeamData.jmp in JMP. Make sure that the five outliers for Yield are hidden and excluded.

1. Select **Fit Model** on the Analyze menu to fit a model for **MFI**, and use all of the continuous predictors (**SA** through **Ambient Temp**) as model effects.

Which of the predictors are significant (with p-values < 0.05)?

M%, **Xf**, **SA**, and **pH** are significant. All four of these predictors have a *p*-value less than 0.05. **Ambient Temp** is close, with a *p*-value of 0.065.

2. The Effect Summary table reports p-values. It also reports the log worth statistic. The higher the log worth statistic, the lower the *p*-value. The blue line in the Effect Summary table is drawn at a log worth of 2.0. This is equivalent to a *p*-value of 0.01.

Based on the log worth statistic in the Effect Summary table, which predictor is the most significant?

M% is most the significant, with a LogWorth of 26.265, followed by **Xf**.

3. Select the **Prediction Profiler** from the top red triangle by selecting **Factor Profiling** and then **Profiler**. Drag the red vertical line for **M%** to the lowest value (**M%** = 0), and then drag it to the highest value (**M%** = 3.67). Do not change the values for the other predictors. As you drag the line, observe how the response, **MFI**, changes.

How does the response, MFI, change as you change M% from its lowest value to its highest value (holding everything else constant)?

It increases by approximately six units. The predicted value for MFI changes from 195.56 to 201.45.

Hide Solution

Close