

Message Administration

This screen is a copy of the Event Messages screen found in every Guidewire application.

Suspend	Resume	Restart Messaging Engine		
<input type="checkbox"/>	Destination ▾	ID ▾	Status ▾	Server Id ▾
<input type="checkbox"/>	Safe Ordering Demo	20	Started	rchiriboga-p53
<input type="checkbox"/>	Message Generator	21	Started	rchiriboga-p53
<input type="checkbox"/>	Fraud Check	30	Started	rchiriboga-p53



Solution 1: Configure an event aware entity and destination

1. Verify ABContact entity delegates to EventAware delegate.

There are two approaches to verify that **ABContact** delegates to **EventAware**:

- Use the data dictionary, or

ABContact (ab_abcontact) (delegates to [ABLinkable](#), [CommonContact](#), [DestructionRootPinnable](#), [EventAware](#), [Validatable](#))

► Description

Attributes: Abstract[?], Editable[?], Exportable[?], Extendable[?], Keyed[?], Loadable[?], Sourceable[?], Supertype[?], Versionable[?]

Messaging Events: The application will generate these events for this entity:

- ABContactResync
- ABContactPendingChangeRejected
- ABContactCreatedApproved
- PersonalDataPurge
- ABContactAdded
- ABContactChanged
- ABContactRemoved

- Verify event delegate was added to **ABContact.eti** file.

This is a read-only file.

Element	Primary Value
onetoone	RetiredMergedContactPair
events	
event	ABContactResync
event	ABContactPendingChangeRejected
event	ABContactCreatedApproved
event	PersonalDataPurge



Important!

Four custom events also exist.

2. Create a new messaging destination called Fraud Check.

- Open **messaging-config.xml** under **configuration.config.Messaging**.
- Click the **PLUS** symbol to create a new destination.
- Populate the required fields:
 - ID = 30
 - Name = Fraud Check
 - Transport Plugin = DefaultPrintToConsoleTransport
 - Events
 - ABContactChanged
 - ABContactAdded



Important!

Do not change default connectivity and error parameters.

ID	Name
65	Java.MessageDestination.Email.Name
70	Java.MessageDestination.PolicySystemTransport.Name
71	Java.MessageDestination.ClaimSystemTransport.Name
72	Java.MessageDestination.BillingSystemTransport.Name
324	Java.MessageDestination.DocumentStore.Name
13	Bank Account Verification
14	Vendor Recommendation
15	Legal Case Report
20	Safe Ordering Demo
21	Message Generator
30	Fraud Check

ID:	30	<input type="button" value="^"/>	<input type="button" value="▼"/>
Environment:			
Name:	Fraud Check	<input type="button" value="^"/>	<input type="button" value="▼"/>
Server:	Host Name:	<input type="button" value="▼"/>	
Transport Plugin:	DefaultPrintToConsoleTransport	<input type="button" value="^"/>	<input type="button" value="▼"/>

Events:	+	-
		ABContactChanged
		ABContactAdded

3. Deploy code changes.

- a) From the Studio menu, **Restart** the server.