✅ DAILY START STEPS (FOLLOW EVERY TIME)

🔹 STEP 1: Start Docker

Open:

👉 Docker Desktop

Wait until:

Docker is running ✅

🔹 STEP 2: Start Kubernetes Cluster

```
minikube start --driver=docker
```

🔹 STEP 3: Check Cluster

```
kubectl get nodes
```

👉 Should show:

```
minikube   Ready
```

🔹 STEP 4: Check if Pods Already Running

```
kubectl get pods
```

✅ Case A: Pods are RUNNING

👉 You DO NOT need to rebuild or redeploy
👉 Just go to Step 6

❌ Case B: No Pods

👉 Deploy again:

```
kubectl apply -f k8s/
```

Wait:

```
kubectl get pods
```

👉 All should be:

Running

🔹 **STEP 5 (Optional): Rebuild (ONLY if code changed)**

```
eval $(minikube docker-env)

docker build -t user-service ./user-service
docker build -t menu-service ./menu-service
docker build -t order-service ./order-service
docker build -t frontend ./frontend

kubectl rollout restart deployment/frontend
kubectl rollout restart deployment/user-service
kubectl rollout restart deployment/menu-service
kubectl rollout restart deployment/order-service
```

🔹 **STEP 6: Start Port Forwarding**

Open **4 terminals**

Terminal 1

```
kubectl port-forward service/user-service 5000:5000
```

Terminal 2

```
kubectl port-forward service/menu-service 5001:5001
```

Terminal 3

kubectl port-forward service/order-service 5002:5002

Terminal 4

kubectl port-forward service/frontend 3000:3000

🔹 **STEP 7: Open App**

http://localhost:3000

🎯 **DONE**

Your app will work exactly like before ✅

🧠 **SHORTCUT VERSION (REMEMBER THIS)**

1. Start Docker
2. minikube start
3. kubectl get pods
4. (if needed) kubectl apply -f k8s/
5. port-forward
6. open localhost:3000

🚨 **WHEN TO RESET (Rare)**

Only if broken:

minikube delete

💡 **PRO TIP (VERY IMPORTANT)**

👉 Kubernetes **keeps everything saved**

So normally you only need:

minikube start
kubectl port-forward ...