

Coolguy and Two Subsequences

Coolguy gives you a simple problem. Given a 1 -indexed array, A , containing N elements, what will ans be after this pseudocode is implemented and executed? Print $ans \% (10^9+7)$.

```
//f(a, b) is a function that returns the minimum element in interval [a, b]

ans = 0

for a -> [1, n]
  for b -> [a, n]
    for c -> [b + 1, n]
      for d -> [c, n]
        ans = ans + min(f(a, b), f(c, d))
```

Input Format

The first line contains N (the size of array A).
The second line contains N space-separated integers describing A .

Constraints

- $1 \leq N \leq 2 \times 10^5$
- $1 \leq A_i \leq 10^9$

Note: A is 1 -indexed (i.e.: $A = \{ A_1, A_2, \dots, A_{N-1}, A_N \}$).

Output Format

Print the integer result of $ans \% (10^9+7)$.

Sample Input

```
3
3 2 1
```

Sample Output

```
6
```

Explanation

$$\begin{aligned} \min(f(1, 1), f(2, 2)) &= 2 \\ \min(f(1, 1), f(2, 3)) &= 1 \\ \min(f(1, 1), f(3, 3)) &= 1 \\ \min(f(1, 2), f(3, 3)) &= 1 \\ \min(f(2, 2), f(3, 3)) &= 1 \end{aligned}$$

We then sum these numbers ($2 + 1 + 1 + 1 + 1 = 6$) and print $6 \% (10^9+7)$, which is 6 .