# Semantic Log Analytics for UAV Flight Logs

## Treating flight logs as a database problem

Sumit Kumar (22CS30056)

Advanced Database Management Systems, term project

github.com/SumitKumar-17/UAVLog

# Motivation: flight logs are a database problem

### Three kinds of data at once

- **Time series**: 300 PX4 flights hold **70.7 M** telemetry samples
- **Text**: 3,401 events (warnings, failure flags, mode changes)
- **Vendor dialects**: PX4 and ArduPilot name the same quantity differently

### What people need

- Questions across many flights, asked in words: *"which flights lost a motor?"*
- Existing tools plot **one log at a time**
- Answers that are exact, explainable, and safe to run on the data

# Research questions and contributions

### Four questions, each answered by an experiment

- **RQ1** How should high-rate telemetry be stored, and at what cost?
- **RQ2** Which vector index and filtering strategy retrieve events best?
- **RQ3** Can a model write safe, correct SQL; what does a semantic layer add?
- **RQ4** Do the event detectors find faults of known size?

### Contributions

- One PostgreSQL schema for telemetry, ontology, events and embeddings
- A measured columnstore design and engine comparison
- A self-routing hybrid search and a filtered-search study
- A four-layer guarded NL-to-SQL with a measured evaluation

# Background: TimescaleDB

## Concepts

- **Hypertable**: one logical table cut into time *chunks*
- **Columnstore**: old chunks stored column-wise and compressed, grouped by `segmentby` and sorted by `orderby`
- **Continuous aggregate**: incrementally maintained rollup (here min, max, mean per second)

## Why it fits telemetry

- Slowly changing sensor values compress to a few bytes
- Queries for one signal of one flight read one compressed segment, not the table
- Postgres features stay: SQL, joins, transactions, roles

# Background: vector search in Postgres

### Index families

- **HNSW**: layered proximity graph; hop toward the query
- **IVFFlat**: sort vectors into clusters; probe the nearest few
- **DiskANN** (pgvectorscale): compressed graph built for disk
- Quality measure: **recall@k** against exact search


### The filtering pitfall

- The index finds neighbours **first**; the SQL filter is applied **after**
- A selective filter can leave fewer rows than requested
- Remedies: iterative scan, exact sort, partial indexes, partitions (all measured here)

# The gap and the architecture

## Gap in existing work

- Log viewers: one flight, no semantics
- Time-series stores: no ontology or vendor mapping
- NL-to-SQL demos: rarely guarded or measured
- To our knowledge no published system combines all three over PX4 logs



# The data


### Corpus

- 300 flights chosen (seeded, stratified) from 478,918 public Flight Review logs; CC-BY
- 8.75 GB of PX4 ULog files, parsed to a Parquet raw layer and the canonical telemetry table
- 70,731,891 telemetry rows, 3,401 events

### Second autopilot

- An ArduPilot MAVLink log is ingested through the same ontology
- It shows the vendor mapping at work: one canonical signal name for both autopilots
- Gaps are documented, not guessed (see the semantic layer)

# Relational schema


flight
event
text
timestamptz
float8
text
points
vendor_field
smallint
text
text
concept
int
text
text
text

# DDL: the telemetry hypertable

### Narrow long format

A new signal adds rows, never columns, and a new autopilot needs no schema change; the ontology maps vendor names to `vendor_field_id`. Seven-day chunks. As a plain rowstore the **index (7.6 GB) was larger than the table (4.9 GB)**.

```
    # ---- Telemetry: only ontology-mapped ("hot") fields; full-rate raw stays in Parquet ----
    op.execute("""
    CREATE TABLE telemetry (
        flight_id       uuid     NOT NULL REFERENCES flight(id) ON DELETE CASCADE,
        ts              timestamptz NOT NULL,
        vendor_field_id smallint NOT NULL REFERENCES vendor_field(id),
        value           double precision NOT NULL
    )""")
    op.execute("""
    SELECT create_hypertable('telemetry', by_range('ts', INTERVAL '7 days'))
    """)
    op.execute("CREATE INDEX telemetry_flight_field_ts ON telemetry (flight_id, vendor_field_id, ts
     DESC)")

    # ---- Semantic view: telemetry expressed in canonical concepts ----
    op.execute("""
    CREATE VIEW canonical_telemetry AS
```

# Inspecting the hypertable: dimensions and columnstore settings

### Reading

One time dimension on `ts` with 7-day chunks, 134 chunks, columnstore enabled and segmented by flight and field, ordered by time.

```
uavlog=# SELECT hypertable_name, num_dimensions, num_chunks, compression_enabled FROM
     timescaledb_information...
 hypertable_name | num_dimensions | num_chunks | compression_enabled
-----------------+----------------+------------+---------------------
 telemetry       |              1 |        134 | t
(1 row)

uavlog=# SELECT column_name, time_interval FROM timescaledb_information.dimensions;
 hypertable_name | column_name | time_interval
-----------------+-------------+---------------
 telemetry       | ts          | 7 days
(1 row)

uavlog=# SELECT * FROM timescaledb_information.hypertable_columnstore_settings;
 hypertable |         segmentby          | orderby
------------+----------------------------+---------
 telemetry  | flight_id,vendor_field_id | ts
(1 row)
```

# Inspecting the hypertable: chunks

### Reading

All chunks are compressed. The earliest ranges (1970, 2005) come from logs with wrong device clocks; they are kept, in their own chunks, and the duration estimate ignores them.

```
uavlog=# SELECT chunk_name, range_start::date, range_end::date, is_compressed FROM timescaledb_information.
     ch...
     chunk_name     | range_start | range_end  | is_compressed
--------------------+-------------+------------+---------------
 _hyper_1_66_chunk  | 1970-01-01  | 1970-01-08 | t
 _hyper_1_38_chunk  | 1970-01-15  | 1970-01-22 | t
 _hyper_1_90_chunk  | 2005-08-25  | 2005-09-01 | t
 _hyper_1_133_chunk | 2014-12-04  | 2014-12-11 | t
 _hyper_1_158_chunk | 2019-08-22  | 2019-08-29 | t
 _hyper_1_100_chunk | 2021-02-18  | 2021-02-25 | t
 _hyper_1_160_chunk | 2022-04-07  | 2022-04-14 | t
 _hyper_1_162_chunk | 2023-04-13  | 2023-04-20 | t
(8 rows)
```

# The event table, as the database reports it

```
uavlog=# \d+ event
                                                                                                  Table "public.
     event"
     Column      |           Type           | Collation | Nullable |
     Defaul...
-----------------+--------------------------+-----------+----------+-------------------------------------...

 id              | bigint                   |           | not null | nextval('event_id_seq'::regclass)
       ...
 flight_id       | uuid                     |           | not null |
       ...
 kind_id         | integer                  |           | not null |
       ...
 ts_start        | timestamp with time zone |           | not null |
       ...
 ts_end          | timestamp with time zone |           | not null |
       ...
 severity        | smallint                 |           | not null | 0
       ...
 source          | text                     |           | not null |
       ...
 attrs           | jsonb                    |           | not null | '{}'::jsonb
       ...
 description     | text                     |           | not null |
       ...
 tsv             | tsvector                 |           |          | generated always as (to_tsvector('
     englis...
 embedding       | vector(1536)             |           |          |
```

# Indexes on the search tables

### Reading

One HNSW index on event embeddings (13 MB), one GIN index on the generated `tsvector`, B-trees for flight, kind and time filters, and a small HNSW index on flight signatures.

```
uavlog=# -- indexes of the semantic search tables
         index          | method |    size
------------------------+--------+------------
 event_embedding_hnsw   | hnsw   | 13 MB
 event_tsv              | gin    | 296 kB
 event_flight_ts        | btree  | 296 kB
 event_pkey             | btree  | 224 kB
 event_kind_ts          | btree  | 224 kB
 flight_signature_hnsw  | hnsw   | 136 kB
 flight_metadata_gin    | gin    | 88 kB
 flight_log_sha256_key  | btree  | 56 kB
 flight_pkey            | btree  | 40 kB
 flight_signature_pkey  | btree  | 32 kB
 flight_started_at      | btree  | 16 kB
 note_pkey              | btree  | 8192 bytes
(12 rows)
```

# Columnstore DDL

### What it does

`segmentby = (flight_id, vendor_field_id)` makes one compressed row group per signal of one flight; `orderby = ts` gives delta and run-length encodings long runs of similar values.

```
    # One segment = one signal of one flight, ordered by time: matches the dominant access path
    # (a single flight's single signal over a time range) and compresses well (smooth series).
    op.execute("""
    ALTER TABLE telemetry SET (
        timescaledb.enable_columnstore = true,
        timescaledb.segmentby = 'flight_id, vendor_field_id',
        timescaledb.orderby = 'ts'
    )""")
```

```
    chunks = [r[0] for r in c.execute(
        "SELECT c.relid::regclass::text FROM _timescaledb_catalog.chunk c "
        "JOIN _timescaledb_catalog.hypertable h ON h.id = c.hypertable_id "
        "WHERE h.table_name = 'telemetry' AND (c.status & 1 = 0 OR c.status & 8 = 8) ORDER BY c.id")
     ]
    if a.limit:
        chunks = chunks[: a.limit]
```

Found by testing: rows inserted into a compressed chunk leave it *partial*; the stage recompresses those too.

# Columnstore design experiment

100 flights, 26.9 M rows, median of 7 warm runs. Q1 one signal of one flight, Q2 one signal across all flights, Q3 every signal of one flight, Q4 one signal in a 90-day window.

| variant | size | Q1 | Q2 | Q3 | Q4 |
|---|---|---|---|---|---|
| rowstore + B-tree | 3,631 MB | 10.8 ms | 1,519 ms | 65 ms | 246 ms |
| **segment (flight, signal), order ts** | **147 MB** | 12.3 | **16** | 10.8 | **2.7** |
| segment flight only | 149 MB | 12.9 | 18.0 | 11.6 | 3.2 |
| segment signal only | 154 MB | 13.0 | 20.3 | 14.1 | 2.2 |
| no segmentby | 157 MB | 15.0 | 29.7 | 13.7 | 3.6 |
| 1-day chunks | 150 MB | 16.3 | 15.3 | 12.3 | 3.4 |
| 30-day chunks | 143 MB | 9.2 | 8.3 | 5.7 | 2.4 |

### Findings

**25× smaller, up to 95× faster** cross-flight queries. Design choices change size by under 10%; chunk count and `segmentby` change cross-flight speed about 2×.

# Storage at full size: 32 times smaller




**Reading**

- 12,459 MB → **385 MB**: 176 → 5.4 bytes per row
- Same query results as the Parquet source
- Matches sorted, zstd Parquet; 1.8× smaller than DuckDB's file
- Row-level ACID and live inserts remain

# TimescaleDB against DuckDB: query latency

70,731,891 rows, median of 5 warm runs, DuckDB with 4 threads (embedded; concurrency not measured)

| query (p50, ms) | Timescale columnstore | DuckDB over Parquet | DuckDB native |
|---|---|---|---|
| Q1 one signal, one flight, 1 s buckets | 25.4 | 25.3 | **4.9** |
| Q2 one signal, all flights | 69.2 | 30.6 | **12.9** |
| Q3 every signal of one flight | **18.7** | 45.7 | 22.5 |
| Q4 one signal, 90-day window | **3.8** | 28.4 | 4.5 |
| Q5 count and mean per signal, all data | 811.8 | 1,057.8 | **478.3** |
| Q6 min/max/mean per flight and signal | **1,007.5** | 2,605.3 | 2,004.0 |

# TimescaleDB against DuckDB: loading and verdict

**Load throughput**

| path | rows/s |
|---|---|
| Timescale `COPY` (uncompressed) | 286,792 |
| DuckDB row-by-row `INSERT` | 603 |
| DuckDB bulk insert from Parquet | 6,153,564 |
| DuckDB write to Parquet | 4,034,708 |

**Verdict**

- DuckDB wins full scans (Q5) and point slices on its native file
- The columnstore wins pruned access (Q3, Q4) and the whole-corpus summary (Q6)
- Postgres adds concurrent writers, transactions, roles and vectors in the **same** engine
- So DuckDB stays a comparator

# Loading: Arrow to CSV to COPY

### Why

Columns are canonicalised in Arrow (scale and offset from `field_mapping`) and streamed as CSV into `COPY`: 287 k rows/s into a hypertable, one transaction per flight.

```
def telemetry_table(r: dict, vf_ids: dict, fid: str) -> pa.Table | None:
    t0_us = np.datetime64(r["t0"].replace(tzinfo=None), "us")
    parts = []
    for topic, field, ts_us, vals in r["hot"]:
        ok = np.isfinite(vals)
        parts.append(pa.table({
            "ts": pa.array(t0_us + ts_us[ok].astype("timedelta64[us]"), pa.timestamp("us")),
            "vf": pa.array(np.full(int(ok.sum()), vf_ids[(topic, field)], np.int16)),
            "value": vals[ok],
        }))
    if not parts:
        return None
    t = pa.concat_tables(parts)
```

# One query, from the Database page: how a signal is read

## Plan of a real query

Buffer hits only, a `ColumnarScan` over compressed chunks, aggregation into 1-second buckets: 8.4 ms for a 901-bucket envelope.


```
-- One signal of one flight, as min/max buckets
SELECT time_bucket(make_interval(secs => 1.0), ts) AS bucket, min(value), max(value), avg(value)
FROM canonical_telemetry
WHERE flight_id = '41868bf1-4fcb-4259-a4c5-129603d0f708' AND signal = 'battery.voltage'
GROUP BY 1 ORDER BY 1

Sort  (cost=3259.19..3259.69 rows=200 width=32) (actual time=4.980..5.086 rows=901 loops=1)
  Sort Key: (time_bucket('00:00:01'::interval, t.ts))
  Sort Method: quicksort  Memory: 67kB
  Buffers: shared hit=522
  ->  HashAggregate  (cost=3248.55..3251.55 rows=200 width=32) (actual time=4.575..4.781 rows=901 loops=1)
        Group Key: time_bucket('00:00:01'::interval, t.ts)
        Batches: 1  Memory Usage: 313kB
        Buffers: shared hit=519
        ->  Nested Loop  (cost=10.68..3217.58 rows=1239 width=32) (actual time=0.621..3.351 rows=4502 loops
    =1)
              Buffers: shared hit=519
              ->  Nested Loop  (cost=0.28..7.36 rows=1 width=18) (actual time=0.034..0.061 rows=2 loops=1)
                    Join Filter: (m.concept_id = c.id)
                    Rows Removed by Join Filter: 50
                    Buffers: shared hit=4
                    ->  Index Scan using field_mapping_pkey on field_mapping m  (cost=0.14..4.22 rows=52
    widt...
```

# The semantic layer

## Ontology in relational tables

- **63 concepts, 55 relations**: 34 signals, 7 subsystems, 7 failure modes, 15 event kinds
- Signal → subsystem → failure mode → event, walked with recursive CTEs
- Each vendor field maps to a signal with **scale, offset, note**
- Queries say `battery.voltage`, not the vendor field



# Documented semantic views

### The only objects the NL-to-SQL role can read

Six views (`flights`, `events`, `signals`, `signal_summary`, `ontology`, `telemetry`); the comments are the documentation the model's prompt is built from.

```
uavlog=# -- the documented semantic layer (view comments are the model's schema description)
      view      |                                comment
----------------+-------------------------------------------------------------------------
 events         | Things that happened during a flight: mode changes, arming, takeoff an
 flights        | One row per flight (a PX4 flight log from Flight Review).
 ontology       | How concepts relate: signal part_of subsystem; signal or event indicat
 signal_summary | Lowest, highest and mean value of every signal in every flight. Use th
 signals        | The canonical telemetry signals (autopilot-independent names).
 telemetry      | Raw time series, about 70 million rows. ALWAYS filter by flight_id and
(6 rows)
```

# A semantic view definition

### Events joined to their concepts

The view resolves kind, severity and source names so the model never sees raw ids.

```
1    CREATE VIEW semantic.events AS
2    SELECT e.id AS event_id, e.flight_id, c.key AS kind,
3           e.severity, CASE e.severity WHEN 2 THEN 'critical' WHEN 1 THEN 'warning' ELSE 'info' END
      AS severity_label,
4           extract(epoch FROM e.ts_start - f.started_at) AS start_s, extract(epoch FROM e.ts_end - f
     .started_at) AS end_s,
5           e.description, e.source, fm.key AS failure_mode
6    FROM event e JOIN concept c ON c.id = e.kind_id JOIN flight f ON f.id = e.flight_id
7    LEFT JOIN concept_relation r ON r.src_id = c.id AND r.rel = 'indicates'
8    LEFT JOIN concept fm ON fm.id = r.dst_id AND fm.kind = 'failure_mode'""")
```

# ArduPilot mapping: a wrong mapping is worse than a gap

### Mapped

Attitude, GPS, position, velocity and battery (52 field mappings in total).

### Deliberately not mapped

Vibration, motor outputs, EKF ratios, barometric altitude and flight mode: they mean different things in the two systems.

```
ARDUPILOT_FIELDS = [
    ("ATTITUDE", "roll", "rad", "attitude.roll", RAD2DEG, 0,
      "radians to degrees"),
    ("ATTITUDE", "pitch", "rad", "attitude.pitch", RAD2DEG,
     0, "radians to degrees"),
    ("ATTITUDE", "yaw", "rad", "attitude.yaw", RAD2DEG, 0, "
     radians to degrees, range -180 to 180"),
    ("GPS_RAW_INT", "lat", "degE7", "gps.lat", 1e-7, 0, "
     degrees times 1e7; 0 means no fix and is dropped"),
    ("GPS_RAW_INT", "lon", "degE7", "gps.lon", 1e-7, 0, "
     degrees times 1e7; 0 means no fix and is dropped"),
    ("GPS_RAW_INT", "alt", "mm", "gps.alt_msl", 0.001, 0, "
     millimetres to metres, above mean sea level"),
    ("GPS_RAW_INT", "fix_type", "enum", "gps.fix_type", 1,
     0, "the same MAVLink enum PX4 uses (3 is a 3D fix)"),
    ("GPS_RAW_INT", "satellites_visible", "count", "gps.
     satellites", 1, 0, "satellites VISIBLE; PX4 reports
     satellites USED, so counts run slightly higher; 255
     means unknown and is dropped"),
```

# Events: three sources

### Sources


- Log transitions and warnings
- The failure detector status flags
- **Gaps-and-islands** rules over telemetry (window functions)

### Quality controls

- Rules fire only against a baseline in the same flight
- Near-duplicate messages collapse: 3,846 $\rightarrow$ 3,401
- Flight duration uses a robust estimate (one garbage timestamp once made a flight $10^{13}$ s long)

```
ISLANDS = """
WITH s AS (SELECT ts, value, (value {op} %(thr)s) AS flag FROM {src}
           WHERE flight_id = %(fid)s AND signal = %(sig)s),
g AS (SELECT *, row_number() OVER (ORDER BY ts) - row_number() OVER (PARTITION BY flag ORDER BY ts) AS grp
      FROM s)
SELECT min(ts), max(ts), min(value), max(value) FROM g
WHERE flag AND EXISTS (SELECT 1 FROM s WHERE NOT flag)  -- an event is a deviation from a baseline seen in
      the same flight
GROUP BY grp HAVING max(ts) - min(ts) >= make_interval(secs => %(min_s)s) ORDER BY 1"""
```

# Fault injection: do the detectors find faults of known size?




**Reading (30 real flights, 1,043 variants)**

- A constant fault is held at a random time; the unchanged rules look for the right event
- Below each rule's minimum duration (2–3 s) detection is 0–7%, by design
- From 5 s, 90–100% detected within about 1 s of onset
- Controls: 23% false alarms for battery low, 3–7% for the others

# Fault injection: the table behind the chart

| fault | min | 1 s | 2 s | 3 s | 5 s | 10 s | controls |
|---|---|---|---|---|---|---|---|
| battery critically low | 3 s | 0.07 | 0.07 | 0.07 | 0.90 | 0.97 | 0.23 |
| GPS lost 3D fix | 2 s | 0.00 | 0.00 | 0.83 | 0.90 | 0.97 | 0.03 |
| GPS accuracy degraded | 3 s | 0.00 | 0.00 | 0.00 | 0.90 | 0.90 | 0.03 |
| high vibration | 3 s | 0.03 | 0.03 | 0.03 | 0.93 | 1.00 | 0.03 |
| estimator rejecting position | 2 s | 0.00 | 0.00 | 0.93 | 0.97 | 1.00 | 0.07 |

Detection rate by fault duration; “controls” is the false-alarm rate on unmodified flights. The small detections below the minimum duration are matches elsewhere in the flight (onset error of −36 to −200 s), not real detections.

# Hybrid search: vector, full text, filters, fused by RRF

## Design

- Event text embedded (`text-embedding-3-small`, 1,536 dims) into `vector` with an HNSW index; full text is a generated `tsvector` with GIN
- SQL filters: kind, flight, time, severity
- **Reciprocal rank fusion** $\sum_i w_i/(k + \mathrm{rank}_i)$; default hybrid weights $(1.0, 0.1)$

# Hybrid search SQL

### One statement

Vector candidates, full-text candidates and SQL filters are ranked separately and fused by RRF inside the database.

```
SQL = """
WITH q AS (SELECT %(vec)s::vector AS v, to_tsquery('english', %(tsq)s) AS tq),
{vec_cte}
fts AS (
    SELECT e.id, row_number() OVER (ORDER BY ts_rank_cd(e.tsv, q.tq) DESC) AS r
    FROM event e, q WHERE e.tsv @@ q.tq {filt}
    ORDER BY ts_rank_cd(e.tsv, q.tq) DESC LIMIT %(pool)s)
SELECT e.id, c.key AS kind, e.severity, e.description, f.source_ref AS flight, f.id::text AS
      flight_uuid, e.ts_start - f.started_at AS t,
       e.embedding <=> (SELECT v FROM q) AS distance,
       %(wv)s * coalesce(1.0 / (%(rrf)s + vec.r), 0) + %(wf)s * coalesce(1.0 / (%(rrf)s + fts.r), 0)
      AS score, vec.r AS vec_rank, fts.r AS fts_rank
FROM vec FULL OUTER JOIN fts ON vec.id = fts.id
JOIN event e ON e.id = coalesce(vec.id, fts.id)
JOIN concept c ON c.id = e.kind_id JOIN flight f ON f.id = e.flight_id
ORDER BY score DESC, vec.r NULLS LAST, fts.r NULLS LAST LIMIT %(k)s"""


def estimated_rows(conn, filt: list[str], params: dict) -> int | None:
```

# Search quality: the hybrid did not win


**nDCG@10, 65 concept queries (39 hard)**

| method | all | hard paraphrases |
|---|---|---|
| vector only | **0.710** | 0.59 |
| vector + light full text (0.1) | **0.709** | 0.59 |
| plain RRF | 0.600 | 0.43 |
| full text only | 0.48 | 0.31 |

**Reading**

- Plain fusion is significantly worse: paired $-0.109$, 95% CI $[-0.172, -0.051]$
- Ten exact-term lookups scored 1.000 for every method
- Cosine distances sit in a narrow 0.40–0.60 band: no honest relevance cutoff

# Vector indexes at 100,000 vectors: recall against latency




**Reading (exact search: 362 ms)**

- HNSW m=32 reaches 0.95 recall in 2.4 ms: over 100× faster than exact
- Up and to the left is better; DiskANN never passes 0.74
- 1,536 dimensions, 200 queries, top 10

# Vector indexes: build time, size and speed at a recall target

| index (100,000 vectors) | build | size | fastest at recall $\geq 0.95$ | $\geq 0.99$ |
|---|---|---|---|---|
| HNSW m=16 | 56 s | 819 MB | 2.7 ms | not reached |
| **HNSW m=32** | 149 s | 819 MB | **2.4 ms** | **3.2 ms** |
| IVFFlat, 316 lists | **17 s** | 822 MB | 5.5 ms | 9.3 ms |
| IVFFlat, 100 lists | 8.5 s | 820 MB | 8.4 ms | 14.8 ms |
| DiskANN | 268 s | **68 MB** | not reached | not reached (max 0.74) |

**Findings**

IVFFlat builds 3–17× faster than HNSW; DiskANN is 12× smaller but loses recall on this data.

# Does data difficulty change the winner? (50,000 vectors)


**Fastest p50 at a recall target; same $N$, only the noise changes**

| index | RC10 | $\geq 0.95$ | $\geq 0.99$ |
|---|---|---|---|
| HNSW m=32, $\sigma$ 0.35 | 6.0 | 1.47 ms | 1.85 ms |
| HNSW m=32, $\sigma$ 0.80 | 2.0 | 1.50 ms | 2.57 ms |
| IVFFlat 224, $\sigma$ 0.35 | 6.0 | 3.93 ms | 3.93 ms |
| IVFFlat 224, $\sigma$ 0.80 | 2.0 | 2.47 ms | 3.76 ms |
| DiskANN, either $\sigma$ | 6.0 / 2.0 | not reached | not reached |

**Reading**

- RC10 is the relative contrast of the 10th neighbour; the real corpus is **20.5**, so both synthetic sets are harder
- HNSW m=32 is fastest at 0.99 in both: the ranking is stable
- DiskANN peaks at 0.85 and 0.89 recall


# Filtered search: post-filtering under-returns




**Reading (100,000 vectors)**

- Post-filter ef 40 returns **0.0** rows at 0.1% and 4.1 at 10%
- Iterative scan fixes the row count, not base recall
- Exact sort over a B-tree filter: 1.0 ms at 0.1%, 55 ms at 10%

# Filtered search: latency and the crossover




**Crossover near 1,000 rows**

- Selective filter: exact sort wins (few rows to sort)
- Unselective filter: HNSW wins (exact sort touches 329 ms at 50%)
- This sets the router's threshold of about 1,500 rows


# The planner picks wrong, so the search routes itself

### Observed

With both indexes present and a filter keeping 10%, Postgres chose HNSW post-filtering: **4.0 rows of 10**, recall **0.37**, in 1.6 ms. Fast and wrong; the cost model cannot know it under-returns.

### The fix

Estimate the filtered row count with `EXPLAIN (FORMAT JSON)` on the filter alone. At about 1,500 rows or fewer, filter first and sort exactly; otherwise HNSW with iterative scan.



# Router code

### The decision

Estimated rows pick the exact path or the HNSW path; the chosen path and the estimate are returned with the result and displayed.

```
    est = estimated_rows(conn, filt, params)
    exact = est is not None and est <= EXACT_ROWS
    if info is not None:
        info["strategy"] = "exact (filter first, then sort by distance)" if exact else "approximate
     (HNSW index)"
        info["filter_estimated_rows"] = est
    conn.execute("SET hnsw.iterative_scan = relaxed_order")
    conn.execute("SET hnsw.ef_search = 100")
    filt_sql = "".join(f" AND {x}" for x in filt)
```

# Router code: estimating the filtered rows

### No count(*)

The estimate comes from the planner (`EXPLAIN (FORMAT JSON)`) rather than from counting, so the filtered rows are not scanned.

```
1 def estimated_rows(conn, filt: list[str], params: dict) -> int | None:
2     """The planner's own estimate of how many events survive the filter (None when there is no
       filter)."""
3     if not filt:
4         return None
5     sql = "EXPLAIN (FORMAT JSON) SELECT 1 FROM event e WHERE e.embedding IS NOT NULL" + "".join(f"
       AND {x}" for x in filt)
6     plan = conn.execute(sql, {k: v for k, v in params.items() if k in ("kinds", "sev", "hw")}).
       fetchone()[0][0]["Plan"]
7     return int(plan["Plan Rows"])
```

# Filter correlated with the query: harmless

**Recall by strategy and kind frequency**

| strategy | common | medium | rare |
|---|---|---|---|
| post-filter ef 40 | 0.92 | 0.66 | 1.00 |
| post-filter ef 400 | 0.99 | 0.95 | 1.00 |
| exact sort | 1.00 | 1.00 | 1.00 |
| partial HNSW per kind | 0.91 | 0.66 | 1.00 |
| list partitions + HNSW | 0.93 | 0.66 | 1.00 |
| DiskANN with labels | 0.77 | 0.46 | 1.00 |

**Reading**

- Every variant returned 10 rows
- Partial indexes and partitions added nothing at this size
- Builds: HNSW 62 s, partial indexes 62 s in total, partitions 101 s, DiskANN with labels 621 s

# Vector search plan from the Database page

### Ten nearest events by meaning

An index scan on event_embedding_hnsw: 10 rows in 41 ms on a cold cache with buffer reads, from 3,401 events.

```
-- Ten nearest events by meaning
SELECT id, description FROM event
WHERE embedding IS NOT NULL
ORDER BY embedding <=> (SELECT embedding FROM event WHERE id = 7772)
LIMIT 10

Limit  (cost=168.04..173.82 rows=10 width=59) (actual time=40.817..40.934 rows=10 loops=1)
  Buffers: shared hit=159 read=125
  InitPlan 1
    ->  Index Scan using event_pkey on event event_1  (cost=0.28..2.50 rows=1 width=18) (actual time
     =0.028..0...
          Index Cond: (id = 7772)
          Buffers: shared hit=6
  ->  Index Scan using event_embedding_hnsw on event  (cost=165.54..2131.62 rows=3401 width=59) (actual
     time=...
        Order By: (embedding <=> (InitPlan 1).col1)
        Buffers: shared hit=159 read=125
Planning:
  Buffers: shared hit=16 read=1
Planning Time: 4.286 ms
Execution Time: 40.992 ms
```

# Natural-language SQL: four defences




### Layers 1 and 2

- **Guard** (`sqlglot`): one SELECT, table and function allow-lists; the SQL that runs is **rebuilt from the parse tree**
- **Role** that reads only documented views

### Layers 3 and 4

- **Read-only transaction**, 8 s statement timeout
- **Cost admission**: planner estimate must be under 100,000

# Guard code: statement checks

### What is rejected

Anything that is not a single SELECT; nested or recursive `WITH`; table-valued functions in `FROM`; catalog-qualified names.

```
    root = statements[0]
    if not isinstance(root, (exp.Select, exp.SetOperation)):
        raise GuardError(f"Only SELECT queries are allowed, got {type(root).__name__.upper()}.")

    bad = next((n for n in root.walk() if isinstance(n, FORBIDDEN_NODES)), None)
    if bad is not None:
        raise GuardError(f"{type(bad).__name__.upper()} is not allowed in a query.")

    withs = [n for n in root.walk() if isinstance(n, exp.With)]
    if any(w is not root.args.get("with_") and w is not root.args.get("with") for w in withs):
        raise GuardError("WITH is only allowed at the top level of the query.")
    if any(w.args.get("recursive") for w in withs):
        raise GuardError("Recursive WITH is not allowed.")
    cte_names = {c.alias_or_name.lower() for c in root.find_all(exp.CTE)}
```

# Guard code: allow-lists and the rebuilt statement

### What is checked is what runs

Tables and functions must be on the allow-lists; a sentinel row limit is injected and the statement is regenerated from the parse tree.

```
    used_tables: list[str] = []
    for t in root.find_all(exp.Table):
        if not isinstance(t.this, exp.Identifier):
            raise GuardError("Table-valued functions are not allowed in FROM.")
        name, schema = t.name.lower(), (t.db or "").lower()
        if t.args.get("catalog"):
            raise GuardError("Catalog-qualified table names are not allowed.")
        if not schema and name in cte_names:
            continue
        if schema and schema != policy.schema:
            raise GuardError(f"Schema '{schema}' is not available. Use only the {policy.schema}
     views: {', '.join(sorted(policy.tables))}.")
        if name not in policy.tables:
            raise GuardError(f"'{name}' is not available. Use only: {', '.join(sorted(policy.tables)
     )}.")
        t.set("db", exp.to_identifier(policy.schema))  # qualify, so search_path never matters
        used_tables.append(name)
    if len(used_tables) > MAX_TABLES:
        raise GuardError(f"The query references {len(used_tables)} tables; the limit is {MAX_TABLES
     }.")
```

# Execution: role, read-only transaction, cost admission

### Order of events

Switch to the restricted role, open a read-only transaction with timeouts, `EXPLAIN` first and refuse when the planner estimate exceeds the limit.

```
def run(pool, sql: str, mode: str = "semantic", max_cost: float = MAX_COST) -> Result:
    role = ROLES[mode]
    source, set_role = _connection_source(pool, mode)
    with source.connection() as c:
        try:
            with c.transaction():
                c.execute("SET TRANSACTION READ ONLY")
                if set_role:
                    c.execute(f"SET LOCAL ROLE {role}")
                c.execute(f"SET LOCAL statement_timeout = {TIMEOUT_MS}")
                c.execute("SET LOCAL idle_in_transaction_session_timeout = 10000")
                cost = float(c.execute("EXPLAIN (FORMAT JSON) " + sql).fetchone()[0][0]["Plan"]["
 Total Cost"])
                if cost > max_cost:
                    raise ExecError(f"The planner estimates this query is too expensive (cost {cost
 :,.0f}, limit {max_cost:,.0f}). "
                                    "Filter telemetry by flight_id and signal, or use signal_summary
  for comparisons across flights.")
                t0 = time.time()
                cur = c.execute(sql)
                fetched = cur.fetchmany(MAX_ROWS + 1)
                cols = [d.name for d in cur.description]
```

# The role boundary, tested in the running database

### Reading

The restricted role sees the 300 flights through the semantic view, is denied the base table, and is denied `pg_read_file`.

```
uavlog=# -- what the restricted role can and cannot do
ERROR:  permission denied for table flight
BEGIN
SET
 flights_visible
-----------------
             300
(1 row)

BEGIN
SET
ERROR:  permission denied for function pg_read_file
```


# Hostile queries

## Results

- **46 hostile queries** refused, each for the intended reason
- 18 legitimate queries still pass
- Realistic questions plan under 5,000; a telemetry self-join plans at **515 million** and is refused
- A fake model that obeys prompt injection is still stopped

```
MUST_REFUSE = {
    "drop": "DROP TABLE flight",
    "delete": "DELETE FROM semantic.flights",
    "update": "UPDATE semantic.flights SET board = 'x'",
    "insert": "INSERT INTO semantic.flights (log_id) VALUES ('x')",
    "stacked statements": "SELECT * FROM semantic.flights; DROP TABLE flight",
    "read file": "SELECT pg_read_file('/etc/passwd')",
    "read file, schema-qualified": "SELECT pg_catalog.pg_read_file('/etc/passwd')",
    "read file, upper case": "SELECT PG_READ_FILE('/etc/passwd')",
    "read file, comment between": "SELECT pg_read_file/* x */('/etc/passwd')",
    "copy program": "COPY flight TO PROGRAM 'id'",
    "dblink": "SELECT dblink('host=x', 'select 1')",
    "set_config": "SELECT set_config('role', 'uavlog', false)",
    "current_setting": "SELECT current_setting('is_superuser')",
```

# Does the semantic layer help NL-to-SQL?




**Reading**

- **Documentation is the big effect**: 0.26 → 0.70 (12 gained, 0 lost, $p = 0.0005$)
- The views add 0.19, **not significant** (6 to 1, $p = 0.125$)
- Without docs, 17 of 27 answers were confident and **wrong**
- Never fabricated an answer to an unanswerable question

# NL-to-SQL evaluation: protocol and honesty

### Protocol

- Dev set for prompt work; separate held-out set scored once per condition
- Strict and lenient execution accuracy; paired sign tests
- Model `gpt-4o-mini` behind an OpenAI-compatible client; prompt hashes saved

### Honesty note

The first run overstated the gap (0.65 vs 0.24): my comparison treated numbers as strings and my guard rejected a safe operator. Fixed, frozen, re-run with identical prompts; **both runs are kept**.

```
  "id": "t11",
  "category": "events",
  "question": "What is the second most common event kind?",
  "answerable": true,
  "semantic_sql": "SELECT kind FROM semantic.events GROUP BY kind ORDER BY count(*) DESC OFFSET 1 LIMIT
    1",
  "raw_sql": "SELECT c.key FROM event e JOIN concept c ON c.id = e.kind_id GROUP BY c.key ORDER BY count
    (*) DESC OFFSET 1 LIMIT 1"
 },
 {
```

# Similar flights by behaviour: signal-shape signatures

### Method

- 145 statistical and spectral features over 30 signals, scaled
- PCA to **32 dimensions** (86% of the variance), stored as `vector(32)` with HNSW
- Check: share of a flight's 5 nearest neighbours on the same board

### Result

Chance 6.9%; scaled features 25.3%; 32-dimension signature 25.0%. Compression to 32 dimensions loses nothing measurable.

```
med = np.nanmedian(X, axis=0)
q75, q25 = np.nanpercentile(X, 75, axis=0), np.nanpercentile(X, 25, axis=0)
scale = np.where((q75 - q25) > 1e-9, q75 - q25, np.where(np.nanstd(X, axis=0) > 1e-9, np.nanstd(X, axis=0), 1.0))
Z = np.clip((X - med) / scale, -5, 5)
Z = np.where(np.isnan(Z), 0.0, Z)
pca_mean = Z.mean(axis=0)
_, _, vt = np.linalg.svd(Z - pca_mean, full_matrices=False)
k = min(DIMS, vt.shape[0])
comp = np.zeros((DIMS, len(names)))
comp[:k] = vt[:k]
S = (Z - pca_mean) @ comp.T
S /= np.maximum(np.linalg.norm(S, axis=1, keepdims=True), 1e-9)
var = np.var((Z - pca_mean) @ vt.T, axis=0)
print(f"PCA keeps {100 * var[:k].sum() / var.sum():.0f}% of the variance in {k} dimensions", flush=True)

scaler = {"names": names, "median": med.tolist(), "scale": scale.tolist(), "pca_mean": pca_mean.tolist(), "components": comp.tolist(), "dims": DIMS}
```

# Concurrent work in the database: SKIP LOCKED job tables





## Design

Each stage claims items with `FOR UPDATE SKIP LOCKED`; status, attempts and last error live in the row; data and status commit together, so a crash returns only that item to the queue. A `MATERIALIZED` CTE was needed: without it the planner claimed 52 rows for a limit of 25.

```
# MATERIALIZED matters: without it Postgres may re-run the
    LIMIT .. FOR UPDATE SKIP LOCKED subquery inside the
# join and claim more rows than the limit.
CLAIM = """
WITH c AS MATERIALIZED (
    SELECT flight_id FROM flight_task
    WHERE stage=%(stage)s AND attempts < %(max)s
      AND (status='pending' OR (status='running' AND
     claimed_at < now() - make_interval(mins => %(lease)s)))
    ORDER BY created_at, flight_id LIMIT %(n)s FOR UPDATE
     SKIP LOCKED)
UPDATE flight_task t SET status='running', attempts=attempts
    +1, claimed_at=now(), worker=%(worker)s
FROM c WHERE t.flight_id = c.flight_id AND t.stage = %(stage
    )s
RETURNING t.flight_id"""



def enqueue(conn, stage: str) -> int:
```

# Interface: the flight explorer




Flights ranked by critical events, with the mode ribbon per flight; filters, free-text search and corpus summary.

# Interface: one flight, overview




Mode ribbon with event marks, altitude chart, ground track and the event list for the flight.

# Interface: one flight, signals





Attitude, battery voltage and battery remaining. Every chart is shaded by the same flight-mode ribbon and zooms by dragging.

# Interface: one flight, diagnostics





Vibration, estimator innovation test ratios and GPS accuracy; min/max envelopes keep spikes visible when zoomed out.

# Interface: notes and similar flights





Investigation notes pinned to a moment, and flights found by signal-shape signature (not by text).

# Interface: semantic search





Hybrid search over event meaning, with the ranking details shown.

# Interface: Ask, question and answer





A plain-English question becomes a checked, read-only query; the answer is a sentence and a table.

# Interface: Ask, how this was answered




The generated SQL, its planner cost and each guard action are shown beside the answer.

# Interface: compare two flights




The same canonical signal from two flights on different boards, aligned at takeoff.


# Interface: compare, event counts




| | A: 968d313d | B: 0376b225 |
|---|---|---|
| Board | CZI_CZ100 | PX4_FMU_V6X |
| Firmware | v1.15.0 255 | v1.0.1 255 |
| Flown | 12:54 | 2:16 |
| attitude limit exceeded events | 1 | 0 |
| battery low events | 2 | 0 |
| disarm events | 1 | 1 |
| failsafe activated events | 1 | 0 |
| landing events | 1 | 1 |
| log error events | 7 | 9 |
| log warning events | 14 | 0 |
| mode change events | 1 | 0 |
| takeoff events | 0 | 1 |


Board, firmware, flight time and event counts side by side.

# Interface: the ontology




Concepts, relations and vendor field mappings for both autopilots.

# Interface: the Database page, space and plans




Live from the database: 12.46 GB rowstore against 385 MB columnstore, and a selectable query with its EXPLAIN ANALYZE plan.

# Interface: the Database page, the plan




The plan, node by node, with buffer counts and actual times.

# Interface: the Database page, indexes and tables



### Indexes

| Name | Method | Size |
|---|---|---|
| event_embedding_hnsw | hnsw | 14 MB |
| event_flight_ts | btree | 303 kB |
| event_tsv | gin | 303 kB |
| event_pkey | btree | 229 kB |
| event_kind_ts | btree | 229 kB |
| flight_metadata_gin | gin | 90 kB |
| flight_log_sha256_key | btree | 57 kB |
| flight_pkey | btree | 41 kB |
| flight_started_at | btree | 16 kB |
| concept_key_key | btree | 16 kB |
| vendor_field_pkey | btree | 16 kB |
| vendor_field_autopilot_topic_field_key | btree | 16 kB |

### Tables

| Name | Rows | Size |
|---|---|---|
| event | 3,401 | 45 MB |
| ingest_job | 300 | 614 kB |
| flight | 300 | 532 kB |
| flight_task | 600 | 385 kB |
| llm_call | 526 | 172 kB |
| concept | 63 | 82 kB |
| vendor_field | 52 | 82 kB |
| field_mapping | 52 | 66 kB |
| concept_relation | 55 | 49 kB |


### Pipeline

Each stage claims work from a table with row locks that skip rows other workers hold, so any number of workers can run side by side and a crash only returns its own rows to the queue.

| Stage | pending | running | done | failed | missing | Last finished |
|---|---|---|---|---|---|---|


Index method and size, row counts and table sizes.

# Interface: the Database page, pipeline





Stage status counts, ingest rate, derived-data counts and LLM call statistics.

# Interface: the Benchmarks page




Every experiment in this talk is a section of this page, drawn from the saved result files.


# Benchmarks page: vector indexes




| Index | Build time | Size | Fastest at recall 0.90 | 0.95 | 0.99 |
|---|---|---|---|---|---|
| HNSW m=16, ef_construction=64 | 56 s | 819 MB | 2.1 ms | 2.7 ms | not reached |
| HNSW m=32, ef_construction=128 | 149 s | 819 MB | 2.0 ms | 2.4 ms | 3.2 ms |
| IVFFlat lists=316 (sqrt N) | 17 s | 822 MB | 3.5 ms | 5.5 ms | 9.3 ms |
| IVFFlat lists=100 (N/1000) | 8 s | 820 MB | 4.2 ms | 8.4 ms | 14.7 ms |
| DiskANN (pgvectorscale), defaults | 268 s | 68 MB | not reached | not reached | not reached |

Recall against median latency for each index and setting, with build time and size.

# Benchmarks page: filtered search





Rows returned, recall or latency by strategy and filter selectivity.

# Benchmarks page: filtered search, tables

**Filter on the query's own event kind (correlated with what is being searched)**

| Strategy | Kind is common (>10%) | Kind is medium (1–10%) | Kind is rare (<1%) |
|---|---|---|---|
| hnsw post-filter, ef_search=40 | 10.0 rows, recall 0.92, 1.2 ms | 10.0 rows, recall 0.66, 1.9 ms | 10.0 rows, recall 1.00, 1.2 ms |
| hnsw post-filter, ef_search=400 | 10.0 rows, recall 0.99, 2.7 ms | 10.0 rows, recall 0.95, 7.8 ms | 10.0 rows, recall 1.00, 2.8 ms |
| hnsw iterative relaxed, ef=40 | 10.0 rows, recall 0.92, 1.4 ms | 10.0 rows, recall 0.66, 2.2 ms | 10.0 rows, recall 1.00, 1.3 ms |
| hnsw iterative strict, ef=40 | 10.0 rows, recall 0.92, 1.3 ms | 10.0 rows, recall 0.66, 2.0 ms | 10.0 rows, recall 1.00, 1.2 ms |
| hnsw iterative relaxed, scan limit N | 10.0 rows, recall 0.92, 1.2 ms | 10.0 rows, recall 0.66, 1.9 ms | 10.0 rows, recall 1.00, 1.2 ms |
| b-tree filter + exact sort | 10.0 rows, recall 1.00, 145.3 ms | 10.0 rows, recall 1.00, 44.2 ms | 10.0 rows, recall 1.00, 8.5 ms |
| planner's choice (hnsw + b-trees) | 10.0 rows, recall 0.91, 1.2 ms | 10.0 rows, recall 0.66, 1.9 ms | 10.0 rows, recall 0.90, 0.6 ms |
| partial hnsw per kind, ef=40 | 10.0 rows, recall 0.91, 1.5 ms | 10.0 rows, recall 0.66, 2.1 ms | 10.0 rows, recall 1.00, 1.3 ms |
| list partitions + hnsw, ef=40 | 10.0 rows, recall 0.93, 1.5 ms | 10.0 rows, recall 0.66, 2.1 ms | 10.0 rows, recall 1.00, 0.8 ms |
| diskann labels, list=100, rescore=200 | 10.0 rows, recall 0.77, 5.0 ms | 10.0 rows, recall 0.46, 8.5 ms | 10.0 rows, recall 1.00, 4.1 ms |

**What each approach costs to build**



# Benchmarks page: search quality, NL-to-SQL and signatures

## Search quality

Natural-language queries against the extracted events: which way of ranking finds the right ones.

3,401 events, 75 concept queries (39 are pure paraphrases). Mean nDCG@10 with 95% bootstrap interval.


| Method | All queries | Easy | Hard paraphrases |
|---|---|---|---|
| Vector only | **0.710** [0.61, 0.81] | **0.889** [0.79, 0.97] | **0.590** [0.45, 0.73] |
| Vector + light full-text (0.1) | **0.709** [0.61, 0.80] | **0.888** [0.79, 0.97] | **0.589** [0.45, 0.72] |
| Plain rank fusion | **0.600** [0.50, 0.69] | **0.855** [0.75, 0.94] | **0.431** [0.32, 0.55] |
| Full-text only | **0.476** [0.38, 0.58] | **0.727** [0.58, 0.85] | **0.309** [0.20, 0.43] |

Plain rank fusion minus vector only: -0.109 [-0.172, -0.051], a significant loss.

## Natural-language SQL

Does a model write correct SQL, and what does the semantic layer add beyond documentation?

Held-out set, model openai/gpt-4o-mini, strict execution accuracy (result set equals the gold query's). nlsql_eval_test_run2_after_infra_fixes





semantic vs raw: 17 to 0, p = 0.0000; semantic vs raw docs: 6 to 1, p = 0.1250; raw docs vs raw: 12 to 0, p = 0.0005.


## Similar flights by behaviour

A sanity check that flights found by signal shape, event rates and mode shares are more alike than chance.


300 flights, 145 features reduced to 32 dimensions (86% of the variance). Share of a flight's 5 nearest neighbours on the same board, leave one out.




# Benchmarks page: fault injection



# Benchmarks page: columnstore design



# Benchmarks page: TimescaleDB against DuckDB



# Environment and method

## Environment

- 4 cores, 15 GB RAM, no GPU; PostgreSQL 17.11, TimescaleDB 2.30.2, pgvector 0.8.7, pgvectorscale 0.9.1, DuckDB 1.5.6
- `shared_buffers` 3,968 MB while benchmarking, `maintenance_work_mem` 1,500 MB

## Method

- One connection, warm cache, 3 measured passes or median of 5–7 runs
- Recall against exact search; 200 held-out queries; top 10
- Dev set and held-out set; bootstrap intervals and paired tests

```
uavlog=# SHOW ... -- configuration the benchmarks ran under
               name               |   value
----------------------------------+-----------
 effective_cache_size             | 15237128kB
 maintenance_work_mem             | 2031616kB
 max_parallel_maintenance_workers | 2
 max_parallel_workers             | 4
 random_page_cost                 | 1.1
 shared_buffers                   | 5079048kB
 work_mem                         | 31746kB
(7 rows)

                                                
```

# Key results

### Storage and retrieval

- **32**× smaller telemetry (12.46 GB → 385 MB)
- **up to 95**× faster cross-flight queries
- **over 100**× faster than exact search at 0.95 recall
- **4 of 10 rows**: the planner's wrong choice at a 10% filter

### Language and detection

- **0.89** NL-to-SQL accuracy on held-out questions
- **0.600 vs 0.710**: plain rank fusion hurts
- **46** hostile queries refused for the intended reason
- **90–100%** of injected faults found once they last 5 s

# Conclusions and limits

## Conclusions

- One PostgreSQL holds time series, ontology, vectors and guarded NL-to-SQL
- Physical design cut storage 32×; filtering strategy mattered more than index choice
- Documentation drives NL-to-SQL accuracy; four layers keep it safe
- Hybrid fusion did *not* help: reported as found

## Limits and next steps

- 300 flights, one machine, one model, author-written questions
- Index-benchmark vectors are perturbed copies of real ones
- Event thresholds are heuristics; battery-low raises 23% false alarms on controls
- Next: 10,000+ logs, ArduPilot at scale, a concurrency benchmark