

Table of Contents

USCSP301-USCS303: Operating System(OS) Practical-08

Practical-08: Page Replacement Algorithm FIFO

Practical Date: 30th Aug, 2021

Practical	Aim:	Page	Replacement	Algorithm	FIFO
Algorithm					3
Solved Example					5
Question.....					6
Implementation					6
Input.....					9
Output.....					9
Sample Output.....					9

Page Replacement Algorithm: FIFO

- Content:
 - In FIFO page replacement algorithm, the oldest page, which has spent the longest time in memory is chosen and replaced.
- Process:
 - Implement FIFO Algorithm and find out page hits and page faults.
- Prior Knowledge:
 - Page Replacement Algorithm.

Page Replacement Algorithm

- In operating systems that use paging for memory management, **page replacement algorithm** are needed to decide which page needed to be replaced when new page comes in.
- Whenever a new page is referred and not present in memory, page fault occurs and Operating System replaces one of the existing pages with newly needed page.
- Different page replacement algorithms suggest different ways to decide which page to replace.
- The target for all algorithms is to reduce number of page faults.
- **Page Fault** – A page fault happens when a running program accesses a memory page that is mapped into the virtual address space, but not loaded in physical memory.

Step 1: First of all, find the location of the desired page on the disk.

Step 2: Find a free Frame:

Step 2.1: If there is a free Frame, then use it.

Step 2.2: If there is no free frame then make use of the page replacement algorithm in order to select the victim frame.

Step 2.3: Then after that write the victim frame to the disk and then make the changes in the page table and frame table accordingly.

Step 3: After that read the desired page into the newly freed frame and then change the page and frame tables.

Step 4: Restart the process.

First In First Out (FIFO)

- It is very simple way of Page replacement and is referred to as **First In First Out (FIFO)**.
- This algorithm mainly replaces the oldest page that has been present in the main memory for the longest time.
- This algorithm is implemented by keeping the track of all the pages in the queue.
- As new pages are requested and are swapped in, they are added to the tail of a queue and the page which is at the head becomes the victim.
- This is not an effective way of page replacement but it can be used for small systems.

EXAMPLE

FIFO Page Replacement Example

- Apply the FIFO replacement algorithm for the following page-reference strings:
0,2,1,6,4,0,1,0,3,1,2,1.
- Indicate the number of page faults for FIFO algorithm assuming demand paging with four frames.
- Find the number of hits, number of faults and hit ratio.

Page Reference String: 0,2,1,6,4,0,1,0,3,1,2,1

Demand Paging or Number of Frames: 4

0 0 0 0 4 4 4 4 4 2 2
-1 2 2 2 2 0 0 0 0 0 0
-1 -1 1 1 1 1 1 1 3 3 3
-1 -1 -1 6 6 6 6 6 6 1 1

0	2	1	6	4	0	1	0	3	1	2	1
×	×	×	×	×	×	✓	✓	×	×	×	✓

Number of Hits: count of no replacements = 3

Number of Faults: count of replacements = 9

Hit Ratio: Number of Hits / Len(Ref String) = 3/12 = 0.25

Question:

Write a Java Program that implements the FIFO page-replacement algorithm.

Source Code:

```
//NAME: Sumit Telawane
```

```
//BATCH: B1
```

```
//PRN: 2020016400825777
```

```
//DATE: 30th Aug, 2021
```

```
//PRAC-08: PAGE REPLACEMENT ALGORITHM
```

```
import java.io.*;
```

```
import java.util.*;
```

```
public class P8_PR_FIFO_ST
```

```
{
```

```
    public static void main(String[] args) throws IOException
```

```
    {
```

```
        Scanner scan = new Scanner(System.in);
```

```
        int frames, pointer = 0, hit = 0, fault = 0, ref_len;
```

```
        int buffer[];
```

```
        int reference[];
```

```
        int mem_layout[][];
```

```
        System.out.print("Please enter the number of Frames: ");
```

```
        frames = scan.nextInt();
```

```
        System.out.print("Please enter the length of the Reference string: ");
```

```
        ref_len = scan.nextInt();
```

```
reference = new int[ref_len];

mem_layout = new int[ref_len][frames];

buffer = new int[frames];

for(int j = 0; j<frames; j++)

    buffer[j] = -1;

System.out.println("Please enter the reference string: ");

for(int i=0; i<ref_len; i++)

{

    reference[i] = scan.nextInt();

}

System.out.println();

for(int i=0; i< ref_len; i++)

{

    int search = -1;

    for(int j=0; j<frames; j++)

    {

        if(buffer[j] ==reference[i])

        {

            search = j;

            hit++;

            break;

        }

    }

}

if (search== -1)
```

```
{
    buffer[pointer]= reference[i];

    fault++;

    pointer++;

    if(pointer==frames)

        pointer = 0;

}

for(int j=0; j<frames; j++)

    mem_layout[i][j]=buffer[j];

}

for(int i=0; i<frames; i++)

{

    for(int j =0; j<ref_len; j++)

        System.out.printf("%3d" , mem_layout[j][i]);

    System.out.println();

}

System.out.println("The number of Hits: "+hit);

System.out.println("Hit Ratio: " +(float)((float)hit/ref_len));

System.out.println("The number of Faults: "+fault);

}

}
```


Input:

```
D:\os\BATCH_B1\USCS3P01_USCS303_OS_B1_P8>java P8_PR_FIFO_ST
Please enter the number of Frames: 4
Please enter the length of the Reference string: 12
Please enter the reference string:
0 2 1 6 4 0 1 0 3 1 2 1
```

Output:

```
0 0 0 0 4 4 4 4 4 4 2 2
-1 2 2 2 2 0 0 0 0 0 0 0
-1 -1 1 1 1 1 1 1 3 3 3 3
-1 -1 -1 6 6 6 6 6 6 1 1 1
The number of Hits: 3
Hit Ratio: 0.25
The number of Faults: 9
```

Sample Output – 01

```
D:\os\BATCH_B1\USCS3P01_USCS303_OS_B1_P8>java P8_PR_FIFO_ST
Please enter the number of Frames: 4
Please enter the length of the Reference string: 12
Please enter the reference string:
0 2 1 6 4 0 1 0 3 1 2 1

0 0 0 0 4 4 4 4 4 4 2 2
-1 2 2 2 2 0 0 0 0 0 0 0
-1 -1 1 1 1 1 1 1 3 3 3 3
-1 -1 -1 6 6 6 6 6 6 1 1 1
The number of Hits: 3
Hit Ratio: 0.25
The number of Faults: 9
```

Sample Output – 02

```
D:\os\BATCH_B1\USCS3P01_USCS303_OS_B1_P8>java P8_PR_FIFO_ST
Please enter the number of Frames: 3
Please enter the length of the Reference string: 7
Please enter the reference string:
1 3 0 3 5 6 3

    1  1  1  1  5  5  5
   -1  3  3  3  3  6  6
   -1 -1  0  0  0  0  3
The number of Hits: 1
Hit Ratio: 0.14285715
The number of Faults: 6
```

Sample Output – 03:

```
D:\OS Pract\Batch 01\USCSP301_USCS303_OS\Prac_08_SS_30_08_2021>java P8_PR_FIFO_S
S
Please enter the number of Frames: 3
Please enter the length of the Reference string: 20
Please enter the reference string:
7 0 1 2 0 3 0 4 2 3 0 3 2 1 2 0 1 7 0 1
  7 7 7 2 2 2 2 4 4 4 0 0 0 0 0 0 7 7 7
-1 0 0 0 0 3 3 3 2 2 2 2 2 1 1 1 1 0 0
-1 -1 1 1 1 1 0 0 0 3 3 3 3 2 2 2 2 2 1
The number of Hits: 5
Hit Ratio: 0.25
The number of Faults: 15
```