REVA University • School of Computing • Department of CSE (AI & ML)

AIML-401: Deep Learning — Revision Study Guide

Topic: **Train Test**

Candidate ID: STU-807	**Target Exam:** Midterm IA-2 & SEE Exam
Curriculum Unit: Unit 1: Mathematical Foundations	**Compiled:** Nov 02, 2026 - 21:16
Faculty Note Ref: syllabus_overview.pdf	**Platform:** PACD-RAG Academic Intelligence

1. Fundamental Concept & Partitioning Principle

Train Test is a fundamental model evaluation methodology in machine learning. It divides an empirical dataset *D* into mutually exclusive partitions: a training set (D_{train}) to fit internal parameters and an unseen testing set (D_{test}) to reliably measure true generalization capability and prevent overfitting.

2. Mathematical Formulation & Generalization Theory (No Code)

In statistical learning theory, empirical risk minimization on training observations alone fails to guarantee low generalization error. By holding out test data, the empirical risk R_emp(h, D_test) provides an unbiased estimator of true risk R(h). Partitioning strictly prevents data snooping and guards against statistical memorization.

Key Theoretical Insight: *Hoeffding's Inequality bounds the discrepancy between training and generalization risk: $P(|R(h) - R_{emp}(h)| > \varepsilon) \leq 2 \exp(-2 N \varepsilon^2)$. An independent test sample guarantees this bound holds without optimistic bias.*

3. 4-Phase Data Partitioning & Validation Pipeline

Phase	Name	Mathematical / Code Operation	Key Objective
1	Shuffling	Random permutation of index array P = perm(N)	Eliminates chronological or ordered bias
2	Stratification	P(y in D_train) == P(y in D_test) == P(y in D)	Preserves minority class ratios
3	Feature Isolation	D_train intersect D_test == empty set	Prevents target leakage across splits
4	Fit & Evaluate	Scaler.fit(X_train); Scaler.transform(X_test)	Strictly avoids data snooping

4. Mathematical Partition Constraints

Given dataset $D = \{(x_i, y_i)\}_{i=1}^N$, train-test splitting guarantees:

- $D_{train} \cup D_{test} = D$ *and* $D_{train} \cap D_{test} = \emptyset$
- $|D_{test}| / |D| = \theta \in$ *(0.1, 0.3) where standard test ratio* $\theta = 0.20$

5. High-Yield Question & Pitfall Checklist for Exams

Top Exam Trap: Fitting preprocessing transformers (e.g. StandardScaler or PCA) on the entire dataset BEFORE splitting. This causes subtle data leakage resulting in overoptimistic test metrics.

Expected Question (8 Marks): *'Explain the mechanism of train-test split in machine learning. Write Python code using scikit-learn demonstrating stratified splitting, and explain why data leakage occurs if feature normalization is applied before splitting.'*

Marking Rubric:

- 2 Marks: Mathematical justification of generalization vs empirical risk.
- 3 Marks: Valid Python code demonstrating train_test_split with stratify and random_state.
- 3 Marks: Clear explanation of data leakage prevention using Pipeline or split-first paradigm.