



Fr. Conceicao Rodrigues College of Engineering Fr. Agnel
Ashram, Bandstand, Bandra (W), Mumbai - 400050

Department of Computer Engineering
Academic Term II: 23-24

Class: B.E (Computer), Sem – VI Subject Name: Artificial Intelligence

Student Name: Sumit Sanjay Rai

Roll No: 9570

Practical No:	2
Title:	Tic Tac Toe game implementation by Magic Square Method
Date of Performance:	05/02/2024
Date of Submission:	12/02/2024

Rubrics for Evaluation:

Sr. No	Performance Indicator	Excellent	Good	Below Average	Marks
1	On time Completion & Submission (01)	01 (On Time)	NA	00 (Not on Time)	
2	Logic/Algorithm Complexity analysis (03)	03(Correct)	02(Partial)	01 (Tried)	
3	Coding Standards (03): Comments/indentation/Naming conventions Test Cases /Output	03(All used)	02 (Partial)	01 (rarely followed)	
4	Post Lab Assignment (03)	03(done well)	2 (Partially Correct)	1(submitted)	

Total	
-------	--

Signature of the Teacher:



8

Fr. Conceicao Rodrigues College of Engineering Fr. Agnel
Ashram, Bandstand, Bandra (W), Mumbai - 400050

Experiment No: 2

Title: Tic Tac Toe game implementation by Magic Square Method

Objective: To write a computer program in such a way that computer wins most of the time using Magic Square Method **Theory:**

A player who places his coins first across the same row or same column or same diagonal wins the game. Let us take a magic square of order 3 x 3 (for 3 coins game). The sum of the numbers across rows, columns and diagonals are the same - it is 15. That is, a player who places his coins such that he gets the perfect score of 15 takes the prize.

- 1) Board is considered to be a magic square of size 3 X 3 with 9 blocks numbered by numbers indicated by the magic square.
- 2) This representation makes the process of checking for a possible win simpler.
Board Layout as magic square. Each row, column and diagonals add to 15.

8	3	4	15
1	5	9	15
6	7	2	15

3) Maintain the list of each player's blocks in which he has played. Consider each pair of blocks that the player owns.

Compute difference D between 15 and the sum of the two blocks.

If $D < 0$ or $D > 9$ then

- i) These two blocks are not collinear and so can be ignored.
- ii) Otherwise, if the block representing difference is blank (i.e., not in either list) then a move in that block will produce a win.

OUTPUT:

```
PROBLEMS  OUTPUT  DEBUG CONSOLE  TERMINAL  PORTS
C:\Users\SANJAY RAI\OneDrive\Desktop\TE_VI\AI_pracs>python TicTacToe_Magic_Square.py
- - -
- - -
- - -
Enter your move (1-9): 6
- - -
- - X
- - -
- - -
- - X
0 - -
Enter your move (1-9): 5
- - -
- X X
0 - -
- - -
- X X
0 0 -
Enter your move (1-9): 4
- - -
X X X
0 0 -
X wins!

C:\Users\SANJAY RAI\OneDrive\Desktop\TE_VI\AI_pracs>
```

Ln 79, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.2 64-bit Go Live

