

RES-STR — Materials, Structural Response and Damage

July 19, 2026

Table of Contents

1	Domain Purpose and Scope	7
2	Domain Deliverables	8
3	RES-STR-MAT — Candidate Materials and Constitutive Properties	8
3.1	Purpose and Scope	8
3.2	Research Questions	8
3.3	Terminology and Definitions	8
3.4	Literature Evidence	8
3.5	Governing Relations and Quantitative Definitions	8
3.6	Material or Structural System	8
3.7	Load Cases	8
3.8	Constitutive Behaviour	8
3.9	Response and Stability Measures	8
3.10	Damage and Failure Modes	8
3.11	Fluid–Structure Coupling Requirements	8
3.12	Candidate Approaches	8
3.13	Critical Comparison	8
3.14	Assumptions and Applicability	8
3.15	Limitations and Failure Conditions	8
3.16	Project-Specific Conclusions	8
3.17	Selected Approach and Rationale	8
3.18	Unresolved Decisions	8
3.19	Requirements and Handoffs	8
3.20	Deliverable Completion Record	8

4	RES-STR-ENV — Marine Exposure, Degradation and Durability	8
4.1	Purpose and Scope	8
4.2	Research Questions	8
4.3	Terminology and Definitions	8
4.4	Literature Evidence	8
4.5	Governing Relations and Quantitative Definitions	8
4.6	Material or Structural System	8
4.7	Load Cases	8
4.8	Constitutive Behaviour	8
4.9	Response and Stability Measures	8
4.10	Damage and Failure Modes	8
4.11	Fluid–Structure Coupling Requirements	8
4.12	Candidate Approaches	8
4.13	Critical Comparison	8
4.14	Assumptions and Applicability	8
4.15	Limitations and Failure Conditions	8
4.16	Project-Specific Conclusions	8
4.17	Selected Approach and Rationale	8
4.18	Unresolved Decisions	8
4.19	Requirements and Handoffs	8
4.20	Deliverable Completion Record	8
5	RES-STR-LOD — Structural Load Cases and Load Transfer	8
5.1	Purpose and Scope	8
5.2	Research Questions	9
5.3	Terminology and Definitions	9
5.4	Literature Evidence	9
5.5	Governing Relations and Quantitative Definitions	9
5.6	Material or Structural System	9
5.7	Load Cases	9
5.8	Hydrodynamic Traction Transfer	9
5.9	Constitutive Behaviour	11
5.10	Response and Stability Measures	11
5.11	Damage and Failure Modes	11
5.12	Fluid–Structure Coupling Requirements	11
5.13	Candidate Approaches	11
5.14	Critical Comparison	11
5.15	Assumptions and Applicability	11
5.16	Limitations and Failure Conditions	11
5.17	Project-Specific Conclusions	11
5.18	Selected Approach and Rationale	11

5.19	Unresolved Decisions	11
5.20	Requirements and Handoffs	11
5.21	Deliverable Completion Record	12
6	RES-STR-RSP — Structural Response and Stability	12
6.1	Purpose and Scope	12
6.2	Research Questions	12
6.3	Terminology and Definitions	12
6.4	Literature Evidence	12
6.5	Governing Relations and Quantitative Definitions	12
6.6	Three-Dimensional Structural Equation of Motion	12
6.7	Updated-Lagrangian Reference Description	12
6.8	Material or Structural System	14
6.9	Load Cases	14
6.10	Constitutive Behaviour	14
6.11	Response and Stability Measures	14
6.12	Damage and Failure Modes	14
6.13	Fluid–Structure Coupling Requirements	14
6.14	Candidate Approaches	14
6.15	Critical Comparison	14
6.16	Assumptions and Applicability	14
6.17	Limitations and Failure Conditions	14
6.18	Project-Specific Conclusions	14
6.19	Selected Approach and Rationale	14
6.20	Unresolved Decisions	14
6.21	Requirements and Handoffs	14
6.22	Deliverable Completion Record	14
7	RES-STR-DMG — Damage, Failure and Performance-Loss Models	14
7.1	Purpose and Scope	14
7.2	Research Questions	15
7.3	Terminology and Definitions	15
7.4	Literature Evidence	15
7.5	Governing Relations and Quantitative Definitions	15
7.6	Material or Structural System	15
7.7	Load Cases	15
7.8	Constitutive Behaviour	15
7.9	Response and Stability Measures	15
7.10	Damage and Failure Modes	15
7.11	Initial Failure-Modelling Scope	15
7.12	Fluid–Structure Coupling Requirements	16

7.13	Candidate Approaches	16
7.14	Critical Comparison	16
7.15	Assumptions and Applicability	16
7.16	Limitations and Failure Conditions	16
7.17	Project-Specific Conclusions	16
7.18	Selected Approach and Rationale	16
7.19	Unresolved Decisions	16
7.20	Requirements and Handoffs	16
7.21	Deliverable Completion Record	17
8	RES-STR-FSI — Fluid–Structure Interaction and Coupling Fidelity	17
8.1	Purpose and Scope	17
8.2	Research Questions	17
8.3	Terminology and Definitions	17
8.4	Literature Evidence	17
8.4.1	Baragamage and Wu (2024)	17
8.4.2	Istrati and Buckle (2019)	17
8.5	Governing Relations and Quantitative Definitions	17
8.5.1	Structural State and Momentum Equation	17
8.6	Fluid–Structure Interaction Model and Activation Strategy	18
8.7	Material or Structural System	19
8.8	Load Cases	19
8.9	Constitutive Behaviour	19
8.10	Response and Stability Measures	19
8.11	Damage and Failure Modes	19
8.12	Fluid–Structure Coupling Requirements	19
8.12.1	Fluid–Structure Interface Conditions	19
8.12.2	FSI Fidelity Hierarchy	19
8.12.3	Two-Way FSI Activation Gate	20
8.13	Reference Descriptions of the Coupled Domains	21
8.14	Fluid–Solid Interface Conditions	21
8.15	Moving-Boundary Treatment	22
8.16	Deferred High-Level FSI Architecture	22
8.17	Candidate Approaches	23
8.18	Critical Comparison	23
8.19	Assumptions and Applicability	23
8.20	Limitations and Failure Conditions	23
8.21	Project-Specific Conclusions	23
8.21.1	Project-Specific FSI Decision	23
8.22	Selected Approach and Rationale	23
8.23	Unresolved Decisions	23

8.24	Requirements and Handoffs	23
8.25	Deliverable Completion Record	24
9	RES-STR-SIM — Structural Simulation and Finite-Element Methodology	24
9.1	Purpose and Scope	24
9.2	Research Questions	24
9.3	Terminology and Definitions	24
9.4	Literature Evidence	24
9.5	Governing Relations and Quantitative Definitions	24
9.6	Material or Structural System	24
9.7	Load Cases	24
9.8	Constitutive Behaviour	24
9.9	Response and Stability Measures	24
9.10	Damage and Failure Modes	24
9.11	Fluid–Structure Coupling Requirements	24
9.12	Structural Spatial and Temporal Discretisation	24
9.13	Nonlinear Equilibrium Solution	25
9.14	Candidate Approaches	26
9.15	Critical Comparison	26
9.16	Assumptions and Applicability	26
9.17	Limitations and Failure Conditions	26
9.18	Project-Specific Conclusions	26
9.19	Selected Approach and Rationale	26
9.20	Unresolved Decisions	26
9.21	Requirements and Handoffs	26
9.22	Deliverable Completion Record	26
10	RES-STR-SPEC — Integrated Structural and Damage Specification	26
10.1	Purpose and Scope	26
10.2	Research Questions	27
10.3	Terminology and Definitions	27
10.4	Literature Evidence	27
10.5	Governing Relations and Quantitative Definitions	27
10.6	Material or Structural System	27
10.7	Load Cases	27
10.8	Constitutive Behaviour	27
10.9	Response and Stability Measures	27
10.10	Damage and Failure Modes	27
10.11	Fluid–Structure Coupling Requirements	27
10.12	Candidate Approaches	27

10.13Critical Comparison	27
10.14Assumptions and Applicability	27
10.15Limitations and Failure Conditions	27
10.16Project-Specific Conclusions	27
10.17Selected Approach and Rationale	27
10.18Unresolved Decisions	28
10.19Requirements and Handoffs	28
10.20Deliverable Completion Record	28
References	29

1 Domain Purpose and Scope

RES-STR records how hydrodynamic pressure, shear, force, impulse and moment histories from the local fixed-rigid barrier simulations will be transferred into later structural analyses. The active Studentship baseline is not a deformable-structure, material-damage, scour or two-way FSI model. Those topics remain stretch extensions after hydrodynamic load extraction, data provenance and the V1–V2–V3 validation hierarchy are stable.

2 Domain Deliverables

3 RES-STR-MAT — Candidate Materials and Constitutive Properties

3.1 Purpose and Scope

3.2 Research Questions

3.3 Terminology and Definitions

3.4 Literature Evidence

3.5 Governing Relations and Quantitative Definitions

3.6 Material or Structural System

3.7 Load Cases

3.8 Constitutive Behaviour

3.9 Response and Stability Measures

3.10 Damage and Failure Modes

3.11 Fluid–Structure Coupling Requirements

3.12 Candidate Approaches

3.13 Critical Comparison

3.14 Assumptions and Applicability

3.15 Limitations and Failure Conditions

3.16 Project-Specific Conclusions

3.17 Selected Approach and Rationale

3.18 Unresolved Decisions

3.19 Requirements and Handoffs

3.20 Deliverable Completion Record

4 RES-STR-ENV — Marine Exposure, Degradation and Durability

4.1 Purpose and Scope

4.2 Research Questions

damage, deformable barriers, scour or two-way fluid–structure coupling in the baseline tsunami-barrier comparison.

5.2 Research Questions

1. Which pressure, shear, force, impulse and moment outputs are required from the local fluid solver?
2. How are distributed fluid tractions reduced or mapped without losing resultant force and moment?
3. Which structural quantities are stretch consumers rather than active baseline outputs?

5.3 Terminology and Definitions

5.4 Literature Evidence

Baragamage and Wu [1] demonstrates the sequence from three-dimensional tsunami fluid loading to structural motion and feedback. Source role: supports preserving distributed load histories for later FSI-capable analysis. Limitation: its reduced bridge structure does not justify activating full deformable barrier analysis in the current baseline.

Istrati and Buckle [2] shows that pressure distribution can alter component demand and moment even where total force is known. Source role: supports retaining spatial pressure/traction fields, not only resultant force. Project conclusion: the local hydrodynamic model shall export complete load histories before any structural extension is attempted.

5.5 Governing Relations and Quantitative Definitions

5.6 Material or Structural System

5.7 Load Cases

5.8 Hydrodynamic Traction Transfer

The local three-dimensional fluid model supplies a transient traction field on the wetted structural surface. The traction exerted by the fluid on the solid is

$$\mathbf{t}_{f \rightarrow s} = \boldsymbol{\sigma}_f \mathbf{n}_s \quad (5.1)$$

where $\mathbf{n}_s$ is the outward unit normal of the current structural surface and the fluid Cauchy stress is

$$\boldsymbol{\sigma}_f = -p\mathbf{I} + \boldsymbol{\tau}_f \quad (5.2)$$

For a finite-element structural discretisation, the distributed interface traction is converted into the structural load vector through

$$\mathbf{f}_{\text{hyd}}(t) = \int_{\Gamma_{fs}(t)} \mathbf{N}_s^\top \mathbf{t}_{f \rightarrow s}(t) \, d\Gamma \quad (5.3)$$

The integration is performed over the current wetted interface $\Gamma_{fs}(t)$. The transferred field must preserve the resultant force and moment and should preserve interface work when the fluid and structural surface discretisations do not match.

The tsunami FSI model of Baragamage and Wu demonstrates the sequence from three-dimensional fluid loading to structural motion and subsequent feedback to the fluid solver, although its structural representation is reduced rather than a full three-dimensional deformable continuum [1]

Selected approach. Hydrodynamic loading is represented as a distributed pressure and viscous traction field on the fixed barrier surface during the active baseline. Reduction to a single resultant force is not sufficient for later structural or damage studies. Decision role: Equation (5.1)–Equation (5.3) define the load-transfer contract. Limitation: the equations are a handoff requirement and do not claim that a structural solver or FSI run has been executed.

5.9 Constitutive Behaviour

5.10 Response and Stability Measures

5.11 Damage and Failure Modes

5.12 Fluid–Structure Coupling Requirements

5.13 Candidate Approaches

5.14 Critical Comparison

5.15 Assumptions and Applicability

5.16 Limitations and Failure Conditions

5.17 Project-Specific Conclusions

The Studentship shall first stabilise hydrodynamic load extraction: pressure, shear, force, moment and impulse histories on fixed barrier patches. Material deformation and damage remain later consumers of these histories.

5.18 Selected Approach and Rationale

The selected near-term approach is one-way hydrodynamic load export from the local URANS–VOF model to structured output. One-way CFD-to-FEA and two-way FSI are retained as stretch paths, not baseline deliverables.

5.19 Unresolved Decisions

Open decisions are load-mapping tolerances, time-history sampling rate, structural mesh target, sign convention for moments and the activation criteria for one-way structural analysis.

5.20 Requirements and Handoffs

Software shall emit patch_id-resolved pressure, shear, resultant force, impulse, overturning moment, torsional moment, centre-of-pressure and integration-window metadata. RES-VER-MET shall define tolerances for force/moment consistency before RES-STR-SIM or RES-STR-FSI consumes the loads.

5.21 Deliverable Completion Record

6 RES-STR-RSP — Structural Response and Stability

6.1 Purpose and Scope

6.2 Research Questions

6.3 Terminology and Definitions

6.4 Literature Evidence

6.5 Governing Relations and Quantitative Definitions

6.6 Three-Dimensional Structural Equation of Motion

For the active hydrodynamic baseline, the barrier is represented in the fluid model as a fixed rigid solid. The deformable three-dimensional solid description below is retained as a future structural-response extension after hydrodynamic load histories have been validated.

Following spatial discretisation, the structural equation of motion is

$$\mathbf{M}_s \ddot{\mathbf{q}} + \mathbf{C}_s \dot{\mathbf{q}} + \mathbf{f}_{\text{int}}(\mathbf{q}, \mathbf{z}) = \mathbf{f}_{\text{hyd}}(t) + \mathbf{f}_{\text{body}}(t) \quad (6.1)$$

where $\mathbf{q}$ contains the structural displacement degrees of freedom, $\mathbf{z}$ contains material-history variables, $\mathbf{M}_s$ is the mass matrix, $\mathbf{C}_s$ is the damping matrix and $\mathbf{f}_{\text{int}}$ is the nonlinear internal-force vector.

The fixed-base boundary condition is

$$\mathbf{d} = \mathbf{0} \quad \text{on } \Gamma_{\text{base}} \quad (6.2)$$

A nonlinear and irregular tsunami load does not itself require nonlinear material behaviour. Structural nonlinearity arises from finite deformation, nonlinear constitutive response, contact, damage or failure. These mechanisms are deferred until a separate structural activation gate is passed.

6.7 Updated-Lagrangian Reference Description

The Lagrangian formulation governs how the deforming solid is referenced during one tsunami simulation. In an Updated-Lagrangian formulation, the latest converged configuration becomes the reference for the following increment

$$\mathbf{x}_{n+1} = \mathbf{x}_n + \Delta \mathbf{d}_{n+1} \quad (6.3)$$

This differs from the barrier-class comparison loop. Each future structural case would begin with its own undeformed design geometry, while the Updated-Lagrangian formulation governs deformation within that structural simulation.

If structural response is activated, candidate geometries may undergo substantial rotation, yielding and permanent shape change. The Updated-Lagrangian description is therefore retained as the preferred finite-deformation reference formulation. It is compatible with three-dimensional transient solid dynamics and incremental constitutive updates [3]

Deferred selected approach. Use an Updated-Lagrangian three-dimensional finite-deformation solid model only after the fixed-rigid hydrodynamic load extraction and validation gate is passed.

6.8 Material or Structural System

6.9 Load Cases

6.10 Constitutive Behaviour

6.11 Response and Stability Measures

6.12 Damage and Failure Modes

6.13 Fluid–Structure Coupling Requirements

6.14 Candidate Approaches

6.15 Critical Comparison

6.16 Assumptions and Applicability

6.17 Limitations and Failure Conditions

6.18 Project-Specific Conclusions

6.19 Selected Approach and Rationale

6.20 Unresolved Decisions

6.21 Requirements and Handoffs

6.22 Deliverable Completion Record

7 RES-STR-DMG — Damage, Failure and Performance-Loss Models

7.1 Purpose and Scope

This Deliverable records damage and failure modelling as a stretch extension. The active project baseline is hydrodynamic comparison of fixed rigid barriers; it shall not infer material damage, scour, fracture or post-failure debris motion from fluid loads alone.

-
- 7.2 Research Questions**
 - 7.3 Terminology and Definitions**
 - 7.4 Literature Evidence**
 - 7.5 Governing Relations and Quantitative Definitions**
 - 7.6 Material or Structural System**
 - 7.7 Load Cases**
 - 7.8 Constitutive Behaviour**
 - 7.9 Response and Stability Measures**
 - 7.10 Damage and Failure Modes**
 - 7.11 Initial Failure-Modelling Scope**

The Updated-Lagrangian formulation permits large deformation but does not independently provide plasticity, damage, fracture or topology change. Earlier structural notes identified this as a possible future route; it is not the active baseline.

Full post-fracture continuation would additionally require crack or damage evolution, contact between separated surfaces, topology change and a fluid treatment for detached structural fragments. These capabilities are outside the active fixed-rigid hydrodynamic baseline.

Selected scope. Defer large nonlinear deformation, material damage, fragmentation, debris–fluid interaction and scour until the fixed-rigid hydrodynamic load histories have been validated and accepted. Source role: Baragamage and Wu [1] demonstrates that tsunami loading can be coupled to structural motion, but also supports treating such coupling as a higher-fidelity extension. Limitation: no project damage model has been selected or executed.

7.12 Fluid–Structure Coupling Requirements

7.13 Candidate Approaches

7.14 Critical Comparison

7.15 Assumptions and Applicability

7.16 Limitations and Failure Conditions

7.17 Project-Specific Conclusions

The current Studentship output is a load dataset suitable for later damage studies, not a damage prediction. Damage claims require a separate constitutive model, validation evidence and acceptance gate.

7.18 Selected Approach and Rationale

The selected approach is formal deferral. Damage metrics may be listed as future consumers of pressure, shear, force, impulse and moment histories, but shall not be reported as baseline simulation outputs.

7.19 Unresolved Decisions

Open decisions are candidate material families, damage variables, failure criteria, scour coupling and validation data for damage or post-failure behaviour.

7.20 Requirements and Handoffs

Software shall not implement damage or deformable-structure logic from this deliverable. It shall preserve hydrodynamic histories and geometry/patch identifiers so a later structural extension can consume them.

7.21 Deliverable Completion Record

8 RES-STR-FSI — Fluid–Structure Interaction and Coupling Fidelity

8.1 Purpose and Scope

This Deliverable records a future FSI capability path and the load history information needed to support it. The active Studentship baseline remains fixed terrain and fixed rigid barriers in the local URANS–VOF model. One-way CFD-to-FEA and two-way FSI are stretch extensions after hydrodynamic load extraction is stable.

8.2 Research Questions

8.3 Terminology and Definitions

8.4 Literature Evidence

8.4.1 Baragamage and Wu (2024)

Baragamage and Wu [1] demonstrated a tsunami-impact framework in which an incompressible free-surface Navier–Stokes model was coupled with a structural equation of motion. Fluid pressure generated structural force, while structural displacement and velocity were returned to the fluid boundary.

The study establishes the feasibility of two-way tsunami FSI but does not establish that two-way coupling is required for every barrier candidate. Its bridge representation was structurally reduced, and parts of the validation used a constrained flow configuration.

8.4.2 Istrati and Buckle (2019)

Istrati and Buckle [2] demonstrated that the distribution of pressure and structural demand cannot always be reconstructed from the total force alone. Changes in internal ventilation altered uplift, moment, and the distribution of demand between structural components.

8.5 Governing Relations and Quantitative Definitions

8.5.1 Structural State and Momentum Equation

The structural state is provisionally defined as:

$$\mathcal{Q}_s = \{\mathbf{d}_s, \dot{\mathbf{d}}_s, \boldsymbol{\sigma}_s, \boldsymbol{\xi}_s\} \quad (8.1)$$

where $\boldsymbol{\xi}_s$ contains the internal variables required by the selected material model. In continuum form, structural momentum conservation is:

$$\rho_s \ddot{\mathbf{d}}_s = \nabla_0 \cdot \mathbf{P}_s + \rho_s \mathbf{b}_s \quad (8.2)$$

where $\mathbf{P}_s$ is the first Piola–Kirchhoff stress tensor. The corresponding finite-element semi-discrete form is:

$$\mathbf{M}_s \ddot{\mathbf{d}}_s + \mathbf{C}_s \dot{\mathbf{d}}_s + \mathbf{f}_{\text{int}}(\mathbf{d}_s, \boldsymbol{\xi}_s) = \mathbf{f}_{\text{fluid}} + \mathbf{f}_{\text{ext}} \quad (8.3)$$

The formulation shall support more than a single structural degree of freedom. The initial structural model may be linear elastic, but the interface shall permit later activation of:

- geometric nonlinearity;
- material plasticity;
- contact and connection behaviour;
- damage and failure variables;
- rigid-body translation and rotation.

8.6 Fluid–Structure Interaction Model and Activation Strategy

The structural formulation shall therefore preserve the spatial and temporal hydrodynamic traction even where the optimisation initially uses a fixed rigid barrier.

For the current project scope, this statement is a data-preservation requirement only: fixed-barrier simulations must retain enough surface history for later structural studies, but they do not move the barrier or solve structural response.

8.7 Material or Structural System

8.8 Load Cases

8.9 Constitutive Behaviour

8.10 Response and Stability Measures

8.11 Damage and Failure Modes

8.12 Fluid–Structure Coupling Requirements

8.12.1 Fluid–Structure Interface Conditions

At the fluid–structure interface Γ_{fs} , kinematic compatibility requires:

$$\mathbf{u}_f = \dot{\mathbf{d}}_s \quad \text{on } \Gamma_{fs} \quad (8.4)$$

Dynamic equilibrium requires:

$$\boldsymbol{\sigma}_f \mathbf{n}_f + \boldsymbol{\sigma}_s \mathbf{n}_s = \mathbf{0} \quad \text{on } \Gamma_{fs} \quad (8.5)$$

The structural load is obtained from the mapped fluid traction:

$$\mathbf{f}_{\text{fluid}} = \mathcal{T}_{f \rightarrow s} [\boldsymbol{\sigma}_f \mathbf{n}_f] \quad (8.6)$$

where $\mathcal{T}_{f \rightarrow s}$ is the fluid-to-structure load-transfer operator.

For two-way coupling, the deformed structural state is returned through:

$$\Gamma_{fs}^{n+1} = \mathcal{T}_{s \rightarrow f} [\mathbf{d}_s^{n+1}] \quad (8.7)$$

The transfer operators shall conserve resultant force and moment to within the tolerances defined by ‘RES-VER-MET’.

8.12.2 FSI Fidelity Hierarchy

The structural-coupling hierarchy is:

Mode	Fluid treatment	Structural treatment	Intended use
0	Local URANS	Fixed rigid barrier	Initial fixed-rigid hydrodynamic comparison
1	Local URANS or LES	One-way CFD-to-FEA	Stress, deformation, stability, and failure screening
2	Local URANS or LES	Partitioned two-way FSI	Cases with material but moderate deformation feedback
3	Local high-fidelity model	Strongly coupled non-linear FSI	Flexible, moving, unstable, or intentionally compliant final designs

Table 1: Fluid–structure coupling hierarchy for candidate and shortlisted barrier designs

8.12.3 Two-Way FSI Activation Gate

Two-way FSI shall be activated where one or more of the following conditions are satisfied:

1. structural displacement changes the exposed geometry or wetted area materially;
2. structural motion changes a flow passage, opening, or overtopping path;
3. structural velocity is no longer negligible relative to the adjacent fluid velocity;
4. rotation or translation changes the reflected or transmitted wave field;
5. connection flexibility controls the global response;
6. instability, uplift, sliding, overturning, or large rotation is predicted;
7. the barrier relies on intentional compliant motion for energy dissipation;
8. one-way and two-way pilot simulations produce materially different hydrodynamic or structural performance measures.

A preliminary motion-feedback indicator may be defined as:

$$\Pi_{\text{fsi}} = \max_{\Gamma_{\text{fs}}, t} \left(\frac{\|\dot{\mathbf{d}}_s\|}{\|\mathbf{u}_f\| + \epsilon_u} \right) \quad (8.8)$$

where ϵ_u prevents division by zero.

The threshold for activating two-way FSI shall be determined through sensitivity testing rather than assigned universally.

8.13 Reference Descriptions of the Coupled Domains

The regional and local fluid models use an Eulerian description in which fluid variables are evaluated at spatial positions

$$\mathbf{u} = \mathbf{u}(\mathbf{x}, t) \quad (8.9)$$

The solid uses a Lagrangian material description

$$\mathbf{x} = \chi(\mathbf{X}, t) = \mathbf{X} + \mathbf{d}(\mathbf{X}, t) \quad (8.10)$$

Impact does not require a Lagrangian fluid description. Retaining an Eulerian fluid mesh is more suitable for breaking, overtopping and free-surface topology change, while the Lagrangian solid description tracks the barrier deformation and material history.

8.14 Fluid–Solid Interface Conditions

Two-way coupling requires kinematic compatibility and dynamic equilibrium on the moving interface

$$\mathbf{u}_f = \dot{\mathbf{d}}_s \quad \text{on } \Gamma_{fs}(t) \quad (8.11)$$

$$\boldsymbol{\sigma}_f \mathbf{n}_f + \boldsymbol{\sigma}_s \mathbf{n}_s = \mathbf{0} \quad \text{on } \Gamma_{fs}(t) \quad (8.12)$$

The fluid solver transfers traction to the structure. The structural solver returns the current interface position and velocity to the fluid representation. A one-way calculation omits the return of structural motion, while a two-way calculation repeats this exchange throughout the transient solution.

8.15 Moving-Boundary Treatment

A body-fitted Arbitrary Lagrangian–Eulerian method moves the fluid mesh with the structure. The fluid advection velocity is then evaluated relative to the mesh velocity

$$\mathbf{u}_{\text{rel}} = \mathbf{u} - \mathbf{w}_m \quad (8.13)$$

ALE provides a direct conforming interface and conventional near-wall treatment. Its principal limitation for the present application is the risk of fluid-mesh distortion under severe structural deformation, followed by remeshing and transfer of pressure, velocity, VOF and turbulence fields. It remains useful as a reference method for moderate-deformation benchmarks [4]

If FSI is activated as a stretch extension, the selected reference family is a sharp immersed structural surface with conservative cut cells on a fixed Eulerian background mesh. The method avoids global fluid-mesh deformation while accounting geometrically for the changing fluid volume and moving solid boundary. Pasquariello et al. demonstrate conservative finite-volume–finite-element coupling with cut cells and nonmatching interface transfer for three-dimensional FSI with large structural deformation [5]. Baragamage and Wu apply a related immersed-boundary and cut-cell strategy to three-dimensional tsunami loading [1]

Deferred selected approach. Retain a sharp immersed-boundary representation with conservative cut-cell treatment as the preferred FSI extension path. Retain ALE as a comparator for moderate-deformation verification cases.

The selected family must subsequently define cut-cell geometry, changing fluid volumes, small-cell stabilisation, reconstructed wall states, traction recovery and conservative transfer between fluid and structural interfaces.

8.16 Deferred High-Level FSI Architecture

The deferred high-level architecture is

$$\begin{aligned} & \text{Eulerian polyhedral finite-volume two-phase fluid} \\ & + \text{VOF free-surface capture} \\ & + \text{Updated-Lagrangian three-dimensional solid FEM} \\ & + \text{generalised-}\alpha \text{ structural time integration} \\ & + \text{Newton-type nonlinear structural solution} \\ & + \text{sharp immersed boundary with conservative cut cells} \end{aligned} \quad (8.14)$$

The following high-level decisions remain unresolved:

-
1. monolithic or partitioned coupling
 2. loose or strong partitioned coupling if the partitioned family is selected
 3. added-mass stabilisation, relaxation and interface quasi-Newton acceleration
 4. conservative transfer of force, moment, displacement and interface work
 5. coordination of fluid and structural time levels
 6. transition criteria between rigid, one-way and two-way FSI calculations

8.17 Candidate Approaches

8.18 Critical Comparison

8.19 Assumptions and Applicability

8.20 Limitations and Failure Conditions

8.21 Project-Specific Conclusions

8.21.1 Project-Specific FSI Decision

The software and data architecture shall be FSI-capable from the outset. The baseline hydrodynamic comparison model shall nevertheless use a fixed rigid barrier and retain complete surface traction histories.

The initial structural verification shall use one-way CFD-to-FEA load transfer. Two-way FSI shall be introduced only where the activation gate demonstrates that structural motion feeds back materially into the hydrodynamic response.

This approach retains the equation-level capability for coupled simulation without imposing fully coupled FSI on the active barrier comparison campaign.

8.22 Selected Approach and Rationale

8.23 Unresolved Decisions

8.24 Requirements and Handoffs

Software shall preserve load, geometry and patch histories in a form that a later FSI extension can consume, but shall not implement moving boundaries, structural time integration or two-way coupling from this Research update. RES-VER-MET shall define force/moment transfer consistency metrics before FSI activation.

8.25 Deliverable Completion Record

9 RES-STR-SIM — Structural Simulation and Finite-Element Methodology

9.1 Purpose and Scope

9.2 Research Questions

9.3 Terminology and Definitions

9.4 Literature Evidence

9.5 Governing Relations and Quantitative Definitions

9.6 Material or Structural System

9.7 Load Cases

9.8 Constitutive Behaviour

9.9 Response and Stability Measures

9.10 Damage and Failure Modes

9.11 Fluid–Structure Coupling Requirements

9.12 Structural Spatial and Temporal Discretisation

The deferred structural solution stack consists of three-dimensional finite elements, Updated-Lagrangian finite-deformation kinematics, generalised- α time integration and Newton-type nonlinear equilibrium iterations. The generalised- α method supplies the temporal discretisation only; it does not replace the finite-element formulation, constitutive law or nonlinear solver. This stack is not part of the active fixed-rigid hydrodynamic baseline.

At each time step, equilibrium is enforced at weighted intermediate states through a residual of the form

$$\mathbf{R}_s = \mathbf{M}_s \ddot{\mathbf{q}}_{n+1-\alpha_m} + \mathbf{C}_s \dot{\mathbf{q}}_{n+1-\alpha_f} + \mathbf{f}_{\text{int}}(\mathbf{q}_{n+1-\alpha_f}, \mathbf{z}_{n+1}) - \mathbf{f}_{\text{ext},n+1-\alpha_f} \quad (9.1)$$

The weighted acceleration and displacement states are

$$\ddot{\mathbf{q}}_{n+1-\alpha_m} = (1 - \alpha_m) \ddot{\mathbf{q}}_{n+1} + \alpha_m \ddot{\mathbf{q}}_n \quad (9.2)$$

$$\mathbf{q}_{n+1-\alpha_f} = (1 - \alpha_f) \mathbf{q}_{n+1} + \alpha_f \mathbf{q}_n \quad (9.3)$$

The displacement and velocity are updated through Newmark-type relations

$$\mathbf{q}_{n+1} = \mathbf{q}_n + \Delta t \dot{\mathbf{q}}_n + \Delta t^2 \left[\left(\frac{1}{2} - \beta \right) \ddot{\mathbf{q}}_n + \beta \ddot{\mathbf{q}}_{n+1} \right] \quad (9.4)$$

$$\dot{\mathbf{q}}_{n+1} = \dot{\mathbf{q}}_n + \Delta t [(1 - \gamma) \ddot{\mathbf{q}}_n + \gamma \ddot{\mathbf{q}}_{n+1}] \quad (9.5)$$

Under the standard parameter conditions, the method provides second-order accuracy and controllable high-frequency numerical dissipation [6]. Liu and Marsden demonstrate its use within a three-dimensional nonlinear solid and FSI framework [7]

9.13 Nonlinear Equilibrium Solution

If structural response is activated, finite deformation and nonlinear constitutive behaviour require an iterative solution at each structural time step. A Newton correction is obtained from

$$\mathbf{K}_{\text{eff}}^{(k)} \Delta \mathbf{q}^{(k)} = -\mathbf{R}_s^{(k)} \quad (9.6)$$

$$\mathbf{q}^{(k+1)} = \mathbf{q}^{(k)} + \Delta \mathbf{q}^{(k)} \quad (9.7)$$

where $\mathbf{K}_{\text{eff}}$ contains the mass, damping and consistent tangent-stiffness contributions. The structural state is accepted only after the residual and displacement correction satisfy the selected nonlinear convergence criteria.

Deferred selected approach. Use generalised- α time integration embedded in a Newton-type nonlinear finite-element solution only after hydrodynamic load extraction is accepted.

Unresolved decisions. The constitutive family, element technology, incompressibility treatment, damping model, spectral-radius parameter and nonlinear convergence tolerances remain to be selected.

9.14 Candidate Approaches**9.15 Critical Comparison****9.16 Assumptions and Applicability****9.17 Limitations and Failure Conditions****9.18 Project-Specific Conclusions****9.19 Selected Approach and Rationale****9.20 Unresolved Decisions****9.21 Requirements and Handoffs****9.22 Deliverable Completion Record****10 RES-STR-SPEC — Integrated Structural and Damage Specification****10.1 Purpose and Scope**

This Deliverable consolidates the current structural decision: baseline simulations treat barriers as fixed rigid geometry and export hydrodynamic pressure, shear, force, impulse and moment histories. Material response, deformation, damage, scour and two-way FSI are stretch extensions requiring separate evidence and validation.

-
- 10.2 Research Questions**
 - 10.3 Terminology and Definitions**
 - 10.4 Literature Evidence**
 - 10.5 Governing Relations and Quantitative Definitions**
 - 10.6 Material or Structural System**
 - 10.7 Load Cases**
 - 10.8 Constitutive Behaviour**
 - 10.9 Response and Stability Measures**
 - 10.10 Damage and Failure Modes**
 - 10.11 Fluid–Structure Coupling Requirements**
 - 10.12 Candidate Approaches**
 - 10.13 Critical Comparison**
 - 10.14 Assumptions and Applicability**
 - 10.15 Limitations and Failure Conditions**
 - 10.16 Project-Specific Conclusions**

The integrated structural output for the current Studentship is a load-transfer specification, not a structural-damage model.

10.17 Selected Approach and Rationale

The selected active approach is fixed-rigid hydrodynamic load extraction with structured one-way handoff. Deformable structural simulation and two-way FSI remain deferred.

10.18 Unresolved Decisions

10.19 Requirements and Handoffs

Software shall preserve load histories, geometry patch identifiers and integration metadata; it shall not implement damage, structural FEM or moving-boundary FSI as part of this Research handoff.

10.20 Deliverable Completion Record

References

1. Baragamage DSPA and Wu W. A Three-Dimensional Fully-Coupled Fluid-Structure Model for Tsunami Loading on Coastal Bridges. *Water* 2024; 16:189. DOI: [10.3390/w16010189](https://doi.org/10.3390/w16010189)
2. Istrati D and Buckle I. Role of Trapped Air on the Tsunami-Induced Transient Loads and Response of Coastal Bridges. *Geosciences* 2019; 9:191. DOI: [10.3390/geosciences9040191](https://doi.org/10.3390/geosciences9040191)
3. Nemer R, Larcher A, Coupez T, and Hachem E. Stabilized Finite Element Method for Incompressible Solid Dynamics Using an Updated Lagrangian Formulation. *Computer Methods in Applied Mechanics and Engineering* 2021; 384:113923. DOI: [10.1016/j.cma.2021.113923](https://doi.org/10.1016/j.cma.2021.113923)
4. Girfoglio M, Quaini A, and Rozza G. Fluid-Structure Interaction Simulations with a LES Filtering Approach in solids4Foam. 2021. DOI: [10.48550/arXiv.2102.08011](https://doi.org/10.48550/arXiv.2102.08011). arXiv: [2102.08011 \[physics.flu-dyn\]](https://arxiv.org/abs/2102.08011)
5. Pasquariello V, Hammerl G, Örley F, Hickel S, Danowski C, Popp A, Wall WA, and Adams NA. A Cut-Cell Finite Volume–Finite Element Coupling Approach for Fluid-Structure Interaction in Compressible Flow. *Journal of Computational Physics* 2016; 307:670–95. DOI: [10.1016/j.jcp.2015.12.013](https://doi.org/10.1016/j.jcp.2015.12.013)
6. Chung J and Hulbert GM. A Time Integration Algorithm for Structural Dynamics with Improved Numerical Dissipation: The Generalized-Alpha Method. *Journal of Applied Mechanics* 1993; 60:371–5. DOI: [10.1115/1.2900803](https://doi.org/10.1115/1.2900803)
7. Liu J and Marsden AL. A Unified Continuum and Variational Multiscale Formulation for Fluids, Solids, and Fluid-Structure Interaction. *Computer Methods in Applied Mechanics and Engineering* 2018; 337:549–97. DOI: [10.1016/j.cma.2018.03.045](https://doi.org/10.1016/j.cma.2018.03.045)