


Machine Learning Foundations

An Introduction to your AI Journey

Sumudu Tennakoon, PhD



© 2021 Sumudu Tennakoon

1

Course Objective

Provide comprehensive understanding of the core principles of Machine Learning with hands-on training on applying machine learning to solve real-world problems.

A learner who completes this course should be able to define a machine learning problem, understand the solution path, and display the ability to carry out the end-to-end process of building a machine learning application.

© 2021 Sumudu Tennakoon

2

Machine Learning Career Prospectus

- Data Scientist
- AI Scientist
- ML/AI Engineer
- Data Engineer
- Data Analyst
- AI/ML Developer
- IoT Developer
- Solutions Architect
- Freelancer
- ...

© 2021 Sumudu Tennakoon

3

Schedule and Format

Duration: 60 hours

Schedule: 3-month program/12 weeks, two sessions per week.

Format: Live/Recorded Lectures, Demonstrations, Hands-on Exercises/Labs.

Evaluation: Quizzes (2), Project (1)

Additional Practice: Students must spend extra time on exercises and the capstone project.

© 2021 Sumudu Tennakoon

4

Prerequisites

- Basics of computer programming, mathematics, and statistics.
- Basic knowledge in computer applications:
 - Spreadsheet
 - word processor
 - presentation authoring

© 2021 Sumudu Tennakoon

5

Platform and Data for Hands-on Exercises and Project

Programing Language: Python 3 will be used as the primary programming language in teaching, practice examples and assignments.

Python Libraries: Scikit-learn, TensorFlow, Pandas, NumPy, Matplotlib, Seaborn, Flask.

Applications/Tools: Jupyter Notebook/Lab, IDE (Spyder/VS Code/Atom/PyCharm), Spreadsheet (MS Excel/LibreOffice Calc).

Data: Data for exercises, case studies, and projects will be obtained from open data repositories.

Computing Environment: Cloud platform (will be decided on class consensus and service availability) or locally installed Python distribution in student's PC.

© 2021 Sumudu Tennakoon

6

Session Topics

#	Topic Name	Training Week #
1	Introduction to Machine Learning (ML), History, and Applications	1
2	Setting up a Computing Environment, Python and Required Libraries.	2
3	Knowledge Foundations to ML (Computing, Statistics, and Mathematics) *	2-3
4	Exploratory Data Analysis (EDA) and Feature Engineering *	4-5
5	Supervised and Unsupervised Learning (concepts)	6
6	Machine Learning Algorithms *	6-7
7	Explaining ML Models and Predictions (introduction) *	7
8	Deep Learning and Neural Networks (introduction) *	8
9	Design and Develop and Deploy ML Solutions *	9-10
10	Capstone Project *	11-12

© 2021 Sumudu Tennakoon

7

Evaluations and Grading

Completion Requirement:

- 80 % Attendance (at least 19 out of 24 sessions)
- Final Grade > 70 %

Completion with Distinction:

- Final Grade > 90 %

Topic #	%
Quiz1 (Basic Concepts)	1-6 20
Quiz 2 (Advanced Concepts, Deep Learning and Application Building)	7-9 20
Deliverable and Project Report	10 50
Presentation (video narration)	10 10
	100

© 2021 Sumudu Tennakoon

8

Introduction to Machine Learning

History and core concepts of ML to navigate the future lessons.

Applications of ML.



© 2021 Sumudu Tennakoon


9

Example: Identify Objects

What facts you consider to identify these object?



Pineapple



Apple

© 2021 Sumudu Tennakoon


10

How we Learn ?


- Memorize Facts
 - Declarative Knowledge
 - Limited by memory and time to observe
- Infer (deduce new information from previously known facts)
 - Imperative Knowledge
 - Limited by accuracy of predictions and drifts (present is not behaving the same way as past)

© 2021 Sumudu Tennakoon


11




12



13



14



15

Exercise

What are the Observations/Measurements can be used to make a determination.

Design a simple classifier logic.

Is it easy or difficult to convert this logic to a computer program (code)?

What are the considerations when converting this logic to a computer program (code)?


What are the points of failures in this approach?

© 2021 Sumudu Tennakoon

16

What is Machine Learning ?

- Learn from Data



17

Machine learning model




“Machine learning models are built on mathematical algorithms and are trained using data and human expertise to help us accurately predict outcomes based on input data such as images, text, or language.”

<https://developer.nvidia.com/ai-models>

© 2021 Sumudu Tennakoon

18



19

What is Machine Learning?

“The field of study that gives computers the ability to learn without being explicitly programmed.”

~ Arthur Samuel (1959)

Author of first self-learning program to learn how to play checkers by learning from experience (past movements and results)

© 2021 Sumudu Tennakoon

20

What is Machine Learning?

“ A computer program is said to learn from experience E with respect to some class of **tasks T** and **performance measure P**, if its performance at tasks in T, as measured by P, improves with **experience E**.“

~ Tom Mitchell (1997)

Example: playing checkers.

- E = the experience of playing many games of checkers
- T = the task of playing checkers.
- P = the probability that the program will win the next game.

Mitchell, T. (1997). *Machine Learning*. McGraw Hill.
© 2021 Sumudu Tennakoon
p. 2. [ISBN 978-0-07-042807-2](#).

21


AI and Machine Learning

- AI (Mimic Cognitive Functions of Human)
 - Computer Vision
 - Speech Recognition and Synthesis
 - Language Processing and Understanding
 - Motion
 - Decision Making
 - Prescribe or Predict
 - Reasoning
- Machine Learning (ML)
 - Machines learn on Data/Prior Knowledge
 - Statistical Modeling/Algorithms
 - Backbone of AI is Machine Learning
 - Algorithms to Find meanings of data
 - Find Relationships
 - Making Predictions
 - Problem-Solution Types
 - Classification
 - Regression
 - Clustering

© 2021 Sumudu Tennakoon

22

Machine Learning/Deep Learning/AI



23

Levels of AI

Artificial General Intelligence (AGI) known as “Strong AI”

- AGI is the ability to solve *any* problem rather than finding a solution to a particular problem.
- Machine can understand or learn any intellectual task that a human being can.
- The machine can think and perform tasks on its own, just like a human being.
- In the Movies! We are not there yet.

Weak Artificial Intelligence (Weak AI),

- Implements a limited part of human cognitive abilities.
- **Narrow AI** is a special case of Weak AI focused on a specific problem or task.
- Currently, existing AI systems are likely operating as a narrow AI.
- devices cannot follow these tasks independently but are made to look intelligent (simulate human behavior).

© 2021 Sumudu Tennakoon

24

Building Blocks of an AI System

- Image recognition (computer vision)
- Signal processing (sound, sensor data feed, etc.)
- Speech Recognition (Speech to text/STT)
- Natural language processing (NLP)
- Visual Synthesis (Computer Graphics)
- Sound Synthesis (Text to Speech/TTS)
- Software/Algorithms
- Applications (Anomaly Detection, Classification, Prediction, Pattern Recognition)
- Memory (Storage, RAM, Cache)
- Processor (GPU, CPU, TPU)
- Connectivity (Wi-Fi, Satellite, 5G, ethernet, etc.)
- Hardware (Computer, Mechanical Components, etc.)



© 2021 Sumudu Tennakoon

25


Precursor to Machine Learning



Pascal's calculator (1642)



Arithmomètre (1887)



Tabulating machine & punched card (1890)



IBM 405 Alphabetical Accounting Machine (1934).

https://en.wikipedia.org/wiki/Pascal%27s_calculator


<https://en.wikipedia.org/wiki/Arithmometer>

https://en.wikipedia.org/wiki/Tabulating_machine

<http://www.columbia.edu/cu/computinghistory/405.html>

26

(Incomplete) Timeline of Machine Learning




27

Hype Cycle for Artificial Intelligence, 2021

Hype Cycle for Emerging Tech

<https://www.gartner.com/en/articles/the-4-trends-that-prevail-on-the-gartner-hype-cycle-for-ai-2021>



28

WORLD
ECONOMIC
FORUM

Job Landscape

Job landscape

By 2025, new jobs will emerge and others will be displaced by a shift in the division of labour between humans and machines, affecting:



Category	Count
Decreasing job demand	97 million
Growing job demand	85 million

Decreasing job demand:

1. Data Entry Clerks
2. Administrative and Executive Secretaries
3. Accounting, Bookkeeping and Payroll Clerks
4. Accountants and Auditors
5. Assembly and Factory Workers
6. Business Services and Administration Managers
7. Client Information and Customer Service Workers
8. General and Operations Managers
9. Mechanics and Machinery Repairers
10. Material-Recording and Stock-Keeping Clerks


Growing job demand:

1. Data Analysts and Scientists
2. AI and Machine Learning Specialists
3. Big Data Specialists
4. Digital Marketing and Strategy Specialists
5. Process Automation Specialists
6. Business Development Professionals
7. Digital Transformation Specialists
8. Information Security Analysts
9. Software and Applications Developers
10. Internet of Things Specialists

Source: Future of Jobs Report 2020, World Economic Forum.

29

Exercise



What are Observations/Measurements can be used to make a determination.

Design a simple classifier logic.

Is it easy or difficult to converting this logic to a computer program (code)?


What are the considerations when converting this logic to a code?

What are the points of failure in this approach?


© 2021 Sumudu Tennakoon

30

Input and Output ?



31



32



33

Tabular Data


	Column 1	Column 2	Column 3	
	ID	Name	DOB	← Column Names
Row 1	10001	John Doe	1988-01-01	
Row 2	10002	Jane Doe	1990-12-31	Row (Record)
Row 3	

Column
(Data Field)

<https://pub.towardsai.net/data-science-for-everyone-getting-to-know-your-data-part-1-bb8b6d7782b1>

34

Understanding Data



© 2020 Sumudu Tennakoon

© 2021 Sumudu Tennakoon

35




© 2021 Sumudu Tennakoon

© 2020 Sumudu Tennakoon

36


Data Types and Representations



<https://pub.towardsai.net/data-science-for-everyone-getting-to-know-your-data-part-1-bb8b6d7782b1>

37


Machine Learning Approaches



© 2021 Sumudu Tennakoon



38



© 2021 Sumudu Tennakoon https://en.wikipedia.org/wiki/Reinforcement_learning

39

Types of ML Algorithms



Regression

Linear
Polynomial



Classification

Tree Classifiers
Logistic Regression
Support Vector Machines (SVM)




Clustering

K-Means

© 2021 Sumudu Tennakoon


40

Regression




41

Classification




42

Clustering




43

Clustering



44


Recommender Systems



© 2021 Sumudu Tennakoon

45


Prediction



$$y = f(X) ?$$


© 2021 Sumudu Tennakoon

46



© 2021 Sumudu Tennakoon

47



48

Why we need Machine Learning?

Simulate human intelligence

Automation


Help humans with informed decision making

Solve multidimensional problems

Predict future outcome based on historical observations

© 2021 Sumudu Tennakoon

49




Source: Hilbert, M., & López, P. (2011). The World's Technological Capacity to Store, Communicate, and Compute Information. *Science*, 332(6025), 60–65. <http://www.martinhilbert.net/WorldInfoCapacity.html>

Scholz, R.. "Sustainable Digital Environments: What Major Challenges Is Humankind Facing?" *Sustainability* 8 (2016): 1-31.

50

Growth of World Data



zetta $1 \text{ ZB} = 10^{21} \text{ B}$

Annual volume of data and information created worldwide
Image: IDC; Seagate; Statista estimates

51

Machine Learning Applications

Spam Email Filtering

Approve or Reject Loan Application

Predicting Stock Price

Credit Card Fraud Detection

Recommending Items to Purchase
(Advertising)

© 2021 Sumudu Tennakoon

52

Application Areas

- Finance
- Marketing
- Information Technology
- Cyber Security
- Agriculture
- Government
- Automobile
- Manufacturing
- Retail
- Entertainment
- ...
- Everywhere!

© 2021 Sumudu Tennakoon

53

Why should everyone get familiar with ML?



Applications of machine learning are all around us.



ML is used in many industries and domains.



Job opportunities.



It is fun to learn and helps train your brain.



© 2021 Sumudu Tennakoon

54

Machine Learning Career Prospectus

- Data Scientist
- AI Scientist
- ML/AI Engineer
- Data Engineer
- Data Analyst
- AI/ML Developer
- IoT Developer
- Solutions Architect
- ...

© 2021 Sumudu Tennakoon




55

Setting up Computing Environment

Cloud Computing Platform
(Google Colab)
Python (Install, Libraries)

© 2021 Sumudu Tennakoon



56

Install Python in Local Computer

- Python: <https://www.python.org/downloads/>
- Anaconda Python: <https://www.anaconda.com/products/individual>
- Python: Libraries: <https://www.anaconda.com/open-source>



© 2021 Sumudu Tennakoon

57

Python Libraries

- Data Handling
 - Pandas
 - Dask (distributed)
- Machine Learning
 - Scikit-learn
 - TensorFlow
 - PyTorch
- Visualizing
 - Matplotlib
 - Seaborn
- Numerical and Scientific Computing
 - SciPy
 - NumPy
- Machine Learning Model Interpretation
 - LIME
 - SHAP
- Web Services/API
 - Flask
 - Django



© 2021 Sumudu Tennakoon

58

Install Python Libraries


- Using pip package manager for Python
 - <https://packaging.python.org/tutorials/installing-packages>
 - pip install some-package-name
 - NumPy: pip install numpy
 - Pandas: pip install pandas
 - Scikit-Learn: pip install scikit-learn
 - Matplotlib: pip install matplotlib

- Using Conda package manager
 - <https://docs.conda.io/projects/conda/en/latest/commands/install.html>
 - conda install -c conda-forge some-package-name
 - NumPy: conda install -c conda-forge numpy
 - Pandas: conda install -c conda-forge pandas
 - Scikit-Learn: conda install -c conda-forge scikit-learn
 - Matplotlib: conda install -c conda-forge matplotlib

© 2021 Sumudu Tennakoon

59

Jupyter Notebook/Lab



© 2021 Sumudu Tennakoon

60

Google Colab

<https://colab.research.google.com>

© 2021 Sumudu Tennakoon

61


Getting Started

- Creating New Notebook
- Opening Notebook from GitHub
- Opening Notebook from file

© 2021 Sumudu Tennakoon

62

Creating New Notebook




63

A screenshot of the Google Colab interface showing a new notebook titled 'Untitled1.ipynb'. The top navigation bar includes 'File', 'Edit', 'view', 'Insert', 'Runtime' (which is circled in red), 'Tools', 'Help', and 'All changes saved'. The main workspace contains two cells: a 'Text/Markdown Cell' with the text '# This is a Text Block' and a 'Code Cell' with the code: # This is a Code Block, 1, a = 2, print(a). Below the code cell is a play button icon (circled in red) and instructions: 'Click to run cell (execute the content)' or 'Press [SHIFT] + [ENTER]'. The bottom status bar shows '© 2021 Sumudu Tennakoon'.


64

Open Notebook




65

Open Notebook from GitHub



66



67

A screenshot of the "Machine Learning Foundations" notebook in Google Colab. The left sidebar shows a "Table of contents" with sections like "Machine Learning Foundations", "Python Basics", "Data Types", "Lists", "Tuples", "Sets", "Dictionary", "Conditions", "Functions", and "Exercise 1:". The main content area displays the following text:

Machine Learning Foundations

Sumudu Tennakoon, PhD

Python Basics


In this notebook we will explore some basic features on Python programming language for those who have a prior programming experience.

To learn more about Python, refer to the following websites

- Python : www.python.org

68

Upload Notebook (.ipynb file)



69

A screenshot of a Google Colab notebook titled "1-PythonBasics.ipynb". The left sidebar contains a "Table of contents" section with the following structure:

- Machine Learning Foundations
 - Python Basics
 - Variables
 - Data Types
 - Lists
 - Tuples
 - Sets
 - Dictionary
 - Conditions
 - Functions
 - Exercise 1:

The main content area displays the first few sections of the notebook:

Machine Learning Foundations

Sumudu Tennakoon, PhD

Python Basics

In this notebook we will explore some basic features on Python programming language for those who have a prior programming experience.

To learn more about Python, refer to the following websites

- Python : www.python.org

70

GitHub Link to Lecture Notebooks

**Folder:**

<https://github.com/sumudutennakoon/mlfoundations/tree/main/lecturenotebooks>

Python basics notebook:

<https://github.com/sumudutennakoon/mlfoundations/blob/main/lecturenotebooks/1-pythonbasics.ipynb>

© 2021 Sumudu Tennakoon

71

Mathematics for Machine Learning

The blackboard contains several mathematical derivations and formulas:

- $D(x) = \dots + 4.31447$
- $V(x) = \dots$
- $x^2 + y^2 = ab + 4c$
- $c(x,y) = \begin{cases} xy = c \\ cx - cy = 3b \\ cz = c \end{cases}$
- $\text{men} = 384. + n \cdot v$
- $x = 920 \quad \left(\sum N_{50} \cdot x - \frac{1}{2} [984 + x] \right)$
- $\beta = 9 + x^2 + y^2$

© 2021 Sumudu Tennakoon

72

Data Representations


- In computing everything must convert into numbers !
- Numeric Data Structures:
 - Scalars: [3.14](#)
 - Vectors (1D): [\[1,2,3\]](#)
 - Matrices (2D): [\[\[1,2\], \[3,4\] \]](#)
 - Tensors (3D+): [\[\[\[1,2\], \[3,4\] \], \[\[5,6\], \[7,8\] \] \]](#)

© 2021 Sumudu Tennakoon





73

Why we need Vectors, Matrices and Tensors in Machine Learning?



```
signal = [0 -2 -4 -2 0 2 3 3 2 -1 -3]
time   = [0 1 2 3 4 5 6 7 8 9 10]
```




1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1.0	0.9	0.8	0.9	0.8	0.9	0.9	0.9	0.9	0.9	0.9
0.7	0.7	0.7	0.8	1.0	0.6	0.8	0.8	0.7	0.7	0.8
0.9	0.9	0.9	0.9	1.0	0.9	0.9	0.9	0.9	0.9	0.9
0.9	1.0	1.0	0.9	1.0	1.0	1.0	1.0	1.0	1.0	1.0
0.7	0.6	0.8	0.8	0.9	0.6	1.0	0.8	0.8	0.7	0.8
1.0	0.9	1.0	1.0	1.0	0.9	1.0	1.0	1.0	1.0	1.0
1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1.0	0.9	0.8	0.9	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1.0	0.9	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0

<https://pub.towardsai.net/data-science-for-everyone-getting-to-know-your-data-part-1-bb8b6d7782b1>

74

Vectors and Matrices



75

Matrix Algebra

- Transpose
- Sum
- Diagonal
- Determinant
- Adjugate
- Inverse

© 2021 Sumudu Tennakoon

76

Matrix Notation

- Matrix Notation

$$\bullet A = \begin{bmatrix} a_{11} & a_{12} & \dots & a_{1n} \\ a_{21} & a_{22} & \dots & a_{2n} \\ \vdots & \vdots & \ddots & \vdots \\ a_{m1} & a_{m2} & \dots & a_{mn} \end{bmatrix}_{m \times n}$$

- Representation of elements in python index numbers

$$\bullet A = \begin{bmatrix} A[0][0] & A[0][1] & \dots & A[0][n-1] \\ A[1][0] & A[1][1] & \dots & A[1][n-1] \\ \vdots & \vdots & \ddots & \vdots \\ A[m-1][0] & A[m-1][1] & \dots & A[m-1][n-1] \end{bmatrix}$$

© 2021 Sumudu Tennakoon

77

Transpose, Sum, Diagonal

• $A = \begin{bmatrix} a_{11} & a_{12} & a_{13} & a_{14} \\ a_{21} & a_{22} & a_{23} & a_{24} \\ a_{31} & a_{32} & a_{33} & a_{34} \\ a_{41} & a_{42} & a_{43} & a_{44} \end{bmatrix} = [a_{ij}]$

• $A^T = \begin{bmatrix} a_{11} & a_{21} & a_{31} & a_{41} \\ a_{12} & a_{22} & a_{32} & a_{42} \\ a_{13} & a_{23} & a_{33} & a_{43} \\ a_{14} & a_{24} & a_{34} & a_{44} \end{bmatrix} = [a_{ji}]$

• $\text{Sum}(A) = \sum_{i,j} a_{ij}$

• $\text{Diagonal}(A) = [a_{11} \ a_{22} \ a_{33} \ a_{44}]$

• $\text{Trace}(A) = a_{11} + a_{22} + a_{33} + a_{44}$

Columns (j)
Rows (i)
Diagonal
Rows \leftrightarrow Columns

E.g.,

• $A = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$

• $A^T = \begin{bmatrix} 1 & 4 & 7 \\ 2 & 5 & 8 \\ 3 & 6 & 9 \end{bmatrix}$

• $\text{Sum}(A) = 1 + 2 + 3 + 4 + 5 + 6 + 7 + 8 + 9 = 45$

• $\text{Diagonal}(A) = [1 \ 5 \ 9]$

• $\text{Trace}(A) = 1 + 5 + 9 = 15$

© 2021 Sumudu Tennakoon

78

Determinant

$$\det \begin{pmatrix} a & b \\ c & d \end{pmatrix} = \begin{vmatrix} a & b \\ c & d \end{vmatrix} = ad - bc$$

$$\det \begin{pmatrix} 1 & 2 \\ 3 & 4 \end{pmatrix} = 1 \times 4 - 2 \times 3 = -2$$

$$\det \begin{pmatrix} a & b & c \\ d & e & f \\ g & h & i \end{pmatrix} = a \begin{vmatrix} e & f \\ h & i \end{vmatrix} - b \begin{vmatrix} d & f \\ g & i \end{vmatrix} + c \begin{vmatrix} d & e \\ g & h \end{vmatrix}$$

$$\det \begin{pmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{pmatrix} = 1 \begin{vmatrix} 5 & 6 \\ 8 & 9 \end{vmatrix} - 2 \begin{vmatrix} 4 & 6 \\ 7 & 9 \end{vmatrix} + 3 \begin{vmatrix} 4 & 5 \\ 7 & 8 \end{vmatrix} = 0$$

© 2021 Sumudu Tennakoon

79

Inverse Matrix

- $A^{-1} = \frac{1}{|A|} adj(A)$

- $A^{-1}A = AA^{-1} = I$

- $A = \begin{bmatrix} a & b \\ c & d \end{bmatrix}$

- $|A| = \begin{vmatrix} a & b \\ c & d \end{vmatrix} = ad - bc$

- $adj(A) = \begin{bmatrix} d & -b \\ -c & a \end{bmatrix}$

- $A^{-1} = \frac{1}{ad-bc} \begin{bmatrix} d & -b \\ -c & a \end{bmatrix}$

© 2021 Sumudu Tennakoon

https://en.wikipedia.org/wiki/Invertible_matrix

https://en.wikipedia.org/wiki/Adjugate_matrix

80

Properties of Matrix

$$\begin{aligned} A + B &= B + A \\ A + 0 &= A \\ AB &\neq BA \end{aligned}$$

$$\begin{aligned} A(BC) &= (AB)C \\ A(B+C) &= AB+AC \\ (A+B)C &= AC+BC \end{aligned}$$

$$\begin{aligned} \alpha(A+B) &= \alpha A + \alpha B \\ (\alpha + \beta)A &= \alpha A + \beta A \end{aligned}$$

$$\begin{aligned} 0.A &= 0 \\ A.0 &= 0 \end{aligned}$$

$$\begin{aligned} (A^T)^T &= A \\ (A+B)^T &= A^T + B^T \\ (AB)^T &= B^T A^T \end{aligned}$$

$$\begin{aligned} (A^{-1})^{-1} &= A \\ A^{-1}A &= AA^{-1} = I \end{aligned}$$

$$A = \begin{bmatrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{bmatrix}$$

$$A^T = \begin{bmatrix} 1 & 4 & 7 \\ 2 & 5 & 8 \\ 3 & 6 & 9 \end{bmatrix}$$

$$\begin{aligned} (A^T)^{-1} &= (A^{-1})^T \\ (AB)^{-1} &= B^{-1}A^{-1} \end{aligned}$$

$$\begin{aligned} |A^{-1}| &= \frac{1}{|A|} \\ |AB| &= |A||B| \end{aligned}$$

© 2021 Sumudu Tennakoon

81

Special Vectors/Matrices

- Square Matrix: $A = \begin{bmatrix} 1 & 2 \\ 3 & 4 \end{bmatrix}_{2 \times 2}$

- Symmetric Matrix: $S = \begin{bmatrix} 1 & 4 & 5 \\ 4 & 2 & 6 \\ 5 & 6 & 3 \end{bmatrix}$

- Zero Matrix: $0 = \begin{bmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}$

- Unit Vector: $\hat{x} = \begin{bmatrix} 1 \\ 0 \\ 0 \end{bmatrix}$

- Diagonal Matrix: $D = \begin{bmatrix} 1 & 0 & 0 \\ 0 & 2 & 0 \\ 0 & 0 & 3 \end{bmatrix}$

- Identity Matrix: $I = \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix}$

- Scalar Diagonal Matrix: $D = \begin{bmatrix} \lambda & 0 & 0 \\ 0 & \lambda & 0 \\ 0 & 0 & \lambda \end{bmatrix} = \lambda \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix} = \lambda I$

- Upper Triangular matrix: $U = \begin{bmatrix} 1 & 4 & 5 \\ 0 & 2 & 6 \\ 0 & 0 & 3 \end{bmatrix}$

- Lower Triangular Matrix: $L = \begin{bmatrix} 1 & 0 & 0 \\ 4 & 2 & 0 \\ 5 & 6 & 3 \end{bmatrix}$

© 2021 Sumudu Tennakoon

82



Matrix Operations and Applications

- Addition/Subtraction
- Scalar Multiplication
- Matrix Multiplication (Dot Product)
- Matrix-Vector Multiplication
- Row operations
- Solving Linear Equations
- Linear transformations
- Decomposition

© 2021 Sumudu Tennakoon

83

Matrix Multiplication

$$\bullet A = \begin{bmatrix} a & b \\ c & d \end{bmatrix}$$

$$\bullet B = \begin{bmatrix} p & q \\ r & s \end{bmatrix}$$

$$\bullet A \cdot B = \begin{bmatrix} a & b \\ c & d \end{bmatrix} \cdot \begin{bmatrix} p & q \\ r & s \end{bmatrix}$$


$$\bullet A \cdot B = \begin{bmatrix} ap + br & aq + bs \\ cp + dr & cq + ds \end{bmatrix}$$

© 2021 Sumudu Tennakoon https://en.wikipedia.org/wiki/Matrix_multiplication

84

Matrix Multiplication (Dot Product)

$$\begin{matrix} & m=3 \\ \text{A} & \cdot \\ & m=3 \end{matrix} \quad \begin{matrix} & n \\ \text{B} & \cdot \\ & n \end{matrix} = \begin{matrix} & n \\ \text{C} & \cdot \\ & n \end{matrix}$$



© 2021 Sumudu Tennakoon https://en.wikipedia.org/wiki/Matrix_multiplication

85

Solving Linear Equations

Problem:

$$\begin{aligned} 3x + 2y &= 12 \rightarrow (1) \\ 4x + 5y &= 23 \rightarrow (2) \end{aligned}$$

$$\begin{aligned} x &=? \\ y &=? \end{aligned}$$

Solution Approach:

$$\begin{aligned} x &= \frac{12 - 2y}{3} = 4 - \frac{2}{3}y \\ 4\left(4 - \frac{2}{3}y\right) + 5y &= 23 \\ 16 - \frac{8}{3}y + 5y &= 16 + \frac{15 - 8}{3}y = 16 + \frac{7}{3}y = 23 \\ y &= \frac{3(23 - 16)}{7} = \frac{3(7)}{7} = 3 \\ x &= 4 - \frac{2}{3}(3) = 4 - 2 = 2 \end{aligned}$$

$$\begin{aligned} x &= 2 \\ y &= 3 \end{aligned}$$

© 2021 Sumudu Tennakoon

86

Formulating the Problem in Matrix Form

$$\begin{aligned}x_1 &= x \\x_2 &= y\end{aligned}$$

$$3x_1 + 2x_2 = 12 \rightarrow (1)$$

$$4x_1 + 5x_2 = 23 \rightarrow (2)$$

Solve using Matrices:

$$\begin{bmatrix} 3 \\ 4 \end{bmatrix} x_1 + \begin{bmatrix} 2 \\ 5 \end{bmatrix} x_2 = \begin{bmatrix} 12 \\ 23 \end{bmatrix}$$

$$\begin{bmatrix} 3 & 2 \\ 4 & 5 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} = \begin{bmatrix} 12 \\ 23 \end{bmatrix}$$

$$A = \begin{bmatrix} 3 & 2 \\ 4 & 5 \end{bmatrix} = \begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix}$$

$$\begin{bmatrix} a_{11} & a_{12} \\ a_{21} & a_{22} \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} = \begin{bmatrix} b_1 \\ b_2 \end{bmatrix}$$

© 2021 Sumudu Tennakoon

$$Ax = b$$

$$x = \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$$

$$b = \begin{bmatrix} b_1 \\ b_2 \end{bmatrix} = \begin{bmatrix} 12 \\ 23 \end{bmatrix}$$

87

Obtaining the Solution in Matrix Form

$$\begin{aligned}Ax &= b \\A^{-1}Ax &= A^{-1}b \\Ix &= A^{-1}b \\x &= A^{-1}b\end{aligned}$$

$$\text{Example} \quad A = \begin{bmatrix} 3 & 2 \\ 4 & 5 \end{bmatrix}$$

$$b = \begin{bmatrix} 12 \\ 23 \end{bmatrix}$$

$$A^{-1} = \frac{1}{|A|} adj(A)$$

$$|A| = 3 \times 5 - 4 \times 2 = 7$$

$$\begin{aligned}x &= A^{-1}b \\x &= \left(\frac{1}{|A|} \times adj(A) \right) b\end{aligned}$$

$$A^{-1} = \frac{1}{7} \begin{bmatrix} 5 & -2 \\ -4 & 3 \end{bmatrix}$$

$$x = \frac{1}{7} \begin{bmatrix} 5 & -2 \\ -4 & 3 \end{bmatrix} \cdot \begin{bmatrix} 12 \\ 23 \end{bmatrix} = \begin{bmatrix} 2 \\ 3 \end{bmatrix} = \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$$

© 2021 Sumudu Tennakoon

88

Solving Linear Equations (General Form)

$$Ax = b$$

$$\begin{bmatrix} a_{11} & a_{12} & \dots & a_{1n} \\ a_{21} & a_{22} & \dots & a_{2n} \\ \vdots & \vdots & \ddots & \vdots \\ a_{m1} & a_{m2} & \dots & a_{mn} \end{bmatrix}_{m \times n} \cdot \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_n \end{bmatrix}_{n \times 1} = \begin{bmatrix} b_1 \\ b_2 \\ \vdots \\ b_m \end{bmatrix}_{m \times 1}$$

$m = \text{number of linearly independent equations}$

$n = \text{number of unknowns } (x_i)$

$m = n \rightarrow \text{unique solution}$

$m < n \rightarrow \text{infinitely many solutions}$

$$x = A^{-1}b$$

$$\begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_n \end{bmatrix}_{n \times 1} = \underbrace{\begin{bmatrix} a'_{11} & a'_{12} & \dots & a'_{1m} \\ a'_{21} & a'_{22} & \dots & a'_{2m} \\ \vdots & \vdots & \ddots & \vdots \\ a'_{n1} & a'_{n2} & \dots & a'_{nm} \end{bmatrix}_{n \times m}}_{A^{-1}} \cdot \begin{bmatrix} b_1 \\ b_2 \\ \vdots \\ b_m \end{bmatrix}_{m \times 1}$$

© 2021 Sumudu Tennakoon

89

Linear Transformations

$$p = \begin{bmatrix} x \\ y \end{bmatrix}$$

$$p' = T \begin{bmatrix} x \\ y \end{bmatrix} = \begin{bmatrix} x' \\ y' \end{bmatrix}$$


- Stretching = $\begin{bmatrix} k & 0 \\ 0 & 1 \end{bmatrix}$

- Squeezing = $\begin{bmatrix} k & 0 \\ 0 & 1/k \end{bmatrix}$

- Rotation = $\begin{bmatrix} \cos(\theta) & -\sin(\theta) \\ \sin(\theta) & \cos(\theta) \end{bmatrix}$

counterclockwise


© 2021 Sumudu Tennakoon



90

Sets

- Basics of Set Theory
- Set Operators
 - Union
 - Intersection
 - Complement
 - Difference



91


Basics of Set Theory

- A set is a collection of things (elements).
 - $A = \{\clubsuit, \diamond, \heartsuit, \spadesuit\}$
 - $B = \{\times, \div, +, -\}$
 - $C = \{apple, orange, mango, banana\}$
 - $D = \{x | x \text{ satisfies some property}\}$
 - $\mathbb{N} = \{1, 2, 3, 4, \dots\}$ is set of natural numbers
 - $\mathbb{Z} = \{\dots, -3, -2, -1, 0, 1, 2, 3, 4, \dots\}$ is set of integers
 - $E = \{x | x \in \mathbb{Z}, -2 \leq x < 10\}$
 - $\emptyset = \{\}$ is Null set
- Items belongs to a set (element of)
 - $\heartsuit \in A$
 - $\div \in B$
 - $apple \in C$
- Items not belongs to a set (not an element of)
 - $\blacksquare \notin A$
 - $*$ $\notin B$
 - $strawberry \notin C$
- Subset
 - $\{\diamond, \heartsuit\} \subset A$
 - $\mathbb{N} \subset \mathbb{Z}$

© 2021 Sumudu Tennakoon

92

Venn Diagrams



93

Cardinality (size of the set)

$$A = \{\clubsuit, \diamondsuit, \heartsuit, \spadesuit\}$$

$$|A| = 4$$


$$B = \{1, 2, 3, 4, 5, 6\}$$

$$|B| = 6$$

© 2021 Sumudu Tennakoon <https://en.wikipedia.org/wiki/Cardinality>

94

Set Operations




95

$$A = \{x | x \in \mathbb{Z}, 1 \leq x < 10, x \text{ is an odd number}\}$$

$$B = \{x | x \in \mathbb{Z}, 1 \leq x < 10, x \text{ is an even number}\}$$

$$C = \{x | x \in \mathbb{Z}, 1 \leq x < 10, x \text{ is a prime number}\}$$



$$D = \{x | x \in \mathbb{Z}, 1 \leq x < 10\}$$



96

Cartesian product

- $A \times B = \{(a, b) | a \in A \text{ and } b \in B\}$
- $A \times B \neq B \times A$




© 2021 Sumudu Tennakoon https://en.wikipedia.org/wiki/Cartesian_product


97

Laws of Set Theory

- Identity
 - $A \cap U = A$
 - $A \cup \emptyset = A$



- Dominance
 - $A \cap \emptyset = \emptyset$
 - $A \cup U = U$
- Idempotence
 - $A \cap A = A$
 - $A \cup A = A$



- Complement
 - $A \cap A' = \emptyset$
 - $A \cup A' = U$


- Double Compliment
 - $(A')' = A$

© 2021 Sumudu Tennakoon

98

Logic Gates

- Logical Statements
- Logical Operators
 - AND
 - OR
 - NOT



99


Logical Statements and Binary Logic

- TRUE = 1
- FALSE = 0
- “5 is an odd number” is **TRUE**
- “4 is a prime number” is **FALSE**
- “Kandy is the Capital City of Sri Lanka” is **FALSE**
- “A triangle has three sides” is **TRUE**


© 2021 Sumudu Tennakoon

100



Logic Gates




A	!A
1	0
0	1



A	B	A & B
1	1	1
1	0	0
0	1	0
0	0	0



© 2014 Sumudu Tennakoon



A	B	A B
1	1	1
1	0	1
0	1	1
0	0	0

https://en.wikipedia.org/wiki/Boolean_algebra

101

Laws of Boolean Algebra

- Identity
 - $A \& 1 = A$
 - $A | 0 = A$

• A is a Boolean variable
• A can take either 1 or 0

- Annihilator
 - $A \& 0 = 0$
 - $A | 1 = 1$

- Idempotence
 - $A \& A = A$
 - $A | A = A$

- Associativity
 - $A \& (B \& C) = (A \& B) \& C$
 - $A | (B | C) = (A | B) | C$

- Commutativity
 - $A \& B = B \& A$
 - $A | B = B | A$

- Distributivity
 - $A \& (B | C) = (A \& B) | (A \& C)$
 - $A | (B \& C) = (A | B) \& (A | C)$

© 2021 Sumudu Tennakoon

102

Laws of Boolean Algebra

- Complement
 - $A \& !A = 0$
 - $A | !A = 1$
- Double Negation
 - $!(!A) = A$
- De Morgan's laws:
 - $!A \& !B = !(A | B)$
 - $!A | !B = !(A \& B)$

© 2021 Sumudu Tennakoon

103

Exponents and Logarithms

	Exponent Representation	Logarithmic representation
Base n	$n^x = y$	$\log_n y = x$
Base 2	$2^3 = 8$	$\log_2 8 = 3$
Base 10	$10^3 = 1000$	$\log_{10} 1000 = 3$
Base e	$e^{6.907755} \approx 1000$	$\log_e 1000 \approx 6.907755$

$$\log_e(1000) = \ln(1000)$$

© 2021 Sumudu Tennakoon

104

Functions

- $y = f(x)$
- $f(x) = \frac{1}{x}$
- $f(x) = a_0 + a_1x + a_2x^2$
- $f(x) = a_0 + a_1x_1 + a_2x_2$
- $f(x) = a_0 + a_1x_1 + a_2x_2$
- *Step Functions*
 - $f(x) = \begin{cases} 0, & x < 0 \\ x, & x \geq 0 \end{cases}$
- *Logistic Function*
 - $f(x) = \frac{L}{1+e^{-k(x-x_0)}}$

© 2021 Sumudu Tennakoon

105

Series

- $S_n = \sum_{i=1}^n a_i = a_1 + a_2 + \dots + a_n$
- Example
 - Let $a_i = 2(i - 1) + 1$
 - $a_1 = 1$
 - $a_2 = 2 + 1 = 3$
 - $a_3 = 2 \times 2 + 1 = 5$
 - $a_4 = 2 \times 3 + 1 = 7$
 - $S_4 = 1 + 3 + 5 + 7 = 16$

© 2021 Sumudu Tennakoon [https://en.wikipedia.org/wiki/Series_\(mathematics\)](https://en.wikipedia.org/wiki/Series_(mathematics))

106

Sequence

- $(a_i)_{i=1}^n = [a_0, a_1, a_2, \dots, a_n]$

- Example

- Let $a_i = i^2$
- $a_1 = 1$
- $a_2 = 2^2 = 4$
- $a_3 = 3^2 = 9$
- $a_4 = 4^2 = 16$

- $(i^2)_{i=1}^4 = 1, 4, 9, 16$

© 2021 Sumudu Tennakoon [https://en.wikipedia.org/wiki/Series_\(mathematics\)](https://en.wikipedia.org/wiki/Series_(mathematics))

107

Trigonometric Functions

- $\sin(x)$
 - $\cos(x)$
 - $\tan(x)$
-
- Sound Signal:
 - amplitude = $\sin(\omega t) = \sin(2\pi f t)$

© 2021 Sumudu Tennakoon

108

Take-home Exercise

- Mention one machine learning problem (specify whether it is a classification, regression or clustering problem) and the training approach you would take (supervised or unsupervised).
- Your answer must be 240 characters or fewer.




© 2021 Sumudu Tennakoon

109

Probability and Statistics Concepts for Machine Learning

- Probability
- Statistical Distributions
- Descriptive Statistics



© 2021 Sumudu Tennakoon

110

Probability

© 2021 Sumudu Tennakoon



111

Probability Example

- Coin (single toss)
 - Possible outcomes: {Head, Tail}



- Dice (single roll)
 - Possible outcomes: {1, 2, 3, 4, 5, 6l}




© 2021 Sumudu Tennakoon

112

Term Definitions

- **Experiment:** A procedure that can be repeated and has a well-defined set of possible outcomes.
 - **Random experiment:** outcome is unknown before the experiment. Results different outcomes when repeating the experiment in the same manner.
 - **Deterministic experiment:** outcome may be predicted with certainty beforehand. Has a definite outcome. Outcome is predictable.
- **Sample Space (Ω):** Set of all possible outcomes or results of an experiment.
- **Outcome:** Possible result of an experiment. An element of Ω .
- **Event:** A set of selected outcomes of an experiment. Subset of the sample space.
 - Independent Event: probabilities of occurrence do not depend on one another
- **Random Variable:** A variable that can take different values of the sample space (describes the outcomes of a random experiment).



© 2021 Sumudu Tennakoon

113

Probability

- Let $\Omega = \{\omega_1, \omega_2, \dots, \omega_n\}$ be a sample space of an experiment.
- Let the event $A \subset \Omega$
- Probability (How likely the event A can occur) : $P(A) = \frac{|A|}{|\Omega|}$
- $0 \leq P(A) \leq 1$
- Random Variable (X): $\{\omega \in \Omega | u < X(\omega) \leq v\}$
- Cumulative Probability: $\sum_x P(X = x) = 1$

© 2021 Sumudu Tennakoon

114

Probability Example


- Coin (single toss)

- Two possible outcomes
- $\Omega = \{H, T\}$
- $|\Omega| = 2$
- $P(A = \{H\}) = \frac{1}{2}$
- $P(A = \{T\}) = \frac{1}{2}$



- Dice (single roll)

- Six possible outcomes
- $\Omega = \{1, 2, 3, 4, 5, 6\}$
- $|\Omega| = 6$
- $P(A = \{1\}) = \frac{1}{6}$
- $P(A = \{6\}) = \frac{1}{6}$
- $P(A = \{1,3,5\}) = \frac{3}{6} = \frac{1}{2}$ (get odd number as outcome)



$$\text{Odd number: } P(A) = \frac{|A|}{|\Omega|} = \frac{1}{6} = \frac{1}{2}$$

$$\text{Even number: } P(B) = \frac{|B|}{|\Omega|} = \frac{1}{2}$$

$$\text{Prime number: } P(C) = \frac{|C|}{|\Omega|} = \frac{1}{2}$$

$$P(A \cup C) = \frac{|A \cup C|}{|\Omega|} = \frac{4}{6} = \frac{2}{3}$$

$$P(A \cap C) = \frac{|A \cap C|}{|\Omega|} = \frac{2}{6} = \frac{1}{3}$$

© 2021 Sumudu Tennakoon

115

Conditional Probability

- Probability of A given B : $P(A|B) = \frac{P(A \cap B)}{P(B)}$, if $P(B) \neq 0$

- Example


- $A = \{2, 3, 5\}$, prime numbers
- $B = \{1, 3, 5\}$, odd numbers



- If the outcome is an odd number, probability of that Number being a prime.

- $P(A|B) = \frac{P(A \cap B)}{P(B)} = \frac{\frac{1}{3}}{\frac{1}{2}} = \frac{2}{3}$
- $P(A \cap B) = \frac{|A \cap B|}{|\Omega|} = \frac{|\{3, 5\}|}{|\{1, 2, 3, 4, 5, 6\}|} = \frac{2}{6} = \frac{1}{3}$
- $P(B) = \frac{|B|}{|\Omega|} = \frac{|\{1, 3, 5\}|}{|\{1, 2, 3, 4, 5, 6\}|} = \frac{3}{6} = \frac{1}{2}$

© 2021 Sumudu Tennakoon



116

Conditional Probability: Example

- A: Selected person is vaccinated
- B: Age of the selected person ≥ 30
- If a person with age ≥ 30 is selected, probability that the person is vaccinated?
 - $P(A) = \frac{|A|}{|\Omega|} = \frac{55}{100}$
 - $P(A \cap B) = \frac{|A \cap B|}{|\Omega|} = \frac{45}{100}$
 - $P(B) = \frac{|B|}{|\Omega|} = \frac{50}{100}$
 - $P(A|B) = \frac{P(A \cap B)}{P(B)} = \frac{\frac{45}{100}}{\frac{50}{100}} = \frac{45}{50} = 0.9$

$$P(A|B) = \frac{P(A \cap B)}{P(B)}$$

	Vaccinated (YES)	Vaccinated (NO)	Total
Age < 30	10	40	50
Age ≥ 30	45	5	50
Total	55	45	100


90 %

© 2021 Sumudu Tennakoon

117

Bayes Rule

- Conditional Probability of A given B
 - $P(A|B) = \frac{P(A \cap B)}{P(B)}$, if $P(B) \neq 0 \rightarrow (1)$
- Commutativity in Set theory
 - $P(A \cap B) = P(B \cap A) \rightarrow (2)$
- (2) in (1)
 - $P(B \cap A) = P(A|B) \cdot P(B) \rightarrow (3)$
- Conditional Probability of B given A
 - $P(B|A) = \frac{P(B \cap A)}{P(A)} \rightarrow (4)$
- (3) in (4)
 - $P(B|A) = \frac{P(A|B) \cdot P(B)}{P(A)}$, if $P(A) \neq 0$



© 2021 Sumudu Tennakoon

https://en.wikipedia.org/wiki/Bayes%27_theorem

118

Conditional Probability: Example

Events

- I : Infected
- N : Not infected
- T_P : Positive Test Result
- T_N : Negative Test Result

Measurements/Probabilities

- known*
- Infected population ratio: $P(I) = 0.04 = 4\%$
 - Positive Test Result if infected: $P(T_P|I) = 0.98 = 98\%$
 - Positive Test Result if not infected: $P(T_P|N) = 0.01 = 1\%$
 - A person get positive result regardless of the infection status: $P(T_P)$
 - $P(N) = 1 - P(I)$
 - $P(T_P) = \sum_{x=\{I,N\}} P(x)P(T_P|x)$
 - $P(T_P) = P(I)P(T_P|I) + P(N)P(T_P|N)$
 - $P(T_P) = 0.04 \times 0.98 + 0.96 \times 0.01 = 0.0488$

John got a positive test result. What is probability that John is infected.

$$P(I|T_P) = \frac{P(T_P|I) \cdot P(I)}{P(T_P)} = \frac{0.98 \times 0.04}{0.0488} = 0.803$$

80 %

119

Probability Distributions

Discrete

- Probability distribution of a random variable that can take only a finite set of values.
- Probability mass function (PMF)
 - $\sum_{x \in X} P(x) = 1$

Continuous

- Probability distribution of a random variable that can take an infinite number of values.
- Probability density function (PDF)
 - $\int P(x) dx = 1$

120

Combinatorics

- Permutations

- Order matters
- Without repetition: $P_x^n = \frac{n!}{(n-x)!}$
- With repetitions: n^x

- Combinations

- Order does not matter
- Can take with or without repetitions
- Without repetitions: $C_x^n = \frac{n!}{x!(n-x)!}$
- With repetitions: $C_x^{n+x-1} = \frac{(n+x-1)!}{x!(n-x)!}$


Example

Set of Digits

- $S = \{0, 1, 2, 3\}$
- $n = |S| = 4$

Pick 2 elements (digits at a time) without repetition.

- $x = 2$



© 2021 Sumudu Tennakoon

121

Permutations and Combinations

Set of Digits

- $S = \{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\}$
- $|S| = 10$

$$P_x^n = \frac{n!}{(n-x)!}$$

$$C_x^n = \frac{n!}{x!(n-x)!}$$

Pick 4 elements (digits at a time)

E.g.,

- $A = 1234$
- $B = 2341$

How many permutations can be made?


How many combinations can be made?

© 2021 Sumudu Tennakoon

122




123



124

Population and Sample



- $P = A \cup B \cup C$
- $S \subset P$
- $S = (A \cap S) \cup (B \cap S) \cup (C \cap S)$
- $|S| = n = |A \cap S| + |B \cap S| + |C \cap S| = a + b + c$

125

Sampling Method depends on

- Nature of population
- Regulatory Restrictions
- Resources available
 - Time
 - Money
 - Data Collectors/Probes

© 2021 Sumudu Tennakoon

126

Sampling Considerations

Unbiased: each element is equally likely to be chosen

Representative of the Population

Minimize the **Sampling Error**

© 2021 Sumudu Tennakoon

127

Probabilistic Sampling Techniques

Simple Random Sampling

Stratified Sampling

Systematic sampling

Cluster Sampling

...

[https://en.wikipedia.org/wiki/Sampling_\(statistics\)](https://en.wikipedia.org/wiki/Sampling_(statistics))
https://en.wikipedia.org/wiki/Stratified_sampling

© 2021 Sumudu Tennakoon

128

Sampling Technique	Description
Random Sampling	Sample in a random manner
Stratified Sampling	Represent subgroups
Systematic Sampling	Include observed population study
Cluster Sampling	Clusters observed represent population identification population

Non- Probabilistic Sampling Techniques

Convenience Sampling

Judgmental Sampling

Quota sampling

Snowball Sampling

...

[https://en.wikipedia.org/wiki/Sampling_\(statistics\)](https://en.wikipedia.org/wiki/Sampling_(statistics))

https://en.wikipedia.org/wiki/Stratified_sampling

© 2021 Sumudu Tennakoon

Types of Statistics

Descriptive Statistics: Organizing and summarizing data. Use data from the population or sample.

Mean, Median, Mode, Range, Variance

Inferential Statistics: Use the sample data to make an inference or draw the population's conclusion. It uses probability to find out the confidence of the predictions we make.

Distributions, Regression, ...

© 2021 Sumudu Tennakoon

Types of Analytics

Descriptive: What do we have now/ had

Predictive: What can happen if the conditions are set to

Prescriptive: Define rules/ constrains

© 2021 Sumudu Tennakoon

131

Descriptive Statistics

Range

Mean

Median

Mode

Variance

Standard Deviation

Coefficient of Variation

Co-variance

Co-relation Coefficient

© 2021 Sumudu Tennakoon

132

Range, Mean, Median and Mode

- Range
 - Max Value - Min value
- Mean
 - Population Mean: $\mu = \frac{\sum_{i=1}^n x_i}{N}$
 - Sample Mean: $\bar{x} = \frac{\sum_{i=1}^n x_i}{n}$
 - Has influence of outliers
- Weighted Mean (w_i s are weights)
 - $\bar{x}_w = \frac{\sum_{i=1}^n w_i x_i}{\sum_{i=1}^n w_i}$
- Geometric Mean:
 - $\bar{x}_g = \sqrt[n]{\prod_{i=1}^n x_i}$
- Median:
 - Mid value when ordered
 - Removes influence of outliers
- Mode
 - Value that occur most often

© 2021 Sumudu Tennakoon

133

Variance , Standard Deviation and Coefficient of variance


- Variance
 - How data spread around mean
- Population : $\sigma^2 = \frac{\sum_{i=1}^n (x_i - \mu)^2}{N}$
- Sample : $S^2 = \frac{\sum_{i=1}^n (x_i - \bar{x})^2}{n-1}$
- Standard Deviation (STD)
 - Population : $\sigma = \sqrt{\frac{\sum_{i=1}^n (x_i - \mu)^2}{N}}$
 - Sample : $S = \sqrt{\frac{\sum_{i=1}^n (x_i - \bar{x})^2}{n-1}}$
- Coefficient of variance (CV)
 - Also known as relative standard deviation (RSD)
 - Population : $CV = \frac{\sigma}{\mu}$
 - Sample : $CV = \frac{S}{\bar{x}}$

© 2021 Sumudu Tennakoon

134

Co-variance and Co-relation Coefficient


- Co-variance:
 - Check whether 2 variables moving together
 - $\text{COV}(x,y) = \frac{\sum_{i=1}^n (x_i - \bar{x})(y_i - \bar{y})}{n-1}$
 - $\text{COV} \begin{cases} < 0, & \text{if variables moving opposite direction} \\ = 0, & \text{if independent variables} \\ > 0, & \text{if variables moving together} \end{cases}$
- Co-relation Coefficient
 - $r = \frac{\text{COV}(x,y)}{S(x) \cdot S(y)}$
 - $-1 \leq r \leq 1$
 - $r = 1$ and $r = -1$: perfect corelation
 - $r \begin{cases} < 0, & \text{if negative corelation} \\ = 0, & \text{if independent variables} \\ > 0, & \text{if positive corelation} \end{cases}$



© 2021 Sumudu Tennakoon

135

Distributions Central value and Spread






© 2021 Sumudu Tennakoon

136

Distributions

Skewness



<https://en.wikipedia.org/wiki/Skewness>

<https://docs.scipy.org/doc/scipy/reference/generated/scipy.stats.skew.html>


© 2021 Sumudu Tennakoon

<https://mathworld.wolfram.com/Pearson'sSkewnessCoefficients.html>

137


Standard Normal Distribution

- Standard Deviation (σ) = 1
- Mean (μ) = 0 = Median = Mode




© 2021 Sumudu Tennakoon https://en.wikipedia.org/wiki/Probability_distribution

138



139



140

Range, Mean, Median and Mode

- Range
 - Max Value - Min value
- Mean
 - Population Mean: $\mu = \frac{\sum_{i=1}^n x_i}{N}$
 - Sample Mean: $\bar{x} = \frac{\sum_{i=1}^n x_i}{n}$
 - Has influence of outliers
- Weighted Mean (w_i s are weights)
 - $\bar{x}_w = \frac{\sum_{i=1}^n w_i x_i}{\sum_{i=1}^n w_i}$
- Geometric Mean:
 - $\bar{x}_g = \sqrt[n]{\prod_{i=1}^n x_i}$
- Median:
 - Mid value when ordered
 - Removes influence of outliers
- Mod
 - Value that occur most often

© 2021 Sumudu Tennakoon

141

Variance , Standard Deviation and Coefficient of variance

- Variance
 - How data spread around mean
- Population : $\sigma^2 = \frac{\sum_{i=1}^n (x_i - \mu)^2}{N}$
- Sample : $S^2 = \frac{\sum_{i=1}^n (x_i - \bar{x})^2}{n-1}$
- Standard Deviation (STD)
 - Population : $\sigma = \sqrt{\frac{\sum_{i=1}^n (x_i - \mu)^2}{N}}$
 - Sample : $S = \sqrt{\frac{\sum_{i=1}^n (x_i - \bar{x})^2}{n-1}}$
- Coefficient of variance (CV)
 - Also known as relative standard deviation (RSD)
 - Population : $CV = \frac{\sigma}{\mu}$
 - Sample : $CV = \frac{S}{\bar{x}}$

© 2021 Sumudu Tennakoon

142

Data Pre-Processing

Treat Missing Values

Treat Outliers

Scaling Variables

© 2021 Sumudu Tennakoon

143

Treat Missing Values

- Drop
 - Drop rows/columns with missing values ✗
- Impute
 - Impute (replacing with value)
 - Interpolate
 - Descriptive statistics: Median, Mean, Mode
 - Use machine learning model
 - Derive using other column (e.g., gender by title, name)
 - Replace with a dummy value (e.g., NA, N/A, null, -9999)
- Revisit
 - Revisit data collection
- Request
 - Request missing information from data provider

© 2021 Sumudu Tennakoon

144

Treating Outliers

- Detecting Outliers
 - Box Plot
 - Percentiles
- Remove Outliers
 - Drop rows/columns
 - Replace outlier values
 - Set cutoff value/clip (piecewise function)
 - Convert to ranges


© 2021 Sumudu Tennakoon

145

Co-variance and Co-relation Coefficient


- Co-variance:
 - Check whether 2 variables moving together
 - $\text{COV}(x,y) = \frac{\sum_{i=1}^n (x_i - \bar{x})(y_i - \bar{y})}{n-1}$
 - $\begin{cases} < 0, & \text{if variables moving opposite direction} \\ = 0, & \text{if independent variables} \\ > 0, & \text{if variables moving together} \end{cases}$
- Co-relation Coefficient
 - $r = \frac{\text{COV}(x,y)}{S(x) \cdot S(y)}$
 - $-1 \leq r \leq 1$
 - $r = 1$ and $r = -1$: perfect corelation
 - $\begin{cases} < 0, & \text{if negative corelation} \\ = 0, & \text{if independent variables} \\ > 0, & \text{if positive corelation} \end{cases}$

© 2021 Sumudu Tennakoon



146

Correlation & Causation



© 2021 Sumudu Tennakoon

147

Univariate Analysis

- Single Variable
- Techniques
 - Descriptive Statistics
 - Frequency Table
 - Count Plot/Bar plot (categorical)
 - Histogram (numerical)
 - Box Plot

© 2021 Sumudu Tennakoon

148

Bivariate Analysis

- Two variables
- Techniques
 - Cross tables (two-way tables)
 - Scatter Plot
 - Correlation coefficient
 - Stacked plot
 - Heatmaps
 - Pair Plot
 - Marginal Probability/Conditional Probability/Joint Probability
 - Regression

© 2021 Sumudu Tennakoon

149

Preparing Dataset for Machine Learning

- Dimensionality Reduction
- Feature Selection
 - Select best features based on highest predictive power
- Feature Engineering
 - Derive new features from existing features
 - Transform features
 - Combine multiple features (create interactions)

© 2021 Sumudu Tennakoon

150

Dimensionality Reduction

- Transform data from higher dimension space to lower dimension space (e.g., 4D to 3D, 3D to 2D)
- Retains characteristics of original data.
- Useful for
 - visualization purpose
 - Observe patterns more clearly
- Methods
 - Principle Component Analysis (PCA)
 - Linear discriminant analysis (LDA)
 - Kernel PCA
 - Autoencoder

© 2021 Sumudu Tennakoon

151

Feature Scaling


- Normalization (value between 0 and 1)
 - Min-max
 - Mean
- Standardization (scale based on standard normal distribution)
 - Z-score
- Other Scaling Techniques
 - Log transform
 - Power transform
- Not necessary in Tree based models

© 2021 Sumudu Tennakoon

152

Standard Normal Distribution

- Standard Deviation (σ) = 1
- Mean (μ) = 0 = Median = Mode



© 2021 Sumudu Tennakoon https://en.wikipedia.org/wiki/Probability_distribution

153

Encoding

- Numerical Variables -> Categorical Variables
- Categorical Variables
 - One hot encoding (1/0, create dummy variables)
 - Mean Encoding (mean of each category)
 - Label Encoding (ordinal)
 - Target guided ordinal encoding (rank of mean)

ID#	Grade	A	B	C	D	N/A
1	A	1	0	0	0	0
2	B	0	1	0	0	0
3	C	0	0	1	0	0
4	D	0	0	0	0	0
5		0	0	0	0	1

ID#	Gender	Male	Female	Is_male?	Gender_ME	Gender_TGOE
1	M	1	0	1	0.48	2
2	F	0	1	0	0.52	1
3	F	0	1	0	0.52	1
4	M	1	0	1	0.48	2
5	M	1	0	1	0.48	1

© 2021 Sumudu Tennakoon

154

Feature Selection

- Based on Missing Values
 - Remove features with high % of missing values (define a threshold)
 - Create new feature to indicate missingness (binary column)
- Based on Variance
 - Remove features with zero variation
 - Remove features with low variation (define a threshold)
- Based on correlation
 - Analyze correlation between features (x variables) and those with the target (y) variable
 - Keep from a set of highly correlated variables
 - Keep one having highest correlation coefficient with the target (y) variable.
 - Drop features with low correlation with the target (y)
 - This could miss a useful feature, therefore use with caution

© 2021 Sumudu Tennakoon

155

Feature Selection

- Forward Selection
 - Start with best feature (feature with most predictive power) to build model
 - Evaluate the model performance
 - Add next feature, build model and evaluate
 - If the model performance increases, keep feature if not, drop
- Backward Elimination
 - Start with all features, build model, evaluate
 - Drop least useful feature in each iteration

© 2021 Sumudu Tennakoon

156

Evaluating Machine Learning Models



© 2021 Sumudu Tennakoon

157

	Positive	Negative	Total
Infected	48	2	50
Not Infected	1	49	50
Total	49	51	100

© 2021 Sumudu Tennakoon

158



Confusion Matrix: Terms

- condition positive (P)
 - the number of real positive cases in the data
- condition negative (N)
 - the number of real negative cases in the data
- true positive (TP)
- true negative (TN)
- false positive (FP)
- false negative (FN)

© 2021 Sumudu Tennakoon

159

Confusion Matrix

		Predicted condition		Sources: [13][14][15][16][17][18][19][20] view talk edit	
		Total population = P + N	Positive (PP)	Negative (PN)	
Actual condition	Positive (P)	True positive (TP), hit	False negative (FN), type II error, miss, underestimation	True positive rate (TPR), recall, sensitivity (SEN), probability of detection, hit rate, power $= \frac{TP}{P} = 1 - FNR$	False negative rate (FNR), miss rate $= \frac{FN}{P} = 1 - TPR$
	Negative (N)	False positive (FP), type I error, false alarm, overestimation	True negative (TN), correct rejection	False positive rate (FPR), probability of false alarm, fall-out $= \frac{FP}{N} = 1 - TNR$	True negative rate (TNR), specificity (SPC), selectivity $= \frac{TN}{N} = 1 - FPR$
	Prevalence $= \frac{P}{P+N}$	Positive predictive value (PPV), precision $= \frac{TP}{PP} = 1 - FDR$	False omission rate (FOR) $= \frac{FN}{PN} = 1 - NPV$	Positive likelihood ratio (LR+) $= \frac{TPR}{FPR}$	Negative likelihood ratio (LR-) $= \frac{FNR}{TNR}$
	Accuracy (ACC) $= \frac{TP+TN}{P+N}$	False discovery rate (FDR) $= \frac{FP}{PP} = 1 - PPV$	Negative predictive value (NPV) $= \frac{TN}{PN} = 1 - FOR$	Markedness (MK), deltaP (Δp) $= PPV + NPV - 1$	Diagnostic odds ratio (DOR) = $\frac{LR+}{LR-}$
	Balanced accuracy (BA) = $\frac{TPR + TNR}{2}$	F_1 score $= \frac{2PPV \times TPR}{PPV + TPR} = \frac{2TP}{2TP + FP + FN}$	Fowlkes–Mallows index (FM) = $\sqrt{PPV \times TPR}$	Matthews correlation coefficient (MCC) $= \sqrt{TPR \times TNR \times PPV \times NPV} - \sqrt{FNR \times FPR \times FOR \times FDR}$	Threat score (TS), critical success index (CSI), Jaccard index $= \frac{TP}{TP + FN + FP}$

© 2021 Sumudu Tennakoon

https://en.wikipedia.org/wiki/Confusion_matrix

160

Evaluating Classification Models

Accuracy (ACC):

$$\frac{TP + TN}{P + N}$$

Precision: Positive Predictive Value (PPV)

$$\frac{TP}{TP + FP}$$

Recall: Sensitivity/Hit rate/True Positive Rate (TPR)

$$\frac{TP}{P}$$

F1 score:

$$2 \times \frac{PPV \times TPR}{PPV + TPR} = \frac{2 \times TP}{2 \times TP + TN + FP + FN}$$

© 2021 Sumudu Tennakoon

161

Visual Methods


Receiver operating characteristic(ROC) curve

- Precision Recall Curve


Sample Mean vs.
Predicted Mean

© 2021 Sumudu Tennakoon

162



163



164

Evaluating Regression Models

Mean Absolute Error (MAE):

$$MAE = \frac{1}{N} \sum_{i=1}^N |y_i - \hat{y}_i|$$

Mean Squared Error (MSE):

$$MSE = \frac{1}{N} \sum_{i=1}^N (y_i - \hat{y}_i)^2$$

Root Mean Squared Error (RMSE):

$$RMSE = \sqrt{\frac{1}{N} \sum_{i=1}^N (y_i - \hat{y}_i)^2}$$

Coefficient of Determination (R-squared):

$$RMSE = 1 - \frac{\sum_{i=1}^N (y_i - \hat{y}_i)^2}{\sum_{i=1}^N (y_i - \bar{y})^2}$$

© 2021 Sumudu Tennakoon

165

Bias and Variance





Fig. 1: Graphical Illustration of bias-variance trade-off , Source: Scott Fortmann-Roe., Understanding Bias-Variance Trade-off

- **Bias:** deviation from the actual value due to the model's simplistic assumptions in fitting the data.
 - High bias: model is unable to capture the patterns in the data and this results in **under-fitting**.
- **Variance:** deviation from the actual value due to the complex model trying to fit the data.
 - High variance: model passes through most of the data points, and it results in **over-fitting** the data.

© 2021 Sumudu Tennakoon

166


Overfitting and Underfitting



167

Bias-Variance Tradeoff


- Ideal Case for a machine learning model :
 - low variance and low bias.
- Reality
 - Bias-Variance trade-off
 - Find the model that performs well on both the train and unseen(test) data.



© 2021 Sumudu Tennakoon

168

Train-Test Split




- No Training data should be used for Testing/Evaluating and vice versa.
- Keep Training and Testing Datasets Separate or properly labeled in the same dataset.
- Do train test split once and use the same two datasets over model tuning process.
- Use random Sampling
- Commonly used Train to Test ratio is 70:30

© 2021 Sumudu Tennakoon

169

Cross Validation




- If required to use all data in the Training Process
 - E.g., small number of observations available.
- K-Fold Cross validation
- Split Dataset into K number of Samples
- Create K number of configurations holding one out of K sample as the Testing Sample
- Train Models using K folds and average results

© 2021 Sumudu Tennakoon

170

Hyperparameter Tuning




© 2021 Sumudu Tennakoon, Pilario, Karl Ezra & Cao, Yi & Shafiee, Mahmood. (2020)

171


Class Imbalance

- Majority Class Minority Class
- Examples
 - Fraud Detection.
 - Churn Prediction.
 - Spam Detection.
- Ways to treat Imbalance
 - Collect More Data
 - (Re)Sampling
 - Stratified sample
 - Over Sampling (multiple copies of some of the minority classes)
 - SMOTE: Synthetic Minority Over-sampling Technique.
 - Under Sampling (Randomly remove samples from the majority class)
 - Data Augmentation (Generate Synthetic Data)
 - Using proper evaluation metric
 - Precision, Recall, F1 Score, AUC (ROC)
 - Do not use accuracy !
 - Split Larger Class into sub classes.
 - Use Ensemble Models



<https://arxiv.org/abs/1106.1813>
 © 2021 Sumudu Tennakoon
<https://link.springer.com/article/10.1007/s13748-016-0094-0>

172



173

The slide features a large, glowing orange lightbulb icon on the left side, with several black curved lines radiating from it to represent light or ideas. To the right of the lightbulb, the title 'Supervised and Unsupervised Machine Learning' is displayed in a large, black, sans-serif font. A thin orange horizontal line serves as a section separator. Below the title, the heading 'Supervised learning' is followed by two bullet points: ' $y = f(x_1, x_2, \dots, x_n)$ ' and ' x_1, x_2, \dots, x_n are independent variables used to analyze the dependent variable (y) and the relation between them.' Underneath this, the heading 'Unsupervised Learning' is followed by two bullet points: 'No dependent variable.' and 'Starts with a collection of variables (x_1, x_2, \dots, x_n) to find out similarity between them and classify them into clusters.' At the very bottom of the slide, there is a small, semi-transparent copyright notice: '© 2021 Sumudu Tennakoon'.

174

Supervised Machine Learning

Regression

- Linear Regression
- Polynomial Regression
- Random Forest Regressor


Classification

- Logistic Regression
- Decision Trees
- Random Forest Classifier
- Support Vector Machine (SVM)
- K-Nearest Neighbors (KNN)

© 2021 Sumudu Tennakoon

175

Unsupervised Machine Learning




© 2021 Sumudu Tennakoon




176

Linear Regression



177


Decision Tree Classifier



© 2021 Sumudu Tennakoon

178

Random Forest Classifier



© 2021 Sumudu Tennakoon

179

Unsupervised Machine Learning

Clustering

- K-Means
- DBSCAN

Dimensionality Reduction


- PCA
- Autoencoder

Generative adversarial networks (GANs)

© 2021 Sumudu Tennakoon

180

Unsupervised Machine Learning



© 2021 Sumudu Tennakoon

181

© 2021 Sumudu Tennakoon

Clustering

Unsupervised learning

Group data points based on their similarities

Considerations

- Representation of a cluster with more than one data points.
- How we define the qualification for a datapoint to be a member of a cluster (nearness)
- When to stop the data point assignments to cluster

182

Applications of Clustering

Market and Customer Segmentation

Recommendation engines

Anomaly Detection / Outlier Detection

Medical Data Analysis (Imaging, Disease Control, etc.)

Data Labeling (Cluster and Label)


Understand the subgroups exists in data

- Number of groups
- Determine Group size
- Study group characteristics (aggregate values).
- Cohesion (togetherness) and separation
- Can those groups combine or further split?

© 2021 Sumudu Tennakoon

183

Centroid Based Clustering




- Step 1: Place K centroids in random locations
- Step 2: Calculate the **distance** between each point to the centroid centers.
- Step 3: Find the nearest centroid to each data point using the get **min(distance)** and assign point to that centroid.
- Step 4: Calculate new center (mean of all assigned points) for the centroid based on the points.
- Loop: Repeat the Steps 2 -4 until converge (no points change cluster assignments)

© 2021 Sumudu Tennakoon

184

Density Based Clustering




- Step 1: Select a random point previously unlabeled.
- Step 2: Count the number of other points (n) enclosed (density) in the defined region.
- Step 3:
 - If $n = 0$ where the current point is the only point in the region, mark the point as noise or outlier.
 - If $n < N_{\min}$
 - If no core point is included in the region, mark the point as noise or outlier.
 - If at least one other core point is included in the region, mark it as a border point.
 - If $n \geq N_{\min}$ mark the point as core point and initiate a cluster or assign the point to the current cluster.
- Step 4 (Loop):
 - If the point is a core point or border point, go to Step 2 covering all points in the cluster.
 - If the point is an outlier, go to Step 1
- Step 4 (Loop Break):
 - If all possible points covered in the current cluster (no more core points to be created), go to Step 1


© 2021 Sumudu Tennakoon

185

Hierarchical Clustering



- Work well with data can be represented as heatmaps
- Dendograms
- Methods
 - Agglomerative (bottom up)
 - Divisive (top-down)



© 2021 Sumudu Tennakoon

186

Explaining ML Models and Predictions

Explainable AI (XAI)

© 2021 Sumudu Tennakoon

187

Why do we need to Explain Models and their Predictions?

© 2021 Sumudu Tennakoon



188

Explaining ML Models and Predictions

- Global
 - Overall understanding of how the model makes a prediction.
 - Feature Importance
- Local
 - Understand how model makes a prediction for a given observation.
 - Positive and Negative contribution of x variables (features) to the prediction.
 - Scale of contribution could be very different from model feature Importance
 - What are the variables contributed the most.



© 2021 Sumudu Tennakoon

189

Explainable AI local methods

Local interpretable model-agnostic explanation (LIME)

Kernel Shapley additive explanations (KernelSHAP)

Integrated gradients (IG)

Explainable explanations through AI (XRAI)

© 2021 Sumudu Tennakoon

190

Explainability

Models can be easily explained


- Regression
- Decision Trees

Models cannot be easily explained (Blackbox Models)

- Ensemble Models (e.g., Random Forest)
- Neural Network (e.g., CNN, RNN)

© 2021 Sumudu Tennakoon

191





© 2021 Sumudu Tennakoon

192

Neuron and Perceptron

- We have approximately 86 billion neurons in our brain.




<https://en.wikipedia.org/wiki/Neuron>


© 2021 Sumudu Tennakoon

193


Activation functions




Sigmoid
 $\sigma(x) = \frac{1}{1+e^{-x}}$




tanh
 $\tanh(x)$




ReLU
 $\max(0, x)$



Leaky ReLU
 $\max(0.1x, x)$




Maxout
 $\max(w_1^T x + b_1, w_2^T x + b_2)$



© 2021 Sumudu Tennakoon


194

Logistic Regression as Perceptron



195


Neural Network



https://en.wikipedia.org/wiki/Artificial_neural_network

© 2021 Sumudu Tennakoon

196






© 2021 Sumudu Tennakoon

197

Traditional ML vs. Deep Learning

- Feature Engineering Workload
- Model Training Recourses
- Amount of Training Data Required
- Solving Complex Problems




CIFAR10

© 2021 Sumudu Tennakoon


198

Convolutional Neural Network



199


Convolutional Neural Network



© 2021 Sumudu Tennakoon

200

Convolutional Neural Network




© 2021 Sumudu Tennakoon

201

1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1.0	0.9	0.7	0.9	0.6	0.8	0.7	0.8
1.0	0.9	0.8	0.9	0.8	0.9	0.9	0.9
0.7	0.7	0.7	0.8	1.0	0.6	0.8	0.8
0.9	0.9	0.9	0.9	1.0	0.9	0.9	0.9
0.9	1.0	1.0	0.9	1.0	1.0	1.0	1.0
0.7	0.6	0.8	0.8	0.9	0.6	1.0	0.8
1.0	0.9	1.0	1.0	1.0	0.9	1.0	1.0


CNN



© 2021 Sumudu Tennakoon

202

Learning Rate



203

Regularization

$$\hat{y} = w_1x_1 + w_2x_2 + \dots + w_Nx_N + b$$

$$Loss = Error(y, \hat{y})$$

Loss function with no regularisation

$$Loss = Error(y, \hat{y}) + \lambda \sum_{i=1}^N |w_i|$$


Loss function with L1 regularisation

$$Loss = Error(y, \hat{y}) + \lambda \sum_{i=1}^N \underline{w_i^2}$$


Loss function with L2 regularisation

© 2021 Sumudu Tennakoon

204



205



206




Building End to End Machine Learning Applications

© 2021 Sumudu Tennakoon

207


Steps of Building ML Model



© 2021 Sumudu Tennakoon

208

Design, Develop and Deploy ML Solutions



© 2021 Sumudu Tennakoon

209

ML Solution Parts to Build

Data Pre-Processing Pipeline

Machine Learning Model Building Pipeline


Machine Learning Model

Prediction (Scoring) Module

Post Processing Pipeline


Interface to accept User Input

Interface to Return Prediction to User



© 2021 Sumudu Tennakoon

210



211

Deployment

- Standalone Application
- Virtual Machines (VM)
- Containerized application
 - Docker (<https://www.ibm.com/cloud/learn/docker>)
 - Kubernetes (<https://www.ibm.com/cloud/learn/Kubernetes>)
- Locally hosted Web API
- Cloud API

© 2021 Sumudu Tennakoon

212

Introduction to Azure ML Platform for Machine Learning Workflow

© 2021 Sumudu Tennakoon

213