Week 7: Designing Model Structure for Optimization | Worked Companion

Mathematical scope of the heating-load decision

The cost used to choose u in [0, 1] is a dimensionless calculation example. It is not a cost law derived from the thermodynamics of a real process.

Consider structural restrictions when there is evidence that the fixed-context cost is convex. Do not transfer this assumption automatically to concentration, yield, or recovery.

Check network convexity, formulation equivalence, and decision quality on the reference function separately.

The induction step in the convexity proof

Assume each component of h is convex and W ≥ 0. Multiplying the componentwise convexity inequality by W preserves its direction for $0 \le \lambda \le 1$.

$$Wh(\lambda u + (1-\lambda)v) \le \lambda Wh(u) + (1-\lambda)Wh(v)$$

The affine term Au + b satisfies equality. Add it, then compose with convex, nondecreasing ReLU to obtain a convex next layer. Apply the same reasoning to the nonnegative output sum.

Two inclusions for the extended epigraph

Let h^* denote actual forward activations. A feasible lifted h satisfies $h \geq h^*$ at the first layer. Substituting this relation and $W \geq 0$ into the next-layer constraints propagates the inequality.

Thus every lifted feasible point has $t \geq f(u)$. Conversely, for any (u, t) with $t \geq f(u)$, choosing $h = h^*$ satisfies the extended constraints.

Projection onto (u, t) is exactly the epigraph. This proof does not require every optimal auxiliary variable to be tight.

Objective monotonicity and auxiliary recovery

If the objective is nondecreasing in t and all other constraints permit reducing t and h to forward values, recovery preserves the optimal value.

This condition holds directly for min t. An upper bound $t \leq b$ also permits reduction. Lower bounds $h \geq b$, output rewards, and state constraints coupled through output equalities require separate inspection.

An activation with zero weight along all output paths can remain slack without affecting the objective. Interpret predictions by reevaluating the network at u.

Piecewise calculation of the two-hinge model

u interval	f(u)	Slope
[0, 0.4]	$0.4 - 0.6u$	-0.6
[0.4, 0.7]	$0.4u$	0.4
[0.7, 1]	$0.9u - 0.35$	0.9

Continuity gives $f(0.4) = 0.16$ and $f(0.7) = 0.28$. The slope switches from negative to positive at the unique minimum 0.4.

Solving $f \le 0.25$ on each interval leaves $u \ge 0.25$ and $u \le 0.625$. The third interval contributes no feasible points.

LP matrices passed to SciPy

The variable order is [u, h_1, h_2]. Add the objective constant 0.4 after solving.

```
result = linprog(
    [-0.6, 1.0, 0.5],
    A_ub=[[1, -1, 0], [1, 0, -1]],
    b_ub=[0.4, 0.7],
    bounds=[(0, 1), (0, None), (0, None)],
    method='highs')
value = result.fun + 0.4
```

The first matrix row is $u - h_1 \leq 0.4$. Check the returned status before using result.x.

Complete solution of the inequality-direction counterexample

The true problem is min u with $0 \leq u \leq 1$ and $\mathrm{ReLU}(u) \geq 0.8$. $\mathrm{ReLU}(u) = u$ on this interval, so the optimum is 0.8.

The relaxation uses $h \geq u$, $h \geq 0$, $h \geq 0.8$. Every $u \in [0, 1]$ can be paired with $h = \max(u, 0.8)$, expanding the projected feasible set to the full interval.

The optimum is 0. The solver correctly solves the revised problem but does not recover the original answer.

The fixed-knot ICNN fitting matrix

$$\Phi_i = \left[1, u_i, \mathrm{ReLU}\left(u_i - \kappa_1\right), \ \ldots, \mathrm{ReLU}\left(u_i - \kappa_9\right)\right]$$

$$\beta = \left[b, a, w_1, \ \ldots, w_9\right]^T$$

$$\min_\beta \left\| \Phi\beta - q \right\|_2^2, w \geq 0$$

b and a are free; only w is nonnegative. At fixed Φ, the Hessian $2\Phi^T\Phi$ is positive semidefinite, so this is a convex quadratic fit.

If knots or deep-layer weights are also learned, Φ depends on the parameters and this argument no longer applies directly.

Reference minimizer and decision loss

$$q(u) = (u - .6)^2 + .1u + .2$$
$$q'(u) = 2(u - .6) + .1 = 0 \Rightarrow u^* = .55$$
$$q(.5) - q(.55) = .2600 - .2575 = .0025$$

Near a flat minimum, a small prediction error can shift the selected input. Input error 0.05 and cost loss 0.0025 are distinct metrics.

The fitted slope on [0.5, 0.6] is approximately 0.0000233, nearly flat. Check solver tolerances alongside the selected point.

Freezing PICNN coefficients and context gates

Suppose a context path $r(c)$ produces a gate $s(c) \geq 0$. At fixed c, nonnegative $W\,\mathrm{diag}(s(c))$ preserves a nonnegative weighted sum of previous convex activations.

A gate multiplying u is a fixed number and can be absorbed into an affine input connection with unrestricted sign.

The lab uses $|u - c| - 0.1c^2$ to check the fixed-context LP and a counterexample to joint convexity. It does not train the paper's full PICNN architecture.

Scaling and physical constraints

Composing convex f with a fixed affine input map u = Sx + r preserves convexity in x. Bounds, units, and context must still agree between the formulation and forward code.

A positive output scale preserves convexity. A negative scale makes a convex function concave, requiring corresponding changes in objective and inequality interpretation.

A concentration-balance projection can mix components with negative coefficients. The Week 4 equality guarantee alone establishes neither componentwise convexity nor this LP representation.

Exercises

1. Determine whether $f(u) = \mathrm{ReLU}(-2u + 1)$ is input-convex and justify it.
2. Find the feasible interval for $f \leq 0.20$ in the two-hinge model.
3. Does adding $h \leq 1$ to the linear inequalities for $h \geq \mathrm{ReLU}(u)$ impose equality? Find a counterexample.
4. Test joint convexity of $f(u;c) = |u - c| - 0.1c^2$ using a midpoint.
5. Does a lower independent RMSE necessarily reduce the error in the selected input? Explain.

Short answer checks

1. Convex: it is the maximum of the affine function $-2u + 1$ and zero.
2. $[1/3, 1/2]$. Solve $0.4 - 0.6u \leq 0.2$ on the left and $0.4u \leq 0.2$ in the middle.
3. $u = 0$, $h = 0.8$ is a counterexample. An upper bound alone does not recover the graph.
4. Endpoint values at $(u, c) = (0, 0)$ and $(1, 1)$ average -0.05; the midpoint value is -0.025.
5. No guarantee: local shape, gradients, and constraint-boundary errors influence the decision.

Reproduction record and review criteria

The lab was run with NumPy 2.5.4 and SciPy 1.18.1. Timing depends on the execution environment.

Include fitted coefficients, data splits, sign checks, LP status and forward error, and reference decision loss. With multiple minimizers, distinguish objective-value equivalence from input nonuniqueness.

Amos, Xu and Kolter, Input Convex Neural Networks, ICML 2017, pp. 146-155

Boyd and Vandenberghe, Convex Optimization, §§3.1-3.2 and 4.1-4.3