
Week 6: Solve Time and Results in Neural-Network Optimization

Reactor conditions that meet product specifications

A reactor design review requires repeated searches over temperature and residence time. After finding conditions that meet the product specifications, we still need to assess how much improvement may remain.



How should we judge the solution available at the deadline?

This week develops ways to assess unfinished solves and adjust bounds and formulations.

The problem and the comparison conditions

Add temperature as an input to the Week 5 reactor setting. At a fixed flow of 1 L/min, residence time also selects reactor volume and is therefore a design variable.

Hold the fitted ReLU model, input domain, objective, and product specifications fixed while comparing formulations. Arbitrarily shrinking the temperature interval changes the design problem.

All LPs and MILPs use the open-source HiGHS solver.

Learning objectives for formulations and solver results

1. Distinguish an incumbent objective from an objective bound and calculate a gap.
2. Compare interval propagation with LP-based bound tightening.
3. Connect a frozen network and its scaling through Pyomo and OMLT.
4. Report termination, time, forward agreement, and constraint residuals.

Review the Week 5 Big-M equivalence and input-bound calculations first.

The frozen network and its MILP representation

For a ReLU input a with valid bounds $L \le a \le U$ and $L < 0 < U$, use these inequalities with binary z.

$$h \ge 0, h \ge a$$
$$h \le Uz, h \le a - L\,(1 - z)$$

Weights, biases, and scaling remain fixed. The full problem is an MILP when the other constraints and objective are linear. Exact network representation is separate from process prediction error.

Incumbents, objective bounds, and gaps

For minimization, the incumbent is the best integer-feasible solution found so far. Its objective value supplies an upper bound that, together with a valid lower bound, brackets the optimum.

$$J_{\text{bound}} \le J_{\text{opt}} \le J_{\text{inc}}$$

$$g_{\text{abs}} = J_{\text{inc}} - J_{\text{bound}}, g_{\text{rel}} = \frac{J_{\text{inc}} - J_{\text{bound}}}{\left|J_{\text{inc}}\right|}$$

An upper bound of 100 and lower bound of 80 give an absolute gap of 20 and a relative gap of 20% under this definition. Without an incumbent this gap is unavailable; near a zero objective, also report the absolute gap.

How branch-and-bound progresses

Relaxing binaries to continuous intervals gives an LP lower bound for minimization. A fractional binary can be branched into subproblems with $z = 0$ and $z = 1$.

An integer-feasible solution updates the incumbent. Infeasible nodes and nodes whose lower bounds cannot improve the incumbent need no further search.

Valid bounds from open nodes form the global lower bound. HiGHS also uses presolve, cuts, and heuristics, so the original LP relaxation value can differ from the final solver bound.

The continuous relaxation of a ReLU

Relaxing z to [0, 1] and eliminating it gives this triangle for L < 0 < U.

$$h \geq 0, h \geq a, h \leq \frac{U}{U-L}\left(a - L\right)$$

At a = 0, the largest allowed h is −UL/(U − L). It is 0.5 when L = −1 and U = 1, although the ReLU output is zero.

This triangle is the convex hull of the scalar (a, h) graph. Correlations across inputs and neurons may require additional constraints.

Two neurons coupled by an equality

Use this dimensionless example to calculate a dependence that box bounds miss.

$$0 \le x_1, x_2 \le 1, x_1 + x_2 = 1$$
$$h_1 = \max\left(0, x_1 + x_2 - 1\right), h_2 = \max\left(0, x_1 - x_2\right)$$
$$\min_{x_1, x_2} x_1 \text{subject to} h_1 + h_2 \ge .4$$

Using only the input box gives [−1, 1] for both pre-activations. The input equality, however, makes the first pre-activation identically zero.


The exact solution of the two-neuron example

$$h_1 = 0, h_2 = \max\left(0, 2x_1 - 1\right)$$
$$h_2 \geq .4 \Rightarrow x_1 \geq .7$$

The minimum x_1 is therefore 0.7. The MILP with box bounds and the MILP using the equality both attain this optimum.

The LP relaxation can place h above the network output, so this conclusion does not immediately apply to its solution.

LP relaxations before and after tightening



The original LP allows $h_1 = 0.4$ even at $x_1 = 0$. Enforcing $h_1 = 0$ raises the LP optimum to 0.4, still below the MILP optimum of 0.7.

The domain over which bounds are valid

Bounds must hold at every allowed input. Training-sample extrema alone do not guarantee coverage of the full input domain.

Overly narrow bounds can cut off valid network points. Wider valid bounds preserve the integer graph but can weaken its relaxation.

Bounds computed using product specifications are valid only over that constrained feasible set. Recheck them when specifications or the input domain change.

Interval propagation with weight signs

Suppose the previous layer satisfies $\ell \le h \le u$, with $w^+ = \max(w, 0)$ and $w^- = \min(w, 0)$.

$$L_j = b_j + \sum_i \left(w_{ij}{}^+ \ell_i + w_{ij}{}^- u_i \right)$$
$$U_j = b_j + \sum_i \left(w_{ij}{}^+ u_i + w_{ij}{}^- \ell_i \right)$$

After a ReLU, pass [max(0, L), max(0, U)] to the next layer. This is inexpensive but does not check whether different variable extremes can occur simultaneously.

LP-based bound tightening

Let P be an LP relaxation containing the network MILP feasible set. Minimize and maximize each pre-activation over P.

$$L_j = \min_{v \in P} a_j(v)$$
$$U_j = \max_{v \in P} a_j(v)$$

This is optimization-based bound tightening, or OBBT. The lab solves 54 LPs over the full input domain without product specifications, then rebuilds the MILP with the resulting bounds.

Handling neurons with fixed activation states

$$U \leq 0 \Rightarrow h = 0$$
$$L \geq 0 \Rightarrow h = a$$

These cases need no binary variable. Only neurons whose intervals cross zero remain candidates for branching.

The hand-built MILP uses 24 binaries with loose bounds, 22 with interval propagation, and 19 with LP-OBBT. These are binary-variable counts before solver presolve.

Input scaling and physical units

$$x_1 = \frac{T - 310}{40}, x_2 = \frac{\tau - 2}{8}$$
$$T = 310 + 40x_1, \tau = 2 + 8x_2$$

Reuse exactly the offsets and scales used during fitting. Supplying physical-input bounds as scaled-input bounds changes the domain evaluated by the network.

Outputs in this lab already use mol/L. If outputs were standardized, include the fixed inverse transform before connecting product specifications.

Objective constants and relative gaps

$$J = \tau + \alpha\left(T - 310\right), \alpha = .02\text{min/K}$$
$$J = 2 + 8x_2 + .8x_1$$

The educational weight α trades residence time against increased temperature. The objective is a min-equivalent score rather than a calibrated process cost.

Dropping the constant 2 preserves the optimizer but changes the denominator of a relative gap. The lab reports objectives and bounds with the constant included.

Roles of the open-source tools

Tool	Role
NumPy	Network forward pass and optional refitting
Pyomo	Variables, objective, and process constraints
OMLT	Frozen-network constraints in Pyomo
HiGHS / highspy	LP and MILP solution

All LPs and MILPs use open-source HiGHS under the MIT license.

Check the input ordering, scaling, and bounds of the constraints generated by OMLT. HiGHS official site

Connecting OMLT to process constraints

Build `definition` from the weights and scaling, then connect the process constraints. `nn.inputs` uses physical units; `scaled_inputs` holds transformed inputs.

```
model.nn = OmltBlock()
model.nn.build_formulation(ReluBigMFormulation(definition))
model.product = pyo.Constraint(expr=model.nn.outputs[1] >= .38)
model.byproduct = pyo.Constraint(expr=model.nn.outputs[2] <= .25)
model.obj = pyo.Objective(
    expr=model.nn.inputs[1] + .02*(model.nn.inputs[0]-310))
```

The lab function `make_omlt` contains the complete construction.

Reproducing Week 5 with OMLT

First check the existing interpolant with residence time as its sole decision, at 330 K and a feed A concentration of 1.2 mol/L. Apply $B \geq 0.40$ and $C \leq 0.25$ mol/L.

Formulation	Minimum residence time [min]	Generated binaries
Hand-built	5.353846	3
OMLT	5.353846	4

This OMLT version creates a binary for each ReLU. The hand-built model represents one always-active neuron linearly, using one fewer binary while giving the same outputs.

Choosing temperature and residence time

$$\min_{T,\tau} J = \tau + .02\left(T - 310\right)$$
$$310 \le T \le 350, 2 \le \tau \le 10$$
$$y = f_\theta\left(T, \tau\right), y_B \ge .38, y_C \le .25$$

Concentrations use mol/L, temperature uses K, and residence time uses min. Predicted concentrations are also constrained to be nonnegative.

The network has two inputs, two hidden layers of 12 ReLUs each, and three linear outputs. Every comparison uses the same frozen coefficients.


Fitting and independently evaluating the frozen model

Generate concentrations at 1,200 training inputs from ideal isothermal A → B → C CSTR balances and fit with 6,000 NumPy Adam updates. Evaluate physical-unit errors at 500 independent random inputs.

Component	Test RMSE [mol/L]
A	0.00546
B	0.00440
C	0.00564


The default lab loads the supplied coefficients. `--refit` optionally refits them; weights never change during optimization.

Comparing relaxation values across bounds



LP-OBBT raises the original LP lower bound from 2.0000 to 2.5215. All three MILPs attain 3.1656. All three comparisons use the same predictor.

Timing including bound computation



In the supplied run, LP-OBBT reduces MILP solve time, but its total time including bounds exceeds interval propagation. These single-run measurements include interface overhead and do not establish a general speed ranking.

Selected conditions and solver conclusions

Item	Supplied run
Temperature [K]	342.059300
Residence time [min]	2.524440
Objective [min-equivalent]	3.165626
Predicted B [mol/L]	0.380000
Termination / relative gap	optimal / 0

HiGHS establishes optimality for this surrogate MILP within the configured numerical tolerances. The B lower bound is active; the C upper bound has slack.

Checking forward agreement and residuals

Remove product specifications, fix the input, and solve only the network representation. Evaluate the four domain corners and 12 independent interior points with both the hand-built and OMLT models.

Across 32 checks, the maximum absolute output difference is 7.77e-16 mol/L. Recompute the forward pass at the selected optimum too.

Check constraint and integrality residuals. Finite samples help detect implementation errors; equivalence over the entire domain follows from the formulation conditions developed in Week 5.

Termination and incumbent availability

Termination	Interpretation
optimal	Completed within gap and numerical tolerances
Time limit, incumbent found	Report the feasible solution and remaining gap
Time limit, no incumbent	No usable solution has been obtained
infeasible	The formulated feasible set is empty
unbounded / error	Inspect bounds, objective, logs, and model

A time limit alone does not establish infeasibility. The lab returns `maxTimeLimit` with no incumbent at a zero-second limit, and `infeasible` when $B \geq 2$.

Checking solution availability and loading results

```
opt = Highs()
opt.config.load_solution = False
opt.config.time_limit = 30.0
result = opt.solve(model)
inc = result.best_feasible_objective
print(result.termination_condition)
if inc is not None and np.isfinite(inc):
    result.solution_loader.load_vars()
    print(inc, result.best_objective_bound)
```

Reading variables after termination without a solution can mistake initial or stale values for results. The complete lab function also returns gaps and constraint residuals.

Solver gaps and process prediction error

At the same selected input	B concentration [mol/L]
Network and MILP	0.380000
Reference CSTR	0.371157
Required minimum	0.380000

The reference CSTR misses the B specification. Forward agreement and a zero solver gap still require a separate process-model feasibility check.

Week 8 uses errors at selected points to reconsider decisions and identify additional data.

Running the lab and reporting comparisons

Extract the lab bundle and run these commands in its directory.

```
python -m pip install -r requirements.txt
python week06_lab.py --output-dir my-results
```

1. Verify the toy LP values 0 and 0.4 and MILP value 0.7 by hand.
2. Compare bounds, binary counts, LP lower bounds, and total times for the same frozen model.
3. Report termination, gap, forward differences, and the reference CSTR B-specification violation.

Reading companion · Lab ZIP

Sources and assigned reading

Ceccon et al., OMLT: Optimization & Machine Learning Toolkit, JMLR 23(349), 2022 · Official quick-start

Anderson et al., Strong mixed-integer programming formulations for trained neural networks, Mathematical Programming, 2020

HiGHS and its MIT license · Pyomo HiGHS interface

Work through the companion derivations of the triangle relaxation, OBBT bound directions, scaling, and gaps. Strong multivariate and partition formulations are optional extensions.