

Solving Linear Matrix Inequalities using the Multi Parametric Toolbox

M. Heemels
D. Rijlaarsdam
M. Lazar

D.J.Rijlaarsdam@tue.nl

TU/e

Technische Universiteit
Eindhoven
University of Technology

November 24, 2009

Where innovation starts

Motivating Examples

From LMI to Matlab code

Matlab Examples

Motivating Examples

From LMI to Matlab code

Matlab Examples

Motivating Examples

From LMI to Matlab code

Matlab Examples

- ▶ Quadratic Lyapunov Function

$$\text{Find } P \text{ s.t. } \begin{cases} A^T P + PA < 0 \\ P > 0 \end{cases}$$

- ▶ Common Quadratic Lyapunov Function

$$\text{Find } P \text{ s.t. } \begin{cases} A_1^T P + PA_1 < 0 \\ A_2^T P + PA_2 < 0 \\ P > 0 \end{cases}$$

- ▶ PWL system, continuity conditions and S-procedure

$$\text{Find } P_i, U_i \text{ and } W_i \text{ s.t. } \begin{cases} A_i^T P_i + P_i A_i + E_i^T U_i E_i < 0 \\ P_i - E_i^T W_i E_i > 0 \\ Z_{ij}^T [P_i - P_j] Z_{ij} = 0 & (i, j) \in \mathcal{J} \end{cases}$$

► Quadratic Lyapunov Function: LMI's

$$\begin{cases} A^T P + P A < Q \\ P > 0 \end{cases}$$

► Matlab code

```
A = [-1 2 0;-3 -4 1;0 0 -2];  
P = sdpvar(3,3); % Unknown 3x3 Hermitian matrix  
Q = 1/100 * eye(3,3); % Decrease rate
```

```
L1 = set(A'*P + P*A + Q < 0); % Constr. 1  
L2 = set(P > 0); % Constr. 2  
L = L1 + L2; % Combine all constraints
```

```
solve(L); % Solving for P (matlab workspace)  
P = double(P); % Converts to standard format
```

- ▶ Define unknowns: `sdpvar(...)` (matrices are symmetric)
- ▶ Define constraints L_i
- ▶ Combine constraints $L = \sum L_i$
- ▶ Solve for unknowns: `solvesdp(L)` or `solvesdp(L,c)`
- ▶ Convert solutions: `double(...)`
- ▶ Check solutions:
 - Substitute in constraints and check manually (recommended)
 - Check yalmip output (sometimes puzzling, overkill for this course)

- ▶ Equality operators: `==`
- ▶ Inequality operators: `<=`, `>=`, `>`, `<`
- ▶ Condition on matrix (eigenvalues): `set (M < 0)`
- ▶ Condition on matrix elements: `set (M(:) < 0)`
- ▶ Solve while minimizing a parameter, matrix elements or eigenvalues: `solvesdp(L, MinCond)`
- ▶ Avoiding the zero solution:
`set (M + epsilon * eye(size(M)) < 0)`

1. Quadratic Lyapunov Function
2. + multiple Lyapunov Functions: stability of PWL system
3. + relaxing the problem: S-procedure
4. Synthesis of a stabilizing controller

For more info type: `yalmipdemo`

On studyweb

- ▶ Examples
- ▶ Presentation
- ▶ Toolbox and installation manual